

Technical Data		STK SERIES ANTENNA					
Nomenclature: Dome Omni Directonal Antenna 2635MHz to 2655MHz						Page No. 1 of 1	
STK-590583971862		Dome Omni Directonal Antenna 2635MHz to 2655MHz					
		OUTLINE DRAWING					
							
TECHNICAL DATA							
ELECTRICAL DATA							
Frequency (MHz)	2635-2655MHz	Impedance (Ω)	50				
Typical Gain (dBi)	10dBi	Lightning Protection	DC Ground				
V.S.W.R	≤ 2	Dimensions (mm)	144mm x ø 127mm				
Azimuth(°)	360 °	Weight (g)	450				
Elivation(°)	75°	Connector Type	N Male/ N Female				
Polarization	VERTICAL	Operational Temperature (o) C	(-30°c) + 60°c				
Max. Power Input (Watts)	150W						
MATERIAL INFORMATION							
Parts	Material		PLATING (µm)				
Connector Body	BRASS		SILVER				
Silver Pin	BECU		GOLD				
GOLD TAFLON	PTFE						
ANTENNA BODY	ABS PLASTIC		BLACK PAINT				
Originated	Date	Approved	Date	Rev	Amend	Name	Date
SANG	02.09.25	Krishnamurthy	-	0	-	-	-
Synergy Telecom P Ltd,				-	-	-	-
WZ-47, Bodella Village, Vikas Puri, New Delhi - 110 018, India				-	-	-	-
							 Synergy Telecom Pvt Ltd Defence & Aerospace Division Email: sales.blr@rfconnector.in
This document is the property of Synergy Telecom P Ltd - New Delhi and contain confidential information this document shall not be used, reproduce or disclosure in whole or in part, without prior written permission from Defense & Aerospace division . This document and al it copies shall be returned to Synergy Telecom P Ltd on demand. www.rfconnector.in							