



SYNERGY TELECOM PVT LTD		 Technical Data Sheet	T.D.S. No.	ST/TDS/150
WZ-47, BODELLA, VIKAS PURI			Issue No & Date	25.11.2025
NEW DELHI-110018			Rev. No & Date	00/00
India			Ref. CR No.	ST/CR/.../25-26 dtd
https://www.rfconnector.in/			Cust. Enq./PO No.	
Item Name	1C X1.5 Sqmm Data Sheet Automotive Cable			
Description	1C X 1.5 Sqmm ABC , PVC "HR FR" Insulated Cable			
Spec. Ref.	ISO: 6722			
Customer Name				
Sr. No.	Parameter	Description	Unit	Specified Value
1	Conductor	Material	-	Annealed Bare Copper
		Dia Of Each wire	mm(Nom)	0.25 ± 0.02
		No of Strand	Nos	30 ± 4
2	Insulation	Material	-	PVC "HR FR"
		Ins. Thickness	mm(Nom)	0.6 (Approx)
		Colour Of Core		Black (AS PER CUSTOMER REQUIRED)
		Dia of Core	Mm (Nom)	3.0 ± 0.2
3	Electrical test	Conductor resistance(max)	Ω/Km at 20deg.oC	12.70
		Spark Test	kv rms (min)	2.0
		Temp Rating	Deg C	60
		Voltage Rating	Volt	60 to 600
		Tensile Strength	N/Sq.mm (min)	12.5
		Elongation (Insulation)	% (min)	150
		Insulation Resistance (min)	MΩ•Km min.	100.0
		Packing		As Per PO

WZ-47, BASEMENT, BUDDHELLA VILAGE VIKAS PURI NEW DELHI - 110018

PH:- 011-28533349, MOB:- 91-7217885948, FAX:- 011-28533349

EMAIL:- INFO@SYNERGYTPL.COM, WEBSITE:- WWW.RFCONNECTOR.IN



SYNERGY TELECOM PVT LTD			T.D.S. No.	ST/TDS/151
WZ-47, BODDELLA, VIKAS PURI			Issue No & Date	24.11.2025
NEW DELHI-110018			Rev. No & Date	00/00
India			Ref. CR No.	ST/CR/.../25-26 dtd
https://www.rfconnector.in/			Cust. Enq./PO No.	
		Technical Data Sheet		
Item Name	1C X 2.0 Sqmm Data Sheet Automotive Cable			
Description	1C X 2.0 Sqmm ABC , PVC "HR FR" Insulated Cable			
Spec. Ref.	ISO: 6722			
Customer Name				
Sr. No.	Parameter	Description	Unit	Specified Value
1	Conductor	Material	-	Annealed Bare Copper
		Dia Of Each wire	mm(Nom)	0.30 ± 0.02
		No of Strand	Nos	28 ± 4
2	Insulation	Material	-	PVC "HR"
		Ins. Thickness	mm(Nom)	0.6 (Approx)
		Colour Of Core		Black (AS PER CUSTOMER REQUIRED)
		Dia of Core	Mm (Nom)	3.3 ± 0.2
3	Electrical test	Conductor resistance(max)	Ω/Km at 20deg.oC	9.42
		Spark Test	kv rms (min)	2.0
		Temp Rating	Deg C	60
		Voltage Rating	Volt	60 to 600
		Tensile Strength	N/Sq.mm (min)	12.5
		Elongation (Insulation)	% (min)	150
		Insulation Resistance (min)	MΩ•Km min.	100.0
		Packing		As Per PO



SYNERGY TELECOM PVT LTD

SYNERGY TELECOM PVT LTD		 Technical Data Sheet	T.D.S. No.	ST/TDS/153
WZ-47, BODELLA, VIKAS PURI			Issue No & Date	25.11.2025
NEW DELHI-110018			Rev. No & Date	00/00
India			Ref. CR No.	ST/CR/.../25-26 dtd
https://www.rfconnector.in/			Cust. Enq./PO No.	
Item Name	1C X 0.35 Sqmm Data Sheet Automotive Cable			
Description	1C X 0.35 Sqmm ABC , PVC HR FR Insulated Cable			
Spec. Ref.	ISO: 6722			
Customer Name				
Sr. No.	Parameter	Description	Unit	Specified Value
1	Conductor	Material	-	Annealed Bare Copper
		Dia Of Each wire	mm(Nom)	0.26 ± 0.02
		No of Strand	Nos	7
2	Insulation	Material	-	PVC "HR FR"
		Ins. Thickness	mm(Nom)	0.25 (Approx)
		Colour Of Core		Black (AS PER CUSTOMER REQUIRED)
		Dia of Core	Mm (Nom)	1.4 ± 0.2
3	Electrical test	Conductor resistance(max)	Ω/Km at 20deg.oC	54.40
		Spark Test	kv rms (min)	2.0
		Temp Rating	Deg C	60
		Voltage Rating	Volt	60 to 600
		Tensile Strength (Insulation)	N/Sq.mm (min)	12.5
		Elongation (Insulation)	% (min)	150
		Insulation Resistance (min)	MΩ•Km min.	100.0
		Packing		As Per PO

WZ-47, BASEMENT, BUDDHELLA VILAGE VIKAS PURI NEW DELHI - 110018

PH:- 011-28533349, MOB:- 91-7217885948, FAX:- 011-28533349

EMAIL:- INFO@SYNERGYTPL.COM, WEBSITE:- WWW.RFCONNECTOR.IN



SYNERGY TELECOM PVT LTD		 Technical Data Sheet	T.D.S. No.	ST/TDS/152
WZ-47 BUDELLA, VIKAS PURI			Issue No & Date	25.11.2025
NEW DELHI-110018			Rev. No & Date	00/00
India			Ref. CR No.	ST/CR/.../25-26 dtd
https://www.rfconnector.in			Cust. Enq./PO No.	
Item Name	1C X 10 Sqmm Data Sheet Automotive Cable			
Description	1C X 10 Sqmm ABC , PVC Insulated Cable			
Spec. Ref.	ISO: 6722			
Customer Name				
Sr. No.	Parameter	Description	Unit	Specified Value
1	Conductor	Material	-	Annealed Bare Copper
		Dia Of Each wire	mm(Nom)	0.40 ± 0.02
		No of Strand	Nos	80 ± 4
2	Insulation	Material	-	PVC " HR"
		Ins. Thickness	mm(Nom)	1.0 (Approx)
		Colour Of Core		Black (AS PER CUSTOMER REQUIRED)
		Dia of Core	Mm (Nom)	6.5 ± 0.5
3	Electrical test	Conductor resistance(max)	Ω/Km at 20deg.oC	1.82
		Spark Test	kv rms (min)	2.0
		Temp Rating	Deg C	60
		Voltage Rating	Volt	60 to 600
		Tensile Strength	N/Sq.mm (min)	12.5
		Elongation (Insulation)	% (min)	150
		Insulation Resistance (min)	MΩ•Km min.	100.0
		Packing		As Per PO

WZ-47, BASEMENT, BUDDHELLA VILAGE VIKAS PURI NEW DELHI - 110018

PH:- 011-28533349, MOB:- 91-7217885948, FAX:- 011-28533349

EMAIL:- INFO@SYNERGYTPL.COM, WEBSITE:- WWW.RFCONNECTOR.IN