



## L1 & L5 Passive GNSS Antenna

### SY1L5-ST-3P



#### Features

- \* Covers Full L1 & L5 Band
- \* Passive Antenna with 3dBic Gain
- \* Low axial ratio
- \* Ground Plane independent
- \* Rugged IP 67 Rating

#### Applications

- \* High Precision Navigation
- \* High Precision Navigation
- \* Marine Systems
- \* Military & Security
- \* UAV / Drones

#### Electrical Specifications

|                 |                   |                  |
|-----------------|-------------------|------------------|
| Frequency Range | 1575.42 MHz (L1)  | 1176.45 MHz (L5) |
| Peak Gain       | 3 dBic            |                  |
| VSWR            | < 2.0 : 1         |                  |
| Polarization    | RHCP              |                  |
| Beamwidth       | ± 45 Degree       |                  |
| Pattern         | Hemispherical     |                  |
| Impedance       | 50 Ω              |                  |
| Antenna Type    | Passive           |                  |
| Axial Ratio     | ≤ 3dB             |                  |
| Connector       | TNC (F) or SMA(F) |                  |

#### Mechanical Specifications

|              |                        |
|--------------|------------------------|
| Dimensions   | Approx Ø 80 x 40 mm    |
| Weight       | < 250 Grams            |
| Enclosure    | UV ABS                 |
| Radome Color | Olive Green            |
| Mounting     | Screw Mount or L Clamp |

#### Environmental Specifications

|                             |                    |
|-----------------------------|--------------------|
| Operating Temperature Range | - 40° C to + 65° C |
| IP Rating                   | IP 67 *            |
| Compliances                 | JSS 55555 *        |