

# 40~43GHz, 10W, Solid State Power Amplifier

## FEATURES

- Instantaneous ultra broadband
- Built-in protection circuits
- High reliability and ruggedness
- Compact size and light weight

## ELECTRICAL SPECIFICATIONS

| Parameter       | Min | Typ | Max | Unit |
|-----------------|-----|-----|-----|------|
| Frequency Range | 40  |     | 43  | GHz  |
| Psat            | 10  |     |     | W    |
| Gain            |     | 45  |     | dB   |
| Gain Flatness   |     |     | ±2  | dB   |
| Harmonics       | -10 |     |     | dBc  |
| Spurious        | -60 |     |     | dBc  |
| VSWR            |     |     | 2:1 | -    |
| Input Power     |     |     | +10 | dBm  |
| DC Voltage      | 26  | 28  | 30  | V    |

## ENVIRONMENTAL SPECIFICATIONS

| Parameter       | Min | Typ | Max | Unit |
|-----------------|-----|-----|-----|------|
| Operating Temp. | -40 |     | +55 | °C   |
| Storage Temp.   | -55 |     | +70 | °C   |

## MECHANICAL SPECIFICATIONS

| Parameter           | Value             | Unit |
|---------------------|-------------------|------|
| Dimensions          | 150×100×28        | mm   |
| Weight              | 2.0               | Kg   |
| RF I/O Connectors   | 2.4mm female      | -    |
| Interface Connector | 15-Pin Male D-Sub | -    |
| Cooling             | External Heatsink | -    |