



SYNERGY TELECOM PVT LTD

UHF RFID Industrial Reader



Name: UHF RFID Industrial Reader

Model Number: SW5401

Size: 95 x 95 x 40mm

WZ-47, BASEMENT, BUDDHELLA VILAGE VIKAS PURI NEW DELHI - 110018

PH:- 011-28533349, MOB:- 91-7217885948, FAX:- 011-28533349

EMAIL:- INFO@SYNERGYTPL.COM, WEBSITE:- WWW.RFCONNECTOR.IN



General Description:

SW5401 is a high performance UHF RFID Industrial Reader. It is designed mainly for industrial production process control system.

Application:

- ◆ Industrial production process control
- ◆ Production flow-line management
- ◆ Attendance management and more
- ◆ AGV Car
- ◆ Tobacco Management
- ◆ Attendance management

Features:

1. Base on the domestic high-performance RF chip design, Self-intellectual property;
2. Support ISO18000-6C (EPC C1G2) protocol tag;
3. 865~868MHz, 902~928MHz frequency band (frequency customization optional by Soft);
4. FHSS or Fix Frequency transmission;
5. RF output power up to 26dBm (adjustable);
6. 3dBi Circular Ceramic Antenna with effect distance up to 0~350cm*;
7. Support active mode, answer mode, trigger-activating and password work mode;
8. Low power dissipation with single +12V DC power supply;
9. Support RS232, RS485 interface, RJ45;
10. One Relay (Optional) can control Beep, Motor, Light;
11. Support ModBus (only RS232, RS485, RJ45 interface);
12. Support for **White List** and **Read By Time** *;
13. Support read **'ON'** temperature tag *.

* Effective distance depends on antenna, tag and environment.

Product mode explanation:

Model	Interface
SW5401	Standard(RS232, RS485, Trigger)
SW5401T	Standard with RJ45
SW5401R	Standard with Relay
SW5401W	Standard with WIFI
SW5401U	Standard with USB
SW5401G	Standard with 4G
-T: RJ45 -T: RJ45 -W: WIFI -R: Relay -U: USB -G: 4G	

Characteristics:

Absolute Maximum Rating

ITEM	SYMBOL	VALUE	UNIT
Power Supply	VCC	24	V
Operating Temp.	T _{OPR}	-20~+60	°C
Storage Temp.	T _{STR}	-40~+85	°C

WZ-47, BASEMENT, BUDDHELLA VILAGE VIKAS PURI NEW DELHI - 110018

PH:- 011-28533349, MOB:- 91-7217885948, FAX:- 011-28533349

EMAIL:- INFO@SYNERGYTPL.COM, WEBSITE:- WWW.RFCONNECTOR.IN



Electrical and Mechanical Specification

Under TA = 25°C, VCC = +12V unless specified

ITEM	SYMBOL	MIN	TYPE	MAX	UNIT
Power Supply	VCC	8	12	24	V
Current Dissipation	I _c		400	600	mA
Frequency	F _{REQ}	865		928	MHz

Product Technical Parameters

Type	
Model Number	SW5401
Type	UHF RFID Industrial Reader
Physical parameters	
Dimensions	95x95x40mm
Net Weight	1.0Kg
Gross Weight	1.5Kg
Package size	24*16*13cm
Carton size	48*32.5*28.5cm, 8pcs/carton
Shell material	ABS
Color	Black
Environmental parameters	
Operation Temperature	-20~+60°C
Storage Temperature	-40~+85%
Humidity	5%~95% RH, Non-condensing
Waterproof Rank	IP65
Performance	
Frequency	902~928MHz,860~868MHz(frequency customization optional)
Ant.	3 dBi Circular Antenna
RF Power	0 - 26dBm
Read Distance *	0-350cm * <i>Effective distance depends on antenna, tag and environment.</i>
Write Distance *	0-150cm * <i>Effective distance depends on antenna, tag and environment.</i>
Read Rate	200cnt / second
Read Type	ISO18000-6C (EPC Gen2)
Reading Prompt	Buzzer
Working Voltage	DC +9 - 24V, 6W
Work Mode	Active mode, Answer mode, Trigger mod, Password mode
Communication	RS232, RS485, WG26, WG34, Trigger, Relay(Optional), RJ45(Optional), WIFI(Optional),USB(Optional)



SYNERGY TELECOM PVT LTD

Read Function	Support for White List and Read By Time*
Other tag type	Support read ' ON ' temperature tag *
Net	RJ45 support TCP Client/Server, Modbus, DNS, DHCP. WIFI support TCP Client, HTTP, MQTT. 4G support TCP Client, HTTP, MQTT. LLRP(Optional)
SDK	
SDK	Support X86 & X64, C++, C#, VB, Delphi, Linux, ARM, Python, NodeJS, QT, JAVA, Android, Modbus.      

Interface

Item	Comment
Red	VCC (DC 9V – 24V)
Black	GND
White	RS232 TXD
Purple	RS232 RXD
Brown	GND
Yellow	Wiegand DATA0
Green	Wiegand DATA1
Gray	GND
Pink	RS485 A+
Orange	RS485 B-
Aqua	Trigger input+ (TTL level)
Blue	Trigger input- (TTL level)

WZ-47, BASEMENT, BUDDHELLA VILAGE VIKAS PURI NEW DELHI - 110018

PH:- 011-28533349, MOB:- 91-7217885948, FAX:- 011-28533349

EMAIL:- INFO@SYNERGYTPL.COM, WEBSITE:- WWW.RFCONNECTOR.IN