

		STK SERIES CONNECTOR		 www.rfconnector.in			
Technical Data		Nomenclature:CONNECTOR COAXIAL JACK RP SMA-F FLMT					
STK-571123981533		CONNECTOR COAXIAL JACK RP SMA-F FLMT					
OUTLINE DRAWING							
							
TECHNICAL DATA							
ELECTRICAL DATA							
Impedance	50 Ω						
Frequency Range	DC to 18 GHz						
VSWR	≤ 1.30:1 (typical)						
Insertion Loss	≤ 0.2 Db						
DielectricWithstandingVoltage	≥ 1000 V RMS						
nsulation Resistance	≥ 5000 MΩ						
ENVIRONMENTAL INFORMATION							
Operation temperature	-65 °C to +125 °C						
MECHANICAL INFORMATION							
Weight	-						
MATERIAL INFORMATION							
COMPONENTS		MATERIAL		PLATING			
BODY		STAINLESS STEEL		GOLD			
CENTER CONTACT		BERYLLIUM COPPER		GOLD			
DIELECTRIC		PTFE		-			
O RING		SILICON RUBBER		-			
Originated	Date	Approved	Date	Rev	Amend	Name	Date
Sang	01.12.25	Krishnamurthy	-	0	-	-	-
Synergy Telecom P Ltd,				-	-	-	-
WZ-47, Bodella Village, Vikas Puri, New Delhi - 110 018, India				-	-	-	-
				 Synergy Telecom Pvt Ltd Defence & Aerospace Division			
				Email: sales.blr@rfconnector.in			
This document is the property of Synergy Telecom P Ltd - New Delhi and contain confidential information this document shall not be used, reproduce or disclosure in whole or in part, without prior written permission from Defense & Aerospace division . This document and al it copies shall be returned to Synergy Telecom P Ltd on demand.							
www.rfconnector.in							