



Technical Data

STK SERIES CONNECTOR



www.rfconnector.in



Nomenclature: CONNECTOR RF50 SMA SQFL JACK RP TAB CONT


Page No.

1 of 1

STK-571127561221

CONNECTOR RF50 SMA SQFL JACK RP TAB CONT

OUTLINE DRAWING



TECHNICAL DATA

ELECTRICAL DATA

Impedance	50 Ω
Frequency	0-18 GHz
VSWR	$1.06^* + 0.002 \times F(\text{GHz})$ Maxi
Insertion loss	$0.07 \sqrt{F(\text{GHz})}$ dB Maxi
RF leakage	- (60 - F(GHz)) dB Maxi
Voltage rating	500 Veff Maxi
Dielectric withstanding voltage	1000 Veff mini
Insulation resistance	5000 M Ω mini

ENVIRONMENTAL INFORMATION

Operation temperature	-65/+165 °C
-----------------------	-------------

MECHANICAL INFORMATION

Mating end	27 N mini
Opposite end	27 N mini
Mating life	500 Cycles mini
Torque	2.8 N.cm mini
Weight	3.003 g

MATERIAL INFORMATION

COMPONENTS		MATERIALS			PLATINGS (mm)			
BODY		STAINLESS STEEL			GOLD 0.5 OVER NICKEL 2			
CENTER CONTACT		BERYLLIUM COPPER			GOLD 1.3 OVER NICKEL 2			
INSULATOR		PTFE			-			
Originated	Date	Approved	Date	Rev	Amend	Name	Date	 Synergy Telecom Pvt Ltd Defence & Aerospace Division Email: sales.blr@rfconnector.in
Sang	01.12.25	Krishnamurthy	-	0	-	-	-	
Synergy Telecom P Ltd,				-	-	-	-	
WZ-47, Bodella Village, Vikas Puri, New Delhi - 110 018, India				-	-	-	-	

This document is the property of **Synergy Telecom P Ltd**- New Delhi and contain confidential information this document shall not be used, reproduce or disclosure in whole or in part, without prior written permission from **Defense & Aerospace division**. This document and all its copies shall be returned to Synergy Telecom P Ltd on demand.
www.rfconnector.in