



Technical Data

STK SERIES CONNECTOR



www.rfconnector.in



Nomenclature: CON RF50 MMCX RECPT PCB EDGE

Page No.

1 of 1

STK-571182401235

CON RF50 MMCX RECPT PCB EDGE

OUTLINE DRAWING



TECHNICAL DATA

ELECTRICAL DATA

Impedance	50 Ω
Frequency	0-6 GHz
VSWR	$1.05 + 0.0080 \times F(\text{GHz})$ Maxi
Insertion loss	$0.03 \times \sqrt{F(\text{GHz})}$ dB Maxi
RF leakage	- (57 - F(GHz)) dB Maxi
Voltage rating	500 Veff Maxi
Dielectric withstanding voltage	1000 Veff mini
Insulation resistance	1000 M Ω mini

ENVIRONMENTAL INFORMATION

Operation temperature	-55/+155 ° C
-----------------------	--------------

MECHANICAL INFORMATION

Board mounting type	edge mount
Weight	0.0007 kg

MATERIAL INFORMATION

COMPONENTS		MATERIALS			PLATINGS (mm)		
BODY		BRASS			Gold Plating (Nickel underplated)		
CENTER CONTACT		Copper Beryllium Alloy			Gold Plating (Nickel underplated)		
INSULATOR		PFA / PTFE			-		
OTHERS PARTS		-			-		
GASKET		-			-		
OUTER CONTACT		BRASS			Gold Plating (Nickel underplated)		
Originated	Date	Approved	Date	Rev	Amend	Name	Date
Sang	01.12.25	Krishnamurthy	-	0	-	-	-
Synergy Telecom P Ltd,				-	-	-	-
WZ-47, Bodella Village, Vikas Puri, New Delhi - 110 018, India				-	-	-	-

Synergy Telecom Pvt Ltd
Defence & Aerospace Division

Email: sales.blr@rfconnector.in

This document is the property of **Synergy Telecom P Ltd**- New Delhi and contain confidential information this document shall not be used, reproduce or disclosure in whole or in part, without prior written permission from **Defense & Aerospace division**. This document and all it copies shall be returned to Synergy Telecom P Ltd on demand.

www.rfconnector.in