



Technical Data

STK SERIES CONNECTOR



www.rfconnector.in



Nomenclature: CONN SMB MALE RECPT SQ FLANGE EXTENDED


Page No.

1 of 1

STK-571183041244

CONN SMB MALE RECPT SQ FLANGE EXTENDED

OUTLINE DRAWING



TECHNICAL DATA

ELECTRICAL DATA

Impedance	50 Ω
Frequency	0-4 GHz
VSWR	1.05 + 0.0080 x F(GHz) Maxi
Insertion loss	0.03* √F(GHz) dB Maxi
RF leakage	- (57 - F(GHz)) dB Maxi
Voltage rating	500 Veff Maxi
Dielectric withstanding voltage	1000 Veff mini
Insulation resistance	1000 MΩ mini

ENVIRONMENTAL INFORMATION

Operation temperature	-65/+165 ° C
-----------------------	--------------

MECHANICAL INFORMATION

Mating End	NA N mini
Opposite end	NA N mini
Mating life	500 Cycles mini
Weight	1,6100 g

MATERIAL INFORMATION

COMPONENTS		MATERIALS			PLATINGS (mm)		
BODY		BRASS			GOLD 0.2 OVER NICKEL 2		
CENTER CONTACT		BRASS			GOLD 1.3 OVER NICKEL 2		
INSULATOR		PTFE					
OTHERS PARTS		BRASS			GOLD 0.2 OVER NICKEL 2		
GASKET		-			-		
OUTER CONTACT		-			-		
Originated	Date	Approved	Date	Rev	Amend	Name	Date
Sang	01.12.25	Krishnamurthy	-	0	-	-	-
Synergy Telecom P Ltd,				-	-	-	-
WZ-47, Bodella Village, Vikas Puri, New Delhi - 110 018, India				-	-	-	-

Synergy Telecom Pvt Ltd
Defence & Aerospace Division

Email: sales.blr@rfconnector.in

This document is the property of Synergy Telecom P Ltd- New Delhi and contain confidential information this document shall not be used, reproduce or disclosure in whole or in part, without prior written permission from Defense & Aerospace division. This document and al it copies shall be returned to Synergy Telecom P Ltd on demand.
www.rfconnector.in