


 Technical Data	STK SERIES CONNECTOR	 www.rfconnector.in						
Nomenclature:JACK/JACK ADAPTER			Page No. 1 of 1					
STK-571626021232	JACK/JACK ADAPTER							
OUTLINE DRAWING								
								
TECHNICAL DATA								
ELECTRICAL DATA								
Impedance	50 Ω							
Frequency	0-65 GHz							
VSWR	00 + 0,0000 x F(GHz) Maxi							
Insertion loss	0.12 √F(GHz) dB Maxi							
RF leakage	- (NA - F(GHz)) dB Maxi D17							
Voltage rating	335 Veff Maxi							
Dielectric withstanding voltage	500 Veff mini							
Insulation resistance	5000 MΩ mini							
ENVIRONMENTAL INFORMATION								
Operation temperature	-65/+165 ° C							
MECHANICAL INFORMATION								
Mating End	6.7 N mini							
Opposite end	6.7 N mini							
Mating life	500 Cycles mini							
Weight	0,0800 g							
MATERIAL INFORMATION								
COMPONENTS		MATERIALS	PLATINGS (mm)					
Body		BERYLLIUM COPPER	GOLD 1.3 OVER NICKEL2					
Center contact		BERYLLIUM COPPER	GOLD 1.3 OVER NICKEL2					
Insulator		PEEK	-					
Gasket		-	-					
Others parts		-	-					
Originated	Date	Approved	Date	Rev	Amend	Name	Date	 Synergy Telecom Pvt Ltd Defence & Aerospace Division
Sang	01.12.25	Krishnamurthy	-	0	-	-	-	
Synergy Telecom P Ltd,				-	-	-	-	
WZ-47, Bodella Village, Vikas Puri, New Delhi - 110 018, India				-	-	-	-	
Email: sales.blr@rfconnector.in								
This document is the property of Synergy Telecom P Ltd- New Delhi and contain confidential information this document shall not be used, reproduce or disclosure in whole or in part, without prior written permission from Defense & Aerospace division. This document and al it copies shall be returned to Synergy Telecom P Ltd on demand.								
www.rfconnector.in								