


 MAKE IN INDIA Technical Data	STK SERIES CONNECTOR		 www.rfconnector.in	 QUALITY PRODUCT of INDIA			
Nomenclature:CON RF50 AD BNC-T/F-F-F PL				Page No. 1 of 1			
STK-571672011260		CON RF50 AD BNC-T/F-F-F PL					
OUTLINE DRAWING							
							
TECHNICAL DATA							
ELECTRICAL DATA							
Impedance	50 Ω						
Frequency	0-4 GHz						
VSWR	NA + 0,000 x F(GHz) Maxi						
Insertion loss	0.175 √F(GHz) dB Maxi						
RF leakage	- (57 - F(GHz)) dB Maxi						
Voltage rating	500 Veff Maxi						
Dielectric withstanding voltage	1500 Veff mini						
Insulation resistance	5000 MΩ mini						
ENVIRONMENTAL INFORMATION							
Operation temperature	-65/+165 ° C						
MECHANICAL INFORMATION							
Mating End	18 N mini						
Opposite end	18 N mini						
Torque	2.8 N.cm mini						
Mating life	500 Cycles mini						
Weight	19.000 g						
MATERIAL INFORMATION							
COMPONENTS		MATERIALS		PLATINGS (mm)			
Body		BRASS		NICKEL 2			
Center contact		BERYLLIUM COPPER		GOLD 0.5 OVER NICKEL 2			
Insulator		PTFE		-			
Gasket		-		-			
Others parts		-		-			
Originated	Date	Approved	Date	Rev	Amend	Name	Date
Sang	01.12.25	Krishnamurthy	-	0	-	-	-
Synergy Telecom P Ltd,				-	-	-	-
WZ-47, Bodella Village, Vikas Puri, New Delhi - 110 018, India				-	-	-	-
				Email: sales.blr@rfconnector.in			
This document is the property of Synergy Telecom P Ltd- New Delhi and contain confidential information this document shall not be used, reproduce or disclosure in whole or in part, without prior written permission from Defense & Aerospace division. This document and al it copies shall be returned to Synergy Telecom P Ltd on demand.							
www.rfconnector.in							