



Technical Data

STK SERIES CONNECTOR



www.rfconnector.in



Nomenclature:CONN COAXIAL RF 50 RCPT MM PCB



Page No.

1 of 1

STK-571123331245

CONN COAXIAL RF 50 RCPT MM PCB

OUTLINE DRAWING



TECHNICAL DATA

ELECTRICAL DATA

Impedance	50 Ω
Frequency	0-4 GHz
VSWR	NA + 0.000 x F(GHz) Maxi
Insertion loss	NA $\sqrt{F}$ (GHz) dB Maxi
RF leakage	-(NA -F(GHz)) dB Maxi
Voltage rating	175 Veff Maxi
Dielectric withstanding voltage	500 Veff mini
Insulation resistance	1000 MQ mini

ENVIRONMENTAL INFORMATION

Operation temperature	65°C ~ 165°C
-----------------------	--------------

MECHANICAL INFORMATION

Mating end	8 N mini
Opposite end	8 N mini
Mating life	500 Cycles mini
Weight	0.000 g

MATERIAL INFORMATION

COMPONENTS		MATERIALS			PLATINGS (mm)		
BODY		BRASS			GOLD 0.5 OVER NICKEL 2		
CENTER CONTACT		BERYLLIUM COPPER			GOLD 1.3 OVER NICKEL 2		
OUTER CONTACT		-			-		
INSULATOR		PTFE			-		
Originated	Date	Approved	Date	Rev	Amend	Name	Date
Sang	01.01.26	Krishnamurthy	-	0	-	-	-
Synergy Telecom P Ltd,				-	-	-	-
WZ-47, Bodella Village, Vikas Puri, New Delhi - 110 018, India				-	-	-	-



Email: sales.blr@rfconnector.in

This document is the property of Synergy Telecom P Ltd- New Delhi and contain confidential information this document shall not be used, reproduce or disclosure in whole or in part, without prior written permission from Defense & Aerospace division. This document and al it copies shall be returned to Synergy Telecom P Ltd on demand.

www.rfconnector.in