




www.rfconnector.in



Page No.
1 of 1

MALE STRAIGHT RECEPTACLE FOR PCB SMT
TYPE - FULL DETENT - REEL 500

OUTLINE DRAWING



TECHNICAL DATA

ELECTRICAL DATA

Impedance	50 Ω
Frequency	0-18 GHz
VSWR	1.15* + 0.0000 x F(GHz) Maxi
Insertion loss	0.12 $\sqrt{F(\text{GHz})}$ dB Maxi
RF leakage	- (N/A - F(GHz)) dB Max
Voltage rating	335 Veff Maxi
Dielectric withstanding voltage	500 Veff mini
Insulation resistance	5000 M Ω mini

ENVIRONMENTAL INFORMATION

Operation temperature	-65/+165 ° C
-----------------------	--------------

MECHANICAL INFORMATION

Mating End	6.8 N mini
Opposite end	6.8 N mini
Torque	NA N.cm mini
Mating life	100 Cycles mini
Weight	0,3200 g

MATERIAL INFORMATION

COMPONENTS		MATERIALS			PLATINGS (mm)		
Body		STAINLESS STEEL + BRASS			PASSIVATED + GOLD 0.5 OVER		
Center contact		BERYLLIUM COPPER			GOLD 1.27 OVER NICKEL 1.27		
Insulator		PTFE			-		
Gasket		-			-		
Others parts							
Originated	Date	Approved	Date	Rev	Amend	Name	Date
Sang	01.12.25	Krishnamurthy	-	0	-	-	-
Synergy Telecom P Ltd,				-	-	-	-
WZ-47, Bodella Village, Vikas Puri, New Delhi - 110 018, India				-	-	-	-



Synergy Telecom Pvt Ltd
Defence & Aerospace Division

Email: sales.blr@rfconnector.in

This document is the property of Synergy Telecom P Ltd- New Delhi and contain confidential information this document shall not be used, reproduce or disclosure in whole or in part, without prior written permission from Defense & Aerospace division. This document and al it copies shall be returned to Synergy Telecom P Ltd on demand. www.rfconnector.in