

Data Literacy Exercise 06

Machine Learning in Science, University of Tübingen, Winter Semester 2022

Theory Questions

EXAMple question

- a) True. We want to show, that there is actually an underlying difference. For this we assume to there be no difference, in order to be able to reject the null-Hypothesis.
- b) False. Firstly, the p-value can only be interpreted as a conditional probability, namely $P(\text{make Type I error} \mid H_0 \text{ is true})$. Second of all, the usual threshold for significance is lower ($p=0.05$).
- c) False. We cannot prove anything. We simply know that assuming H_0 , we are very unlikely to make a Type I error.
- d) False. The p-value cannot tell us this. This is a probability that would have to be calculated separately.

Theory Question

a) Assuming $x_1, \dots, x_n \sim \mathcal{N}(\mu, \sigma^2)$, we can interpret x_i as the outcome of the random variable X_i .

With $\sum X_i \sim \mathcal{N}(\sum \mu_{X_i}, \sum \sigma_{X_i}^2)$ and $\alpha X \sim \mathcal{N}(\alpha \mu, \alpha^2 \sigma^2)$ follows that, $T(X_1, \dots, X_N) = \frac{1}{N} \sum x_i \sim \mathcal{N}(\frac{1}{N} \sum \mu_{X_i}, \frac{1}{N^2} \sum \sigma_{X_i}^2) = \mathcal{N}(\mu, \frac{1}{N} \sigma^2)$

b) Let $t = T(x) \sim \mathcal{N}(\mu, \frac{1}{N} \sigma^2)$.

Then let $\tilde{t} = \frac{t - \mu}{\frac{1}{\sqrt{N}} \sigma} \sim \mathcal{N}(0, 1)$

We have

$$\begin{aligned} P(t > q \vee t < -q) &\overset{\mathcal{N}(0,1) \text{ symm.}}{=} 2P(t > q) = 2(1 - P(t < q)) \\ &= 2(1 - P(\frac{t - \mu}{\frac{1}{\sqrt{N}} \sigma} < \frac{q - \mu}{\frac{1}{\sqrt{N}} \sigma})) \\ &= 2(1 - \Phi(\frac{\sqrt{N}}{\sigma} (q - \mu))) \end{aligned}$$

c)

$$\begin{aligned} \beta(\mu) &= 2(1 - \Phi(\frac{\sqrt{N}}{\sigma} (c_{\alpha} - \mu))) = 2(1 - \Phi(\frac{\sqrt{N}}{\sigma} \cdot \frac{\sigma}{\sqrt{N}} \Phi^{-1}(1 - \frac{\alpha}{2}) - \mu)) \\ &= 2(1 - \Phi(\Phi^{-1}(1 - \frac{\alpha}{2}) - \mu)) \overset{\mu = 0}{=} 2(1 - \Phi(\Phi^{-1}(1 - \frac{\alpha}{2}))) = \alpha \end{aligned}$$

Introduction

Permutation testing is a procedure which can be used to test whether there is an association between two random variables Z and Y . Given a set of pairs $D = \{(z_1, y_1), (z_2, y_2), \dots, (z_N, y_N)\}$, we want to

test whether Z_i and Y_i are statistically independent or not.

Permutation tests can be defined for different test statistics, but for example we can apply it to $T(D) = \sum_i (z_i - y_i)^2$. The beauty of the permutation test is that there is a very simple way to compute the distribution of the test statistic under the null hypothesis: If z_i and y_i are independent (which they are under H_0), then it should not matter whether we compute $(z_i - y_i)$ or $(z_i - y_j)$ for a j which is drawn (uniformly) at random! One way to implement this is to simply permute the indices of the y 's, and to compute $T(D^*)$ on this permuted data set. By repeating this many times for different (uniformly) random permutations, we can thus compute a histogram of the test statistic under the null. Finally, we can then calculate the p-value by checking what fraction of the (permuted) statistic is smaller than the one we observed!

As a concrete example, let's apply this to a regression task. In this case, we assume we have some algorithm that computed predictions z_i , and we want to see whether these predictions are closer to the targets y_i than one would expect under the null hypothesis, using the test statistic introduced above.

```
In [1]: import pandas as pd
import numpy as np
import scipy.stats.distributions

np.random.seed(42)
```

```
<frozen importlib._bootstrap>:219: RuntimeWarning: scipy._lib.messagestream.MessageStream size changed, may indicate binary incompatibility. Expected 56 from C header, got 64 from PyObject
```

Predicting bike rentals from weather

1. Load our dataset

We will be using the [Bike Sharing Dataset](#) from University of Porto to predict the number of rental bikes from the weather (you can download the .csv from Ilias).

```
In [2]: # Load csv data using the pandas library
df = pd.read_csv("bikedata.csv")
```

```
In [3]: df.head()
```

```
Out[3]:
```

	instant	dteday	season	yr	mnth	holiday	weekday	workingday	weathersit	temp	atemp	hum
0	1	2011-01-01	1	0	1	0	6	0	2	0.344167	0.363625	0.805833
1	2	2011-01-02	1	0	1	0	0	0	2	0.363478	0.353739	0.696087
2	3	2011-01-03	1	0	1	0	1	1	1	0.196364	0.189405	0.437273
3	4	2011-01-04	1	0	1	0	2	1	1	0.200000	0.212122	0.590435
4	5	2011-01-05	1	0	1	0	3	1	1	0.226957	0.229270	0.436957

```
In [4]: # Use the "temp" column as our features (X), and the "cnt" column for labels (y)
```

```
X = df['temp'].to_numpy()
y = df['cnt'].to_numpy()
```

2. Splitting into train and test sets

```
In [5]: from sklearn.model_selection import train_test_split
```

```
In [6]: X = X.reshape(-1, 1)
y = y.reshape(-1, 1)

# Split the arrays into training and test sets, using 30% for test
X_train, X_test, y_train, y_test = train_test_split(X, y, test_size=0.3)
```

3. Linear regression

```
In [7]: from sklearn.linear_model import LinearRegression
```

```
# Fit a linear regression model to the data
reg = LinearRegression().fit(X_train, y_train)
```

```
In [8]: from sklearn.metrics import mean_squared_error
```

```
# Generate a vector of predictions
y_pred = reg.predict(X_test)

# Calculate the mean squared error (you can use the sklearn method above for this)
mse = mean_squared_error(y_test, y_pred)
```

4. Implement permutation testing

Permutation testing is a procedure which allows us to measure how likely the observed metric (in this case, the mean squared error) is obtained by chance. In this case, a p-value represents the fraction of random data sets under a certain null hypothesis where the model performed as well as or better than our observed metric (which was obtained on the true labels).

Here, our null hypothesis (H_0) is that there is no difference between the performance of our trained model and chance (random guessing). To reject this hypothesis, we must create a null distribution, or a set of random (i.e. permuted, or shuffled) data sets. We then calculate our p-value by comparing the error between our observed predictions (calculated above) and the shuffled data (chance level, to be filled in below).

```
In [9]: from numpy.random import shuffle

perm_scores = []

for i in np.arange(0, 1000):

    # Shuffle the labels
    np.random.shuffle(y_pred)

    # Calculate the MSE
    mse_perm = mean_squared_error(y_test, y_pred)

    # Append the MSE to perm_scores
    perm_scores.append(mse_perm)
```


5. Plot

Plot a histogram of the test statistic under the null hypothesis. Additionally, plot a vertical line for the value of the observed test statistic.

```
In [10]: import matplotlib.pyplot as plt
```

```
plt.vlines(mse, ymin=0, ymax=140, colors=['r'], label='mse from unshuffled data')
plt.hist(perm_scores, bins=15)
plt.ylabel('counts for mean squared errors on shuffled data')
plt.xlabel('mean squared error')
plt.legend()
```

```
Out[10]: <matplotlib.legend.Legend at 0x2151365efd0>
```



6. Calculate p-value

```
In [11]: from scipy.stats import norm
# Calculate the p-value
# This will reflect the proportion of MSE from our permuted labels which are lower than
mean = np.mean(perm_scores)
std = np.std(perm_scores)
p_val = 2*(1 - norm.cdf(np.sqrt(len(perm_scores)) / std * mse))
```

```
In [12]: p_val
```

```
Out[12]: 0.0
```

If you get a p-value of 0, this means that your observed MSE was better than random guessing across all permutations. You would report this by saying that your p-value is less than the minimum, i.e. $p < .001$ (since we do 1000 permutations).

6. Interpret your results

What statement can you make based on the p-value you obtained?

Assuming that H_0 is true, we have a chance of 0.1 % of making a Type I error. Meaning that given our assumption that there is no dependence of the two datasets, it's very unlikely that random shuffling the data will yield a lower MSE.

A Type I Error is to wrongly reject the null hypothesis. Thus, given that we assumed no dependence between the two datasets, we would be at low risk of rejecting H_0 wrongly.

(We note that permutation testing is often presented as a way to test whether there is a difference in distribution between two sets of observations (see e.g. Wasserman 10.5, or the [Wikipedia entry](#). Permutation tests can be used for either the purpose described here or for testing for a difference between groups, and the two are indeed related.)

Predicting diabetes from a single feature

Similar to what you just did above, we will recreate the pipeline using different data.

1. Making our dataset

```
In [32]: from sklearn import datasets

# Load the diabetes dataset
diabetes_X, diabetes_y = datasets.load_diabetes(return_X_y=True)

# Use only one feature
diabetes_X = diabetes_X[:, np.newaxis, 0] # TO BE CHANGED LATER ON
```

2. Splitting into train and test sets

```
In [33]: # Split the data into training/testing sets
# In this case we just take the last 20 samples for test
diabetes_X_train = diabetes_X[:-20]
diabetes_X_test = diabetes_X[-20:]

diabetes_y_train = diabetes_y[:-20]
diabetes_y_test = diabetes_y[-20:]
```

3. Linear regression

```
In [34]: reg = LinearRegression().fit(diabetes_X_train, diabetes_y_train)
```

```
In [35]: diabetes_y_pred = reg.predict(diabetes_X_test)
mse = mean_squared_error(diabetes_y_pred, diabetes_y_test)
```

4. Implement permutation testing

```
In [36]: perm_scores = []
```

```

for i in np.arange(0, 1000):

    # Shuffle the labels
    np.random.shuffle(diabetes_y_pred)

    # Calculate the MSE
    mse_perm = mean_squared_error(diabetes_y_pred, diabetes_y_test)

    # Append the MSE to perm_scores
    perm_scores.append(mse_perm)

```

5. Plot

Plot a histogram of the test statistic under the null hypothesis. Additionally, plot a vertical line for the value of the observed test statistic.


```

In [37]: import matplotlib.pyplot as plt

plt.vlines(mse, ymin=0, ymax=160, colors=['r'], label='mse from unshuffled data')
plt.hist(perm_scores, bins=15)
plt.ylabel('counts for mean squared errors on shuffled data')
plt.xlabel('mean squared error')
plt.legend()

```

Out[37]: <matplotlib.legend.Legend at 0x21515c3b2e0>



6. Calculate p-value

```

In [64]: mean = np.mean(perm_scores)
std = np.std(perm_scores)

t_hat = (mean - mse) / std

p_val = 2 * (1 - norm.cdf(t_hat))

```

```
In [65]: p_val
```

```
Out[65]: 0.7617586796462401
```

7. Interpret your results

What statement can you make based on the p-value you obtained?

We see that assuming the null hypothesis, that the two datasets are independant of each other, the risk of wrongly dropping H₀ is quite large.

8. Try again with a different feature

```
In [53]: from sklearn import datasets
data = datasets.load_diabetes()

data['feature_names']
```

```
Out[53]: ['age', 'sex', 'bmi', 'bp', 's1', 's2', 's3', 's4', 's5', 's6']
```

In the code above, we can see that the feature we used previously was 'age'.

Copy and paste the code from "Predicting diabetes from a single feature" into the cell below, then change the "0" to a "2" (there is a comment in the code indicating where to do this). By making this change, we are using BMI as our feature, instead of age.

```
In [70]: # Load the diabetes dataset
Diabetes_X, Diabetes_y = datasets.load_diabetes(return_X_y=True)
```

```
In [73]: for i, feature in enumerate(data['feature_names']):

    # get features
    diabetes_X = Diabetes_X[:, np.newaxis, i]
    X_train, X_test, y_train, y_test = train_test_split(diabetes_X, Diabetes_y, test_size=0.2, random_state=0)

    # fit linearRegressor
    reg = LinearRegression().fit(X_train, y_train)
    y_pred = reg.predict(X_test)

    mse = mean_squared_error(y_test, y_pred)

    perm_scores = []

    for _ in np.arange(0, 1000):

        # Shuffle the labels
        np.random.shuffle(diabetes_y_pred)

        # Calculate the MSE
        mse_perm = mean_squared_error(diabetes_y_pred, diabetes_y_test)

        # Append the MSE to perm_scores
        perm_scores.append(mse_perm)

    mean = np.mean(perm_scores)
    std = np.std(perm_scores)
```


```

t_hat = abs(mean - mse) / std
p_val = 2*(1 - norm.cdf(t_hat))


plt.vlines(mse, ymin=0, ymax=200, colors=['r'], label='mse from unshuffled data')
plt.hist(perm_scores, bins=15)
plt.ylabel('counts for mean squared errors on shuffled data')
plt.xlabel('mean squared error')
plt.title(f'Distribution of MSE of permutation test for feature {feature}. p-value: {p_val}')
plt.legend()
plt.show()

```


Distribution of MSE of permutation test for feature age. p-value: 0.1988174170932986




Distribution of MSE of permutation test for feature sex. p-value: 0.3059826579081435




Distribution of MSE of permutation test for feature bmi. p-value: 5.345452988425592e-05




Distribution of MSE of permutation test for feature bp. p-value: 0.14128244133002021




Distribution of MSE of permutation test for feature s1. p-value: 0.5833540936603527




Distribution of MSE of permutation test for feature s2. p-value: 0.3263845534583991




Distribution of MSE of permutation test for feature s3. p-value: 0.10395752895504318




Distribution of MSE of permutation test for feature s4. p-value: 0.5524601201822654



Distribution of MSE of permutation test for feature s5. p-value: 2.6057913380173048e-05



Distribution of MSE of permutation test for feature s6. p-value: 0.25434824136926615



In []: