

# Rethinking legal probabilism

Rafał Urbaniak

## Contents

<b>1</b>	<b>Scientific goal</b>	<b>1</b>
<b>2</b>	<b>Significance</b>	<b>2</b>
2.1	State of the art . . . . .	2
2.1.1	Legal probabilism . . . . .	2
2.1.2	Skeptical voices and challenges . . . . .	3
2.1.3	The narrative approach . . . . .	4
2.1.4	Bayesian networks as a tool for legal probabilism . . . . .	4
2.2	Pioneering nature of the project . . . . .	6
2.3	Choice of problem . . . . .	8
2.4	Pioneering nature & impact . . . . .	8
<b>3</b>	<b>Concept and work plan</b>	<b>8</b>
<b>4</b>	<b>Research methodology</b>	<b>8</b>
	<b>References</b>	<b>8</b>

## 1 Scientific goal

As many miscarriages of justice indicate, scientific evidence is easily misinterpreted in court. This happens partially due to miscommunication between the parties involved, partially due to the usual probabilistic fallacies, but also because incorporating scientific evidence in the context of a whole case can be really hard. While probabilistic tools for piecemeal evaluation of scientific evidence and spotting probabilistic fallacies in legal contexts are quite well developed, the construction of a more general probabilistic model of incorporating such evidence in a wider context of a whole case, probabilistic explication of and theorizing about evidence evaluation and legal decision standards, remain a challenge. Legal probabilism (LP), for our purpose, is the view that this challenge can and should be met. This project intends to contribute to further development of this enterprise in a philosophically motivated manner.

The assessment of evidence in the court of law can be viewed from at least three perspectives: as an interplay of arguments, as an assessment of probabilities involved, or as an interaction of competing narrations. Each perspective presents an account of legal reasoning (Di Bello & Verheij, 2018; van Eemeren & Verheij, 2017). Individually, each of these strains has been investigated. The probabilistic approach is the most developed one but LP is still underdeveloped —to a large extent this is so in light of various lines of criticism developed by the representatives of the other strains.

The **goal of this project** is to contribute to the **development of legal probabilism** by formulating its variant that accomodates important **insights provided by its critics**. A crucial point of criticism is that the fact-finding process should be conceptualized as **a competition of narrations**. I plan to develop methods that allow the probabilist to take this perspective, and explain how such methods allow the legal probabilist to address various objections present in the literature. The key idea is that once **narrations are represented as bayesian networks, various criteria on, features of and operations on narrations can be explicated in terms of corresponding properties of and operations on bayesian networks**. Further, the hypothesis is that such an improved framework will facilitate addressing key objections raised against LP.

say sth  
about  
repli-  
cability  
crisis in  
forensic  
sciences  
at some  
point?

The conceptual developments will be accompanied by technical accounts. **R** code capturing the technical features developed will be made available to the reader. Thus, the output will be a **unifying extended probabilistic model embracing key aspects of the narrative and argumentative approaches, susceptible to AI implementation**. The methods employed include: Bayesian statistical methods (including Bayesian approach to higher-order probability), imprecise probabilities, and Bayesian networks.

## 2 Significance

(state of the art, justification for tackling a specific scientific problem, justification for the pioneering nature of the project, the impact of the project results on the development of the research field and scientific discipline);

### 2.1 State of the art

#### 2.1.1 Legal probabilism

One of the functions of the trial is to resolve disputes about questions of facts. Did the defendant rob the bank? Who is the father of the child? Did this drug cause birth defects? To answer such questions, the litigants will present evidence of different kinds: eyewitness testimonies, DNA matches, epidemiological studies, etc. The evidence presented will often be in conflict with other evidence. In a bank robbery case, for example, the prosecution may present eyewitness testimony that the defendant was seen driving a truck near the bank a few minutes after the robbery took place. The defense may respond that no traces were found at the crime scene that would match the defendant. The fact-finders, judges or lay jurors, should address these conflicts by assessing and weighing the evidence, and on that basis reach a final decision. This is a difficult task. The evidence presented at trial can be complex and open to multiple interpretations, and even when it is assessed carefully, it may still lead to an incorrect verdict. How should judges and jurors respond to this uncertainty?

From among the three perspectives mentioned in the beginning, the probabilistic approach will be my point of departure, for the following key reasons:

- The project is to be informed by and reflect on the actual practice of legal evidence evaluation, and much of scientific evidence in such contexts has probabilistic form.
- Probabilistic tools are fairly well-developed both for applications and within formal epistemology, reaching a state of fruition which should inspire deeper reflection.
- Statistical computing tools for such methods are available, which makes programming development and preliminary computational and data-driven evaluation of the ideas to be defended a viable enterprise.

Accordingly, the view in focus of this research is legal probabilism (LP)—an ongoing research program that comprises a variety of claims about evidence assessment and decision-making at trial. At its simplest, it comprises two core tenets: first, that the evidence presented at trial can be assessed, weighed and combined by means of probability theory; and second, that legal decision rules, such as proof beyond a reasonable doubt in criminal cases, can be explicated in probabilistic terms.

In the Middle Ages, before the advent of probability theory, there existed an informal mathematics of legal evidence (Wigmore, 1901). Formalistic procedures fixed the number of witnesses required to establish a claim. Lawyers would list ways in which items of evidence could be added or subtracted to weaken or strengthen one's case. This formalistic system fell into disrepute as the Enlightenment principle of 'free proof' gained wide acceptance (Damaška, 1995). Concurrently, the development of probability theory brought forth a new approach to weighing evidence and making decisions under uncertainty. The early theorists of probability in the 17th and 18th century were as much interested in games of chance as they were interested in the uncertainty of trial decisions (Daston, 1988; Franklin, 2001; Hacking, 1975). Bernoulli (1713) was one of the first to formulate probabilistic rules for combining different pieces of evidence in legal cases and assessing to what extent they supported a claim of interest. He was also one of the first to suggest that decision rules at trial could be understood as probability thresholds.

Bernoulli's prescient insights attained greater popularity in the 20th century amidst the law and economics movement (Becker, 1968; Calabresi, 1961; Posner, 1973). In a seminal article, Finkelstein & Fairley (1970) gave one of the first systematic analyses of how probability theory, and Bayes' theorem in particular, can help to weigh evidence at trial. Lempert (1977) was one of the first to rely on probability theory, specifically likelihood ratios, for assessing the relevance of evidence. Such contributions fueled what has been called the New Evidence Scholarship, a rigorous way of studying the process of legal proof at trial (Lempert, 1986).

### 2.1.2 Skeptical voices and challenges

In response to such developments, Tribe (1971) attacked what he called ‘trial by mathematics’. His critique ranged from listing well-known cases of misuse or probabilities in legal contexts and practical difficulties in assessing the probability of someone’s criminal or civil liability to the dehumanization of trial decisions. After Tribe, many have criticized legal probabilism on a variety of grounds, both theoretical and practical, arguing that probabilistic models are either inadequate or unhelpful (Brilmayer, 1986; Dant, 1988, pp. @Allen1986A–Reconceptuali; Underwood, 1977, p. cohen86).

After the discovery of DNA fingerprinting in the eighties, many legal probabilists focused on how probability theory could be used to quantify the strength of a DNA match under various circumstances (Kaye, 1986, 2010; Koehler, 1996; National Research Council, 1992; Robertson & Vignaux, 1995).

Some legal scholars and practitioners have voiced their support for legal probabilism explicitly (Tillers & Gottfried, 2007). Yet skepticism about mathematical and quantitative models of legal evidence is still widespread among prominent legal scholars and practitioners (see, for example, Allen & Pardo, 2007). Even among legal probabilists, few would think it possible to quantify precisely the probability of someone’s guilt or civil liability. In response, Taroni, Biedermann, Bozza, Garbolino, & Aitken (2014) suggest that the probabilistic formalism ‘should primarily be considered as an aid to structure and guide one’s inferences under uncertainty, rather than a way to reach precise numerical assessments’ (p. xv).

Perhaps the most difficult conceptual challenge for legal probabilism—at least, one that has galvanized philosophical attention in recent years—comes from the paradoxes of legal proof or puzzles of naked statistical evidence. In a number of seminal papers, (Cohen, 1981; Nesson, 1979; Thomson, 1986) formulated scenarios in which, even if the probability of guilt or civil liability, based on the available evidence, is particularly high, a verdict against the defendant seems unwarranted.

Imagine you are a trier of fact in a legal proceeding in which the defendant’s guilt is identified as equivalent to a certain factual statement  $G$  and that somehow you succeeded in properly evaluating  $P(G|E)$ —the probability of  $G$  given the total evidence presented to you,  $E$ . One question that arises in such a situation is: when should you decide against the defendant? when is the evidence good enough? What we are after here is a condition  $\Psi$ , formulated in (primarily) probabilistic terms, such that the trier of fact, at least ideally, should accept any relevant claim  $A$  (including  $G$ ) just in case  $\Psi(A, E)$ . One straightforward attempt might be to say: convict if  $P(G|E)$  is above a certain threshold, otherwise acquit.

The difficulty about conjunction arises because intuitively there should be no difference between the trier’s acceptance of  $A$  and  $B$  separately, and her acceptance of their conjunction,  $A \wedge B$ , that is, that  $\Psi(A, E)$  and  $\Psi(B, E)$  just in case  $\Psi(A \wedge B, E)$ . If  $\Psi(H, E)$  just the threshold criterion, requiring that  $P(H|E)$  be sufficiently high,  $\Psi$  in general fails to satisfy this equivalence.

A variant of the gatecrasher paradox goes as follows. suppose our guilt threshold is high, say at 0.99. Consider the situation in which 1000 fans enter a football stadium, and 991 of them avoid paying for their tickets. A random spectator is tried for not paying. The probability that the spectator under trial did not pay exceeds 0.99. Yet, intuitively, a spectator cannot be considered liable on the sole basis of the number of people who did and did not pay.

Arguably, these scenarios underscore a theoretical difficulty with probabilistic accounts of legal standards of proof. Many articles have been written on the topic, initially by legal scholars. In the last decade, philosophers have also joined the debate. [For critical surveys see [Redmayne (2008); Gardiner (2018); pardo2019]] Crucially, even recent proposals to mend the situation on the part of the legal probabilist have failed (Urbaniak, 2019 contains a detailed analysis).

At least *prima facie*, then, it seems that some conditions other than high posterior probability of liability have to be satisfied for the decision to penalize (or find liable) to be justified. Accordingly, various informal notions have been claimed to be essential for a proper explication of judiciary decision standards (Haack, 2014; Wells, 1992). For instance, evidence is claimed to be insufficient for conviction if it is not *sensitive* to the issue at hand: if it remained the same even if the accused was innocent (Enoch & Fisher, 2015). Or, to look at another approach, evidence is claimed to be insufficient for conviction if it doesn’t *normically support* it: if—given the same evidence—no explanation would be needed even if the accused was innocent (Smith, 2017). A legal probabilist needs either to show that these notions are unnecessary or inadequate for the purpose at hand, or to indicate how they can be explicated in probabilistic terms.

### 2.1.3 The narrative approach


More recently, alternative frameworks for modeling evidential reasoning and decision-making at trial have been proposed. They are based on inference to the best explanation (Allen, 2010; Pardo & Allen, 2008), narratives and stories (Allen, 1986, 2010; Allen & Leiter, 2001; Clermont, 2015; Pardo, 2018; Pennington & Hastie, 1991a), and argumentation theory (Bex, 2011; Gordon, Prakken, & Walton, 2007; Walton, 2002). Those who favor a conciliatory stance have combined legal probabilism with other frameworks, offering preliminary sketches of hybrid theories (Urbaniak, 2018; Verheij, 2014).

Another important point of criticism of LP is that legal proceedings are back-and-forth between opposing parties in which cross-examination is of crucial importance, reasoning goes not only evidence-to-hypothesis, but also hypotheses-to-evidence (Allen & Pardo, 2007; Wells, 1992) in a way that seems analogous to inference to the best explanation (Dant, 1988), which notoriously is claimed to not be susceptible to probabilistic analysis (Lipton, 2004). An informal philosophical account inspired by such considerations—The **No Plausible Alternative Story (NPAS)** theory (Allen, 2010)—is that the courtroom is a confrontation of competing narrations (Ho, 2008; Wagenaar, Van Koppen, & Crombag, 1993) offered by the sides, and the narrative to be selected should be the most plausible one. The view is conceptually plausible (Di Bello, 2013), and finds support in psychological evidence (Pennington & Hastie, 1991b, 1992).

It would be a great advantage of legal probabilism if it could model phenomena captured by the narrative approach. But how is the legal probabilist to make sense of them? From her perspective, the key disadvantage of NPAS is that it abandons the rich toolbox of probabilistic methods and takes the key notion of plausibility to be a primitive notion which should be understood only intuitively.

### 2.1.4 Bayesian networks as a tool for legal probabilism

The idea that Bayesian networks can be used for probabilistic reasoning in legal fact-finding started gaining traction in late eighties (???) and early nineties (Edwards, 1991). Two recent books on the topic with an emphasis on legal applications are (Fenton & Neil, 2018) and (Taroni et al., 2014). A Bayesian network comprises two components: first, a directed acyclic graph of relations of dependence (represented by arrows) between variables (represented by nodes); second, conditional probability tables. Consider the graphical component first. The graph is acyclic because the arrows connecting the nodes do not form loops. As an illustration, let  $H$  be the claim that the suspect committed the murder,  $BT$  the presence of a blood type B match with a crime scene stain, and  $W$  the fact that an eyewitness observed the suspect near the scene around the time of the crime. The graphical component of the Bayesian network would look like this:



The *ancestors* of a node  $X$  are all those nodes from which we can reach  $X$  by following the arrows going forwards. The *parents* of a node  $X$  are those for which we can do this in one step. The *descendants* of  $X$  are all which can be reached from  $X$  by following the arrows going forward. The *children* are those for which we can do this in one step. In the example,  $H$  is the parent (and ancestor) of both  $W$  and  $BT$ , which are its children (and descendants). There are no non-parent ancestors or non-children descendants.

The variables, which are represented by nodes and are connected by arrows, stand in relation of probabilistic dependence. To describe these relations, the graphical model is accompanied by conditional probability tables. For parentless nodes such as  $H$ , the tables specify the prior probabilities of all their possible states. Assuming  $H$  stands for a binary random variable, with two possible states, the prior probabilities could be:

	Prior
H=murder	.01
H=no.murder	.99

The .01 figure for H=murder rests on the assumption that, absent any incriminating evidence, the defendant is unlikely to be guilty. For children nodes, the tables specify their conditional probability given combinations of their parents' states. If the variables are binary, an assignment of values for them could be:

	H=murder	H=no.murder
W=seen	.7	.4
W=not.seen	.3	.6

	H=murder	H=no.murder
BT=match	1	.063
BT=no.match	0	.937

According to the tables above, even if the defendant is not the culprit, the eyewitness testimony would still incriminate him with probability of .4, while the blood evidence with probability equal to only .063. The blood type frequency estimate is realistic (Lucy, 2013), and so are the conditional probabilities for the eyewitness identification. As expected, eyewitness testimony is assumed to be less trustworthy than blood match evidence [but for complications about assessing eyewitness testimony, see Wixted & Wells (2017); Urbaniak2020Decision].

The three probability tables above are all that is needed to define the probability distribution. The tables do not specify probabilistic dependencies between nodes that are not in a relation of child/parent, such as *BT* and *W*. Since there is no arrow between them, nodes *BT* and *W* are assumed to be independent conditional on *H*, that is,  $P(W|H) = P(W|H \wedge BT)$ . This fact represents, as part of the structure of the network, the independence between eyewitness testimony and blood evidence. A generalization of this fact is the so-called Markov condition. While the Bayesian network above—comprising a directed acyclic graph along with probability tables—is simple, a correct intuitive assessment of the probability of the hypothesis given the evidence is already challenging. Try to estimate intuitively the probability that the defendant committed the murder (H=murder) given the following states of the evidence:

- The suspect's blood type matches the crime stain but information about the witness is unavailable.
- The suspect's blood type matches the crime stain but the witness says they did not see the suspect near the crime scene.
- The suspect's blood type matches the crime stain and the witness says they saw the suspect near the crime scene.


Already at this level of complexity, calculations by hand become cumbersome. In contrast, software for Bayesian networks (see, for example, the **R** package **bnlearn** developed by Marco Scutari and described in Scutari & Denis, 2015) will easily give the following results:

	H=murder
BT=match,W=?	.138
BT=match,W=not.seen	.074
BT=match, W=seen	.219

Perhaps surprisingly the posterior probability of *H* is about .22 even when both pieces of evidence are incriminating (BT=match, W=seen).


Simple graphical patterns (called *idioms*) often recur while modeling the relationships between evidence and hypotheses. Complex graphical models can be created by combining these basic patterns in a modular way. Discussion of general methods for Bayesian network constructions can be found in (Neil, Fenton, & Nielson, 2000), (Hepler, Dawid, & Leucari, 2007) and general idioms are discussed in (Fenton, Neil, & Lagnado, 2013).

As an example, consider the *evidence idiom* is the most basic graphical representation of the relation between a hypothesis and a piece of evidence:



This directed graph suggests that the direction of influence—which could, but need not, be interpreted as causal influence—goes from hypothesis to evidence (though the probabilistic dependence goes both ways). The hypothesis node and the evidence node can be binary variables, such as 'The defendant was the source of the crime scene traces' (hypothesis) and 'The defendant genetically matches the crime traces' (evidence). But the variables need not be binary. The hypothesis node might take values from the range of 1 – 40, say the distance in meters from which the gun was shot, and the evidence node might be a continuous variable representing the density of gun shot residues (Taroni et al., 2014).

As an example of a more complex idiom, called the *evidence accuracy idiom*, consists of two arrows going into the evidence node [Bovens & Hartmann (2004); Friedman 1974]. One incoming arrow comes from the hypothesis node and the other from the accuracy node. This idiom can be used to model, say, an alcohol test:



The directions of the arrows indicate that the accuracy of the evidence (accuracy node) and the alcohol level (hypothesis node) influence the outcome of the test (evidence node). The graphical model represents different sources of uncertainty. The uncertainty associated with the sensitivity and specificity of the test—that is, the probability that the test reports excessive alcohol level when the level is excessive (sensitivity) and the probability that the test reports normal alcohol level when the level is normal (specificity)—is captured by the arrow going from the hypothesis node (Excess alcohol level) to the evidence node (Evidence for excess). Other sources of uncertainty comprise the possibility that the police officer lied about the test report or the possibility that the driver took medications which then affected the alcohol level. These possibilities can be taken into consideration by adding an accuracy node (or multiple accuracy nodes, if each factor is kept separate from the other).


## 2.2 Pioneering nature of the project

It is quite clear that BNs are a useful tool when it comes to piecemeal modeling and evaluation of scientific evidence in court. The question is, whether they can be useful for modeling whole cases and casting light on both the conceptual challenges that we already mention and for incorporating the points made by the representatives of other strains of research, most crucially, the NPAS.

Attempts have been made to use Bayesian networks to weigh and assess complex bodies of evidence consisting

Mention many others, add refs?

of multiple components. On one hand, we have serious reconstructions of real complex cases. Kadane & Schum (2011) made one the first attempts to model an entire criminal case, Sacco & Vanzetti from 1920, using probabilistic graphs. More recently, Fenton & Neil (2018) constructed a Bayesian network for the famous Sally Clark case:




The arrows depict relationships of influence between variables. Whether Sally Clark's sons, call them *A* and *B*, died by SIDS or murder (*A.cause* and *B.cause*) influences whether signs of disease (*A.disease* and *B.disease*) and bruising (*A.brushing* and *B.brushing*) were present. Since son *A* died first, whether *A* was murdered or died by SIDS (*A.cause*) influences how son *B* died (*B.cause*). How the sons died determines how many sons were murdered (*No.murdered*), and how many sons were murdered decides whether Sally Clark is guilty (*Guilty*).

According to the calculation by ?, the prior probability of *Guilty* = Yes should be .0789. After taking into account the incriminating evidence presented at trial, such as that there were signs of bruising but no signs of a preexisting disease affecting the children, the posterior probabilities are as follows:

Evidence (cumulative)	P( )Clark guilty)
A bruising	.2887
A no signs of disease	.3093
B bruising	.6913
B no signs of disease	.7019

The incriminating evidence, combined, brings the probability of guilt from .0789 to .7019. This is a significant increase, but not quite enough for a conviction. If one wishes to perform sensitivity analysis by modifying some of the probabilities, this can be easily done. During the appeal trial, new evidence was discovered, in particular, evidence that son *A* was affected by a disease. Once this evidence is taken into account, the probability of guilt drops to .00459 (and if signs of disease were also present on *B*, the guilt probability would drop even further to .0009). For a general discussion on how to elicit probabilities, see (Renooij, 2001) and (Gaag, Renooij, Witteman, Aleman, & Taal, 2013).

On the other hand, we have more general methodological reflection on the use of BNs for modeling whole cases. The main idea is that once all the pieces of evidence and claims are represented as nodes, one should use the *scenario idiom* to model complex hypotheses, consisting of a sequence of events organized in space and time: a scenario (Vlek, Prakken, Renooij, & Verheij, 2014). A graphical model that uses the scenario idiom would consist of the following components: first, nodes for the states and events in the scenario, with each node linked to the supporting evidence; second, a separate scenario node that has states and events as its children; finally, a node corresponding to the ultimate hypothesis as a child of the scenario node. The graphical model would look like this:



The scenario node unifies the different events and states.

Because of this unifying role, increasing the probability of one part of the scenario (say State/event 2) will also increase the probability of the other parts (State/event 1 and State/event 3). This is intended to capture the idea that the different components of a scenario form an interconnected sequence of events.<sup>1</sup>, Bex (2011), Bex (2015) and Verheij (2017). See also the survey by Di Bello & Verheij (2018). Dawid & Mortera (2018) give a treatment of scenarios in terms of Bayesian networks. Lacave & Di Bello (2018) and Verheij (2017) show how Bayesian Network can be used to construct explanations.

Some preliminary moves towards such an explication have been made in (Urbaniak, 2018). However, as (Neil, Fenton, Lagnado, & Gill, 2019) correctly points out that the paper fails to offer a convincing and operational means to structure and compare competing narratives.

Initial philosophical analysis of the approach has been performed, (Di Bello, 2013) pioneering a probabilistic understanding of narrations.

add more  
about  
Marcello

## 2.3 Choice of problem

## 2.4 Pioneering nature & impact

# 3 Concept and work plan

(general work plan, specific research goals, results of preliminary research, risk analysis);

## 4 Research methodology

(underlying scientific methodology, methods, techniques and research tools, methods of results analysis, equipment and devices to be used in research);

## References

Allen, R. J. (1986). A reconceptualization of civil trials. *Boston University Law Review*, 66, 401–437.

Allen, R. J. (2010). No plausible alternative to a plausible story of guilt as the rule of decision in criminal cases. In J. Cruz & L. Laudan (Eds.), *Prueba y esandares de prueba en el derecho*. Instituto de Investigaciones Filosóficas-UNAM.

<sup>1</sup> A discussion of modelling crime scenarios by means of graphical devices mixed with probabilities can be also found in the work of @shen2007ScenariodriveDecisionSupporta



- Allen, R. J., & Leiter, B. (2001). Naturalized epistemology and the law of evidence. *Virginia Law Review*, 87(8), 1491–1550. JSTOR.
- Allen, R., & Pardo, M. (2007). The problematic value of mathematical models of evidence. *The Journal of Legal Studies*, 36(1), 107–140. JSTOR.
- Becker, G. S. (1968). Crime and punishment: An economic approach. *Journal of Political Economy*, 76, 169–217. Springer.
- Bernoulli, J. (1713). *Ars conjectandi*.
- Bex, F. (2015). An integrated theory of causal stories and evidential arguments. In *Proceedings of the 15th International Conference on Artificial Intelligence and Law - ICAIL '15* (pp. 13–22). San Diego, California: ACM Press.
- Bex, F. J. (2011). *Arguments, stories and criminal evidence: A formal hybrid theory*. Law and philosophy library. Dordrecht ; New York: Springer.
- Bovens, L., & Hartmann, S. (2004). *Bayesian epistemology*. Oxford University Press.
- Brilmayer, L. (1986). Second-order evidence and bayesian logic. *Boston University Law Review*, 66, 673–691.
- Calabresi, G. (1961). Some thoughts on risk distribution and the law of torts. *Yale Law Journal*, 70, 499–553.
- Clermont, K. M. (2015). Trial by Traditional Probability, Relative Plausibility, or Belief Function? *Case Western Reserve Law Review*, 66(2), 353–391.
- Cohen, J. L. (1981). Subjective probability and the paradox of the Gatecrasher. *Arizona State Law Journal*, 627–634.
- Damaška, M. R. (1995). Free proof and its detractors. *The American Journal of Comparative Law*, 43(3), 343–357.
- Dant, M. (1988). Gambling on the truth: The use of purely statistical evidence as a basis for civil liability. *Columbia Journal of Law and Social Problems*, 22, 31–70. HeinOnline.
- Daston, L. (1988). *Classical probability in the enlightenment*. Princeton University Press.
- Dawid, A. P., & Mortera, J. (2018). Graphical models for forensic analysis. In *Handbook of graphical models* (pp. 491–514). CRC Press.
- Di Bello, M. (2013). *Statistics and probability in criminal trials* (PhD thesis). University of Stanford.
- Di Bello, M., & Verheij, B. (2018). Evidential reasoning. In *Handbook of legal reasoning and argumentation* (pp. 447–493). Springer.
- Edwards, W. (1991). Influence diagrams, bayesian imperialism, and the collins case: An appeal to reason. *Cardozo Law Review*, 13, 1025–1074.
- Enoch, D., & Fisher, T. (2015). Sense and sensitivity: Epistemic and instrumental approaches to statistical evidence. *Stan. L. Rev.*, 67, 557–611. HeinOnline.
- Fenton, N., & Neil, M. (2018). *Risk assessment and decision analysis with bayesian networks*. Chapman; Hall.
- Fenton, N., Neil, M., & Lagnado, D. A. (2013). A General Structure for Legal Arguments About Evidence Using Bayesian Networks. *Cognitive Science*, 37(1), 61–102.
- Finkelstein, M. O., & Fairley, W. B. (1970). A Bayesian approach to identification evidence. *Harvard Law Review*, 83(3), 489–517.
- Franklin, J. (2001). *The science of conjecture: Evidence and probability before pascal*. John Hopkins University Press.
- Gaag, L. C. van der, Renooij, S., Witteman, C. L. M., Aleman, B. M. P., & Taal, B. G. (2013). How to elicit many probabilities. Retrieved from <http://arxiv.org/abs/1301.6745>
- Gardiner, G. (2018). Legal burdens of proof and statistical evidence. In D. Coady & J. Chase (Eds.), *Routledge handbook of applied epistemology*. Routledge.
- Gordon, T. F., Prakken, H., & Walton, D. (2007). The Carneades model of argument and burden of proof. *Artificial Intelligence*, 171(10-15), 875–896.
- Haack, S. (2014). Legal probabilism: An epistemological dissent. In *Haack2014-HAAEMS* (pp. 47–77).
- Hacking, I. (1975). *The emergence of probability: A philosophical study of early ideas about probability, induction and statistical inference*. Cambridge University Press.
- Hepler, A. B., Dawid, A. P., & Leucari, V. (2007). Object-oriented graphical representations of complex patterns of evidence. *Law, Probability and Risk*, 6(1-4), 275–293.
- Ho, H. L. (2008). *A philosophy of evidence law: Justice in the search for truth*. Oxford University Press.

- Kadane, J. B., & Schum, D. A. (2011). *A probabilistic analysis of the sacco and vanzetti evidence*. John Wiley & Sons.
- Kaye, D. H. (1986). The admissibility of "probability evidence" in criminal trials—part I. *Jurimetrics Journal*, 343–346.
- Kaye, D. H. (2010). *The double helix and the law of evidence*. Harvard University Press.
- Koehler, J. J. (1996). On conveying the probative value of DNA evidence: Frequencies, likelihood ratios, and error rates. *University of Colorado law Review*, 67, 859–886.
- Lacave, C., & Ditzler, F. J. (2002). A review of explanation methods for Bayesian networks. *The Knowledge Engineering Review*, 17(2), 107–127.
- Lempert, R. O. (1977). Modeling relevance. *Michigan Law Review*, 75, 1021–1057. JSTOR.
- Lempert, R. O. (1986). The new evidence scholarship: Analysing the process of proof. *Boston University Law Review*, 66, 439–477.
- Lipton, P. (2004). *Inference to the best explanation*. Routledge/Taylor; Francis Group.
- Lucy, D. (2013). *Introduction to statistics for forensic scientists*. John Wiley & Sons.
- National Research Council. (1992). *DNA technology in forensic science* [NRC I]. Committee on DNA technology in Forensic Science, National Research Council.
- Neil, M., Fenton, N., Lagnado, D., & Gill, R. D. (2019). Modelling competing legal arguments using bayesian model comparison and averaging. *Artificial Intelligence and Law*. Retrieved from <https://doi.org/10.1007/s10506-019-09250-3>
- Neil, M., Fenton, N., & Nielson, L. (2000). Building large-scale Bayesian Networks. *The Knowledge Engineering Review*, 15(3), 257–284.
- Nesson, C. R. (1979). Reasonable doubt and permissive inferences: The value of complexity. *Harvard Law Review*, 92(6), 1187–1225.
- Pardo, M. S. (2018). Safety vs. Sensitivity: Possible worlds and the law of evidence. *Legal Theory*, 24(1), 50–75.
- Pardo, M. S., & Allen, R. J. (2008). Judicial proof and the best explanation. *Law and Philosophy*, 27(3), 223–268.
- Pennington, N., & Hastie, R. (1991a). A cognitive theory of juror decision making: The story model. *Cardozo Law Review*, 13, 519–557.
- Pennington, N., & Hastie, R. (1991b). A cognitive theory of juror decision making: The story model. *Cardozo Law Review*, 13, 519–557. HeinOnline.
- Pennington, N., & Hastie, R. (1992). Explaining the evidence: Tests of the story model for juror decision making. *Journal of personality and social psychology*, 62(2), 189–204. American Psychological Association.
- Posner, R. (1973). *The economic analysis of law*. Brown & Company.
- Redmayne, M. (2008). Exploring the proof paradoxes. *Legal Theory*, 14(4), 281–309. Cambridge University Press.
- Renooij, S. (2001). Probability elicitation for belief networks: Issues to consider. *The Knowledge Engineering Review*, 16(3), 255–269.
- Robertson, B., & Vignaux, G. A. (1995). DNA evidence: Wrong answers or wrong questions? *Genetica*, 96, 145–152.
- Scutari, M., & Denis, J.-B. (2015). *Bayesian networks in R*. CRC Press.
- Smith, M. (2017). When does evidence suffice for conviction? *Mind*.
- Taroni, F., Biedermann, A., Bozza, S., Garbolino, P., & Aitken, C. (2014). *Bayesian networks for probabilistic inference and decision analysis in forensic science* (2nd ed.). John Wiley & Sons.
- Thomson, J. J. (1986). Liability and individualized evidence. *Law and Contemporary Problems*, 49(3), 199–219.
- Tillers, P., & Gottfried, J. (2007). Case comment—United States v. Copeland, 369 F. Supp. 2d 275 (E.D.N.Y. 2005): A collateral attack on the legal maxim that proof beyond a reasonable doubt is unquantifiable? *Law, Probability and Risk*, 5(2), 135–157.
- Tribe, L. H. (1971). Trial by mathematics: Precision and ritual in the legal process. *Harvard Law Review*, 84(6), 1329–1393.
- Underwood, B. D. (1977). The thumb on the scale of justice: Burdens of persuasion in criminal cases. *Yale Law Journal*, 86(7), 1299–1348.

- Urbaniak, R. (2018). Narration in judiciary fact-finding: A probabilistic explication. *Artificial Intelligence and Law*, 1–32.
- Urbaniak, R. (2019). Probabilistic legal decision standards still fail. *Journal of Applied Logics*, 6(5).
- van Eemeren, F., & Verheij, B. (2017). Argumentation theory in formal and computational perspective. *IFCoLog Journal of Logics and Their Applications*, 4(8), 2099–2181.
- Verheij, B. (2014). To catch a thief with and without numbers: Arguments, scenarios and probabilities in evidential reasoning. *Law, Probability and Risk*, 13(3–4), 307–325. Citeseer.
- Verheij, B. (2017). Proof with and without probabilities. Correct evidential reasoning with presumptive arguments, coherent hypotheses and degrees of uncertainty. *Artificial Intelligence and Law*, 1–28. Springer.
- Vlek, C., Prakken, H., Renooij, S., & Verheij, B. (2014). Building bayesian networks for legal evidence with narratives: A case study evaluation. *Artificial Intelligence and Law*, 22, 375–421. Springer.
- Wagenaar, W., Van Koppen, P., & Crombag, H. (1993). *Anchored narratives: The psychology of criminal evidence*. St Martin's Press.
- Walton, D. N. (2002). *Legal argumentation and evidence*. Penn State University Press.
- Wells, G. (1992). Naked statistical evidence of liability: Is subjective probability enough? *Journal of Personality and Social Psychology*, 62(5), 739–752. American Psychological Association.
- Wigmore, J. H. (1901). Required numbers of witnesses; a brief history of the numerical system in england. *Harvard Law Review*, 15(2), 83–108.
- Wixted, J. T., & Wells, G. L. (2017). The Relationship Between Eyewitness Confidence and Identification Accuracy: A New Synthesis. *Psychological Science in the Public Interest*, 18(1), 10–65.