CY7C1049D

4-Mbit (512 K × 8) Static RAM

Features

- Pin- and function-compatible with CY7C1049B
- High speed
  - t_{AA} = 10 ns
- Low active power
  - I_{CC} = 90 mA at 10 ns
- Low CMOS Standby power
  - I_{SB2} = 10 mA
- 2.0 V data retention
- Automatic power-down when deselected
- TTL-compatible inputs and outputs
- Easy memory expansion with $\overline{CE}$ and $\overline{OE}$ features
- Available in Pb-free 36-Pin (400-Mil) Molded SOJ package

Functional Description[1]

The CY7C1049D is a high-performance CMOS static RAM organized as 512K words by 8 bits. Easy memory expansion is provided by an active LOW Chip Enable ($\overline{CE}$), an active LOW Output Enable ($\overline{OE}$), and tri-state drivers. Writing to the device is accomplished by taking Chip Enable ($\overline{CE}$) and Write Enable ($\overline{WE}$) inputs LOW. Data on the eight I/O pins (I/O_0 through I/O_7) is then written into the location specified on the address pins (A_0 through A_{18}).

Reading from the device is accomplished by taking Chip Enable ($\overline{CE}$) and Output Enable ($\overline{OE}$) LOW while forcing Write Enable ($\overline{WE}$) HIGH. Under these conditions, the contents of the memory location specified by the address pins will appear on the I/O pins.

The eight input/output pins (I/O_0 through I/O_7) are placed in a high-impedance state when the device is deselected ($\overline{CE}$ HIGH), the outputs are disabled ($\overline{OE}$ HIGH), or during a write operation ($\overline{CE}$ LOW, and $\overline{WE}$ LOW).

The CY7C1049D is available in a standard 400-mil-wide 36-pin SOJ package with center power and ground (revolutionary) pinout.

Logic Block Diagram



Selection Guide

	–10	Unit
Maximum access time	10	ns
Maximum operating current	90	mA
Maximum CMOS standby current	10	mA

Note

1. For guidelines on SRAM system design, refer to the 'System Design Guidelines' Cypress application note, available on the internet at www.cypress.com.

Contents

Pin Configuration

SOJ
Top View



Maximum Ratings

Exceeding maximum ratings may shorten the useful life of the device. User guidelines are not tested.

Storage Temperature ..... –65°C to +150°C

Ambient Temperature with Power Applied ..... –55°C to +125°C

Supply Voltage on V_{CC} to Relative GND[2] ...–0.5 V to +6.0 V

DC Voltage Applied to Outputs in High Z State[2] ..... –0.5 V to V_{CC} + 0.5 V

DC Input Voltage[2] ..... –0.5 V to V_{CC} + 0.5 V

Current into Outputs (LOW)..... 20 mA

Static Discharge Voltage..... >2001 V (per MIL-STD-883, Method 3015)

Latch-Up Current..... >200 mA

Operating Range

Range	Ambient Temperature	V_{CC}
Industrial	–40°C to +85°C	4.5 V–5.5 V

Electrical Characteristics Over the Operating Range

Parameter	Description	Test Conditions		–10		Unit
				Min.	Max.	
V_{OH}	Output HIGH Voltage	V_{CC} = Min., I_{OH} = –4.0 mA		2.4	–	V
V_{OL}	Output LOW Voltage	V_{CC} = Min., I_{OL} = 8.0 mA		–	0.4	V
V_{IH}[2]	Input HIGH Voltage			2.0	V_{CC}+ 0.5	V
V_{IL}[2]	Input LOW Voltage[2]			–0.5	0.8	V
I_{IX}	Input Leakage Current	GND < V_I < V_{CC}		–1	+1	µA
I_{OZ}	Output Leakage Current	GND < V_{OUT} < V_{CC}, Output Disabled		–1	+1	µA
I_{CC}	VCC Operating Supply Current	V_{CC} = Max., f = f_{MAX} = $1/t_{RC}$	100 MHz	–	90	mA
				–		
			83 MHz	–	80	mA
				–		
			66 MHz	–	70	mA
				–		
			40 MHz	–	60	mA
				–		
I_{SB1}	Automatic CE Power-Down Current —TTL Inputs	Max. V_{CC}, CE > V_{IH}, V_{IN} > V_{IH} or V_{IN} < V_{IL}, f = f_{MAX}		–	20	mA
I_{SB2}	Automatic CE Power-Down Current —CMOS Inputs	Max. V_{CC}, CE > V_{CC} – 0.3 V, V_{IN} > V_{CC} – 0.3 V, or V_{IN} < 0.3 V, f = 0		–	10	mA

Capacitance[3]

Parameter	Description	Test Conditions	Max.	Unit
C_{IN}	Input capacitance	T_A = 25°C, f = 1 MHz, V_{CC} = 5.0 V	8	pF
C_{OUT}	I/O capacitance		8	pF

Thermal Resistance[3]

Parameter	Description	Test Conditions	SOJ Package	Unit
Θ_{JA}	Thermal resistance (Junction to Ambient)[3]	Still Air, soldered on a 3 × 4.5 inch, four-layer printed circuit board	57.91	°C/W
Θ_{JC}	Thermal resistance (Junction to Case)[3]		36.73	°C/W

AC Test Loads and Waveforms[4]



Notes
2. Minimum voltage is –2.0 V and V_{IH}(max) = V_{CC} + 2 V for pulse durations of less than 20 ns.
3. Tested initially and after any design or process changes that may affect these parameters.

Switching Characteristics[5] Over the Operating Range

Parameter	Description	-10		Unit
		Min.	Max.	
Read Cycle				
t_{power}	V_{CC}(typical) to the First Access[6]	100	–	µs
t_{RC}	Read Cycle Time	10	–	ns
t_{AA}	Address to Data Valid	–	10	ns
t_{OHA}	Data Hold from Address Change	3	–	ns
t_{ACE}	$\overline{CE}$ LOW to Data Valid	–	10	ns
t_{DOE}	$\overline{OE}$ LOW to Data Valid	–	5	ns
t_{LZOE}	$\overline{OE}$ LOW to Low Z[8]	0	–	ns
t_{HZOE}	$\overline{OE}$ HIGH to High Z[7, 8]	–	5	ns
t_{LZCE}	$\overline{CE}$ LOW to Low Z[8]	3	–	ns
t_{HZCE}	$\overline{CE}$ HIGH to High Z[7, 8]	–	5	ns
t_{PU}	$\overline{CE}$ LOW to Power-Up	0	–	ns
t_{PD}	$\overline{CE}$ HIGH to Power-Down	–	10	ns
Write Cycle[9, 10]				
t_{WC}	Write Cycle Time	10	–	ns
t_{SCE}	$\overline{CE}$ LOW to Write End	7	–	ns
t_{AW}	Address Set-Up to Write End	7	–	ns
t_{HA}	Address Hold from Write End	0	–	ns
t_{SA}	Address Set-Up to Write Start	0	–	ns
t_{PWE}	$\overline{WE}$ Pulse Width	7	–	ns
t_{SD}	Data Set-Up to Write End	6	–	ns
t_{HD}	Data Hold from Write End	0	–	ns
t_{LZWE}	$\overline{WE}$ HIGH to Low Z[8]	3	–	ns
t_{HZWE}	$\overline{WE}$ LOW to High Z[7, 8]	–	5	ns

Data Retention Characteristics Over the Operating Range

Parameter	Description	Conditions[12]	Min.	Max	Unit
V_{DR}	V_{CC} for Data Retention		2.0	–	V
I_{CCDR}	Data Retention Current	$\underline{V_{CC}} = V_{DR} = 2.0$ V, $\overline{CE} \geq V_{CC} - 0.3$ V, $V_{IN} \geq V_{CC} - 0.3$ V or $V_{IN} \leq 0.3$ V	–	10	mA
t_{CDR}[3]	Chip Deselect to Data Retention Time		0	–	ns
t_R[11]	Operation Recovery Time		t_{RC}	–	ns

Notes

4. AC characteristics (except High-Z) for 10-ns parts are tested using the load conditions shown in Figure (a). High-Z characteristics are tested for all speeds using the test load shown in Figure (c)
5. Test conditions assume signal transition time of 3 ns or less, timing reference levels of 1.5 V, input pulse levels of 0 to 3.0 V, and output loading of the specified I_{OL}/I_{OH} and 30-pF load capacitance.
6. t_{POWER} gives the minimum amount of time that the power supply should be at typical V_{CC} values until the first memory access can be performed.
7. t_{HZOE}, t_{HZCE}, and t_{HZWE} are specified with a load capacitance of 5 pF as in part (c) of AC Test Loads. Transition is measured when the outputs enter a high impedance state.
8. At any given temperature and voltage condition, t_{HZCE} is less than t_{LZCE}, t_{HZOE} is less than t_{LZOE}, and t_{HZWE} is less than t_{LZWE} for any given device.
9. The internal write time of the memory is defined by the overlap of CE LOW, and WE LOW. CE and WE must be LOW to initiate a write, and the transition of either of these signals can terminate the write. The input data set-up and hold timing should be referenced to the leading edge of the signal that terminates the write.
10. The minimum write cycle time for Write Cycle no. 3 ($\overline{WE}$ controlled, $\overline{OE}$ LOW) is the sum of t_{HZWE} and t_{SD}.

Data Retention Waveform



Switching Waveforms

Figure 1. Read Cycle No. 1[13, 14]



Notes
11. Full device operation requires linear V_{CC} ramp from V_{DR} to $V_{CC(min.)} \geq 50$ µs or stable at $V_{CC(min.)} \geq 50$ µs
12. No input may exceed V_{CC} + 0.5 V.
13. Device is continuously selected. $\overline{OE}$, $\overline{CE} = V_{IL}$.
14. $\overline{WE}$ is HIGH for read cycle.

Switching Waveforms(continued)

Figure 2. Read Cycle No. 2 ($\overline{OE}$ Controlled)[14, 15]



Figure 3. Write Cycle No. 1 ($\overline{CE}$ Controlled)[16, 17]



Notes
15. Address valid prior to or coincident with $\overline{CE}$ transition LOW.
16. Data I/O is high impedance if $\overline{OE}$ = V_{IH}.
17. If $\overline{CE}$ goes HIGH simultaneously with $\overline{WE}$ going HIGH, the output remains in a high-impedance state.

Switching Waveforms(continued)

Figure 4. Write Cycle No. 2 ($\overline{WE}$ Controlled, $\overline{OE}$ HIGH During Write)[16, 17]



Figure 5. Write Cycle No. 3 ($\overline{WE}$ Controlled, $\overline{OE}$ LOW)[17]



Truth Table

$\overline{CE}$	$\overline{OE}$	$\overline{WE}$	I/O_0–I/O_7	Mode	Power
H	X	X	High-Z	Power-down	Standby (I_{SB})
L	L	H	Data Out	Read	Active (I_{CC})
L	X	L	Data In	Write	Active (I_{CC})
L	H	H	High-Z	Selected, Outputs Disabled	Active (I_{CC})

Ordering Information

Speed (ns)	Ordering Code	Package Diagram	Package Type	Operating Range
10	CY7C1049D-10VXI	51-85090	36-Lead (400-Mil) Molded SOJ (Pb-free)	Industrial

Ordering Code Definitions



Please contact your local Cypress sales representative for availability of these parts.

Note
18. During this period the I/Os are in the output state and input signals should not be applied.

Package Diagram

Figure 6. 36-Pin (400-Mil) Molded SOJ (51-85090)



Acronyms

Acronym	Description
CE	chip enable
CMOS	Complementary metal oxide semiconductor
I/O	Input/output
OE	output enable
SRAM	Static random access memory
SOJ	Small Outline J-Lead
TSOP	Thin Small Outline Package
VFBGA	Very Fine-Pitch Ball Grid Array

Document Conventions

Units of Measure

Symbol	Unit of Measure
ns	nano seconds
V	Volts
µA	micro Amperes
mA	milli Amperes
mV	milli Volts
mW	milli Watts
MHz	Mega Hertz
pF	pico Farad
°C	degree Celcius
W	Watts

Document History Page

Document Title: CY7C1049D 4-Mbit (512K x 8) Static RAM Document Number: 38-05474				
Revision	**ECN**	**Orig. of Change**	**Submission Date**	**Description of Change**
**	201560	SWI	See ECN	Advance Datasheet for C9 IPP
*A	233729	RKF	See ECN	1.AC, DC parameters are modified as per EROS(Spec # 01-2165) 2.Pb-free offering in the 'ordering information'
*B	351096	PCI	See ECN	Changed from Advance to Preliminary Removed 17, 20 ns Speed bin Added footnote # 4 Redefined I_{CC} values for Com'l and Ind'l temperature ranges I_{CC} (Com'l): Changed from 67 and 54 mA to 75 and 70 mA for 12 and 15 ns speed bins respectively I_{CC} (Ind'l): Changed from 80, 67 and 54 mA to 90, 85 and 80 mA for 10, 12 and 15 ns speed bins respectively Added $V_{IH(max)}$ spec in Note# 2 Modified Note# 10 on t_R Changed t_{SCE} from 8 to 7 ns for 10 ns speed bin Changed reference voltage level for measurement of Hi-Z parameters from ±500 mV to ±200 mV Added Truth Table on page# 6 Removed L-Version Added 10 ns parts in the Ordering Information Table Added Lead-Free Product Information Shaded Ordering Information Table
*C	446328	NXR	See ECN	Converted from Preliminary to Final Removed -12 and -15 speed bins Removed Commercial Operating Range product information Changed Maximum Rating for supply voltage from 7 V to 6 V Updated Thermal Resistance table Changed t_{HZWE} from 6 ns to 5 ns Updated footnote #7 on High-Z parameter measurement Replaced Package Name column with Package Diagram in the Ordering Information table
*D	3109184	AJU	12/13/2010	Added Ordering Code Definitions. Updated Package Diagram.
*E	3235742	PRAS	04/20/2011	Updated template. Added Acronyms and Units of measure.

Sales, Solutions, and Legal Information

Worldwide Sales and Design Support

Cypress maintains a worldwide network of offices, solution centers, manufacturer's representatives, and distributors. To find the office closest to you, visit us at Cypress Locations.

Products

Automotive	cypress.com/go/automotive
Clocks & Buffers	cypress.com/go/clocks
Interface	cypress.com/go/interface
Lighting & Power Control	cypress.com/go/powerpsoc cypress.com/go/plc
Memory	cypress.com/go/memory
Optical & Image Sensing	cypress.com/go/image
PSoC	cypress.com/go/psoc
Touch Sensing	cypress.com/go/touch
USB Controllers	cypress.com/go/USB
Wireless/RF	cypress.com/go/wireless

PSoC Solutions

psoc.cypress.com/solutions

PSoC 1 | PSoC 3 | PSoC 5