

Package ‘eat’

December 9, 2011

Type Package

Title eat

Version 1.2.0

Depends R(>= 2.13.2), sendmailR, gdata, xlsx, car, reshape, foreign,date

Date 2011-12-09

Author ZKD <zkdaemon-discuss@googlegroups.com>

Maintainer ZKD <zkdaemon-discuss@googlegroups.com>

Description create and run models

License GPL 3

LazyLoad yes

LazyData yes

R topics documented:

eat-package	2
aggregateData	2
automateConquestModel	4
automateDataPreparation	6
automateModels	8
bi.linking	10
checkData	11
checkInput	12
collapseMissings	13
crop	14
get.dsc	14
get.itn	15
get.plausible	15
get.shw	16
get.wle	17
inputDat	18
inputList	18
loadSav	20
long2matrix	21

makeCodebookInput	23
makeInputLists	23
makeNumeric	24
mergeData	25
prepare.package	26
readDaemonXlsx	26
recodeData	27
reinsort.col	28
source.it.all	29
source.it.all2	29
sunk	30
writeSpss	31

Index	33
--------------	-----------

eat-package	<i>eat-package</i>
-------------	--------------------

Description

More about what it does (maybe more than one line) ~~ A concise (1-5 lines) description of the package ~~

Details

Package:	eat
Type:	Package
Version:	1.0
Date:	2011-10-20
License:	What license is it under?
LazyLoad:	yes

~~ An overview of how to use the package, including the most important functions ~~

Author(s)

Who wrote it
Maintainer: Who to complain to <yourfault@somewhere.net> ~~ The author and/or maintainer of the package ~~

References

~~ Literature or other references for background information ~~

aggregateData	<i>Aggregate Datasets with Missing Values</i>
---------------	---

Description

Aggregates datasets with constraints on missing values

Usage

```
aggregateData(dat, subunits, units, aggregatemissings = "use.default", rename = FALSE, recodedData
```

Arguments

<code>dat</code>	A data frame.
<code>subunits</code>	A data frame with subunit information. See 'Details'.
<code>units</code>	A data frame with unit information. See 'Details'.
<code>aggregatemissings</code>	Either the character string "use.default" or a $n \times n$ matrix with information on how missing values should be aggregated. See 'Details'.
<code>rename</code>	Should units with only one subunit be renamed to their unit name? Default is FALSE.
<code>recodedData</code>	Logical indicating whether colnames in dataset to aggregate are the subunit names (as in <code>subunits\$subunit</code>) or recoded subunit names (as in <code>subunits\$subunitRecoded</code>). Default is TRUE, meaning that colnames are recoded subitem names.

Details

`aggregateData` aggregates units in data frames with special consideration of missing values. The aggregation of missing values is specified in argument `aggregatemissings`.

The results of `aggregateData` will be written to a protocol file with sunk.

Examples of data frames `subunits` and `units` can be found via `data(inputList)`.

Value

A data frame with aggregated units and, if `rename = TRUE`, renamed subunits.

Warning

Missings are only correctly aggregated if their values correspond to the values given in `aggregatemissings`. `aggregateData` does not check for value types or whether codes are valid. Use of `checkData` and `recodeData` before using `aggregateData` is therefore strongly recommended.

Author(s)

Nicole Haag, Anna Lenski

References

For missing types see <http://code.google.com/p/zkdlb/wiki/MissingHandling>

See Also

[recodeData](#), [checkData](#)

Examples

```
data(inputDat)
data(inputList)

dat1 <- inputDat[[1]] # get first dataset from inputDat
datRec <- recodeData(dat1, inputList$values, inputList$subunits) # recode Data first
datAggr <- aggregateData(datRec, inputList$subunits, inputList$units, rename = TRUE, recodedData = TRUE)
```

```
automateConquestModel automateConquestModel
```

Description

Wrapper function which calls several functions to build and write Conquest input files.

Usage

```
automateConquestModel(dataset, ID, regression=NULL, DIF=NULL, group.var=NULL, weight=NULL, testitems=NULL, na=NULL, item.grouping=NULL, person.grouping=NULL)
```

Arguments

dataset	data.frame containing all variables necessary for analysis
ID	name or column number of 'id' variable
regression	character vector with names or integer vector with column numbers of one or more 'context' variables (e.g. sex, school , ...)
DIF	character string with name or scalar with column number of only one variable denominating groups for which analysis of differential item functioning is to be done (e.g. sex, class , ...)
group.var	character vector with names or integer vector with column numbers of one or more 'group' variables (e.g. sex, school , ...)
weight	character string with name or scalar with column number of only one 'weighting' variable
testitems	character vector with names or integer vector with column numbers of 'item' variables (e.g. sex, school , ...)
na	List of numerical vector including numbers to be considered as 'sysmis'. Specific missing codes can be defined for each type of variable, e.g. testitems, DIF variables, ...
item.grouping	data.frame with grouping information of items, first column must be 'item' which includes item names, further columns contain scale definitions, 0 indicates that the respective item is NOT part of the scale, 1 indicates that this item is part of the scale, colnames of columns are the names of the scales
person.grouping	data.frame with grouping information of persons, first column must be the name of 'id' (e.g. idstud), further columns contain group definitions, 0 indicates that the respective person is NOT part of the group, 1 indicates that this person is part of the group, colnames of columns are the names of the groups

model.statement	character string which appears in Conquest Syntax as model statement. Set to item by default. When DIF variable is specified, statement is set to item - [name of DIF variable] + item*[name of DIF variable] by default. However, user's specification of model.statement overwrites default in each case.
m.model	character string specifying the IRT model used for analysis. At the time, only "1PL" is available.
Title	optional: character string with title of analysis which appears in Conquest Syntax. If no title is specified, informations about computer and user name and R version are printed in Conquest Syntax.
jobName	character string specifying name of analysis. All Conquest input and output files will named by jobName and their corresponding suffixes.
jobFolder	character string specifying the folder where all analysis files will be generated, for example "C:/programme/analysis"
subFolder	optional: List of character strings specifying maximal 2 optional subfolders relative to jobFolder for the data and the output files. Character strings must be named with data and out, for example subFolder=list(data=" ../../dataset/analysis1", out=" ../../output/analysis1") Double dots .. indicates to move one level above in folder structure. For example, if jobFolder is "C:/programme/analysis" and subFolder is list(data=" ../dataset/analysis1", out=" ../output/analysis1"), dataset is written to "C:/programme/dataset/analysis1" and output is written to "C:/output/analysis1". When subFolder\$data == NULL, dataset is written to the folder specified by jobFolder. Same is true for subFolder\$out == NULL.
dataName	optional: character string specifying name of dataset if intend to differ from name specified by jobName. When dataName == NULL, dataset is named [jobName].dat
anchor	optional: data frame with anchor parameters. First column of anchor refers to item name, second columns refers to parameter used as reference for anchoring.
pathConquest	character string with path and name of Conquest console, for example "c:/programme/conquest/co
method	optional: character string with method for analysis. Possible options are "gauss" (default), "quadrature", "montecarlo". See Conquest manual, pp.225.
std.err	optional: character string specifying types of standard errors to be estimated. Possible options are "full", "quick" (default), "none". See Conquest manual, pp.167.
distribution	optional: character string with a priori trait distribution. Possible options are "normal" (default), "discrete". See Conquest manual, pp.167.
n.plausible	optional: integer scalar specifying numbers of plausible values to draw. Default is 5.
set.constraints	optional: character string specifying the constraints of the scale. Possible options are "cases" (default), "items", "none". When anchor parameter are specified in anchor, constraints will set to "none" in each case.
nodes	optional: integer scalar specifying numbers of nodes in analysis. Default is 15.
p.nodes	optional: integer scalar specifying numbers of p nodes in analysis. Sets the number of nodes that are used in the approximation of the posterior distributions, which are used in the drawing of plausible values and in the calculation of EAP estimates. The default is 2000.

f.nodes	optional: integer scalar specifying numbers of f nodes in analysis. Sets the number of nodes that are used in the approximation of the posterior distributions in the calculation of fit statistics. The default is 2000.
n.iterations	optional integer scalar. Sets the maximum number of iterations for which estimation will proceed without improvement in the deviance. The minimum value permitted is 5. The default value is 20.
converge	optional scalar. Instructs estimation to terminate when the largest change in any parameter estimate between successive iterations of the EM algorithm is less than converge. The default value is 0.0001.
deviancechange	optional scalar. Instructs estimation to terminate when the change in the deviance between successive iterations of the EM algorithm is less than deviancechange. The default value is 0.0001.
name.unidim	optional: character string with name of one latent dimension, if not specified in labels.
equivalence.table	optional: character string specifying type of equivalence table to print. Possible options are "wle" (default), "mle" or NULL.
use.letters	logical: Should values coded als letters? May be relevant only in partial credit models comprising items with more than 10 categories to avoid columns with width 2 in Conquest.

Value

No results are returned to console. Input files and batch string are written to disk in specified folder(s).

Author(s)

Sebastian Weirich, Karoline Sachse, Martin Hecht

automateDataPreparation
automateDataPreparation

Description

prepare datasets for [automateModels](#)

Usage

```
automateDataPreparation( inputDat = NULL, inputList, path = NULL, loadSav,
  checkData, mergeData, recodeData, aggregateData, scoreData, writeSpss,
  filedat = "zkddata.txt", filesps = "readZkdData.sps",
  aggregatemissings = "use.default", rename = TRUE, recodedData = TRUE,
  correctDigits=FALSE, truncateSpaceChar = TRUE, newID = NULL, oldIDs = NULL,
  missing.rule = list(mvi=0, mnr=0, mci=0, mbd=NA, mir=0, mbi=0))
```

Arguments

inputDat	A list of data frames if no .sav files shall be read in.
inputList	A list of data frames containing additional information (see Details).
path	A character string containing the path where the logfolder will be created. Also required by loadSav (source of SPSS files) and writeSpss . Default is the current R working directory.
loadSav	logical (whether function loadSav shall be called).
checkData	logical (whether function checkData shall be called).
mergeData	logical (whether function mergeData shall be called).
recodeData	logical (whether function recodeData shall be called for subunits).
aggregateData	logical (whether function aggregateData shall be called).
scoreData	logical (whether function recodeData shall be called for units).
writeSpss	logical (whether function writeSpss shall be called).
filedat	A character string with the name of the output data file required by writeSpss .
filesps	A character string with the name of the output syntax file required by writeSpss .
missing.rule	A list containing recode information for character missings required by writeSpss . See 'References' for description of default values.
aggregatemissings	A character string. Either "use.default" or "seeInputList", if pattern was specified in inputList\$aggrMiss.
rename	logical. See aggregateData .
recodedData	logical. See aggregateData .
correctDigits	logical. See loadSav .
truncateSpaceChar	logical. See loadSav .
newID	A character string containing the case IDs name in the final data frame. Default is "ID" or a character string specified in inputList sheet 6 (see readDaemonXlsx).
oldIDs	A vector of character strings containing the IDs names in the original datasets. Default is as specified in inputList\$savFiles.

Details

inputList is a list of data frames. It can be created either by ZKDaemon via [readDaemonXlsx](#) or by [makeInputLists](#). Compulsory: units, subunits, values. Optional: unitRecodings, savFiles, newID, aggregateMissings.

Value

A single data frame in last transformation status.

Author(s)

Karoline Sachse

References

<http://code.google.com/p/zkdlb/wiki/MissingHandling>

Examples

```
inpList <- inputList
inpDat <- inputDat
test <- automateDataPreparation (inputList=inpList, inputDat = inpDat,
  path = "c:/temp/test_eat", loadSav = FALSE, checkData=TRUE,
  mergeData = TRUE, recodeData=TRUE, aggregateData=TRUE, scoreData= TRUE,
  writeSpss=TRUE)
```

automateModels

automateModels

Description

specify and run several ConQuest models

Usage

```
automateModels(dataset, id = NULL, context.vars = NULL, items = NULL, item.grouping = NULL,
  select.item.group = NULL, person.grouping.vars = NULL, person.grouping.vars.include.all = FALSE,
  person.grouping = NULL, select.person.group = NULL, additional.item.props = NULL, folder,
  overwrite.folder = TRUE, analyse.name.prefix = NULL, analyse.name = NULL, analyse.name.elements
  data.name = NULL, m.model = NULL, software = NULL, dif = NULL, weight = NULL, anchor = NULL,
  regression = NULL, adjust.for.regression = FALSE, missing.rule = NULL, cross = NULL, subfolder.c
  subfolder.mode = NULL, additionalSubFolder = NULL, run.mode = NULL, n.batches = NULL, run.timeou
  run.status.refresh = 0.2, email = NULL, smtpServer = NULL, write.txt.dataset = FALSE, delete.fol
  conquestParameters = NULL )
```

Arguments

dataset	data.frame containing all variables type of variables ("id" , "context.vars" or "items") must be set using options id, context.vars, items
id	name or column number of 'id' variable in dataset
context.vars	names or column numbers of 'context' variables (e.g. sex, school , ...) in dataset
items	names or column numbers of 'item' variables in dataset if omitted, all variables that are not classified as 'id' or 'context' variables are treated as 'items'
item.grouping	data.frame with grouping information of items, first column must be 'item' which includes item names, further columns contain scale definitions, 0 indicates that the respective item is NOT part of the scale, 1 indicates that this item is part of the scale, colnames of columns are the names of the scales
select.item.group	character vector of scale names chosen for analysis
person.grouping.vars	character vector of 'context' variables in dataset which are used to automatically generate 'person.grouping', each category is transformed into the 'person.grouping' format
person.grouping.vars.include.all	logical vector (along person.grouping.vars), indicates whether to generate a variable 'all' for the specific variable

person.grouping	data.frame with grouping information of persons, first column must be the name of 'id' (e.g. idstud), further columns contain group definitions, 0 indicates that the respective person is NOT part of the group, 1 indicates that this person is part of the group, colnames of columns are the names of the groups
select.person.group	character vector of group names chosen for analysis
additional.item.props	data.frame of additional item information to be merged to model results, first column must be 'item' and contain item names
folder	folder to write output into
overwrite.folder	logical, if TRUE (default), folder is completely emptied
analyse.name.prefix	prefix (e.g. "pilotStudy") to be attached to all analyses names
analyse.name	analyses names are usually automatically set, if you want to set them manually use this option
analyse.name.elements	analyses names are set automatically using these elements: c ("scale" , "group" , "dif" , "regression" , "anchor"), use this option to change composition and order of the analyses names generation
data.name	optional: character string specifying name of dataset if intend to differ from name specified by jobName. When dataName == NULL, dataset is named [jobName].dat
m.model	measurement model, "1pl" (default), "2pl", "3pl", "4pl"
software	"conquest" (default) no other software implemented yet
dif	variable that is used for differential item functioning
weight	case weight variable
anchor	data.frame with anchor information
regression	variable(s) that is/are used
adjust.for.regression	if TRUE item parameters (difficulty) are centered on the mean of the entire sample if FALSE (default) item parameters (difficulty) are centered on the mean of the regression reference group
missing.rule	definition how to recode distinct missings in dataset
cross	scales in 'item.grouping' and groups in 'person.grouping' can be crossed to define distinct analyses "all": scales and groups are crossed "item.groups", scales are separately (unidimensional) run (instead of one multidimensional model) "person.groups", person groups are separately (single group) run (instead of one multigroup model)
subfolder.order	subfolders are automatically generated in this order c ("i.model" , "p.model" , "m.model" , "software" , "dif" , "regression" , "anchor")
subfolder.mode	"none": no subfolders are created "full": complete subfolders are created according to 'subfolder.order' "intelligent" (default): meaningful subfolders are created
additionalSubFolder	specification for 'data' and 'out' subfolder (constant over all analyses)

run.mode	"serial": serial runs on local machine "parallel": batch files must be started manually (e.g. on several machines)
n.batches	number of batch files that are created, batch files contain one or more analyses
run.timeout	minutes to wait for analyses to finish, default: 1440 (24h)
run.status.refresh	time for console refresh of model run status, default: 0.2 (12sec)
email	set email address to receive an email when analyses are finished or time's up
smtpServer	smtpServer for sending emails, default: "mailhost.cms.hu-berlin.de"
write.txt.dataset	write out datasets as ascii, default: FALSE
delete.folder.countdown	countdown for deletion of 'folder', default: 5 (seconds)
conquestParameters	Set ConQuest parameters as a named list. Available option are: "pathConquest", "method", "std.err", "distribution", "n.plausible", "set.constraints", "nodes", "p.nodes", "f.nodes", "n.iterations", "converge", "deviancechange", "equivalence.table", "use.letters", "na" See automateConquestModel documentation for details.

Details

To run several models list parameters as corresponding lists Explicitly list NULL if parameter should not be set or be defaulted See examples

Value

returns results in specific format

Author(s)

Martin Hecht, Karoline Sachse, Sebastian Weirich, Christiane Penk, Malte Jansen, Sebastian Wurster

bi.linking

bi.linking

Description

Links results from several analysis. Each analysis is linked with each other.

Usage

```
bi.linking ( results , scales=NULL , folder=NULL , file.name=NULL , method = NULL , lower.triang
```

Arguments

results	result list from automateModels run
scales	Character vector of scales for which linking should separately done. If NULL, all analysis in the results list are linked. Note: due to suboptimalities in development process, analysis name must contain scale!!
folder	output folder, will be emptied!
file.name	file.name for output excel, default: "bi.linking.results.xlsx"
method	set linking method to either "Mean-Mean" , "Haebara" or "Stocking-Lord" (default)
lower.triangle	set reference groups for the linking

Value

writes linking results to excel file. returns linking results as list.

Author(s)

Martin Hecht

checkData

Check Datasets for Missing Values and Invalid Codes

Description

Check data frames for missing or duplicated entries in the ID variable, persons and/or variables without valid codes, and invalid codes. Invalid codes are codes which are not specified in table values.

Usage

```
checkData (dat, values, subunits, units)
```

Arguments

dat	A data frame
values	A data frame with code information. See 'Details'.
subunits	A data frame with subunit information. See 'Details'.
units	A data frame with unit information. See 'Details'.

Details

The results of checkData will be written to a protocol file with sunk.

Examples of data frames values, subunits and units can be found via data(inputList).

Value

Used for its side effects. The return value is NULL.

Author(s)

Nicole Haag, Anna Lenski

References

For missing types see <http://code.google.com/p/zkdlb/wiki/MissingHandling>

See Also

[sunk](#)

checkInput

Check Input Data Frames

Description

Check input data frames for consistency and replace missing information with default values (if necessary).

Usage

```
checkInput(values, subunits, units, checkValues = TRUE, checkUnits = TRUE)
```

Arguments

values	A data frame with code information. See 'Details'
subunits	A data frame with subunit information. See 'Details'
units	A data frame with unit information. See 'Details'.
checkValues	Logical: Should data frame values be checked?
checkUnits	Logical: Should data frame units be checked?

Details

This function is largely for internal use and is called by `makeInputLists` before lists are generated. Examples of data frames `values`, `subunits` and `units` can be found via `data(inputList)`.

Value

A list containing the checked and (if necessary) defaulted input data frames:

values	Checked data frame with code information. Will be returned if <code>checkValues = TRUE</code> .
subunits	A data frame with subunit information.
units	A data frame with unit information. Will be returned if <code>checkUnits = TRUE</code> .

Warning

Function will not check input data frames if `checkValues` and `checkUnits` are both `FALSE`.

Author(s)

Nicole Haag

See Also[makeInputLists](#)

collapseMissings *Collapse Missings*

Description

converts character missings of different types to 0 or NA

Usage

```
collapseMissings(dat, missing.rule = NULL, item.names)
```

Arguments

dat	data frame containing character missings (e.g. type 'mbd' - missing by design)
missing.rule	list, definition how to recode distinct missings in dataset. See details for default.
item.names	character vector containing column names of the data frames whose character missings are to be collapsed

Details

Default missing.rule in collapseMissings is: text volume insufficient = 0 , missing not reached = 0 , missing coding impossible = NA , missing by design = NA , missing invalid response = 0 , missing by intention = 0

The results of collapseMissings will be written to a protocol file with sunk.

Value

A data frame with recoded missings.

Author(s)

Karoline Sachse, Martin Hecht

References

For missing types see <http://code.google.com/p/zkdlb/wiki/MissingHandling>

Examples

```
data(inputDat)
dat1 <- inputDat[[1]] # get first dataset from inputDat
datColMis <- collapseMissings(dat = dat1,
missing.rule = list(mvi = 0 ,mnr = 0 ,mci = 0 ,mbd = NA ,mir = 0 ,mbi = 0),
item.names=colnames(dat1)[- c(1:2)])
```

crop	<i>crop</i>
------	-------------

Description

remove trailing and leading characters from character strings

Usage

```
crop ( x , char = " " )
```

Arguments

x	character string
char	character to be removed from beginning and end of x

Author(s)

Martin Hecht, Sebastian Weirich

get.dsc	<i>Reads Conquest descriptive files.</i>
---------	--

Description

Reads Conquest files comprising descriptive population statistics generated by the 'descriptives' statement.

Usage

```
get.dsc(file)
```

Arguments

file	Character string of the Conquest descriptives file.
------	---

Value

A list of n elements, with n the number of groups in the analysis. Each element is a list with two data frames, the single and aggregated descriptives of the corresponding group. Single descriptives give for each dimension the number of observations, mean, standard deviation and variance of the corresponding estimate, i.e. the WLE or the plausible values (PVs). When descriptives for PVs are read in, mean, standard deviation and variance for each plausible value is given. Aggregated descriptives give mean, standard deviation and variance of the standard error of corresponding estimate. When descriptives vor plausible values are read in, aggregated descriptives gibe also mean, standard deviation and variance of all plausible values.

References

See Conquest manual, pp.162.

get.itn	<i>get.itn</i>
---------	----------------

Description

blablabla

Usage

```
get.itn(file)
```

Arguments

file

get.plausible	<i>Reads Conquest plausible values files</i>
---------------	--

Description

Function reads Conquest plausible value files and transforms them into a R data frame.

Usage

```
get.plausible(file)
```

Arguments

file Character string of the Conquest plausible values file to be read in.

Details

Funktion identifies number of cases, number of plausible values and number of dimensions.

Value

A data frame, where each row corresponds to one case. Columns are labeled with dimension names and number of corresponding plausible value.

case	Case number. Each row represents one person.
ID	Case ID, if listed in Conquest plausible values file.
pv	Plausible value. Denotation of columns names is pv.[name of dimension]_[number of plausible value]. For example, pv.reading_6 refers to the 6th plausible value of reading dimension.
eap	Expectation value of the a posterio distribution of the corresponding dimension.
eap.se	Standard error of the EAP estimate.

get.shw

*Reads Conquest showfiles***Description**

Function reads Conquest showfiles and transforms them into a R list of data frames.

Usage

```
get.shw(file, dif.term = NULL, split.dif = TRUE,
        abs.dif.bound = 0.64, sig.dif.bound = 0.43)
```

Arguments

file	Character string of the Conquest showfile to be read in.
dif.term	Optional: Character string. Name of the term considered to be DIF-term. Must match corresponding term in showfile.
split.dif	Logical: When TRUE, DIF-Parameter are only given for Reference group.
abs.dif.bound	When DIF-Parameter are evaluated, this specifies the critical value for absolute DIF.
sig.dif.bound	When DIF-Parameter are evaluated, this specifies the critical value for confidence interval DIF.

Details

Funktion searches for 'TERM'-statements in Conquest showfile and reads the tables associated with. If one statement is specified to contain DIF analyses, absolute DIF value is computed $2 \times [\text{group-specific parameter}]$. Confidence intervals for 90, 95 and 99 percent are computed via the standard error of specific parameters. If both criteria - absolute DIF exceeds `abs.dif.bound` and the confidence interval does not include `sig.dif.bound`, item is considered to have DIF.

Value

A list of data frames, named by the 'TERM'-statements in Conquest showfile, plus an additional data frame with regression coefficients when latent linear regression model was specified in Conquest analysis. If one term was specified as DIF-statement, the corresponding data frame is augmented with additional columns for confidence intervals and indicators specifying significant DIF.

Each data frame corresponding to a 'TERM' statement contains following columns:

item	Name of item
ESTIMATE	Estimated difficulty of item
ERROR	Standard error of estimated item difficulty
MNSQ	Item's 'Outfit'
MNSQ.1	Items's 'Infit'
CI	Lower and upper bound confidence intervals
T	T values, corresponding to confidence intervals
filename	Name of show file read in

abs.dif	Only for DIF analysis. Absolute DIF, computed as $2 \times [\text{group-specific parameter}]$.
ci.lb	Lower bound confidence interval for specific significance level of 90, 95 or 99 percent.
ci.ub	Upper bound confidence interval for specific significance level of 90, 95 or 99 percent.
sig	Indicates whether the corresponding item matches both DIF criteria. See details.

When latent regression was specified, the last element of the returned list is a data frame with regression coefficients, corresponding to the number of dimensions and the number of regressors. Regressor names, regression coefficients and its standard errors are given for each dimension.

Rows represent the regressors, columns represent the latent dimension to which the regression is fitted.

get.wle	<i>Reads Conquest WLE or MLE files.</i>
---------	---

Description

Reads Conquest files comprising maximum likelihood estimates (MLE) or weighted likelihood estimates (WLE).

Usage

```
get.wle(file)
```

Arguments

file	Character string of the Conquest MLE or WLE file to be read in.
------	---

Value

A data frame with columns according to the corresponding MLE or WLE file. For each dimension of the analysis number of solved items, number of presented items, point estimate and its standard error is given. Each row represents one person. Columns are named as follows:

case	Case number. Each row represents one person.
n.solved	Number of solved items by the i-th person.
n.total	Number of total items presented to the i-th person.
wle	WLE or MLE estimate.
wle.se	Standard error of WLE or MLE estimate.

The last number of columns names represents the dimension the WLE or MLE estimate belongs to.

inputDat

List of Three Datasets from Educational Assessment

Description

Simulated data for three booklets for an educational assessment study.

Usage

```
data(inputDat)
```

Format

This list contains 3 data frames, each with the following columns:

ID Person-ID

Hisei A continuous covariate.

Ixx Item responses to a selection of 30 test items.

Details

code, subunit and unit descriptions are stored in dataset [inputList](#).

Examples

```
data(inputDat)
str(inputDat)
```

inputList

*Data Frames with Code, Subunit and Unit Information for Datasets in
[inputDat](#)*

Description

These data frames contain information about codes, subunits and units for the datasets in [inputDat](#) and are necessary inputs for functions [automateDataPreparation](#), [checkData](#), [recodeData](#) and [aggregateData](#).

Usage

```
data(inputList)
```

Format

A list with three data frames:

1. **units**: Unit information, contains the following columns:
 - unit** Unit name.
 - unitType** Subunit types: ID = ID variable; TI = test item; CV = context variable.
 - unitLabel** Unit label, to be used by [writeSpss](#).
 - unitDescription** Unit description.
 - unitAggregateRule** Aggregate rule for unit: SUM; MEAN.
 - unitScoreRule** Scoring rule for unit (not sure how this will be used in the future.)
2. **subunits**: Subunit information, contains the following columns:
 - unit** Unit name, for which subunits are given.
 - subunit** Subunit name.
 - subunitType** Subunit types: ' ? '.
 - subunitLabel** Subunit label, to be used by [writeSpss](#).
 - subunitDescription** Subunit descriptions.
 - subunitPosition** Subunit position in test booklet (e.g., line 1).
 - subunitTransniveau** Subunit transformation level.
 - subunitRecoded** Name of recoded subunit.
 - subunitLabelRecoded** Label for recoded subunit, to be used when [writeSpss](#) is applied to a dataset produced by [recodeData](#).
3. **values**: Value information, contains the following columns:
 - subunit** Subunit name, for which values are given.
 - value** Valid values for the respective subunit.
 - valueRecode** Recode values for the respective value.
 - valueType** Value types: vc = valid code; mbd = missing – by design; mvi = missing – volume insufficient; mnrr = missing – not reached; mci = missing – coding impossible; mbi = missing – by intention.
 - valueLabel** Value labels, to be used by [writeSpss](#).
 - valueDescription** Value descriptions.
 - valueLabelRecoded** Labels for recoded values, to be used when [writeSpss](#) is applied to a dataset produced by [recodeData](#).
 - valueDescriptionRecoded** Descriptions for recoded values.
4. **unitRecodings**: Unit recoding information, contains the following columns:
 - unit** Unit name
 - value** Valid values for the respective unit.
 - valueRecode** Recode values for the respective value.
 - valueType** Value types: vc = valid code; mbd = missing – by design; mvi = missing – volume insufficient; mnrr = missing – not reached; mci = missing – coding impossible; mbi = missing – by intention.
 - valueLabel** Value labels, to be used by [writeSpss](#).
 - valueDescription** Value descriptions.
 - valueLabelRecoded** Labels for recoded values, to be used when [writeSpss](#) is applied to a dataset produced by [recodeData](#).
5. **savFiles**: information for [loadSav](#), contains the following columns:

- filename** SPSS filenames
- case.id** ID variable in the respective dataset, used by [mergeData](#)
- 6. **newID**: information for [mergeData](#), contains the following columns:
 - key** one of the entries should be master-id
 - value** the corresponding value; how the ID variable in the final dataset shall be named
- 7. **aggrMiss**: missing aggregation pattern for [aggregateData](#)

Examples

```
data(inputList)
str(inputList)
```

loadSav	<i>loadSav</i>
---------	----------------

Description

read SPSS data files and change id names, if necessary

Usage

```
loadSav(path = getwd(), savFiles = NULL, oldIDS, newID, correctDigits = FALSE, truncateSpaceChar
```

Arguments

- path
- savFiles
- oldIDS
- newID
- correctDigits
- truncateSpaceChar

Examples

```
##---- Should be DIRECTLY executable !! ----
##-- ==> Define data, use random,
##--or do help(data=index) for the standard data sets.

## The function is currently defined as
function ( path=getwd(), savFiles=NULL, oldIDS, newID, correctDigits=FALSE, truncateSpaceChar = TRUE ) {
  funVersion <- "loadSAV_0.0.2"
  if(missing(oldIDS)) {stop(paste("Error in ",funVersion,": 'oldIDS' is missing.\n",sep="")) }
  if(missing(newID)) {stop(paste("Error in ",funVersion,": 'newID' is missing.\n",sep="")) }
  if(length(newID)!=1) {stop(paste("Error in ",funVersion,": 'newID' has to be of length 1.\n",sep="")) }
  # if(!exists("read.spss")) {library(foreign)}
  if(!is.null(savFiles)) {
    fileExists <- file.exists(file.path(path,savFiles))
    if(all(!fileExists)) {
      stop(paste("Error in ",funVersion,": None of the files specified in 'savFiles' were found
```

```

    }
    if(!all(fileExists)) {
      cat(paste(funVersion,": Following files specified in 'savFiles' were not found in ",path,
      notFoundFiles <- savFiles[!fileExists]
      FoundFiles <- savFiles[fileExists]
      cat(paste(notFoundFiles,collapse=", "))
      cat("\nOnly found files will be read in.\n")
      savFiles <- savFiles[fileExists]
    }
  }
  if(is.null(savFiles)) {
    savFiles <- list.files(path=path,pattern=".sav|.SAV",recursive=FALSE)
    if(length(savFiles)==0) {
      stop(paste("No '.sav'-files found in ",path,".\n",sep=""))
    }
  }
  cat(paste(funVersion,": Found ", length(savFiles), " 'savFiles' in ",path,".\n",sep=""))
}
### hier beginnt das eigentliche Einlesen
allDataFrames <- NULL
for (i in seq(along=savFiles)) {
  file.i <- data.frame(read.spss(file.path(path,savFiles[i]),to.data.frame=FALSE, use.value.1
  idCol <- unique(unlist(lapply(oldIDS, FUN=function(ii) {grep(ii,colnames(file.i))})))
  if(length(idCol)<1) {
    stop(paste("Error in ",funVersion,": None of the specified 'oldIDS' were found in dataset
  }
  if(length(idCol)>1) {
    stop(paste("Error in ",funVersion,": More than one of the specified 'oldIDS' were found
  }
  colnames(file.i)[idCol] <- newID
  ### Leerzeichen abschnipseln
  if(truncateSpaceChar == TRUE) {
    for (ii in 1:ncol(file.i)) {
      file.i[,ii] <- crop(file.i[,ii])
    }
  }
  ### Stelligkeitskorrektur
  if(correctDigits == TRUE) {
    colsToCorrect <- lapply(1:ncol(file.i), FUN=function(ii) { sort(unique(nchar(file.i[,ii]
    options(warn = -1)
    colsToCorrect <- which( unlist( lapply(colsToCorrect, FUN=function(ii) { all(ii == c(1
    options(warn = 0)
    if(length(colsToCorrect)>0) {
      cat(paste(funVersion,": ",length(colsToCorrect)," columns are corrected for column w
      for (ii in colsToCorrect) {
        file.i[,ii] <- gsub(" ", "0", formatC(as.character(file.i[,ii]),width=2))
      }
    }
  }
  allDataFrames[[i]] <- file.i
}
return(allDataFrames)
}

```

Description

transforms long format data.frame into a matrix format data.frame

Usage

```
long2matrix ( data , sort = TRUE , triangle = NULL ,
force.diagonal = FALSE , exclude.diagonal = FALSE ,
long2matrix = TRUE )
```

Arguments

data	data.frame with columns "row", "col", "val"
sort	sort rows and columns of matrix
triangle	if not NULL a symmetric matrix will be constructed available options are "upper", "lower", "both"
force.diagonal	a diagonal is forced into matrix even if no diagonal elements are in data
exclude.diagonal	the diagonal is excluded if possible
long2matrix	if FALSE data is not transformed

Value

```
long2matrix = TRUE
      data.frame in matrix format
long2matrix = FALSE
      data.frame in long format
```

Author(s)

Martin Hecht

Examples

```
d1 <- data.frame (
"row" = c ( "v1" , "v2" , "v2" , "v3" , "v1" , "v3" ) ,
"col" = c ( "v1" , "v3" , "v2" , "v1" , "v2" , "v3" ) ,
"val" = c ( 1 , 5 , 4 , 3 , 2 , 6 ) , stringsAsFactors = FALSE )

# unsorted matrix
long2matrix ( data = d1 , sort = FALSE )
# sorted by default
long2matrix ( data = d1 )
# extract upper triangle of symmetric matrix
long2matrix ( data = d1 , triangle = "upper" )
# exclude diagonal elements
long2matrix ( data = d1 , triangle = "upper" , exclude.diagonal = TRUE )
# if full matrix ("both" triangles) is requested, the diagonal cannot be excluded, option is ignored
long2matrix ( data = d1 , triangle = "both" , exclude.diagonal = TRUE )

# no diagonal elements are specified
d2 <- data.frame (
"row" = c ( "v2" , "v1" , "v1" ) ,
"col" = c ( "v3" , "v3" , "v2" ) ,
"val" = c ( 5 , 3 , 2 ) , stringsAsFactors = FALSE )
```

```
long2matrix ( data = d2 )
# diagonal is set (with NAs)
long2matrix ( data = d2 , triangle = "upper" , force.diagonal = TRUE )
```

makeCodebookInput	<i>Make Input Data Frames From IQB-Codebooks</i>
-------------------	--

Description

Make Input Data Frames From IQB-Codebooks

Usage

```
makeCodebookInput(codebook)
```

Arguments

codebook	dataframe IQB-Codebook
----------	------------------------

Details

xxx

Value

xxx

makeInputLists	<i>Generate Input Lists for Functions checkData, recodeData and aggregateData</i>
----------------	---

Description

Transforms information given in values, subunits and units in a format that is used by checkData, recodeData and aggregateData.

Usage

```
makeInputLists(values, subunits, units, recodedData = TRUE)
makeInputCheckData(values, subunits, units)
makeInputRecodeData(values, subunits)
makeInputAggregateData(subunits, units, recodedData = TRUE)
```

Arguments

values	A data frame with code information. See Details.
subunits	A data frame with subunit information. See Details.
units	A data frame with unit information. See Details.
recodedData	Logical indicating whether colnames in dataset to aggregate are the subunit names (as in subunits\$subunit) or recoded subunit names (as in subunits\$subunitRecoded). Default is TRUE, meaning that colnames are recoded subitem names. This parameter is only relevant when input for aggregateData is generated.

Details

This function generates specific inputs for the data preparation functions `checkData`, `recodeData` and `aggregateData`. It is largely for internal use of these functions, who call their respective version.

Examples of data frames values, subunits and units can be found via `data(inputLists)`.

Value

A list with several of the following entries (depending on which version of the function is called):

<code>varinfoRaw</code>	A list with information about variables and their values expected in raw data.
<code>varinfoRecoded</code>	A list with information about variables and their values expected in recoded data.
<code>varinfoAggregated</code>	A list with information about variables and their values expected in aggregated data.
<code>recodeinfo</code>	A list with information needed for recoding of data.
<code>aggregateinfo</code>	A list with information needed for aggregation of data.

Author(s)

Nicole Haag

Examples

```
data(inputList)
lists <- makeInputLists(inputList$values, inputList$subunits, inputList$units, recodedData = TRUE)
str(lists)
```

makeNumeric

Change Character Variables to numeric

Description

Converts character variables, which contain only values, to `numeric`. Character variables containing letters are not converted. This avoids warnings, if conversion to `numeric` is attempted for variables, which contain characters.

Usage

```
makeNumeric(variable)
```

Arguments

<code>variable</code>	Variable to be changed to <code>numeric</code> .
-----------------------	--

Value

Variable converted to `numeric`, if possible.

Author(s)

Nicole Haag

Examples

```
a <- c("1", "2", "3", "4")
b <- c("1", "2", "x", "4")
makeNumeric(a)
makeNumeric(b)
```

mergeData

*Merge Data Frames using one Key Variable***Description**

Merges several data frames and matches them using one key variable

Usage

```
mergeData(newID = "ID", datList, oldIDs, addMbd = TRUE)
```

Arguments

newID	character string containing the key variable's name in the merged dataset
datList	list of data frames to be merged
oldIDs	character vector OR numeric vector containing either names of the key variables in datList or their column number in each dataframe in datList
addMbd	logical; string "mbd" (missing by desgin) will be added instead of NA

Details

Errors and warnings of mergeData will be written to a protocol file with [sunk](#).

Value

A data frame containing unique cases and unique variables. All cases and all variables that could be identified the original data frames will be kept and matched.

Author(s)

Karoline Sachse, Nicole Haag

Examples

```
data(inputDat)
str(inputDat)

mergedDataset <- mergeData("person-id", inputDat, c("idstud", "idstud", "idstud"), addMbd=TRUE)
str(mergedDataset)
```

prepare.package	<i>prepare.package</i>
-----------------	------------------------

Description

prepares package

Usage

```
prepare.package ( source.folder = "p:/ZKD/development" ,
  files ,
  package.folder = "p:/ZKD/packages" ,
  package.name ,
  package.version )
```

Arguments

source.folder	folder of R files
files	character vector of R files that should be included in the package
package.folder	folder of packages
package.name	name of package
package.version	version of package, must be in format "0.0.0"

Details

copies R files from source.folder to package folder copies "x.x.x" folder content to package folder modifies version and date in DESCRIPTION and automateModels creates ChangeLog

Author(s)

Martin Hecht

readDaemonXlsx	<i>read xlsx-Files produced by ZKDaemon</i>
----------------	---

Description

read xlsx-Files produced by ZKDaemon

Usage

```
readDaemonXlsx(filename)
```

Arguments

filename	A character string containing path, name and extension of .xlsx produced by ZKDaemon. Caution! Sheet order is important (see Details).
----------	--

Details

Compulsory: 1st sheet: units. 2nd sheet: subunits. 3rd sheet: values. Optional: 4th sheet: unitRecodings. 5th sheet: savFiles. 6th sheet: newID. 7th sheet: aggregateMissings. 8th sheet: unitProperties. 9th sheet: property labels. 10th sheet: booklets.

Value

A list of data frames containing information that is required by [automateDataPreparation](#)

Author(s)

Karoline Sachse

Examples

```
str(inputList)
```

recodeData	<i>Recode Datasets with Missing Values</i>
------------	--

Description

Recode datasets with special consideration of missing values.

Usage

```
recodeData(dat, values, subunits)
```

Arguments

dat	A data frame
values	A data frame with code information. See 'Details'.
subunits	A data frame with subunit information. See 'Details'.

Details

recodeData recodes data frames with special consideration of missing values. The results of recodeData will be written to a protocol file with sunk. recodeData will give warnings, if missing or incomplete recode informations are found. Values without recode information will NOT be recoded!

Examples of data frames values and subunits can be found via `data(inputList)`

Value

A data frame with recoded variables according to the specifications in values and subunits. Column names will be the names specified in `subunits$subunitRecoded`.

Author(s)

Martin Hecht, Christiane Penk, Nicole Haag

References

<http://code.google.com/p/zkdlb/wiki/MissingHandling>

See Also

[aggregateData](#), [checkData](#)

Examples

```
data(inputDat)
data(inputList)
# library(car)

dat1 <- inputDat[[1]] # get first dataset from inputDat
datRec <- recodeData(dat1, inputList$values, inputList$subunits)
str(datRec)
```

reinsort.col

reinsort.col

Description

insert columns of dataframe in specific position

Usage

```
reinsort.col ( dat , toreinsort , after )
```

Arguments

dat	data.frame on which operation should be performed
toreinsort	column name(s) or numeric indicator(s) that should be relocated
after	column name or numeric indicator after that toreinsort should be located

Value

data.frame

Author(s)

Martin Hecht

source.it.all	<i>source.it.all</i>
---------------	----------------------

Description

sources *.R files of folder

Usage

```
source.it.all ( folder="p:/ZKD/development" , develop.modules = NULL , return.stable = FALSE )
```

Arguments

folder	folder with *.R files
develop.modules	character vector of R files that should be sourced in development status
return.stable	if TRUE nothing is sourced and a vector of all stable versions is returned

Value

return.stable = FALSE	sources R files
return.stable = TRUE	character vector of stable R files

Author(s)

Christiane Penk, Martin Hecht

source.it.all2	<i>source.it.all2</i>
----------------	-----------------------

Description

sources *.R files of folder

Usage

```
source.it.all2 ( folder="p:/ZKD/development" , development = TRUE , development.only = FALSE , e
```

Arguments

folder	folder with *.R files
development	if TRUE development versions are sourced (if non-existent the latest stable is sourced or nothing is sourced, see option development.only\ if FALSE stable versions are sourced
development.only	if TRUE only development versions are sourced \ if FALSE stable versions are included
exclude	character vector of R files that should not be sourced

Value

sources R files

Author(s)

Martin Hecht, Christiane Penk

sunk	<i>sunk</i>
------	-------------

Description

writes output to file

Usage

```
sunk ( cmd = NULL , path = NULL , write = TRUE , console.output = TRUE , new.file = FALSE , text
```

Arguments

cmd	character string of element to write, may be either text (e.g. "write me to file") or a function call (e.g. "summary(lm)")
path	path (folder and name) to output file if NULL path is defaulted to getwd()+"sunk.txt" all environments are searched for sunk.path, if sunk.path is found (exists), it is used
write	logical, if TRUE (default) output is written to file
console.output	logical, if TRUE (default) output is displayed on console
new.file	logical, if TRUE the output file is created if FALSE (default) output is appended to existing file
text.on.error	logical, sunk checks if the character string 'cmd' is an evaluable expression if TRUE (default), 'cmd' is treated as text if an error occurs when trying to evaluate string if FALSE, sunk stops on errors/not evaluable expressions
text.out.method	choose "cat" (default) or "print" as the output method for text

Value

writes to disk

Author(s)

Martin Hecht

writeSpss

*Export Datasets to SPSS***Description**

Writes data and SPSS syntax files.

Usage

```
writeSpss(dat, values, subunits, units,
  filedat = "zkddata.txt", filesps = "readZkdData.sps",
  missing.rule = list(mvi = 0, mnr = 0, mci = NA, mbd = NA, mir = 0, mbi = 0),
  path = getwd(), sep = "\t", dec = ",", silent = FALSE)
```

Arguments

dat	A data frame
values	A data frame with code information. See 'Details'.
subunits	A data frame with subunit information. See 'Details'.
units	A data frame with unit information. See 'Details'.
filedat	A character string with the name of the output data file.
filesps	A character string with the name of the output syntax file.
missing.rule	A list containing recode information for character missings. See 'References' for description of default values.
path	A character string containing the path of the output file. The value in path is appended to filedat and filesps. By default, files are written to the current R working directory. If path=NULL then no file path appending is done.
sep	The separator between the data fields.
dec	The decimal separator for numerical data.
silent	A logical flag stating whether the names of the files should be printed.

Details

This function automates most of the work needed to export a dataset to SPSS. It uses a modified version of `writeForeignSPSS()` from the `foreign()` package and of `mids2spss()` from the `mice` package. The modified version allows for a choice of the field and decimal separators, makes some improvements to the formatting and provides variable labels and value labels according to the information in the data frames `values`, `subunits` and `units`.

Examples of data frames `values`, `subunits` and `units` can be found on `data(inputList)`

The SPSS syntax file has the proper file names and separators set, so in principle it should run and read the data without alteration. SPSS is more strict than R with respect to the paths. Always use the full path, otherwise SPSS may not be able to find the data file.

Value

Used for its side effects. The return value is NULL.

Author(s)

Nicole Haag

References

<http://code.google.com/p/zkdlb/wiki/MissingHandling>

Index

*Topic \textasciitildekw1

- automateConquestModel, 4
- automateDataPreparation, 6
- automateModels, 8
- bi.linking, 10
- checkData, 11
- checkInput, 12
- collapseMissings, 13
- crop, 14
- get.dsc, 14
- get.itn, 15
- get.plausible, 15
- get.shw, 16
- get.wle, 17
- loadSav, 20
- long2matrix, 21
- makeCodebookInput, 23
- makeNumeric, 24
- mergeData, 25
- prepare.package, 26
- recodeData, 27
- reinsort.col, 28
- source.it.all, 29
- source.it.all2, 29
- sunk, 30

*Topic \textasciitildekw2

- automateConquestModel, 4
- automateDataPreparation, 6
- automateModels, 8
- bi.linking, 10
- checkData, 11
- checkInput, 12
- collapseMissings, 13
- crop, 14
- get.dsc, 14
- get.itn, 15
- get.plausible, 15
- get.shw, 16
- get.wle, 17
- loadSav, 20
- long2matrix, 21
- makeCodebookInput, 23
- makeNumeric, 24

- mergeData, 25
- prepare.package, 26
- recodeData, 27
- reinsort.col, 28
- source.it.all, 29
- source.it.all2, 29
- sunk, 30

*Topic datasets

- inputDat, 18
- inputList, 18

*Topic package

- eat-package, 2

- aggregateData, 2, 7, 20, 28
- automateConquestModel, 4, 10
- automateDataPreparation, 6, 18, 27
- automateModels, 6, 8

- bi.linking, 10

- checkData, 3, 7, 11, 18, 28
- checkInput, 12
- collapseMissings, 13
- crop, 14

- eat-package, 2

- get.dsc, 14
- get.itn, 15
- get.plausible, 15
- get.shw, 16
- get.wle, 17

- inputDat, 18, 18
- inputList, 18, 18

- loadSav, 7, 19, 20
- long2matrix, 21

- makeCodebookInput, 23
- makeInputAggregateData
(makeInputLists), 23
- makeInputCheckData (makeInputLists), 23
- makeInputLists, 7, 13, 23
- makeInputRecodeData (makeInputLists), 23

makeNumeric, [24](#)
mergeData, [7](#), [20](#), [25](#)

prepare.package, [26](#)

readDaemonXlsx, [7](#), [26](#)
recodeData, [3](#), [7](#), [18](#), [19](#), [27](#)
reinsort.col, [28](#)

source.it.all, [29](#)
source.it.all2, [29](#)
sunk, [12](#), [25](#), [30](#)

writeSpss, [7](#), [19](#), [31](#)