

Package ‘lrgpr’

June 14, 2017

Title lrgpr

Version 0.1.9

Date April 5, 2017

Author Gabriel E. Hoffman

Maintainer Gabriel E. Hoffman <gabriel.hoffman@mssm.edu>

Description Fit a Low Rank Gaussian Process Regression (LRGPR) / Linear Mixed Model (LMM) for large datasets. These models are widely used in statistical genetics as a test of association while correcting for the confounding effects of kinship and population structure.

Depends R (>= 3.0.0), methods, Rcpp, RcppGSL, RcppProgress, MASS, BH, doParallel, bigmemory (>= 4.4.7), bigmemory.sri, aod

LinkingTo Rcpp, RcppGSL

URL <http://lrgpr.r-forge.r-project.org/>

License GPL (>= 2)

RoxygenNote 6.0.1

NeedsCompilation yes

R topics documented:

AIC.lrgpr	2
BIC.lrgpr	3
coefficients.lrgpr	3
convertToBinary	4
cooks.distance.lrgpr	5
criterion.lrgpr	5
cv.lrgpr	6
df.residual.lrgpr	7
error.bar	8
getAlleleFreq	8
getAlleleVariance	9
getMACHrsq	9
getMissingCount	10

glmApply	10
glmApply2	11
influence.lrgpr	12
leverage.lrgpr	12
lm.influence.lrgpr	12
logLik.lrgpr	13
loss.lrgpr	13
lrgpr	14
lrgprApply	17
plot.criterion.lrgpr	18
plot.cv.lrgpr	19
plot.lrgpr	19
predict.lrgpr	21
print.lrgpr	21
print.summary.lrgpr	22
QQ_plot	22
read.fam	23
read.tfam	23
residuals.lrgpr	24
rstandard.lrgpr	24
set_missing_to_mean	25
summary.lrgpr	25
vcov.lrgpr	25
wald	26
Index	27

AIC.lrgpr	<i>Akaike's Information Criterion (AIC)</i>
-----------	---

Description

AIC for model fit by lrgpr

Usage

AIC.lrgpr(object, ..., k = 2)

Arguments

- | | |
|--------|-----------------------------|
| object | model fit with lrgpr |
| ... | other arguments |
| k | for compotability, not used |

BIC.lrgpr	<i>Bayesian Information Criterion (BIC)</i>
-----------	---

Description

BIC for model fit by `lrgpr`

Usage

```
## S3 method for class 'lrgpr'  
BIC(object, ...)
```

Arguments

object	model fit with <code>lrgpr</code>
...	other arguments

<code>coefficients.lrgpr</code>	<i>Extract Model Coefficients</i>
---------------------------------	-----------------------------------

Description

Coefficients estimated with `lrgpr`

Usage

```
## S3 method for class 'lrgpr'  
coefficients(object, ...)
```

Arguments

object	model fit with <code>lrgpr</code>
...	other arguments

convertToBinary	<i>Convert ASCII to binary file</i>
-----------------	-------------------------------------

Description

Converts TPED/DOSAGE/GEN files to binary format

Usage

```
convertToBinary(filename, filenameOut, format, nthreads = detectCores(logical
= TRUE), onlyCheckFormat = FALSE, rowNames = NULL,
simpleAnnotation = TRUE)
```

Arguments

filename	file to be converted
filenameOut	name of binary file produced
format	specify 'TPED', 'DOSAGE' or 'GEN'
nthreads	number of threads to use
onlyCheckFormat	only check the format of the input file and don't perform conversion
rowNames	Define custom rowNames
simpleAnnotation	write FILE_alleles with name, allele1, allele2. If FALSE, write chrom id genetic_position position allele1 allele2

Details

- TPED: plink file can be in either --recode or --recode12 format
- DOSAGE: file follows plink format: <http://pngu.mgh.harvard.edu/~purcell/plink/dosage.shtml>

Example:

```
SNP A1 A2 F1 I1 F2 I2 F3 I3
rs0001 A C 0.98 0.02 1.00 0.00 0.00 0.01
rs0002 G A 0.00 1.00 0.00 0.00 0.99 0.01
```

where the F* values correspond to the dosage values

- GEN: file follows OXFORD format

cooks.distance.lrgpr

Regression Deletion Diagnostics

Description

Basic quantities for regression deletion diagnostics from fit of `lrgpr`

Usage

```
## S3 method for class 'lrgpr'
cooks.distance(model, infl = lm.influence(model, do.coef =
  FALSE), res = weighted.residuals(model),
  sd = sqrt(deviance(model)/df.residual(model)), hat = infl$hat, ...)
```

Arguments

<code>model</code>	model fit with <code>lrgpr</code>
<code>infl</code>	influence structure as returned by <code>lm.influence</code>
<code>res</code>	residuals
<code>sd</code>	standard deviation to use
<code>hat</code>	hat values
<code>...</code>	other arguments

`criterion.lrgpr` *Compute AIC/BIC/GCV for `lrgpr` model as rank changes*

Description

Evaluate information criteria to select an optimal rank for model fit by `lrgpr`

Usage

```
criterion.lrgpr(formula, features, order, rank = c(seq(1, 10), seq(20, 100, by
  = 10), seq(200, 1000, by = 100)))
```

Arguments

<code>formula</code>	standard linear modeling syntax as used in ‘lm’
<code>features</code>	matrix from which the SVD is performed
<code>order</code>	sorted indices of features. When rank is 10, <code>decomp = svd(X[,order[1:10]])</code>
<code>rank</code>	array with elements indicating the number of confounding covariates to be used in the random effect.

See Also

plot.criterion.lrgpr, cv.lrgpr

Examples

```
n = 300
p = 5000
X = matrix(sample(0:2, n*p, replace=TRUE), nrow=n)

dcmp = svd(X)

# simulate response
h_sq = .8
eta = dcmp$u[,1:2] %*% rgamma(2, 2, 1)
error_var = (1-h_sq) / h_sq * var(eta)
y = eta + rnorm(n, sd=sqrt(error_var))

# Get ordering based on marginal correlation
i = order(cor(y, X)^2, decreasing=TRUE)

# Fit AIC / BIC / GCV based on degrees of freedom
fit = criterion.lrgpr( y ~ 1, features=X, order=i)

plot(fit)
```

cv.lrgpr

Cross-validation for lrgpr

Description

Fit cross-validation for multiple ranks of [lrgpr](#)

Usage

```
cv.lrgpr(formula, features, order, nfolds = 10, rank = c(seq(0, 10), seq(20,
  100, by = 10), seq(200, 1000, by = 100)), nthreads = 1)
```

Arguments

formula	standard linear modeling syntax as used in ‘lm’
features	matrix from which the SVD is performed
order	sorted indices of features. When rank is 10, decomp = svd(X[,order[1:10]])
nfolds	number of training sets
rank	array with elements indicating the number of confounding covariates to be used in the random effect.
nthreads	number of threads to be used

Examples

```
n = 300
p = 5000
X = matrix(sample(0:2, n*p, replace=TRUE), nrow=n)

dcmp = svd(X)

# simulate response
h_sq = .8
eta = dcmp$u[,1:2] %*% rgamma(2, 2, 1)
error_var = (1-h_sq) / h_sq * var(eta)
y = eta + rnorm(n, sd=sqrt(error_var))

# Get ordering based on marginal correlation
i = order(cor(y, X)^2, decreasing=TRUE)

# Fit cross-validation
fit = cv.lrgpr( y ~ 1, features=X, order=i)

plot(fit)
```

df.residual.lrgpr *Residual Degrees-of-Freedom*

Description

Residual df from fit of `lrgpr`

Usage

```
df.residual.lrgpr(object, ...)
```

Arguments

object	model fit with <code>lrgpr</code>
...	other arguments

`error.bar`*Plot Error Bars*

Description

Plot error bars for a confidence interval

Usage

```
error.bar(x, y, upper, lower = upper, length = 0.1, ...)
```

Arguments

<code>x</code>	x-axis position
<code>y</code>	y-axis position
<code>upper</code>	height of bar above y
<code>lower</code>	height of bar below y
<code>length</code>	horizontal length of the error bar
<code>...</code>	arguments for <code>arrows(...)</code>

`getAlleleFreq`*Calculate allele frequency*

Description

Calculate allele frequency

Usage

```
getAlleleFreq(X, nthreads = detectCores(logical = TRUE), progress = TRUE)
```

Arguments

<code>X</code>	matrix where each column is a marker coded 0,1,2 or with dosage values in this range
<code>nthreads</code>	number of threads to use
<code>progress</code>	show progress bar

getAlleleVariance *Evaluate variance for each column*

Description

Evaluate variance for each column

Usage

```
getAlleleVariance(X, nthreads = detectCores(logical = TRUE),
  progress = TRUE)
```

Arguments

X	matrix where each column is a marker
nthreads	number of threads to use
progress	show progress bar

getMACHrsq *Evaluate MACH r^2 information metric for each column*

Description

Evaluate MACH r^2 information metric for each column

Usage

```
getMACHrsq(X, nthreads = detectCores(logical = TRUE), progress = TRUE)
```

Arguments

X	matrix where each column is a marker
nthreads	number of threads to use
progress	show progress bar

See definition in Supplementary information S3 for Marchini and Howie (2010):
<http://www.nature.com/nrg/journal/v11/n7/extref/nrg2796-s3.pdf>.
 #' @references Marchini, J. and B. Howie. (2010) Genotype imputation for genome-wide association studies. *Nature Reviews Genetics* 11, 499-511 '

getMissingCount	<i>Count missing values</i>
-----------------	-----------------------------

Description

Count missing values

Usage

```
getMissingCount(X, nthreads = detectCores(logical = TRUE), progress = TRUE)
```

Arguments

X	matrix where each column is a marker
nthreads	number of threads to use
progress	show progress bar

glmApply	<i>Fit standard (i.e. fixed effects) linear or logistic model for many markers</i>
----------	--

Description

Analogous to [lrgprApply](#), but fits standard (i.e. fixed effects) linear or logistic models for many markers

Usage

```
glmApply(formula, features, terms = NULL, family = gaussian(),
  useMean = TRUE, nthreads = detectCores(logical = TRUE), verbose = FALSE,
  progress = TRUE, cincl = c(), cexcl = c())
```

Arguments

formula	standard linear modeling syntax as used in 'lm'. SNP is a place holder for the each successive column of features
features	a matrix where the statistical model is evaluated with SNP if formula replace by each column successively
terms	indices of the coefficients to be tested. The indices corresponding to SNP are used if terms is not specified
family	gaussian() for a continuous response, and binomial() to fit a logit model for a binary response
useMean	if TRUE, replace missing entries with column mean. Otherwise, do not evaluate the model for that column

nthreads	number of to use for parallel execution
verbose	print additional information
progress	show progress bar
cincl	column indeces of features to include for analysis
cexcl	column indeces of features to exclude for analysis

Examples

```
# Generate data
n = 100
p = 500
X = matrix(sample(0:2, n*p, replace=TRUE), nrow=n)
y = rnorm(n)
sex = as.factor(sample(1:2, n, replace=TRUE))

# Fit model for all markers
pValues = glmApply( y ~ sex + sex:SNP, features=X, terms=c(3,4))

# Multivariate model
n = 100
p = 1000
m = 10

Y = matrix(rnorm(n*m), nrow=n, ncol=m)
X = matrix(rnorm(n*p), nrow=n, ncol=p)

res = glmApply( Y ~ SNP, features = X, terms=2)

# p-values for univariate hypothesis test of each feature against
# each response
res$pValues
```

glmApply2

(Experimental) faster version of glmApply

Description

Like glmApply, by linear instead of quadratic as a function of the number of covariates. This is still experimental

Usage

```
glmApply2(formula, features, terms = NULL, family = gaussian(),
  useMean = TRUE, nthreads = detectCores(logical = TRUE), verbose = FALSE,
  progress = TRUE, cincl = c(), cexcl = c())
```

influence.lrgpr	Regression Diagnostics
-----------------	------------------------

Description

Basic quantities for regression diagnostics from fit of `lrgpr`

Usage

```
## S3 method for class 'lrgpr'  
influence(model, ...)
```

Arguments

model	model fit with <code>lrgpr</code>
...	other arguments

leverage.lrgpr	Regression Diagnostics
----------------	------------------------

Description

Basic quantities for regression diagnostics from fit of `lrgpr`

Usage

```
leverage.lrgpr(object)
```

Arguments

object	model fit with <code>lrgpr</code>
--------	-----------------------------------

lm.influence.lrgpr	Regression Diagnostics
--------------------	------------------------

Description

Basic quantities for regression diagnostics from fit of `lrgpr`

Usage

```
lm.influence.lrgpr(object, ...)
```

Arguments

object	model fit with <code>lrgpr</code>
...	other arguments

logLik.lrgpr	<i>Extract Log-Likelihood</i>
--------------	-------------------------------

Description

Log-Likelihood for model fit by `lrgpr`

Usage

```
logLik.lrgpr(object, ...)
```

Arguments

object	model fit with <code>lrgpr</code>
...	other arguments

loss.lrgpr	<i>Loss function</i>
------------	----------------------

Description

Compare observed and fitted response under some loss function

Usage

```
loss.lrgpr(y, yhat, family)
```

Arguments

y	observed response
yhat	fitted response
family	"gaussian" or "binomial"

lrgpr	<i>Fit a Low Rank Gaussian Process Regression (LRGPR) / Linear Mixed Model (LMM)</i>
-------	--

Description

Fit LRGPR/LMM models that account for covariance in response values, but where the scale of the covariance is unknown. Standard linear modeling syntax is used for the model specification in addition to a covariance matrix or its eigen-decomposition.

Usage

```
lrgpr(formula, decomp, rank = max(ncol(decomp$u), ncol(decomp$vectors)),
      delta = NULL, nthreads = 4, W_til = NULL, scale = TRUE,
      diagnostic = FALSE)
```

Arguments

formula	standard linear modeling syntax as used in ‘lm’
decomp	eigen-decomposition produced from eigen(K), where K is the covariance matrix. Or singular value decomposition svd(X[,1:100]) based on a subset of markers
rank	decomposition is truncated to the first rank eigen-vectors
delta	ratio of variance components governing the fit of the model. This should be estimated from a previous evaluation of ‘lm’ on the same response and eigen-decomposition
nthreads	number of threads to use for parallel execution
W_til	markers used to construct decomp that should now be removed from construction of decomp. This is the proximal contamination term of Listgarten, et al. (2012)
scale	should W_til be scaled and centered
diagnostic	compute diagnostic statistics to be used with plot()

Value

coefficients	regression coefficients for each covariate
p.values	p-values from Wald test of each coefficient
sd	standard deviation of each coefficient estimate
sigSq_e	variance component σ_e^2
	corresponding to the residual error
sigSq_a	variance component σ_a^2
	corresponding the scale of the covariance, K

delta	ratio of variance components:	σ_e^2/σ_a^2
rank	the rank of the random effect	
logLik	log-likelihood of the model fit	
fitted.values	estimated response values: y_{hat}	
alpha	BLUP of the random effect	
Sigma	variance-covariate matrix of estimate of beta	
hii	diagonals of the matrix H such that $y_{\text{hat}} = Hy$	
y	responses	
x	design matrix	
df	effective degrees of freedom: trace(H) based on Hoffman (2013)	
residuals	residuals of model fit: $y - y_{\text{hat}}$	
AIC	Akaike information criterion	
BIC	Bayesian information criterion	
GCV	generalized cross-validation	
eigenVectors	eigen-vectors in decomp	
eigenValues	eigen-values in decomp	
df.residual	$n - \text{ncol}(X)$	
rank	rank of decomposition used, where only non-negative eigen/singular values are considered	

Details

`lrgpr` fits the model:

$$y = X\beta + \alpha + \epsilon$$

$$\alpha \sim N(0, K\sigma_a^2)$$

$$\epsilon \sim N(0, \sigma_e^2)$$

where

$$\delta = \sigma_e^2/\sigma_a^2$$

In practice the eigen-decomposition of K , and not K itself is required. The rank can be set to use only eigen-vectors 1:rank in the model.

This package allows hypothesis tests of single coefficients using `fit$p.values` which fits a Wald test. Composite hypothesis tests of multiple coefficients are performed with `wald(fit, terms=1:3)`.

Note that likelihood ratio tests with linear mixed models do not perform well and the resulting p-values often do not follow a uniform distribution under the null (Pinheiro and Bates, 2000). We strongly advise against using it with this model.

`lrgpr` uses the algorithm of Lippert, et al. (2011).

See Hoffman (2013) for an interpretation of the linear mixed model.

References

- Kang, H. M., et al. (2010) Variance component model to account for sample structure in genome-wide association studies. *Nature Genetics* 42, 348-54
- Lippert, C., et al. (2011) FaST linear mixed models for genome-wide association studies. *Nature Methods* 9, 525-26
- Listgarten, J., et al. (2012) Improved linear mixed models for genome-wide association studies. *Nature Methods* 8, 833-5
- Rasmussen, C. E. and Williams, C. K. I. (2006) Gaussian processes for machine learning. MIT Press
- Pinheiro, J. C. and Bates, D. M. (2000) Mixed-Effects Models in S and S-PLUS. Springer, New York
- Hoffman, G. E. (2013) Correcting for Population Structure and Kinship Using the Linear Mixed Model: Theory and Extensions. *PLoS ONE* 8(10):e75707
- Note that degrees freedom and some diagnostic statistics are not currently calculated when `W_til` is specified.

See Also

`wald`, `lrgprApply`

Examples

```
# Generate random data
set.seed(1)
n <- 200
y <- rnorm(n)
K <- crossprod( matrix(rnorm(n*1000), ncol=n) )
age <- rpois(n, 50)
sex <- as.factor(sample(1:2, n, replace=TRUE))
decomp <- eigen(K)

# Fit the model
fit <- lrgpr( y ~ sex + age, decomp, diagnostic=TRUE)

# Print results
fit

# Print more detailed results
summary(fit)

# P-values for each covariate
fit$p.values

# Visualize fit of the model like for `lm'
par(mfrow=c(2,2))
plot(fit)

# Composite hypothesis test using Wald's test
# Joint test of coefficients 2:3
```



```
wald( fit, terms=2:3)
```

lrgprApply

Fit a Low Rank Gaussian Process Regression (LRGPR) / Linear Mixed Model (LMM) for many markers

Description

Fit LRGPR/LMM models that account for covariance in response values, but where the scale of the covariance is unknown. It returns p-values from a Wald test equivalent to the results of using [lrgpr](#) and [wald](#), but is designed to analyze thousands of markers in a single function call.

Usage

```
lrgprApply(formula, features, decomp, terms = NULL,
  rank = max(ncol(decomp$u), ncol(decomp$vectors)), map = NULL,
  distance = NULL, dcmp_features = NULL, W_til = NULL, scale = TRUE,
  delta = NULL, reEstimateDelta = FALSE, nthreads = detectCores(logical =
  TRUE), verbose = FALSE, progress = TRUE, cincl = c(), cexcl = c())
```

Arguments

formula	standard linear modeling syntax as used in ‘lm’. SNP is a place holder for the each successive column of features
features	a matrix where the statistical model is evaluated with SNP if formula replace by each column successively
decomp	eigen-decomposition produced from eigen(K), where K is the covariance matrix. Or singular value decomposition svd(features[,1:100]) based on a subset of markers
terms	indices of the coefficients to be tested. The indices corresponding to SNP are used if terms is not specified
rank	decomposition is truncated to the first rank eigen-vectors
map	p x 2 matrix where each entry corresponds to a marker in features. First column is the marker names, second columns is the genetic or physical location
distance	size of the proximal contamination window in units specified by map.
dcmp_features	the indices in features of the markers used to construct dcmp
W_til	markers used to construct decomp that should now be removed from construction of decomp. This is the proximal contamination term of Listgarten, et al. (2012)
scale	should W_til be scaled and centered
delta	ratio of variance components governing the fit of the model. This should be estimated from a previous evaluation of ‘lm’ on the same response and eigen-decomposition

reEstimateDelta	should delta be re-estimated for every marker. Note: reEstimateDelta=TRUE is much slower
nthreads	number of to use for parallel execution
verbose	print extra information
progress	show progress bar
cincl	column indeces of features to include for analysis
cexcl	column indeces of features to exclude for analysis

Examples

```
# Generate data
n = 100
p = 500
X = matrix(sample(0:2, n*p, replace=TRUE), nrow=n)
y = rnorm(n)
sex = as.factor(sample(1:2, n, replace=TRUE))

K = tcrossprod(matrix(rnorm(n*n*3), nrow=n))
decomp = eigen(K, symmetric=TRUE)

# Fit null model
fit = lrgpr( y ~ sex, decomp)

# Fit model for all markers
pValues = lrgprApply( y ~ sex + sex:SNP, features=X, decomp, terms=c(3,4), delta=fit$delta)
```

```
plot.criterion.lrgpr
```

Plot AIC/BIC/GCV values for lrgpr() model as rank changes

Description

Plots the criteria metrics returned by `criterion.lrgpr`

Usage

```
## S3 method for class 'criterion.lrgpr'
plot(x, col = rainbow(3), ...)
```

Arguments

x	list returned by <code>criterion.lrgpr</code>
col	array of 3 colors
...	other arguments

See Also[criterion.lrgpr](#)

plot.cv.lrgpr*Plot Results of Cross-validation*

Description

Plot results of [cv.lrgpr](#), which fits cross-validation for multiple ranks of the LRGPR

Usage

```
## S3 method for class 'cv.lrgpr'
plot(x, ylim = c(min(x$cve - x$cvse), max(x$cve + x$cvse)),
     xlim = range(x$rank), pch = 20, col = "red",
     main = "Cross validation", xlab = "# of markers used",
     ylab = "Cross validation error", ...)
```

Arguments

x	result of cv.lrgpr
ylim	limits of y-axis
xlim	limits of x-axis
pch	pch
col	col
main	main
xlab	xlab
ylab	ylab
...	other parameters fed to plot()

plot.lrgpr*Plot Diagnostics for an [lrgpr](#) Object*

Description

Six plots (selectable by "which") are currently available: a plot of residuals against fitted values, a Scale-Location plot of $\sqrt{| \text{residuals} |}$ against fitted values, a Normal Q-Q plot, a plot of Cook's distances versus row labels, a plot of residuals against leverages, and a plot of Cook's distances against leverage/(1-leverage). By default, the first three and "5" are provided.

Usage

```
## S3 method for class 'lrgpr'
plot(x, which = c(1L:3L, 5L),
     caption = list("Residuals vs Fitted", "Normal Q-Q", "Scale-Location",
                    "Cook's distance", "Residuals vs Leverage",
                    expression("Cook's dist vs Leverage " * h[ii]/(1 - h[ii]))), panel = if
(add.smooth) panel.smooth else points, sub.caption = NULL, main = "",
ask = prod(par("mfcol")) < length(which) && dev.interactive(), ...,
id.n = 3, labels.id = names(residuals(x)), cex.id = 0.75,
qqline = TRUE, cook.levels = c(0.5, 1),
add.smooth = getOption("add.smooth"), label.pos = c(4, 2),
cex.caption = 1)
```

Arguments

<code>x</code>	<code>lrgpr</code> object.
<code>which</code>	if a subset of the plots is required, specify a subset of the numbers "1:6".
<code>caption</code>	captions to appear above the plots; "character" vector or "list" of valid graphics annotations, see "as.graphicsAnnot". Can be set to "" or "NA" to suppress all captions.
<code>panel</code>	panel function. The useful alternative to "points", "panel.smooth" can be chosen by "add.smooth = TRUE".
<code>sub.caption</code>	common title-above the figures if there are more than one; used as "sub" (s."title") otherwise. If "NULL", as by default, a possible abbreviated version of "deparse(x\$call)" is used.
<code>main</code>	title to each plot-in addition to "caption".
<code>ask</code>	logical; if "TRUE", the user is <code>_ask_ed</code> before each plot, see "par(ask=.)".
<code>...</code>	other parameters to be passed through to plotting functions.
<code>id.n</code>	number of points to be labelled in each plot, starting with the most extreme.
<code>labels.id</code>	vector of labels, from which the labels for extreme points will be chosen. "NULL" uses observation numbers.
<code>cex.id</code>	magnification of point labels.
<code>qqline</code>	logical indicating if a "qqline()" should be added to the normal Q-Q plot.
<code>cook.levels</code>	levels of Cook's distance at which to draw contours.
<code>add.smooth</code>	logical indicating if a smoother should be added to most plots; see also "panel" above.
<code>label.pos</code>	positioning of labels, for the left half and right half of the graph respectively, for plots 1-3.
<code>cex.caption</code>	controls the size of "caption".

See Also

`plot.lm`

predict.lrgpr	<i>Predict response</i>
---------------	-------------------------

Description

Predict response values after training with [lrgpr](#). Leaving X_test and K_test as NULL returns the fitted values on the training set

Usage

```
predict.lrgpr(object, X_test = NULL, K_test = NULL, ...)
```

Arguments

object	model fit from lrgpr on training samples
X_test	design matrix of covariates for test samples
K_test	covariance matrix between samples in the test set and training set
...	other arguments

print.lrgpr	<i>Print Values</i>
-------------	---------------------

Description

Print details for fit from [lrgpr](#)

Usage

```
print.lrgpr(x, ...)
```

Arguments

x	model fit from lrgpr
...	other arguments

```
print.summary.lrgpr
```

Object Summaries

Description

Print summary for fit from `lrgpr`

Usage

```
print.summary.lrgpr(x, ...)
```

Arguments

<code>x</code>	model fit from <code>lrgpr</code>
<code>...</code>	other arguments

```
QQ_plot
```

QQ plot

Description

QQ plot and lambda_GC optimized for large datasets.

Usage

```
QQ_plot(p_values, col = rainbow(min(length(p_values), ncol(p_values))),
  main = "", pch = 20, errors = TRUE, lambda = TRUE, p_thresh = 1e-06,
  showNames = FALSE, ylim = NULL, xlim = NULL, plot = TRUE,
  new = TRUE, box.lty = par("lty"), collapse = FALSE, ...)
```

Arguments

<code>p_values</code>	vector, matrix or list of p-values
<code>col</code>	colors corresponding to the number of columns in matrix, or entries in the list
<code>main</code>	title
<code>pch</code>	pch
<code>errors</code>	show 95% confidence interval
<code>lambda</code>	calculate and show genomic control lambda. Lambda_GC is calculated using the 'median' method on p-values > <code>p_thresh</code> .
<code>p_thresh</code>	Lambda_GC is calculated using the 'median' method on p-values > <code>p_thresh</code> .
<code>showNames</code>	show column names or list keys in the legend
<code>ylim</code>	ylim

xlim	xlim
plot	make a plot. If FALSE, returns lamda_GC values without making plot
new	make a new plot. If FALSE, overlays QQ over current plot
box.lty	box line type
collapse	combine entries in matrix or list into a single vector
...	other arguments

Examples

```
p = runif(1e6)
QQ_plot(p)

# get lambda_GC values without making plot
lambda = QQ_plot(p, plot=FALSE)
```

read.fam	<i>Read plink FAM/TFAM files</i>
----------	----------------------------------

Description

Read FAM/TFAM file into a dataframe. This function is the same as read.tfam

Usage

```
read.fam(file, checkFileExtension = TRUE)
```

Arguments

file	location of FAM/TFAM file
checkFileExtension	If TRUE, throw error if file doesn't end with fam/tfam

read.tfam	<i>Read plink FAM/TFAM files</i>
-----------	----------------------------------

Description

Read FAM/TFAM file into a dataframe. This function is the same as read.fam

Usage

```
read.tfam(file, checkFileExtension = TRUE)
```

Arguments

file location of FAM/TFAM file
 checkFileExtension If TRUE, throw error if file doesn't end with fam/tfam

residuals.lrgpr *Extract Model Residuals*

Description

Residuals fitted with `lrgpr`

Usage

```
residuals.lrgpr(object, type = "working", ...)
```

Arguments

object model fit with `lrgpr`
 type the type of residual, but there is only one option here
 ... other arguments

rstandard.lrgpr *Regression Deletion Diagnostics*

Description

Basic quantities for regression deletion diagnostics from fit of `lrgpr`

Usage

```
## S3 method for class 'lrgpr'
rstandard(model, ...)
```

Arguments

model model fit with `lrgpr`
 ... other arguments

`set_missing_to_mean`*Replace Missing Values with Mean*

Description

For each column, replace NA values with the column mean

Usage

```
set_missing_to_mean(A)
```

Arguments

A	matrix
---	--------

`summary.lrgpr`*Summarizing LRGPR / Linear Mixed Model Fits*

Description

Print summary for fit from `lrgpr`

Usage

```
summary.lrgpr(object, ...)
```

Arguments

object	model fit from <code>lrgpr</code>
...	other arguments

`vcov.lrgpr`*Calculate Variance-Covariance Matrix for a `lrgpr` Object*

Description

Returns the variance-covariance matrix of the main parameters of a fitted model object

Usage

```
vcov.lrgpr(object, ...)
```

Arguments

object	model fit with <code>lrgpr</code>
...	other arguments

 wald

Composite hypothesis test of multiple coefficients

Description

Performs a multi-dimensional Wald test against $H_0: \beta_i \dots \beta_j = 0$ using the estimated coefficients and their variance-covariance matrix

Usage

```
wald(fit, terms)
```

Arguments

fit	result of fitting with lrgpr
terms	indices of the coefficients to be tested

Details

The Wald statistic is

$$\beta_h^T \Sigma_h^{-1} \beta_h \sim \chi_{|h|}^2$$

where

h

specifies the coefficients being tested and

$|h|$

is the number of entries

See Also

[lrgpr](#)

Index

AIC.lrgpr, [2](#)
BIC.lrgpr, [3](#)

coefficients.lrgpr, [3](#)
convertToBinary, [4](#)
cooks.distance.lrgpr, [5](#)
criterion.lrgpr, [5](#), [18](#), [19](#)
cv.lrgpr, [6](#), [19](#)

df.residual.lrgpr, [7](#)

error.bar, [8](#)

getAlleleFreq, [8](#)
getAlleleVariance, [9](#)
getMACHrsq, [9](#)
getMissingCount, [10](#)
glmApply, [10](#)
glmApply2, [11](#)

influence.lrgpr, [12](#)

leverage.lrgpr, [12](#)
lm.influence, [5](#)
lm.influence.lrgpr, [12](#)
logLik.lrgpr, [13](#)
loss.lrgpr, [13](#)
lrgpr, [2](#), [3](#), [5–7](#), [12](#), [13](#), [14](#), [15](#), [17](#), [19–22](#),
[24–26](#)
lrgprApply, [10](#), [16](#), [17](#)

plot.criterion.lrgpr, [18](#)
plot.cv.lrgpr, [19](#)
plot.lrgpr, [19](#)
predict.lrgpr, [21](#)
print.lrgpr, [21](#)
print.summary.lrgpr, [22](#)

QQ_plot, [22](#)

read.fam, [23](#)

read.tfam, [23](#)
residuals.lrgpr, [24](#)
rstandard.lrgpr, [24](#)

set_missing_to_mean, [25](#)
summary.lrgpr, [25](#)

vcov.lrgpr, [25](#)

wald, [16](#), [17](#), [26](#)