

# Package ‘MuMIn’

September 2, 2010

**Type** Package

**Title** Multi-model inference

**Version** 0.13.13

**Date** 2010-09-02

**Encoding** UTF-8

**Author** Kamil Barton

**Maintainer** Kamil Barton <kamil.barton@go2.pl>

**Description** Model selection and model averaging based on information criteria (AICc and alike).

**License** GPL

**Suggests** lme4, nlme

**LazyLoad** yes

## R topics documented:

|                                  |           |
|----------------------------------|-----------|
| MuMIn-package . . . . .          | 2         |
| AICc . . . . .                   | 3         |
| Cement . . . . .                 | 3         |
| dredge . . . . .                 | 4         |
| get.models . . . . .             | 6         |
| miscellaneous . . . . .          | 7         |
| model.avg . . . . .              | 8         |
| par.avg . . . . .                | 12        |
| QAIC . . . . .                   | 13        |
| subset.model.selection . . . . . | 14        |
| <b>Index</b>                     | <b>16</b> |

---

MuMIn-package

*Multi-model inference*

---

## Description

The package `MuMIn` contains functions for (automated) model selection and model averaging based on information criteria (AIC alike).

## Details

User level functions include:

`model.avg` does model averaging.

`get.models` evaluates models from the table returned by `dredge`.

`dredge` runs models with combinations of terms of the supplied 'global.model'.

`AICc` calculates second-order Akaike information criterion for one or several fitted model objects.

## Author(s)

Kamil Bartoń <kamil.barton@go2.pl>

## References

Burnham, K. P. and Anderson, D. R (2002) *Model selection and multimodel inference: a practical information-theoretic approach*. 2nd ed.

## See Also

[AIC](#), [step](#)

## Examples

```
fm1 <- lm(Fertility ~ . , data = swiss)

dd <- dredge(fm1)
top.models.1 <- get.models(dd, subset = delta < 4)
model.avg(top.models.1) # get averaged coefficients

top.models.2 <- get.models(dd, cumsum(weight) <= .95)
model.avg(top.models.2) # get averaged coefficients

# Mixed models:
# modified example(lme)
data(Orthodont, package="nlme")
require(nlme)
fm2 <- lme(distance ~ age + Sex, data = Orthodont, random = ~ 1 | Subject,
method="ML")
dredge(fm2)
```

AICc

*Second-order Akaike Information Criterion***Description**

Calculates second-order Akaike information criterion for one or several fitted model objects (AIC for small samples).

**Usage**

```
AICc(object, ..., k = 2)
```

**Arguments**

|                     |  |
|---------------------|--|
| <code>object</code> | a fitted model object  |
| <code>...</code>    | optionally more fitted model objects   |
| <code>k</code>      | the “penalty” per parameter to be used; the default $k = 2$ is the classical <a href="#">AIC</a> |

**Value**

If just one object is provided, returns a numeric value with the corresponding AICc; if more than one object are provided, returns a `data.frame` with rows corresponding to the objects and columns representing the number of parameters in the model (`df`), AICc and the [AIC](#).

**Author(s)**

Kamil Bartoń

**References**

Burnham, K. P. and Anderson, D. R (2002) *Model selection and multimodel inference: a practical information-theoretic approach*. 2nd ed.

**See Also**

Akaike’s An Information Criterion: [AIC](#)

Cement

*Cement hardening data***Description**

Cement hardening data from Woods et al (1939).

**Usage**

```
data(Cement)
```

**Format**

Cement is a data frame with 5 variables. x1-x4 are four predictor variables expressed as a percentage of weight.

**X1** calcium aluminate

**X2** tricalcium silicate

**X3** tetracalcium alumino ferrite

**X4** dicalcium silicate

**y** calories of heat evolved per gram of cement after 180 days of hardening

**Author(s)**

Kamil Barton

**Source**

Woods H., Steinour H.H., Starke H.R. (1932) Effect of composition of Portland cement on heat evolved during hardening. *Industrial & Engineering Chemistry* 24, 1207-1214

**References**

Burnham, K. P. and Anderson, D. R (2002) *Model selection and multimodel inference: a practical information-theoretic approach*. 2nd ed.

---

dredge

---

*Evaluate "all possible" models*


---

**Description**

Runs models with all possible combinations of the explanatory variables in the supplied model.

**Usage**

```
dredge(global.model, beta = FALSE, eval = TRUE, rank = "AICc",
       fixed = NULL, m.max = NA, subset, marg.ex = NULL, trace = FALSE, ...)
```

```
## S3 method for class 'model.selection':
print(x, abbrev.names = TRUE, ...)
```

**Arguments**

|                           |   |
|---------------------------|---|
| <code>global.model</code> | a fitted 'global' model object. Currently, it can be a <code>lm</code> , <code>glm</code> , <code>rlm</code> , <code>gam</code> , <code>gls</code> , <code>lme</code> , <code>lmer</code> , <code>sarlm</code> or <code>spautolm</code> , but also other types are likely to work (untested). |
| <code>beta</code>         | logical should standardized coefficients be returned rather than normal ones?   |
| <code>eval</code>         | whether to evaluate and rank the models. If <code>FALSE</code> , a list of all possible model formulas is returned  |
| <code>rank</code>         | optional custom rank function (information criterion) to be used instead <code>AICc</code> , e.g. <code>QAIC</code> or <code>BIC</code> , See 'Details'   |

|                           |  |
|---------------------------|--|
| <code>fixed</code>        | optional, either a single sided formula or a character vector giving names of terms to be included in all models   |
| <code>m.max</code>        | optional, maximum number of terms to be included in single model, defaults to the number of terms in <code>global.model</code>   |
| <code>subset</code>       | logical expression to put additional constraints for the set of models. Can contain any of the <code>global.model</code> terms. Run <code>getAllTerms(global.model)</code> to list all the terms. Complex expressions (e.g smooth functions in <a href="#">gam</a> models) should be treated as non-syntactic names and enclosed in backticks (see <a href="#">Quotes</a> ). Mind the spacing, names must match exactly the term names in model's formula. To simply keep variables in all models, use of <code>fixed</code> is preferred. |
| <code>marg.ex</code>      | a character vector specifying names of variables for which NOT to check for marginality restrictions when generating model formulas. If this argument is set to TRUE, all model formulas are used (i.e. no checking). See 'Details'.   |
| <code>trace</code>        | if TRUE, all calls to the fitting function (i.e. updated <code>global.model</code> calls) are printed.   |
| <code>x</code>            | a <code>model.selection</code> object, returned by <code>dredge</code> .   |
| <code>abbrev.names</code> | Should variable names be abbreviated when printing? (useful with many variables)   |
| <code>...</code>          | optional arguments for the <code>rank</code> function. Any can be an expression (of model call), in which case any <code>x</code> within it will be substituted with a current model.  |

## Details

Models are run one by one by calling [update](#) with modified `formula` argument. This method, while robust in that it can be applied to a variety of different models, is not very efficient, so may be time (and memory) consuming.

Handling interactions, `dredge` respects marginality constraints, so "all possible combinations" do not include models containing interactions without their respective main effects. This behaviour can be altered by `marg.ex` argument. It can be used to allow for simple nested designs. For example, with global model of form `a / (x + z)`, use `marg.ex = "a"` and `fixed = "a"`.

`rank` is found by a call to `match.fun` and typically is specified as a function or a symbol (e.g. a backquoted name) or a character string specifying a function to be searched for from the environment of the call to `lapply`.

Function `rank` must be able to accept model as a first argument and must always return a scalar.

## Value

`dredge` returns an object of class `model.selection`, being a [data.frame](#) with models' coefficients, k, deviance/RSS, R-squared, AIC, AICc, delta and weight. This depends on a type of model. Models are ordered according to [AICc](#) (lowest on top), or by `rank` function if specified. The attribute "formulas" is a list containing model formulas.

## Note

Make sure there is no `na.action` set to `na.omit` in `global.model`. This can result with models fitted to different data sets, if there are NA's present.

## Author(s)

Kamil Bartoń

**See Also**

[get.models](#), [model.avg](#). [QAIC](#) has examples of using custom rank function.

There is also [subset.model.selection](#) method.

**Examples**

```
# Example from Burnham and Anderson (2002), page 100:
data(Cement)
lm1 <- lm(y ~ ., data = Cement)
dd <- dredge(lm1)
subset(dd, delta < 4)

#models with delta.aicc < 4
model.avg(get.models(dd, subset = delta < 4)) # get averaged coefficients

#or as a 95% confidence set:
top.models <- get.models(dd, cumsum(weight) <= .95)

model.avg(top.models) # get averaged coefficients

#topmost model:
top.models[[1]]

## Not run:
# Examples of using 'subset':
# exclude models with with both X1 and X2
dredge(lm1, subset = !X1 | !X2)
# keep only models with X3
dredge(lm1, subset = X3)
# the same, but more effective:
dredge(lm1, fixed = ~ X3)

## End(Not run)
```

---

get.models

*Get models*


---

**Description**

Gets list of models from a `model.selection` object

**Usage**

```
get.models(dd, subset = delta <= 4, ...)
```

**Arguments**

|                     |   |
|---------------------|---|
| <code>dd</code>     | object returned by <a href="#">dredge</a>   |
| <code>subset</code> | subset of models  |
| <code>...</code>    | additional parameters passed to <code>update</code> , for example, in <code>lme/lmer</code> one may want to use <code>method = "REML"</code> while using "ML" for model selection |

**Value**

`list` of models.

**Author(s)**

Kamil Bartoń

**See Also**

`dredge`, `model.avg`

**Examples**

```
# Mixed models:

require(nlme)
fm2 <- lme(distance ~ age + Sex, data = Orthodont,
  random = ~ 1 | Subject, method="ML")
dd2 <- dredge(fm2)

# Get top-most models, but fitted by REML:
(top.models.2 <- get.models(dd2, subset = delta < 4, method = "REML"))
```

---

miscellaneous

*Helper functions*

---

**Description**

`beta.weights` - computes standardized coefficients (beta weights) for a model;  
`coeffs` - extracts model coefficients;  
`getAllTerms` - extracts independent variable names from a model object;  
`tTable` - extracts a table of coefficients, standard errors, and p-values from a model object;  
`Weights` - calculates Akaike weights (normalized relative likelihoods)

**Usage**

```
beta.weights(model)
coeffs(model)
getAllTerms(x, ...)
## S3 method for class 'terms':
getAllTerms(x, offset = TRUE, ...)
tTable(model, ...)
Weights(aic, ...)

cbindDataFrameList(x)
rbindDataFrameList(x)
```

**Arguments**

|                     |   |
|---------------------|---|
| <code>model</code>  | a fitted model object   |
| <code>x</code>      | a fitted model object or a <a href="#">formula</a> . for <code>*bindDataFrameList</code> , a list of <code>data.frames</code> |
| <code>offset</code> | should 'offset' terms be included?  |
| <code>...</code>    | other arguments, not used   |
| <code>aic</code>    | a vector of AIC (or other information criterion) values   |

**Details**

The functions `coeffs`, `getAllTerms` and `tTable` provide an interface between the model and `model.avg` (as well as `dredge`). Custom methods can be written to provide support for additional classes of models. Also, a `logLik` method must exist for object.

**Note**

`coeffs`'s value is in most cases identical to that returned by `coef`, the only difference is that it returns fixed effects' coefficients for mixed models.

Functions `*bindDataFrameList` are not exported from the name space, use `MuMIn:::cbindDataFrameList` to access them.

**Author(s)**

Kamil Bartoń

**See Also**

[dredge](#)

---

`model.avg`

*Model averaging*

---

**Description**

Model averaging based on an information criterion.

**Usage**

```
model.avg(m1, ..., beta = FALSE, method = c("0", "NA"), rank = NULL,
rank.args = NULL, alpha = 0.05)

## S3 method for class 'averaging':
coef(object, ...)

## S3 method for class 'averaging':
predict(object, newdata, se.fit = NULL, interval = NULL,
type=NULL, ...)
```



## Arguments

|                               |   |
|-------------------------------|---|
| <code>m1</code>               | A fitted model object or a list of such objects. See ‘Details’  |
| <code>beta</code>             | Logical, should standardized coefficients be returned rather than normal ones?  |
| <code>method</code>           | If set to “0” (default), terms missing in one model are assumed to be 0’s, otherwise they are omitted from the weighted average. See ‘Details’.                                     |
| <code>rank</code>             | Custom rank function (information criterion) to use instead of AICc, e.g. QAIC or BIC, may be omitted if <code>m1</code> is a list returned by <code>dredge</code> . See ‘Details’. |
| <code>rank.args</code>        | Optional list of arguments for the <code>rank</code> function. If one is an expression, an <code>x</code> within it is substituted with a current model.                            |
| <code>alpha</code>            | Significance level for calculating confidence intervals.  |
| <code>object</code>           | An object returned by <code>model.avg</code> .  |
| <code>newdata</code>          | An optional data frame in which to look for variables with which to predict. If omitted, the fitted values are used.  |
| <code>se.fit, interval</code> | Currently not used.   |
| <code>type</code>             | Ignored. Only predictions on the link scale are allowed. Warning is given if user tries something else here.  |
| <code>...</code>              | for <code>model.avg</code> - more fitted model objects, for <code>predict</code> - arguments to be passed to respective <code>predict</code> method                                 |

## Details

`model.avg` has been tested to work with `lm`, `glm`; `rlm` (**MASS**); `gam` (**mgcv**); `lme`, `gls` (**nlme**), `lmer` (**lme4**), as well as with `sarlm` and `spauto1m` (**spdep**). Other types are also likely to work, in particular when they inherit from the supported classes. See ‘Details’ section of the [Miscellaneous](#) page to see how to provide support for other types of models.

`rank` is found by a call to `match.fun` and typically is specified as a function or a symbol (e.g. a backquoted name) or a character string specifying a function to be searched for from the environment of the call to `lapply`.

Function `rank` must be able to accept `model` as a first argument and must always return a scalar.

`predict.averaging` supports `method="NA"` only for linear, fixed effect models. In other cases (e.g. nonlinear or mixed models), prediction is obtained using “brute force”, i.e. by calling `predict` on each component model and weighted averaging the results, which is equivalent to assuming that missing coefficients equal zero (`method="0"`).

Apart from `predict` and `coef`, other default methods, such as `formula` and `residuals` may be used.

## Value

An object of class `averaging`, being a list with elements:

|                           |   |
|---------------------------|---|
| <code>summary</code>      | Model table with deviance, AICc, Delta and weight.  |
| <code>coefficients</code> | the model coefficients  |
| <code>variance</code>     | variance of coefficients  |
| <code>avg.model</code>    | averaged model summary ( <a href="#">data.frame</a> with columns: <code>coef</code> - averaged coefficients, <code>var</code> - unconditional variance estimator, <code>ase</code> - adjusted standard error estimator, <code>lci</code> , <code>uci</code> - unconditional confidence intervals) |

```

relative.importance
    relative variable importances
variable.codes
    Variable names with numerical codes used in the summary
relative.importance
    Relative importance of variables
weights
beta
    (logical) were standardized coefficients used?
model
    the model matrix, analogical to one that would be used in a single model.
residuals
    the residuals (response minus fitted values).

```

**Note**

`predict.averaging` relies on availability of the `predict` methods for the component model classes (except for (g) `lm`).

**Author(s)**

Kamil Bartoń

**References**

Burnham, K. P. and Anderson, D. R (2002) *Model selection and multimodel inference: a practical information-theoretic approach*. 2nd ed.

**See Also**

[dredge](#), [get.models](#). [QAIC](#) has examples of using custom rank function.

**Examples**

```

require(graphics)

# Example from Burnham and Anderson (2002), page 100:
data(Cement)
lm1 <- lm(y ~ ., data = Cement)
dd <- dredge(lm1)
dd

#models with delta.aicc < 4
model.avg(get.models(dd, subset = delta < 4)) # get averaged coefficients

#or as a 95% confidence set:
top.models <- get.models(dd, cumsum(weight) <= .95)

model.avg(top.models) # get averaged coefficients

#topmost model:
top.models[[1]]

## Not run:
# using BIC (Schwarz's Bayesian criterion) to rank the models
BIC <- function(x) AIC(x, k=log(length(residuals(x))))

```

```

mav <- model.avg(top.models, rank=BIC)

## End(Not run)

# Predicted values
nseq <- function(x, len=length(x)) seq(min(x, na.rm=TRUE), max(x, na.rm=TRUE),
length=len)

# New predictors: X1 along the range of original data, other variables held
# constant at their means
newdata <- as.data.frame(lapply(lapply(Cement[1:5], mean), rep, 25))
newdata$X1 <- nseq(Cement$X1, nrow(newdata))

# Predictions from each of the models in a set:
pred <- sapply(top.models, predict, newdata=newdata)
# Add predictions from the models averaged using two methods:
pred <- cbind(pred,
averaged.0=predict(model.avg(top.models, method="0"), newdata),
averaged.NA=predict(model.avg(top.models, method="NA"), newdata)
)

matplot(x=newdata$X1, y=pred, type="l", lwd=c(rep(1,ncol(pred)-2), 2, 2),
xlab="X1", ylab="y")

legend("topleft",
legend=c(lapply(top.models, formula),
paste("Averaged model (method=", c("0", "NA"), ")", sep="")),
col=1:6, lty=1:5, lwd=c(rep(1,ncol(pred)-2), 2, 2), cex = .75
)

## Not run:
# Example with gam models (based on "example(gam)")
require(mgcv)
dat <- gamSim(1, n = 500, dist="poisson", scale=0.1)

gam1 <- gam(y ~ s(x0) + s(x1) + s(x2) + s(x3) + (x1+x2+x3)^2,
family = poisson, data = dat, method = "REML")

cat(dQuote(getAllTerms(gam1)), "\n")

# include only models with smooth OR linear term (but not both) for each variable:
dd <- dredge(gam1, subset=(!`s(x1)` | !x1) & (!`s(x2)` | !x2) & (!`s(x3)` | !x3))
# ...this may take a while.

subset(dd, cumsum(weight) < .95)

top.models <- get.models(dd, cumsum(weight) <= .95)

newdata <- as.data.frame(lapply(lapply(dat, mean), rep, 50))
newdata$x1 <- nseq(dat$x1, nrow(newdata))
pred <- cbind(
sapply(top.models, predict, newdata=newdata),
averaged=predict(model.avg(top.models), newdata)
)

```

```
matplot(x=newdata$x1, y=pred, type="l", lwd=c(rep(1,ncol(pred)-2), 2, 2),
        xlab="x1", ylab="y")

## End(Not run)
```

---

par.avg

*Parameter averaging*


---

## Description

Averages single parameter based on provided weights

## Usage

```
par.avg(x, se, npar, weight, alpha = 0.05)
```

## Arguments

|        |   |
|--------|---|
| x      | vector of parameters                                    |
| se     | vector of standard errors                               |
| npar   | vector giving numbers of estimated parameters           |
| weight | vector of weights                                       |
| alpha  | significance level for calculating confidence intervals |

## Value

par.avg returns a vector with named elements:

|                    |  |
|--------------------|--|
| Coefficient        | model coefficients                     |
| Variance           | unconditional variance of coefficients |
| Unconditional SE   |  |
| Lower CI, Upper CI | relative variable importances          |

## Author(s)

Kamil Bartoń

## References

Burnham, K. P. and Anderson, D. R (2002) *Model selection and multimodel inference: a practical information-theoretic approach*. 2nd ed.

## See Also

[model.avg](#) for averaging models.

---

|      |                  |
|------|------------------|
| QAIC | <i>Quasi AIC</i> |
|------|------------------|

---

## Description

Calculates “quasi AIC” for one or several fitted model objects. This function is provided just as an example of custom rank function for use with `model.avg` and `dredge`

## Usage

```
QAIC(object, ..., chat)
```

## Arguments

|                     |                                       |
|---------------------|---------------------------------------|
| <code>object</code> | a fitted model object.                |
| <code>...</code>    | optionally more fitted model objects. |
| <code>chat</code>   | c - hat                               |

## Details

`rank` is specified as a function or a symbol (e.g. a backquoted name) or a character string specifying a function.

Function `rank` must be able to accept `model` as a first argument and must always return a scalar.

## Value

If just one object is provided, returns a numeric value with the corresponding QAIC; if more than one object are provided, returns a data.frame with rows corresponding to the objects.

## Author(s)

Kamil Barton

## Examples

```
# Based on "example(predict.glm)"
require(graphics)

budworm <- data.frame(ldose = rep(0:5, 2), numdead = c(1, 4, 9, 13, 18, 20, 0,
2, 6, 10, 12, 16), sex = factor(rep(c("M", "F"), c(6, 6))))
budworm$SF = cbind(numdead = budworm$numdead, numalive = 20 - budworm$numdead)

budworm.lg <- glm(SF ~ sex*ldose, data = budworm, family = quasibinomial)

plot(c(1,32), c(0,1), type = "n", xlab = "dose",
      ylab = "prob", log = "x")
text(2^budworm$ldose, budworm$numdead/20, as.character(budworm$sex))
ld <- seq(0, 5, 0.1)
lines(2^ld, predict(budworm.lg, data.frame(ldose=ld,
      sex=factor(rep("M", length(ld)), levels=levels(budworm$sex))),
      type = "response"))
```

```

lines(2^ld, predict(budworm.lg, data.frame(ldose=ld,
      sex=factor(rep("F", length(ld)), levels=levels(budworm$sex))),
      type = "response"))

dd <- dredge(budworm.lg, rank = "QAIC",
chat = summary(budworm.lg)$dispersion)
mod <- get.models(dd, seq(nrow(dd)))
budworm.avg <- model.avg(mod)
model.avg(mod[[1]], mod[[2]], rank = "QAIC", rank.args = list(chat = 1))

linkinv <- quasibinomial()$linkinv
lines(2^ld, linkinv(predict(budworm.avg, data.frame(ldose=ld,
      sex=factor(rep("M", length(ld)), levels=levels(budworm$sex))))) , col=2)
lines(2^ld, linkinv(predict(budworm.avg, data.frame(ldose=ld,
      sex=factor(rep("F", length(ld)), levels=levels(budworm$sex))))) , col=2)
legend("bottomright", legend=c("full", "averaged"), title="Model",
      col=1:2, lty=1)

```

---

subset.model.selection

*Subsetting model selection table*

---

## Description

Return subsets of a model selection table returned by dredge.

## Usage

```

## S3 method for class 'model.selection':
subset(x, subset, select, recalc.weights = TRUE, ...)
## S3 method for class 'model.selection':
x[i, j, recalc.weights = TRUE, ...]

```

## Arguments

|                             |  |
|-----------------------------|--|
| <code>x</code>              | a <code>model.selection</code> object to be subsetting.  |
| <code>subset, select</code> | logical expressions indicating columns and rows to keep. See <a href="#">subset</a> .                            |
| <code>i, j</code>           | indices specifying elements to extract.  |
| <code>recalc.weights</code> | logical value specifying whether Akaike weights should be normalized across the new set of models to sum to one. |
| <code>...</code>            | further arguments passed to <a href="#">[.data.frame]</a> .  |

## Value

A `model.selection` object containing only the selected models (rows). When columns are selected (arguments `select` or `j` are provided), a plain `data.frame` is returned.

**Author(s)**

Kamil Bartoń

**See Also**

[dredge](#), [subset](#) and [\[.data.frame\]](#) for subsetting and extracting from data.frames.

# Index

## \*Topic **datasets**

Cement, [3](#)

## \*Topic **manip**

miscellaneous, [7](#)

subset.model.selection, [13](#)

## \*Topic **models**

AICc, [2](#)

dredge, [4](#)

get.models, [6](#)

miscellaneous, [7](#)

model.avg, [8](#)

MuMin-package, [1](#)

par.avg, [11](#)

QAIC, [12](#)

## \*Topic **package**

MuMin-package, [1](#)

[.data.frame, [14](#)

[.model.selection  
(subset.model.selection),  
[13](#)

AIC, [2](#), [3](#)

AICc, [2](#), [5](#)

beta.weights (miscellaneous), [7](#)

cbindDataFrameList  
(miscellaneous), [7](#)

Cement, [3](#)

coef, [7](#)

coef.averaging (model.avg), [8](#)

coeffs (miscellaneous), [7](#)

data.frame, [5](#), [9](#)

dredge, [4](#), [6](#), [8](#), [10](#), [12](#), [14](#)

formula, [7](#)

gam, [4](#)

get.models, [5](#), [6](#), [10](#)

getAllTerms (miscellaneous), [7](#)

list, [6](#)

Miscellaneous, [9](#)

Miscellaneous (miscellaneous), [7](#)

miscellaneous, [7](#)

model.avg, [5](#), [6](#), [8](#), [12](#)

MuMin (MuMin-package), [1](#)

MuMin-package, [1](#)

par.avg, [11](#)

predict.averaging (model.avg), [8](#)

print.averaging (model.avg), [8](#)

print.model.selection (dredge), [4](#)

QAIC, [5](#), [10](#), [12](#)

Quotes, [4](#)

rbindDataFrameList  
(miscellaneous), [7](#)

step, [2](#)

subset, [14](#)

subset.model.selection, [5](#), [13](#)

tTable (miscellaneous), [7](#)

update, [5](#)

Weights (miscellaneous), [7](#)