



1.6 Legalese

This program is free software; you can redistribute it and/or modify it under the terms of the GNU

3.2 Threshold Selection

The location for the GPD or equivalently the threshold is a particular parameter as must often it is not






Figure 2: The threshold selection using the mrlplot function

The quantity

3.2.3 L-Moments plot: *lmomplot*

L-moments are summary statistics for probability distributions and data samples. They are analogous to ordinary moments – they provide measures of location, dispersion, skewness, kurtosis, and other aspects of the shape of probability distributions or data samples – but are computed from linear combinations of the ordered data values (hence the prefix L).

For the GPD, the following relation holds:




Figure 3: fig: The threshold selection using the Imomplot function

3.3 Fitting the GPD

3.3.1 The univariate case

The main function to fit the GPD is called **fitgpd**. This is a generic function which can fit the GPD according several estimators. There are currently 7 estimators available: method of moments moments, maximum likelihood mle

Standard Error Type: observed

Standard Errors

scale

0.2178

Asymptotic Variance Covariance

scale

scale 0.04744

Optimization Information

Convergence: successful

Function Evaluations: 6

Threshold Call: c(1, 2)
Number Above: 500
Proportion Above: 1

Estimates
scale shape
0.330151 -0.009522

Standard Error Type: observed

Standard Errors
scale shape
0.02172 0.04827

Asymptotic Variance Covariance
scale shape
scale 0.0004719 -0.0007754
shape -0.0007754 0.0023297

Optimization Information
Convergence: successful
Function Evaluations: 52
Gradient Evaluations: 12

scal e1 shape1 scal e2 shape2 al pha

structure using a Markov Chains while the joint distribution is obviously a multivariate extreme value


```
> x <- rgpd(200, 1, 2, 0.25)
> mle <- fitgpd(x, 1, method = "mle")
> mom <- fitgpd(x, 1, method = "moments")
```

If there is some troubles try to put `vert.lines = FALSE` or change the range...

```
conf.inf conf.sup
1.719697 2.468182
```

If there is some troubles try to put `vert.lines = FALSE` or change the range...

```
conf.inf conf.sup
0.1424242 0.3909091
```





Figure 6: The profile log-likelihood confidence intervals¹⁸


conf. inf conf. sup
9.368588 11.270484

there...
conf. inf conf. sup


Probability plot




QQ-plot




Density Plot



Return Level Plot








Figure 10: Instantaneous flood discharges and averaged discharged over duration 3 days. Data ardieres

3.7.2 Unbiased Sample L-Moments: *samlmu*

The function **samlmu** computes the unbiased sample L-Moments.

```
> x <- runif(50)
> samlmu(x, nmom = 5)
```


| time | | obs | |
|---------|--------|---------|---------|
| Min. | : 1970 | Min. | : 0.022 |
| 1st Qu. | : 1981 | 1st Qu. | : 0.236 |

The result of function **fitgpd** gives the name of the estimator, if a varying threshold was used, the threshold value, the number and the proportion of observations above the threshold, parameter estimates, standard error estimates and type, the asymptotic variance-covariance matrix and convergence diagnostic.

Figure 12 shows graphic diagnostics for the fitted model. It can be seen that the fitted model "mle" seems to be appropriate. Suppose we want to know the return level associated to the 100-year return period.

```
> rp2prob(retper = 100, npy = npy)
```

```
      npy retper      prob
1 1.707897    100 0.9941448
```

```
> prob <- rp2prob(retper = 100, npy = npy)[, "prob"]
> qgpd(prob, loc = 6, scale = mle$param["scale"], shape = mle$param["shape"])
```

```
      scale
36.44331
```

To take into account uncertainties, Figure 13 depicts the profile confidence interval for the quantile associated to the 100-year return period.

```
> gpd.pfci(mle, prob, range = c(25, 100), nrang = 200)
```

If there is some troubles try to put `vert.lines = FALSE` or change the range...

```
conf.inf conf.sup
25.56533 90.76633
```

Sometimes it is necessary to know the estimated return period of a specified events. Lets do it with the larger events in "events1".

