Interface to use SIMPLACE from R

Gunther Krauss

December 3, 2013

1 Introduction

This package provides methods to interact with the modelling framework SIMPLACE¹. SIMPLACE is written in Java (and some parts in Scala) so one can access it from R via rJava. The purpose of this package is to simplify the interaction between R and SIMPLACE, by providing functions to:

- initialize and configure SIMPLACE
- load a simulation (solution and project)
- parameterize the simulation
- run whole simulation or run it stepwise
- get simulation output and convert it to formats suitable for R

2 Installing the Simplace Framework

For installing SIMPLACE, please consult the webpage www.simplace.net. A brief guide to install SIMPLACE:

- If you don't have installed Java, please install an appropriate version of the (JRE or JDK) from java.com
- Download the console mode of Simplace from www.simplace.net
- Unpack the zip archive to your disk. You have to unpack the whole directory SIMPLACE and the directory must not be renamed.
- Install the simplace package in R: install.packages('simplace',repos='http://r-forge.r-project.org')

3 Basic Usage

The usage of Simplace in R follows roughly this scheme:

- init Simplace by providing the path to your simplace installation directory, your working directory and your outputs
- open a Simplace project form a solution (and project) file
- create a list of simulation parameters you want to change
- create and run a Simulation

 $^{^1}$ Scientific Impact assessment and Modelling PLatform for Advanced Crop and Ecosystem management - www.simplace.net

- get the result from the simulation
- convert the result to a R object (data.frame, list etc.)


4 Example

4.1 Run the simulation

```
> library(simplace)
> SimplaceInstallationDir <- "c:/software/entwicklung/"
> SimplaceDataDir <- "D:/java/simplace/"</pre>
> SimplaceWorkDir <- paste(SimplaceInstallationDir, "SIMPLACE/SIMPLACE_WORK/", sep="")
> SimplaceOutputDir <- paste(SimplaceInstallationDir, "SIMPLACE/output/", sep="")
> Solution <- paste(SimplaceWorkDir, "gk/solution/complete/Complete.sol.xml", sep="")
> simplace <- initSimplace(SimplaceInstallationDir,SimplaceWorkDir,SimplaceOutputDir)
> openProject(simplace, Solution)
> parameter <- list()</pre>
> parameter$enddate <- "31-12-1993"
> createSimulation(simplace, parameter)
[1] "testproject__TESTSIMULATIONOOO"
> runSimulations(simplace)
> simulationlist <-getSimulationIDs(simplace)</pre>
> result <- getResult(simplace, "DIAGRAM_OUT", simulationlist[[1]]);</pre>
> closeProject(simplace)
```

4.2 Get the result and plot it


Simulated Biomass



4.3 Get arrays and plot them as contour plot

- > resultlistexp <- resultToList(result,expand=TRUE)</pre>
- > water <- resultlistexp\$BOTTOM_ARRAY_VolumetricWaterContent
- > wmat <- do.call(rbind, water)</pre>
- > wmatpart <- wmat[dates,]</pre>
- > filled.contour(dates,1:dim(wmatpart)[2],wmatpart,
- + xlab="Day", ylab="Layer", main="Water content in soil")

Water content in soil



Contents

1	Introduction	1
2	Installing the Simplace Framework	1
3	Basic Usage	1
4	Example	2
	4.1 Run the simulation	2
	4.2 Get the result and plot it	2
	4.3 Get arrays and plot them as contour plot	3