

Package ‘SuperCurveGUI’

July 6, 2017

Version 2.1.5

Date 2015-07-27

Title 'SuperCurve' GUI Package

Author P. Roebuck

Maintainer ``P. Roebuck" <proebuck@mdanderson.org>

Description Graphical User Interface for RPPA analysis using the 'SuperCurve' package.

Depends R (>= 2.15)

Imports methods, tcltk, SuperCurve (>= 1.5), tclish (>= 1.0)

SystemRequirements Tcl/Tk

NeedsCompilation no

URL <http://supercurve.r-forge.r-project.org/#SuperCurveGUI>

License Artistic-2.0

Copyright file COPYRIGHTS

LazyLoad yes

Repository R-Forge

Repository/R-Forge/Project supercurve

R topics documented:

SuperCurveGUI-package	1
supercurveGUI	2
Index	4

SuperCurveGUI-package *GUI for reverse phase protein lysate array analysis*

Description

A package for analyzing reverse phase protein lysate arrays (RPPA).

Details

Package: SuperCurveGUI
 Type: Package
 Version: 2.1.5
 Date: 2015-07-27
 License: Artistic-2.0

For a complete list of functions, use `library(help="SuperCurveGUI")`.
 For a high-level summary of the changes for each revision, use
`file.show(system.file("NEWS", package="SuperCurveGUI"))`.

Author(s)

P. Roebuck <proebuck@mdanderson.org>

supercurveGUI

Graphical User Interface for the SuperCurve package

Description

Graphical User Interface for the SuperCurve package.

Usage

```
supercurveGUI()
scui()
```

Details

The function `supercurveGUI` launches a Graphical User Interface for the **SuperCurve** package. The GUI uses Tk widgets (via the R-Tcl/Tk interface by Peter Dalgaard) in order to provide a simple interface to the SuperCurve functions for analyzing reverse phase protein lysate arrays.

The function `scui` is an alias for the aforementioned function.

If set, the environment variable `SC_DIR` will be used as the initial location for the directory containing quantification files.

Resources

The Tk options database is loaded from user-specific defaults files, such as `‘.Xdefaults’`, and resource databases loaded into the X server. The package will attempt to load its resources upon startup, following the X11R5 method of merging app-default files from multiple sources. The standard X11 paths are searched first, followed by paths specified by the environment variables `XFILESEARCHPATH`, `XAPPLRESDIR`, `XUSERFILESEARCHPATH`, respectively. Unlike X11, **ALL** matching files will be loaded, not just the first.

One way to make use of the options database is to create a file named `‘supercurveGUI.ad’` in your home directory, specifying any desired resources. Set your `XUSERFILESEARCHPATH` environment variable within R with the command:

```
Sys.setenv(XUSERFILESEARCHPATH=file.path(path.expand("~"), "%N.ad"))
```

For example, to cause **SuperCurve** to convert each quantification file as it's read from a single subgrid physical layout into its actual logical one by default, add the following resource value to the app-defaults file mentioned above:

```
*software: superslide
```

Author(s)

P. Roebuck <proebuck@mdanderson.org>

Examples

```
## Not run:
supercurveGUI()
# -or-
scui()

## End(Not run)
```

Index

*Topic **IO**

supercurveGUI, [2](#)

*Topic **package**

SuperCurveGUI-package, [1](#)

scui (supercurveGUI), [2](#)

supercurveGUI, [2](#)

SuperCurveGUI-package, [1](#)