

Package ‘Wats’

December 16, 2013

Title Wrap Around Time Series graphics

Description Wrap-around Time Series (WATS) Plots for Interrupted Time Series Designs

Version 0.1-11

Author Will Beasley [aut, cre], Joe Rodgers [aut], Matthew Schuelke [ctb]

Maintainer Will Beasley <wibeasley@hotmail.com>

URL <https://github.com/wibeasley/Wats>, <https://r-forge.r-project.org/projects/wats/>

Depends R (>= 3.0.0), stats

Imports colorspace, ggplot2, grid, lubridate, plyr, RColorBrewer, scales, testit, zoo

Suggests devtools, knitr, testthat

License GPL (>= 2)

LazyData TRUE

VignetteBuilder knitr

Date 2013-12-13

R topics documented:

AnnotateData	2
AugmentCycleData	3
LinearPeriodicPlot	3
LinearRollingPlot	5
Wats	7
Index	8

AnnotateData

Finds midpoints and bands for the within and between cycles.

Description

Finds midpoints and bands for the within and between cycles.

Usage

```
AnnotateData(dsLinear, dvName, centerFunction, spreadFunction,
  cycleTallyName = "CycleTally", stageIDName = "StageID",
  stageProgressName = "StageProgress",
  proportionThroughCycleName = "ProportionThroughCycle",
  proportionIDName = "ProportionID",
  terminalPointInCycleName = "TerminalPointInCycle")
```

Arguments

<code>dsLinear</code>	The data.frame to containing the detailed data.
<code>dvName</code>	The name of the dependent/criterion variable.
<code>centerFunction</code>	A function to calculate the center of a subsample.
<code>spreadFunction</code>	A function to calculate the bands of a subsample.
<code>cycleTallyName</code>	The variable name indicating how many cycles have been completed.
<code>stageIDName</code>	The variable name indicating the stage. In a typical interrupted time series, these values are 1 before the interruption and 2 after.
<code>stageProgressName</code>	The variable name indicating the stage in a decimal form. This is mostly for internal uses.
<code>proportionThroughCycleName</code>	The variable name indicating how far the point is through a cycle. For example, 0 degrees would be 0, 180 degrees would be 0.5, 359 degrees would be 0.9972, and 360 degrees would be 0.
<code>proportionIDName</code>	The variable name indicating the ordinal position through a cycle.
<code>terminalPointInCycleName</code>	The variable name indicating the last point within a given cycle.

Value

Returns a data.frame with additional variables «Say what they are».

Examples

```
a <- 32+323
```

AugmentCycleData	<i>Calculates variables necessary for WATS Plots</i>
------------------	--

Description

Calculates variables necessary for WATS Plots

Usage

```
AugmentYearDataWithMonthResolution(dsLinear, dateName, stageIDName)
```

Arguments

dsLinear	The data.frame to containing the detailed data.
dateName	The variable name in dsLinear containing the date or datetime value.
stageIDName	The variable name indicating the stage. In a typical interrupted time series, these values are 1 before the interruption and 2 after.

Value

Returns a data.frame with additional variables: CycleTally, ProportionThroughCycle, ProportionID, and TerminalPointInCycle.

Examples

```
a <- 32+323
```

LinearPeriodicPlot	<i>Linear Plot with Periodic Elements</i>
--------------------	---

Description

Shows the interrupted time series in Cartesian coordinates and its a periodic/cyclic components.

Usage

```
LinearPeriodicPlot(dsLinear, dsPeriodic, xName, yName, stageIDName,
  periodicLowerName = "PositionLower", periodicUpperName = "PositionUpper",
  paletteDark = NULL, paletteLight = NULL, changePoints = NULL,
  changePointLabels = NULL, jaggedPointSize = 2, jaggedLineSize = 0.5,
  bandAlphaDark = 0.4, bandAlphaLight = 0.15, changeLineAlpha = 0.5,
  changeLineSize = 3, title = NULL, xTitle = NULL, yTitle = NULL)
```

Arguments

<code>dsLinear</code>	The <code>data.frame</code> to containing the simple linear data. There should be one record per observation.
<code>dsPeriodic</code>	The <code>data.frame</code> to containing the reoccurring/periodic bands. There should be one record per observation per stage. If there are three stages, this <code>data.frame</code> should have three times as many rows as <code>dsLinear</code> .
<code>xName</code>	The variable name containing the date.
<code>yName</code>	The variable name containing the dependent/criterion variable.
<code>stageIDName</code>	The variable name indicating which stage the record belongs to. For example, before the first interruption, the <code>StageID</code> is 1, and is 2 afterwards.
<code>periodicLowerName</code>	The variable name showing the lower bound of a stage's periodic estimate.
<code>periodicUpperName</code>	The variable name showing the upper bound of a stage's periodic estimate.
<code>paletteDark</code>	A vector of colors used for the dark/heavy graphical elements. The vector should have one color for each <code>StageID</code> value. If no vector is specified, a default will be chosen, based on the number of stages.
<code>palettelight</code>	A vector of colors used for the light graphical elements. The vector should have one color for each <code>StageID</code> value. If no vector is specified, a default will be chosen, based on the number of stages.
<code>changePoints</code>	A vector of values indicate the interruptions between stages. It typically works best as a <code>Date</code> or a <code>POSIXct</code> class.
<code>changePointLabels</code>	The text plotted above each interruption.
<code>jaggedPointSize</code>	The size of the observed data points.
<code>jaggedLineSize</code>	The size of the line connecting the observed data points.
<code>bandAlphaDark</code>	The amount of transparency of the band appropriate for a stage's x values.
<code>bandAlphaLight</code>	The amount of transparency of the band comparison stages for a given x value.
<code>changeLineAlpha</code>	The amount of transparency marking each interruption.
<code>changeLineSize</code>	The width of a line marking an interruption.
<code>title</code>	The string describing the plot.
<code>xTitle</code>	The string describing the x -axis.
<code>yTitle</code>	The string describing the y -axis.

Value

Returns a `ggplot2` graphing object

Examples

```
require(Wats) #Load the package
filePathOutcomes <- file.path(devtools::inst(name="Wats"), "extdata", "BirthRates0k.txt")
dsLinear <- read.table(filePathOutcomes, header=TRUE, sep="\t", stringsAsFactors=FALSE)
dsLinear$Date <- as.Date(dsLinear$Date)
dsLinear$MonthID <- NULL
changeMonth <- as.Date("1996-02-15")
```

```

dsLinear$StageID <- ifelse(dsLinear$Date < changeMonth, 1L, 2L)
dsLinear <- AugmentYearDataWithMonthResolution(dsLinear=dsLinear, dateName="Date")
hSpread <- function( scores ) { return( quantile(x=scores, probs=c(.25, .75)) ) }
portfolio <- AnnotateData(
  dsLinear,
  dvName = "BirthRate",
  centerFunction = median,
  spreadFunction = hSpread
)

LinearPeriodicPlot(
  portfolio$dsLinear,
  portfolio$dsPeriodic,
  xName = "Date",
  yName = "BirthRate",
  stageIDName = "StageID",
  changePoints = changeMonth,
  changePointLabels = "Bombing Effect"
)

```

LinearRollingPlot	<i>Linear Plot with Rolling Summaries</i>
-------------------	---

Description

Shows the interrupted time series in Cartesian coordinates without a periodic/cyclic components.

Usage

```

LinearRollingPlot(dsLinear, xName, yName, stageIDName,
  rollingLowerName = "RollingLower", rollingCenterName = "RollingCenter",
  rollingUpperName = "RollingUpper", paletteDark = NULL,
  paletteLight = NULL, colorSparse = grDevices::adjustcolor("tan1", 0.5),
  changePoints = NULL, changePointLabels = NULL, drawJaggedLine = TRUE,
  drawRollingLine = TRUE, drawRollingBands = TRUE,
  drawSparseLineAndPoints = TRUE, jaggedPointSize = 2,
  jaggedLineSize = 0.5, rollingLineSize = 1, sparsePointSize = 4,
  sparseLineSize = 0.5, bandAlpha = 0.4, changeLineAlpha = 0.5,
  changeLineSize = 3, title = NULL, xTitle = NULL, yTitle = NULL)

```

Arguments

dsLinear	The data.frame to containing the data.
xName	The variable name containing the date.
yName	The variable name containing the dependent/criterion variable.
stageIDName	The variable name indicating which stage the record belongs to. For example, before the first interruption, the StageID is 1, and is 2 afterwards.
rollingLowerName	The variable name showing the lower bound of the rolling estimate.
rollingCenterName	The variable name showing the rolling estimate.

rollingUpperName	The variable name showing the upper bound of the rolling estimate.
paletteDark	A vector of colors used for the dark/heavy graphical elements. The vector should have one color for each StageID value. If no vector is specified, a default will be chosen, based on the number of stages.
paletteLight	A vector of colors used for the light graphical elements. The vector should have one color for each StageID value. If no vector is specified, a default will be chosen, based on the number of stages.
colorSparse	The color of the 'slowest' trend line, which plots only one value per cycle.
changePoints	A vector of values indicate the interruptions between stages. It typically works best as a Date or a POSIXct class.
changePointLabels	The text plotted above each interruption.
drawJaggedLine	A boolean value indicating if a line should be plotted that connects the observed data points.
drawRollingLine	A boolean value indicating if a line should be plotted that connects the rolling estimates specified by rollingCenterName.
drawRollingBands	A boolean value indicating if a band should be plotted that envelopes the rolling estimates (whose values are take from the rollingLowerName and rollingUpperName).
drawSparseLineAndPoints	A boolean value indicating if the sparse line and points should be plotted.
jaggedPointSize	The size of the observed data points.
jaggedLineSize	The size of the line connecting the observed data points.
rollingLineSize	The size of the line connecting the rolling estimates.
sparsePointSize	The size of the sparse estimates.
sparseLineSize	The size of the line connecting the sparse estimates.
bandAlpha	The amount of transparency of the rolling estimate band.
changeLineAlpha	The amount of transparency marking each interruption.
changeLineSize	The width of a line marking an interruption.
title	The string describing the plot.
xTitle	The string describing the x -axis.
yTitle	The string describing the y -axis.

Value

Returns a ggplot2 graphing object

Examples

```

require(Wats) #Load the package
filePathOutcomes <- file.path(devtools::inst(name="Wats"), "extdata", "BirthRatesOk.txt")
dsLinear <- read.table(filePathOutcomes, header=TRUE, sep="\t", stringsAsFactors=FALSE)
dsLinear$Date <- as.Date(dsLinear$Date)
dsLinear$MonthID <- NULL
changeMonth <- as.Date("1996-02-15")
dsLinear$StageID <- ifelse(dsLinear$Date < changeMonth, 1L, 2L)
dsLinear <- AugmentYearDataWithMonthResolution(dsLinear=dsLinear, dateName="Date")
hSpread <- function( scores ) { return( quantile(x=scores, probs=c(.25, .75)) ) }
portfolio <- AnnotateData(
  dsLinear,
  dvName = "BirthRate",
  centerFunction = median,
  spreadFunction = hSpread
)

LinearRollingPlot(
  portfolio$dsLinear,
  xName = "Date",
  yName = "BirthRate",
  stageIDName = "StageID",
  changePoints = changeMonth,
  changePointLabels = "Bombing Effect"
)

```

Wats

Wats

Description

Wats

Index

*Topic **linear**

LinearPeriodicPlot, [3](#)

LinearRollingPlot, [5](#)

AnnotateData, [2](#)

AugmentCycleData, [3](#)

AugmentYearDataWithMonthResolution
(AugmentCycleData), [3](#)

AugmentYearDataWithSecondResolution
(AugmentCycleData), [3](#)

LinearPeriodicPlot, [3](#)

LinearRollingPlot, [5](#)

Wats, [7](#)

Wats-package (Wats), [7](#)