
# Spectra: A Flexible Infrastructure for Mass Spectrometry Data

Sebastian  $\mathsf{Gibb}^1$ , Laurent  $\mathsf{Gatto}^2$  and  $\mathsf{Johannes}\ \mathsf{Rainer}^3$ 



<sup>&</sup>lt;sup>2</sup> de Duve Institute, UCLouvain, Brussels, Belgium



## Mass Spectrometry (MS) Data

- Paired measurements:
  - intensity (counts) vs m/z (mass-to-charge ratio).
  - intensity vs retention time.
- Additional various metatdata.

### Problems

- Vendor-specific, closed file formats.
- Various open-formats, e.g. mzML, mzXML, mz5, CDF, MGF, CSV.
- Spectra libraries/Annotation information in databases, e.g.
   SQL.
- Multiple R -packages require different file formats and/or data structures.
- Larger experiments don't fit into RAM.

# Solution: Spectra[1]

- Common, flexible data structure and interface.
- Lazy and parallel evaluation.
- Supports various file formats by different backends.

#### Spectra class

- Handles one or multiple MS spectra.
- Implements typical processing functionality.
- Isolation from type of data storage (handled by backend classes)

## MsBackend classes

- Isolation from spectra handling and processing.
- Specific class for each type of data storage.

| class                     | source.files        | storage   | writeable |
|---------------------------|---------------------|-----------|-----------|
| MsBackendDataFrame[1]     | manual              | in-memory | yes       |
| MsBackendHdf5Peaks[1]     | hdf5                | on-disk   | yes       |
| MsBackendMzR[1]           | mzML, mzXML and CDF | on-disk   | no        |
| MsBackendHmdbXml[2]       | XML                 | on-disk   | yes       |
| MsBackendRawFileReader[3] | Thermo .raw         | on-disk   | no        |




Figure 1: The user interacts with a Spectra object. It takes care of the data storage by different backend classes.

## Example

```
# Load packages
library("Spectra")
library("magrittr")
# Import data
sps <- Spectra(</pre>
    "20191107_Mix2_CE20.mzML",
    backend = MsBackendMzR()
# Select all MS2 spectra for a [M+H]+ ion of
# Histidine
mzr <- 156.07675 # Histidine
his <- sps %>%
    filterMsLevel(2) %>%
    filterPrecursorMz(
        mz = mzr + ppm(c(-mzr, mzr), 20)
# Centroid and clean spectra.
his <- fruct %>%
    pickPeaks() %>%
    removePeaks(threshold = 500) %>%
    clean(all = TRUE)
## Error in eval(lhs, parent, parent): object 'fruct' not
found
# Change backend: load data in memory.
his <- setBackend(his, MsBackendDataFrame())</pre>
```

#### Contact

- https://github.com/rformassspectrometry/Spectra
- https://rformassspectrometry.org
- https://twitter.com/search?q=%23rformassspec

## References

- [1] Laurent Gatto, Johannes Rainer, and Sebastian Gibb.
   Spectra: Spectra Infrastructure for Mass Spectrometry Data, 2019.
   R package version 0.3.0.
- [2] Laurent Gatto, Johannes Rainer, and Sebastian Gibb.
   MsBackendHmdb: Mass spectrometry data backends for The Human Metabolome Database, 2019.
   R package version 0.1.0.
- [3] Christian Panse and Tobias Kockmann.
  MsBackendRawFileReader: Bridging Spectra and ThermoFinnigan raw files, 2019.
  R package version 0.0.1.

<sup>&</sup>lt;sup>3</sup> Institute for Biomedicine, Eurac Research, Italy