

Your Title Here

Optional Subtitle

Raphaël Fournier^{1*} , Paul Downing² & Richard Ramsey¹

¹Neural Control of Movement Laboratory, Department of Health Sciences and Technology, ETH Zurich

²Name, department

Your abstract goes here. This will appear prominently at the top of your document.

Keywords: keyword1, keyword2, keyword3

Words: 4063

Introduction

The ability to quickly and correctly recognize a familiar face is important in our everyday life. Not only does this ability allow us to anticipate another person's behaviour, but this recognition will influence our own behaviour as well. People will behave differently in function of the identity of the person they are interacting with. Most of the previous research focusing on face recognition has used manifest measures (i.e. response times and accuracy) to assess one's ability to recognize faces. However, less is known about the computational processes that support face recognition. We investigated how different types of face familiarity affected the latent variables estimated by evidence accumulation models (EAMs; Ratcliff and Rouder (1998)). This computational approach has provided new insights on the dynamics of the decision process supporting face recognition.

The face recognition process has been intensely investigated over the last 50 years (Johnston and Edmonds 2009; Natu and O'Toole 2011). One of the most influential models describing the face recognition process is the functional model of face recognition proposed by Bruce and Young (1986). This model advances that visual recognition happens when the encoded structural representation of a face matches the stored structural code of the same face. These structural codes are contained in the face recognition units (FRUs) which have access to person identity nodes that contains identity-specific semantic information. Based on neuroimaging findings, researchers have adapted this model to relate its different components to specific brain areas (Gobbini and Haxby 2006, 2007; Haxby, Hoffman, and Gobbini 2000). This general model of the distributed neural system for familiar face recognition incorporates two distinct systems. The core system, composed by the inferior occipital gyrus (occipital face area, OFA), the inferior fusiform gyrus (fusiform face area, FFA) and the posterior superior temporal sulcus (pSTS), is dedicated to modality-specific visual processing of faces. The core system is involved in the recognition of faces established on visual features only. The extended system participates in the encoding of the person knowledge and is mediated by a broader

network of brain areas (Duchaine and Yovel 2015; Gobbini and Haxby 2007; Haxby, Hoffman, and Gobbini 2000; Ishai 2008; Kanwisher and Barton 2011). The extended system support the recognition of faces for which prior semantic knowledge have been stored, like famous faces (Ida Gobbini et al. 2004) or personally familiar faces (Leibenluft et al. 2004), by mediating the retrieval of identity-specific information from memory. **The (duality) in cortical structures involved in the recognition of personally familiar faces and visually familiar faces has also been found in monkeys studies, supposing that (cross-species) - Landi et al. (2021).**

Previous studies have shown that the association of visual familiarity and identity-specific information was also reflected on manifest variables (i.e response times and accuracy) in tasks assessing face recognition ability. Several studies have shown that exposures accompanied by conceptual information such as name or occupation (Akan and Benjamin 2023; Schwartz and Yovel 2016), or involving a deeper level of processing (Schwartz and Yovel 2019) increased one's ability to discriminate **well-familiar faces** from novel faces compared to the ability to discriminate visually familiar faces from novel faces. Conceptual representations associated with a specific face improves the later recognition of this face. Another line of work on face recognition memory has also investigated how prior familiarity (familiarity of a face before a study) influences performance during a face recognition task. Using famous faces (i.e faces of celebrities) or personally familiar faces (i.e. faces of friends or family members), these studies has reported a superior discriminability for these **well-familiar faces** over visually familiar faces (Akan and Benjamin 2023; Bird et al. 2011; Klatzky and Forrest 1984; Schwaninger, Lobmaier, and Collishaw 2002). **Final sentence here**

For the last 50 years, research on face perception and face recognition has been singularly dominated by the separate analysis of manifest variables (i.e. response times and accuracy; ref) or a discriminability score, d' , calculated as the ratio between the number of hits (when the target was correctly recognized) and the number of false alarm (FA, when the distractor was wrongly recognized as a target, ref.). The analysis of these variables has outlined the understanding framework (or how we understand) of face perception and face recognition. The

*Send correspondence to: Raphaël Fournier, rfournier@ethz.ch.
Author notes go here.

ability to recognize a face is defined in terms of response times and accuracy/ d' , separately. Inferences are then drawn from the difference in these manifest variables across different stimuli (ex: famous faces vs visually familiar faces). However, defining an ability based on the separate effects on RT and accuracy not only narrows the inferences that could be drawn regarding the studied ability, but could lead to misinformed inferences regarding underlying cognitive phenomenon (Ratcliff, Thapar, and McKoon 2001). **Need a link sentence here.** In human neuroscience and social cognition research, there is a lack of application these computational approaches (Parker and Ramsey, n.d.; Forstmann and Turner 2024). While computational cognitive models provide simplified accounts of how cognition arise, their application have the potential to fine-tune hypotheses about cognitive processes and to further develop already established theories.

Evidence accumulation models (EAM) are one approach to investigate the computational processes involved in face recognition. For the last two decades, the application of these models has defined the computational mechanisms involved in several cognitive processes (for a review, see Ratcliff et al. (2016)). One class of these models are the race models. Race models assume that evidence for each response option accumulates at different rate and the response is determined by the accumulator that crosses a specific threshold first (see Figure 1 for an example of a race model, the linear ballistic accumulator (LBA) model; Brown and Heathcote (2008)). While a variety of different evidence accumulation models exists, they all share the same

aim: translating accuracy and the distribution of RTs for correct and incorrect responses into estimates of latent variables assumed to underlie the decision-making process (Brown and Heathcote 2008; Donkin, Brown, and Heathcote 2011). Drift rate is the rate at which evidence in favor of a decision accumulates over time, reflecting the signal-to-noise ratio provided by the stimulus. Threshold represents the amount of accumulated evidence needed to trigger the decision, reflecting the response caution towards a specific response. The starting point is the amount of evidence towards a response before the accumulation of evidence begins, reflecting the *a priori* bias towards a response. Finally, the non-decision time is an estimation of the time taken to complete processes uninvolved in the decision time, such as pressing a response key. The collected response time is the sum of the non-decision time and the decision time.

A particular interest for the drift rate (the quality of the accumulation of evidence) and the threshold parameter (response caution) has risen in the field of cognitive psychology and cognitive neuroscience since the introduction of these models. With a new way to model how people make decision, research has been applying these models to investigate a wide range of psychological and cognitive processes like discrimination based on attractiveness (Axt & Johnston, 2021), the decision to use a firearm (), consumm and relationship between covert and overt shifts in attention (Parker et al, 2020a, 2020b, 2021, Parker & Ramsey, 2024). **Linking sentence here.** When considering the RT and accuracy results obtained in previous studies investigating face recognition, considering the application of evidence-accumulation models




Figure 1. Schematic of the linear ballistic accumulator (LBA) model

This diagram represents the accumulation process one trial of a perceptual decision task for the linear ballistic accumulator (LBA). Participants are required to choose between two options (Response 1 and Response 2). In a LBA model, there is a separated accumulation of evidence (v) for each response option. In this example, the correct response is Response 1. The accumulator on the left is the accumulator for the correct response (Response 1), and the green line represents the rate at which the evidence accumulates in favor of that response option. The accumulator on the right is the accumulator for the incorrect response (Response 2), and the dash red line represents the rate at which the evidence accumulates in favor of this response option. Once the accumulated evidence crosses the threshold (b) of a response option, the corresponding response is chosen (in this case Response 1).

introduces new important questions. Are the variations in RT and accuracy observed in face recognition studies between familiar faces and novel faces generated by different response caution towards the two responses? Or is the quality of evidence-accumulation fundamentally different when recognizing familiar faces or novel faces? And how modulation in the familiarity level (visually familiar and well-familiar faces) affect these latent processes?

Four experiments were conducted to investigate how familiarity affects the decision-making process of face recognition using evidence-accumulation models, more specifically the LBA model. In Experiment 1 and 2, face familiarity was experimentally induced. Each participants underwent a familiarization part where they got visually familiar with 30 previously unseen faces. In the recognition part, participants had to choose if the presented face has been previously seen during the familiarization part (learned faces) or not (novel faces). Experiment 2 was a replication of Experiment 1 conducted on an online platform for data collection (<https://pavlovvia.org>). In Experiment 3 and 4, familiarity was modulated using prior familiarity of the participants towards celebrities faces. The first part of the experiment was a rating part to assess the familiarity level of the participants towards 60 famous face. In the recognition part, the 30 most familiar faces were mixed to novel faces. For all experiments, we hypothesized that either drift rate and/or threshold would be affected by the face familiarity manipulation. The direction of the effects would be similar when comparing Experiment 1 and 2 and when comparing Experiment 3 and 4.

Experiment 1

Method and Materials

Pre-registration and open science

The research question, hypotheses, experimental design, planned analysis, and exclusion criteria were preregistered ([link](#)). All raw data, stimuli, data wrangling and analysis code are available on the open science framework ([see link](#)).

<code here for number of participants and age>

Participants

All participant were recruited using either an online recruiting platform (<https://marktplatz.uzhalumni.ch>) or via a mailing list dedicated to students from the Department of Psychology of the University of Zurich. Sample size was determined in advance. Following previous suggestions from Heathcote et al. (2019), a parameter recovery study was run to estimate if 30 usable participant datasets were sufficient to accurately recover the parameter estimates. The parameter recovery study included 30 participant datasets, each with 180 trials (90 trials “familiar” and 90 trials “unfamiliar”) and with our selected model parameterisation. The data-generated parameters were sufficiently well-recovered (See Supplementary Materials).

(From code) healthy participants took part in experiment 1 (From code). Ages ranged from (From code). All participants reported normal or corrected-to-normal vision and received payment (20 CHF) for participating in the experiment. Based on our preregistration, response times longer than 2.5 seconds were removed from the analysis. However, this cutoff value led to the the removal of 59% of the trials of one participant. Given the recommendation of having a certain number of trials per condition per participant when using evidence-accumulation models (Heathcote et al. 2019; Parker and Ramsey, n.d.), this participant was excluded from the data analysis. This experiment was accepted by the ethics committee of the Federal Institute of Technology Zurich (ETHZ), and all participant gave their informed consent to participate in the study.

Stimuli

The stimuli consisted of images selected from two different data sets of face images: the Face Research Lab London Set (DeBruine, Lisa; Jones, Benedict (2017). Face Research Lab London Set. figshare. Data set. <https://doi.org/10.6084/m9.figshare.5047666.v5>) and the (other data set). Each of these data sets is composed of images of different identities faces taken from different angle points. (X) identities were selected from the Face Research Lab London Set and (X) from the (other data set). For each selected identity, three pictures of the face at three different view points (3/4 left view, frontal view and 3/4 right view) were cropped to remove any (Fig. 1). All of the images processing was realized using the GNU Image Manipulation Program (GIMP, ref). After 4 pilots experiments, we removed 27 identities (21 from the Face Research Lab London Set and 6 from the blablabla) due to to the presence of (blablabla). In total, the data set of face images used in the main experiment contained 756 images: one set of three colorful face images and one set of three gray scaled face images for each of the 126 identities.

Material

Stimuli were presented on the screen of MacBook (blabla). The experiment was run on Psychopy Coder (version: 2022.5, ref).

Procedure

The experimental task was divided into two distinct parts: a familiarization part and a recognition part (Fig.2). In the familiarization part, the face of 30 unknown identities were presented on the screen and participants were told to memorize the identity of the faces. One familiarization trial consisted of the presentation of 6 face images, one after the other, depicting the same identity but varying in viewing points (3/4 left view, frontal view and 3/4 right view) and the colorimetry (colorful image, gray scale image). The duration of each image presentation was 0.75 second. Each participant underwent 30 familiarization trials. During the familiarization, we introduced catch trials to ensure participants attention. After some familiarization trials, a gray scale image of a person’s face was presented on the screen. Participants were asked to press the “q” key if the face belonged to the last seen identity or the “p” key if it was not. The faces seen during

the familiarization were considered the “Learned faces” within-subject condition.

In the recognition part, participants completed three blocks of 90 recognition trials. Each block was separated from another by a short break. Half of the trials were learned identities trials and the other half were new, previously unseen identities trials. At each trial, a gray scale image of a face was shown on the screen. Participants were asked to choose if they had previously seen this face in the familiarization part or not. If they did, they should press the “q” key and if they did not, the “p” key. Response time [s] and accuracy were collected after each recognition trial.

<Here schematic of Experiment 1 procedure>

Data analysis

Following our preregistration, trials with a response time longer than 2.5s were removed from the analysis. The evidence-accumulation modelling analyses of the distributions of response times for the correct and wrong answers were realized using the EMC2 R package (Cit. Niek Stevenson). For the separate analysis of response times and accuracy, we used (blablabla).

Results

Analysis of manifest variables

Analysis of RT and accuracy
Evidence-accumulation modeling
Model specification

Experiment 2: replication of Experiment 1 online

Method and Materials

Pre-registration and open science

The research question, hypotheses, experimental design, planned analysis, and exclusion criteria were preregistered (<https://osf.io/xehf4>). All raw data, stimuli, data wrangling and analysis code are available on the open science framework (see link).

<code here for number of participants and age>

Participants

Prolific

We deviated from our preregistration in...

This experiment was accepted by the ethics committee of the Federal Institute of Technology Zurich (ETHZ), and all participant gave their informed consent to participate in the study.

Stimuli

Same stimuli as Experiment 1 Two types of pictures were used for this experiment to create our within-subject stimuli conditions. Pictures depicting celebrities were taken from the internet The stimuli consisted of images selected from two different data sets of face images: the Face Research Lab London Set (DeBruine, Lisa; Jones, Benedict (2017). Face Research Lab London Set. figshare. Data set. <https://doi.org/10.6084/m9.figshare.5047666.v5>) and the (other data set). Each of these data sets is composed of images of different identities faces taken from

different angle points. (X) identities were selected from the Face Research Lab London Set and (X) from the . For each selected identity, three pictures of the face at three different view points (3/4 left view, frontal view and 3/4 right view) were cropped to remove any (Fig. 1). All of the images processing was realized using the GNU Image Manipulation Program (GIMP, ref). After 4 pilots experiments, we removed 27 identities (21 from the Face Research Lab London Set and 6 from the blablabla) due to to the presence of (blablabla). In total, the data set of face images used in the main experiment contained 756 images: one set of three colorful face images and one set of three gray scaled face images for each of the 126 identities.

Material

From Prolific

Procedure

Pavlovica

Same procedure The experimental task was divided into two distinct parts: a rating part and a recognition part (Fig.3). During the rating part, participants were presented pictures of 60 celebrities. They were asked to rate these celebrities, based on two dimensions: how familiar the celebrity was to them and how positive or negative were their feelings towards the celebrity. The familiarity rating scale went from 0 (Highly unfamiliar) to 10 (Highly familiar).

In the recognition part, participants completed three blocks of 90 recognition trials. Each block was separated from another by a short break. Half of the trials were famous identities trials and the other half were new, previously unseen identities trials. At each trial, a gray scale image of a face was shown on the screen. Participants were asked to choose if they recognize the face (and not the picture) seen this face in the familiarization part or not. If they did, they should press the “q” key and if they did not, the “p” key. Response time [s] and accuracy were collected after each trial. Time limit

Results

Discussion

Experiment 3: Famous faces

Method and Materials

Pre-registration and open science

The research question, hypotheses, experimental design, planned analysis, and exclusion criteria were preregistered (<https://osf.io/xehf4>). All raw data, stimuli, data wrangling and analysis code are available on the open science framework (see link).

<code here for number of participants and age>

Participants

All participant were recruited using either an online recruiting platform (<https://marktplatz.uzhalumni.ch>) or via a mailing list dedicated to students from the Department of Psychology of the University of Zurich. Sample size was determined in advance. Following previous sug-

gestions from (heathcote2019?), a parameter recovery study was run to estimate if 30 usable participant data sets were sufficient to accurately recover the parameter estimates. The parameter recovery study included 30 participant data sets, each with 180 trials (90 trials “famous” and 90 trials “novel”) and with our selected model parameterisation. The data-generated parameters were sufficiently well-recovered (See Supplementary Materials).

Stimuli

Material

Procedure

Data analysis

Results

Discussion

Experiment 4: replication of Experiment 3 online

Method and Materials

Pre-registration and open science

The research question, hypotheses, experimental design, planned analysis, and exclusion criteria were preregistered (<https://osf.io/xehf4>). All raw data, stimuli, data wrangling and analysis code are available on the open science framework (see link).

<code here for number of participants and age>

Participants

Prolific

Stimuli

Material

Procedure

Pavlovian

Data analysis

Results

Discussion

General discussion

Here we demonstrated that different computational processes support the recognition of different types of face. Whereas the signal-to-noise ratio provided by visual familiarity was poorer compared to novelty in the first experiment, the combination of visual and semantic knowledge about the individual in the second experiment induced a quicker evidence accumulation for familiar faces compared to novel faces. This would suggest that the quality of the information processing varies as a function of the nature of the information. Such inference about the computational mechanisms involved in face recognition could not have been possible based on the commonly used separate analysis of response times and accuracy. Therefore, we suggest that further work uses evidence-accumulation models (EAM) and other cognitive modelling approaches to build a richer computational understanding of face recognition and familiarity effects.

Accumulation of evidence for visually familiar faces was slower compared to novel faces in Experiment 1. This would suggest that when only surface level visual features are available for recognition, the novelty of the information prevails. In the case of short prior exposure to visual stimuli, our findings are in agreement with other studies that reported a better recognition ability for novel faces than for visually familiar faces (Bindemann, Attard, and Johnston 2014; Read, Vokey, and Hammersley, n.d.). Visually familiar faces are processed in the core network of face recognition (Bruce and Young 1986; Gobbini and Haxby 2006). This core network manages and synthesizes the visual analysis of low-level visual features to the construction of a detailed perceptual representation of the face. The next step requires the activation of face memory representations, giving rise to a feeling of familiarity proportionate to the degree of overlap between the presented face and the memory trace (Rapsak 2019). In the case of short prior visual exposure, these face memory traces might not be stable enough for the recognition process, leading to a slower evidence accumulation towards the “familiar” decision.

- Here, add the novelty effect (old/new references and explanations)

P3: Effects of person identity (visual + semantic) knowledge (Experiment 2) and the extended network of the functional model of face recognition (Bruce & Young, 1986; Haxby et al., 2000). - 1 sentence: main finding: When richer semantic features available, familiarity prevails (faster accumulation of evidence in favor of familiar information vs novel information). - Extended network - Experiment 2: why Experiment 2 would elicit the extended network of face recognition. - Interpretation of our results within the functional model of face recognition framework. - Suggestion: (Landi et al., 2021) They suggest that there may be two pathways of face memory:

□ Pathway 1: from Anterior Medial Face area (AM) – Anterior Temporal lobe: facilitate the formation of new associations and feeling of familiarity (Learned Faces) □ Pathway 2: from Anterior Medial Face area (AM) – Temporal Pole Face area (TP): access to long-term semantic face information (Familiar Faces) - Evidence accumulation faster for familiar faces could reflect the pathway 2 where semantic face information is accessed quicker than for visually learned faces which, without being associated with semantic information, would need further processing into the Anterior Temporal Lobe (pathway 1), leading to a slower accumulation of evidence.

P3.5: Interpretation of drift rate results for Experiment 2: general issue

P4: Constraints on generality (Simons et al., 2017) - Suggestion: visual familiarity effects not specific to faces - Here we used faces as recognition stimuli - Suggestion: experiment 1 effects generalizable to other visual stimuli processing (objects, scenes...) - However, experiment 2 effects more constrained to faces: difficult to imagine a similar semantic knowledge for objects or scenes that we do for faces. Maybe for very specific and personal object

but not comparable to the number of faces that we have a rich semantic knowledge about (or something like that).

P5: Limitations We do not exclude that our parameter estimation might have been affected by our restricted number of trials. Previous studies have investigated how a low number of trials have influenced the model fitting, leading to an incorrect parameter estimation (ref from Manke). While our two experimental designs reach the threshold of the required number of trials to use EAM, more trials could have been more appropriate. Our decision of using 90 trials for each condition was motivated by the fact that it is especially challenging to find or create a face pictures dataset that includes a large number of identities. Another limitation to note concerns the use of celebrities' picture in the second experiment. Indeed, we cannot exclude the fact that the categorization between familiar faces and novel faces might have been facilitated by low visual features from the celebrities' pictures (e.g. slightly different orientation of the face, different overall picture quality...). While we tried to control for these features as much as possible, this remains a possibility.

P6: Future research To provide more evidence towards the findings of Landi et al.(2021), a joint-modelling approach could be applied/used/exploited (ref). Joint-modelling designates the particularity of modelling two different source of data (e.g. choice-response data and fMRI data) at the same time. This approach could provide precious insights about the relationship between latent variables and brain areas activity, like the temporal lobe face area (TP). Another direction for future studies would be to investigate how variability in the face recognition ability in the general population accounts for these latent variables' estimation. (develop this a little more, introducing our possible next experiment). - Last point: Familiarity as a continuum and not binary categorisation

References

- Akan, Melisa, and Aaron S. Benjamin. 2023. "Haven't i Seen You Before? Conceptual but Not Perceptual Prior Familiarity Enhances Face Recognition Memory." *Journal of Memory and Language* 131 (August): 104433. <https://doi.org/10.1016/j.jml.2023.104433>.
- Bindemann, Markus, Janice Attard, and Robert A. Johnston. 2014. "Perceived Ability and Actual Recognition Accuracy for Unfamiliar and Famous Faces." Edited by Peter Walla. *Cogent Psychology* 1 (1): 986903. <https://doi.org/10.1080/23311908.2014.986903>.
- Bird, Chris M., Rachel A. Davies, Jamie Ward, and Neil Burgess. 2011. "Effects of Pre-Experimental Knowledge on Recognition Memory." *Learning & Memory* 18 (1): 11–14. <https://doi.org/10.1101/lm.195211>.
- Brown, Scott D., and Andrew Heathcote. 2008. "The Simplest Complete Model of Choice Response Time: Linear Ballistic Accumulation." *Cognitive Psychology* 57 (3): 153–78. <https://doi.org/10.1016/j.cogpsych.2007.12.002>.
- Bruce, Vicki, and Andy Young. 1986. "Understanding Face Recognition." *British Journal of Psychology* 77 (3): 305–27. <https://doi.org/10.1111/j.2044-8295.1986.tb02199.x>.
- Donkin, Chris, Scott Brown, and Andrew Heathcote. 2011. "Drawing Conclusions from Choice Response Time Models: A Tutorial Using the Linear Ballistic Accumulator." *Journal of Mathematical Psychology* 55 (2): 140–51. <https://doi.org/10.1016/j.jmp.2010.10.001>.
- Duchaine, Brad, and Galit Yovel. 2015. "A Revised Neural Framework for Face Processing." *Annual Review of Vision Science* 1 (1): 393–416. <https://doi.org/10.1146/annurev-vision-082114-035518>.
- Forstmann, Birte U., and Brandon M. Turner, eds. 2024. *An Introduction to Model-Based Cognitive Neuroscience*. Springer International Publishing. <https://doi.org/10.1007/978-3-031-45271-0>.
- Gobbini, M. Ida, and James V. Haxby. 2006. "Neural Response to the Visual Familiarity of Faces." *Brain Research Bulletin* 71 (1-3): 76–82. <https://doi.org/10.1016/j.brainresbull.2006.08.003>.
- . 2007. "Neural Systems for Recognition of Familiar Faces." *Neuropsychologia* 45 (1): 32–41. <https://doi.org/10.1016/j.neuropsychologia.2006.04.015>.
- Haxby, James V., Elizabeth A. Hoffman, and M.Ida Gobbini. 2000. "The Distributed Human Neural System for Face Perception." *Trends in Cognitive Sciences* 4 (6): 223–33. [https://doi.org/10.1016/S1364-6613\(00\)01482-0](https://doi.org/10.1016/S1364-6613(00)01482-0).
- Heathcote, Andrew, Yi-Shin Lin, Angus Reynolds, Luke Strickland, Matthew Gretton, and Dora Matzke. 2019. "Dynamic Models of Choice." *Behavior Research Methods* 51 (2): 961–85. <https://doi.org/10.3758/s13428-018-1067-y>.
- Ida Gobbini, M, Ellen Leibenluft, Neil Santiago, and James V Haxby. 2004. "Social and Emotional Attachment in the Neural Representation of Faces." *NeuroImage* 22 (4): 1628–35. <https://doi.org/10.1016/j.neuroimage.2004.03.049>.
- Ishai, Alomit. 2008. "Let's Face It: It's a Cortical Network." *NeuroImage* 40 (2): 415–19. <https://doi.org/10.1016/j.neuroimage.2007.10.040>.
- Johnston, Robert A., and Andrew J. Edmonds. 2009. "Familiar and Unfamiliar Face Recognition: A Review." *Memory* 17 (5): 577–96. <https://doi.org/10.1080/09658210902976969>.
- Kanwisher, Nancy, and Jason J. S. Barton. 2011. "111 the Functional Architecture of the Face System: Integrating Evidence from fMRI and Patient Studies." In *Oxford Handbook of Face Perception*, edited by Andrew J. Calder, Gillian Rhodes, Mark H. Johnson, and James V. Haxby, 0. Oxford University Press. <https://doi.org/10.1093/oxfordhb/9780199559053.013.0007>.
- Klatzky, Roberta L., and Fiona H. Forrest. 1984. "Recognizing Familiar and Unfamiliar Faces." *Memory & Cognition* 12 (1): 60–70. <https://doi.org/10.3758/BF03196998>.
- Landi, Sofia M., Pooja Viswanathan, Stephen Serene, and Winrich A. Freiwald. 2021. "A Fast Link Between Face Perception and Memory in the Temporal Pole." *Science* 373 (6554): 581–85. <https://doi.org/10.1126/science.abi6671>.
- Leibenluft, Ellen, M.Ida Gobbini, Tara Harrison, and James V. Haxby. 2004. "Mothers' Neural Activation in Response to Pictures of Their Children and Other Children." *Biological Psychiatry* 56 (4): 225–32. <https://doi.org/10.1016/j.biopsych.2004.05.017>.

- Natu, Vaidehi, and Alice J. O'Toole. 2011. "The Neural Processing of Familiar and Unfamiliar Faces: A Review and Synopsis." *British Journal of Psychology* 102 (4): 726–47. <https://doi.org/10.1111/j.2044-8295.2011.02053.x>.
- Parker, Samantha, and Richard Ramsey. n.d. "What Can Evidence Accumulation Modelling Tell Us about Human Social Cognition?" *Quarterly Journal of Experimental Psychology*.
- Rapcsak, Steven Z. 2019. "Face Recognition." *Current Neurology and Neuroscience Reports* 19 (7): 41. <https://doi.org/10.1007/s11910-019-0960-9>.
- Ratcliff, Roger, and Jeffrey N. Rouder. 1998. "Modeling Response Times for Two-Choice Decisions." *Psychological Science* 9 (5): 347–56. <https://doi.org/10.1111/1467-9280.00067>.
- Ratcliff, Roger, Philip L. Smith, Scott D. Brown, and Gail McKoon. 2016. "Diffusion Decision Model: Current Issues and History." *Trends in Cognitive Sciences* 20 (4): 260–81. <https://doi.org/10.1016/j.tics.2016.01.007>.
- Ratcliff, Roger, Anjali Thapar, and Gail McKoon. 2001. "The Effects of Aging on Reaction Time in a Signal Detection Task." *Psychology and Aging* 16 (2): 323–41. <https://doi.org/10.1037/0882-7974.16.2.323>.
- Read, J Don, John R Vokey, and Richard Hammersley. n.d. "Changing Photos of Faces: Effects of Exposure Duration and Photo Similarity on Recognition and the Accuracy-Confidence Relationship."
- Schwaninger, Adrian, Janek S. Lobmaier, and Stephan M. Collishaw. 2002. "Role of Featural and Configural Information in Familiar and Unfamiliar Face Recognition." In *Biologically Motivated Computer Vision*, edited by Heinrich H. Bülthoff, Christian Wallraven, Seong-Whan Lee, and Tomaso A. Poggio, 2525:643–50. Springer Berlin Heidelberg. http://link.springer.com/10.1007/3-540-36181-2_64.
- Schwartz, Linoy, and Galit Yovel. 2016. "The Roles of Perceptual and Conceptual Information in Face Recognition." *Journal of Experimental Psychology: General* 145 (11): 1493–1511. <https://doi.org/10.1037/xge0000220>.
- . 2019. "Independent Contribution of Perceptual Experience and Social Cognition to Face Recognition." *Cognition* 183 (February): 131–38. <https://doi.org/10.1016/j.cognition.2018.11.003>.

A1 Appendix content here