

Individual differences in the computational processes of face recognition and their association to face recognition ability

Raphaël Fournier¹, Paul Downing² & Richard Ramsey^{1,3,4*}

¹ETH Zürich, Neural Control of Movement Laboratory, Department of Health Sciences and Technology

²Bangor University, School of Psychology and Sports Science

³ETH Zürich, Social Brain Sciences Laboratory, Department of Humanities, Social and Political Sciences

⁴ETH Zürich, Learning and Instruction Laboratory, Department of Humanities, Social and Political Sciences

2026-07-08

Keywords: face perception, memory, individual difference, familiarity, decision models, evidence accumulation modelling

Words: 4953

*Send correspondence to: Richard Ramsey, rramsey@ethz.ch.

1. Introduction

Paragraph 1: general comment on face recognition and on the important variability in the “normal” population

Being able to quickly and accurately identify a face is blabla in every day’s life. This ability becomes even more important in several real-life task, like eye-witness identification or passport control. However, face recognition ability is not distributed equally across the population. Without organic cause (like brain damage), people affected with developmental prosopagnosia show a poor face recognition ability throughout their life (Dobel et al., 2007; McConachie, 1976) and report an inability to recognize familiar faces. The other end of the face recognition ability spectrum regroups the “super-recognizers”. These individuals show a remarkably high face recognition ability compared to the average person (Bobak et al., 2016; Russell et al., 2009). However, even when ignoring these two extreme cases, face recognition ability remains highly variable in the normal population, especially for unfamiliar faces recognition (Dowsett & Burton, 2015; White et al., 2014).

Paragraph 2: past investigation of individual difference in face identity processing

There is a growing interest in the value of investigating individual differences across the entire spectrum of face recognition ability, and not only by using group-level comparisons between the two extremes (prosopagnosic patients and “super-recognizers”) and average recognizers (White & Kitchen, 2022). Several tests have been designed to measure performance on defined set of tasks like new faces learning (Cambridge Face Memory test, CFMT; Duchaine & Nakayama (2006)), unfamiliar face perception (Glasgow Face Matching Test, GFMT; Burton et al. (2010)) or familiar face perception (Before They Were Famous, BTWF; Russell et al. (2009)). Using correlational approaches, past research has derived quantitative measures of the association between the performances at these tests or between test scores and other broader perceptual and cognitive processes (McCaffery et al., 2018; Noyes et al., 2018). This individual difference approach provide an opportunity to investigate the relationships between fundamental processes that are difficult to uncover using group-level analyses. One key question that association studies have investigated is to what extent individual difference in face processing reflect domain-general differences in other perceptual and cognitive abilities (McCaffery et al., 2018; Verhallen et al., 2017). Using tests scores as variables of interest, some studies have shown that face and general object perception ability are indeed associated (r value ranging from 0.00 to 0.37; Dennett et al. (2012a); Richler et al. (n.d.); Wilmer et al. (2012)). However, these associations remains constantly weaker than those between different face or object recognition task (Fysh et al., 2020; McCaffery et al., 2018; Wilmer et al., 2010), suggesting that domain-specific processing explains at least some part of the variance between these tasks (Richler et al. (n.d.)).

Paragraph 3: Investigating individual differences in latent processes using computational approaches

While the associations between manifest measures like test scores remains important to understand relationship between fundamental processes, performance remains a distant proxy of the underlying cognitive processes at work during face recognition, thus could not be ideal for capturing individual differences in these processes (Haines et al. (n.d.)). Using a computational approach to disentangle the multiple components of these processes could provide meaningful information regarding the relationships between the specific parts of the face recognition process and face recognition ability (Yarkoni, 2022). This model-based analysis of individual differences could provide cleaner measures of the processes of interest and could enhance our understanding on how variation in these latent unobserved processes, which are driving behavior, is related to (White et al. (2016)).

Paragraph 4: building upon our past project results summary and application of individual differences in face recognition ability

One of our previous work (Fournier, Downing & Ramsey, in press) has used Bayesian hierarchical evidence-accumulation models (see Figure 1) to fit choice-rt data in a face recognition (old/new) task (for a review on evidence-accumulation models see Ratcliff et al. (2016)). We found that distinct computational processes involved in the decision-making process of face recognition are

affect by face familiarity. Compared to learned faces, novel faces induced a great accumulation of evidence (drift rate) and the response caution (threshold) towards the novel response was higher as well. However these conclusions were drawn from the group-average posterior distributions of these two parameter and the between-subject variability in these estimated parameters was important. In the present study, we used an individual difference approach to investigate the between-subject variability found in these estimated parameters. More specifically, we were interested to see if the estimated parameters computed from choice-rt data in a face memory task were associated with face recognition ability specifically or if they reflect a general recognition ability unspecific to faces. We think that this approach could give precious insights about what do the parameters reflect and how specific to face recognition the inferences which are drawn from their investigation are.

Paragraph 5: Short description of how we are going to address the questions

We used a similar face memory task to the one described in Fournier et al. (in press) to compute the threshold and drift rate parameter for both learned and novel faces. In addition to this task, face recognition ability was assessed using the Cambridge Face Memory Test (CFMT) and general object recognition ability was assessed by using the Cambridge Car Memory Test (CCMT). We wanted to investigate to what extend do drift rate and threshold vary as a function of face recognition ability alone and when adjusted by general object recognition ability. Based on our pilot work, we hypothesized that the accumulation of evidence for learned faces when (drift rate learned-TRUE) will be positively associated with face recognition ability and that this association will remain after adjusting for general object recognition.

2. Method and Materials

2.1. Pre-registration and open science

We report how we determined our sample size, all data exclusions (if any), all manipulations, and all measures in the study (Simons et al., 2017). The research question, hypotheses, experimental design, planned analysis, and exclusion criteria were preregistered (<https://osf.io/b74gt/overview>).




Figure 1. Schematic of the linear ballistic accumulator (LBA) model

This diagram represents the accumulation process one trial of a perceptual decision task for the linear ballistic accumulator (LBA; Brown & Heathcote (2008)). Participants are required to choose between two options (Response 1 and Response 2). In a LBA model, there is a separated accumulation of evidence (v) for each response option. In this example, the correct response is Response 1. The accumulator on the left is the accumulator for the correct response (Response 1), and the green line in represents the rate at which the evidence accumulates in favor of that response option. The accumulator on the right is the accumulator for the incorrect response (Response 2), and the dash red line represents the rate at which the evidence accumulates in favor of this response option. Once the accumulated evidence crosses the threshold (b) of a response option, the corresponding response is chosen (in this case Response 1).

The raw data, experimental materials, and analysis code are available on GitHub (add link) or the Open Science Framework (add link).

2.2. Participants

All participants were recruited on the Prolific platform (<https://www.prolific.com>). Participants had to be located in the United Kingdom or in the United States, be aged between 18-65 years old, with normal or corrected-to-normal vision and speak fluent English. Furthermore, Prolific offers the option to choose the approval rate of the participants willing to take part in the study. The approval rate is the percentage for which participants have been approved in previous experiments. An approval rating between 95% and 100% was chosen in our study to try to ensure high data quality. 383 participants completed the experiment. Following our preregistered exclusion criterion, 2 participants were excluded because their percentage of missed trials was higher than 40%, 3 because their percentage of RT outside the established range (0.2 to 2 seconds) were higher than 25% and 78 were removed because the overall accuracy was lower than 55%. In the end, data from 300 participants (141 men and 159 women) were retained for the analysis and the LBA modeling. Ages ranged from 19 to 64 ($M_{age} = 42$, $SD_{age} = 11.2$). Following Prolific payment principles, each participant received 9£ for the completion of the study. This experiment was accepted by the ethics committee of the Federal Institute of Technology (ETH) Zurich.

2.3. Material

Participants were asked to complete the study using a desktop computer. Beforehand, the paradigm was tested on three different operating systems (PC, Macintosh and Linux) and on three web browsers (Google Chrome, Safari and Firefox). Participants were aware that using any other combination of operating systems and web browsers might lead to the inability to complete the experiment and were asked to follow these directives to ensure a consistent procedure and participant experience.

2.4. Procedure

The experiment was divided into three experimental tasks. A face recognition task was used to estimate the LBA parameters from manifest measures (accuracy and response times). Face and car recognition ability were assessed using the Cambridge Face Memory Test and the Cambridge Car Memory Test. Participants always first underwent the face recognition task and the order of two memory tests was counterbalanced.

2.4.1. Face recognition task

The face recognition task was divided into two distinct parts: a familiarization part and a recognition part. During the familiarization part, unknown identities were presented on the screen and participants were instructed to memorize the identity of the faces. One familiarization trial consisted of the presentation of 6 face images, one after the other, showing the same identity but varying in viewing points (3/4 left view, frontal view and 3/4 right view) and the colorimetry (colorful image, gray scale image). The duration of each image presentation was set to 0.75 second and each participant underwent 30 familiarization trials (for 30 unknown identities). During the familiarization, we introduced catch trials to ensure participants' attention. After some familiarization trials, a gray scale image of a person's face was presented on the screen. Participants were asked to press the "q" key if the face belonged to the last seen identity or the "p" key if it was not. The faces seen during the familiarization were considered the "Learned faces" within-subject condition.

In the recognition part, participants completed three blocks of 90 recognition trials. Each block was separated from another by a short break. Half of the trials were learned identities trials and the other half were new, previously unseen identities trials. In each trial, a gray scale image of a face was shown on the screen. Participants were asked to choose if they had previously seen this face in the familiarization part or not. If they did, they should press the "q" key and if they did not, the "p" key. Participants were asked to respond as quickly and accurately as possible. It is important to note that participants never saw two pictures of the same learned identity in the same block and never saw the same picture (3/4 left view, frontal view, or 3/4 right view) of a learned identity

during the entire recognition part. Furthermore, each novel identity was only presented once in the entire recognition part. Response time [s] and accuracy were collected after each recognition trial. A response time limit of 2 seconds has been set for each recognition trial. If participants took longer than 2 seconds to press a response key, the text “Too late!” appeared in red on the screen and the trial was discarded, but not replaced.

2.4.2. Cambridge Memory Tests

The method of the CFMT was described in Duchaine & Nakayama (2006). Participants learned 6 Caucasian male faces in three views and had to discriminate them later from distractor faces (no time response limit, three-alternative forced-choice task, Figure 3 a). Regarding the CCMT, the method has been described in Dennett et al. (2012a) and has a highly similar structure, format and scoring as the CFMT, but uses cars instead of faces as stimuli.

2.5. Stimuli

The face images used in the faces recognition task consisted of images selected from two different data sets of face images: the Face Research Lab London Set (DeBruine, Lisa; Jones, Benedict (2017): <https://doi.org/10.6084/m9.figshare.5047666.v5>) and the Color FERET Database (<https://www.nist.gov/itl/products-and-services/color-feret-database>). Each of these data sets is composed of images of different identities faces taken from different angle points. 102 identities were selected from the Face Research Lab London Set and 51 from the Color FERET Database. For each selected identity, three pictures of the face at three different view points (3/4 left view, frontal view and 3/4 right view) were cropped following the outline of the face.




Figure 2. Experimental procedure of the face recognition task

The experimental procedure was divided into two parts: a familiarization part and a recognition part. a) In the familiarization part, participants were asked to memorize the face identity of 30 identities. For each identity, participants looked at 6 pictures depicting the same identity with different face orientation (3/4 left view, frontal view and 3/4 right view) and different colorimetry (color and gray scale images) in the order presented here: 3/4 left view, frontal view and 3/4 right view in color, followed by 3/4 right view, frontal view and 3/4 left view in gray scale. b) In each trial of the recognition part, participants had to decide if they recognize the face shown on the screen from the familiarization part. If they did, they had to press the “q” key and if they did not, the “p” key. They completed three blocks of 60 trials (half of them were from the familiarization part, half were novel faces). For the recognition part, only gray scale images of faces were used (for both learned faces and novel faces).

To ensure that the stimuli that we used are reproducible, we used the webmorphR R Package (version?) -> NEED info from Rich here.

2.6. Evidence accumulation modeling

The model and priors specification as well as the model estimation are all identical to the one described in (ref: Fournier et al., in press).

2.6.1. Model specification

A hierarchical LBA models was fit to the accuracy and response times of the face recognition task. The model specifications are outlined in our preregistration (Table 1). The LBA framework assumes a separate evidence accumulator for each response alternative, with potentially different parameter values. Accordingly, one accumulator corresponded to the “Learned” response and the other to the “Novel” response. Threshold was allowed to vary by participants’ response (Learned/Novel) and mean drift rate varied as a function of both stimulus type (Learned/Novel) and whether the accumulator corresponded to the correct response for that stimulus (TRUE vs. FALSE). For example, when a Learned stimulus was presented, the Learned accumulator was designed as TRUE, whereas the Novel accumulator was designed as FALSE. The difference in drift rate between the TRUE and FALSE accumulators reflects the quality of information supporting a decision, with larger differences indicating stronger and more discriminative evidence accumulation (Lewandowsky & Oberauer (2018)). The standard deviation of the TRUE accumulator was allowed to vary according to accumulator match status, whereas the standard deviation of the FALSE accumulator was constrained to be constant to ensure model identifiability (Donkin et al. (2009)). In the preregistered




Figure 3. The two Cambridge Memory Tests

Illustration of (a) the Cambridge Face Memory Test (CFMT; ref Duchain & Nakayama, 2006) and (b) the Cambridge Car Memory Test (CCMT; red Dennett et al., 2012a). These two tests are highly similar, differing only in the category of the presented stimuli. Both tests are composed of three stages: Learn (including Study and Test), Novel Images and Novel Images with Noise. In the Learn stage, participants learn target faces/cars and are then tested on the recognition of the identical images to the learned targets. In the Novel Images and Novel Images with Noise stages, recognition targets are different pictures of the same learned targets, but differing in views, lightning or both. For the CCMT (b), the car pictures showed here are not the one used in the CCMT and served only as a representation of the stimuli used in the Learn stage and the Novel stages of the CCMT. This illustration has been taken and slightly modified from Dennett et al. (2012b). 3AFC = three-alternative forced choice; ISI = interstimulus interval.

model, a single start-point parameter (A), and single non-decision time parameter (t_0) were estimated. Alternative model specifications that permitted variation in these parameters are reported in the Supplementary Materials.

Table 1. Formula specification for the pre-registered linear ballistic accumulator model.

Parameter	Label	Condition	Response	Accuracy	Fixed
Start point	A	-	-	-	1
Mean drift rate	v	yes	no	yes	-
SD drift rate	sd_v	no	no	yes	-
SD false drift rate	false.sd_v	-	-	-	1
Threshold	b	yes	yes	no	-
Non-decision time	t_0	yes	no	no	-
SD Non-decision time	st_0	-	-	-	0

Condition = training condition (Learned vs. Novel); Response = key-press response (same vs. different); Accuracy = (true/correct vs false/incorrect); SD = standard deviation.

2.6.2. Model estimation

Bayesian model estimated was carried using the EMC2 R package (Stevenson et al., 2026). Priors were chosen to be weakly-informative, meaning that they have little influence on the estimation (for more details regarding the priors of each model, see Supplementary Materials). Two sampling steps were used to estimate the parameters. First, a separate estimation of the fixed effects for each participant was conducted. Parameter estimations were then used as the starting point for the full hierarchical parameter estimation.

2.6.3. Model fit

To ensure that the fit of our model can capture most of the main trends in the data, graphical summaries of the posterior predictions were examined. (Check fit of the model, Supplementary Materials)

2.7. Data analysis

Regarding the general analytical strategy, two main approaches were considered. Correlations and data visualizations were used to characterize the zero-order relationships between parameters of interest (drift rate and threshold) from the LBA model with face and object recognition ability. Linear regression was then conducted to estimate how much LBA parameters vary as a function of face recognition ability, as well as how much these parameters vary after adjusting for car recognition ability. The details of the analytical strategy were preregistered (<https://osf.io/b74gt/overview>).

2.7.1. LBA parameters

In order to make inference about the magnitude of familiarity effects, differences in parameter estimates across conditions were compared. To summarize the distribution of parameters of interest, we report the median of the posterior distribution together with 95% quantile interval of the posterior distribution.

2.7.2. Classical correlational analysis

The median value of each parameter's posterior distribution was correlated with the two centred scores of each of the Cambridge Memory Tests to assess the relationship between these variables.

2.7.3. Bayesian plausible value correlational analysis

In addition to the classical correlational analysis described above, we conducted a Bayesian plausible value correlation approach (Ly et al., 2017; Matzke et al., 2017). Instead of using point estimates (median value of each parameter's posterior distribution), this approach permits the estimation of uncertainty in likely correlational values by correlating the parameter estimation from each sample (or "draw") from the posterior distribution with the memory scores. A distribution of the

plausible correlations between each parameter and the memory scores can then obtained. These distributions can compared between stimuli conditions (Learned vs Novel) or memory scores (face vs car) using difference contrasts. It allowed us to estimate if the strength of the correlation differs or not between conditions of interest.

2.7.4. Linear regression

Based on our pilot results, we preregistered two Bayesian linear regression models to quantify the extent to which drift rate vary as a function of face recognition ability alone and when accounting for car recognition ability. The results of the linear regresison for the threshold parameter are available in the Supplementary materials. An index coding approach was used (no grand interecept) where each condition of interest has its own intercept (see Table 2 for the details of each regression models).

Table 2. Formula specification for the pre-registered linear regression models.

Parameter	Condition	Ability	Formula
Median drift rate	familiarity:accuracy	Face	Median drift rate 0 + familiarity:accuracy + face_ability + (0 participant)
Median drift rate	familiarity:accuracy	Face + Car	Median drift rate 0 + familiarity:accuracy + face_ability + car_ability + (0 participant)

familiarity = face familiarity (Learned vs. Novel); accuracy = response accuracy (TRUE vs. FALSE)

2.7.5. Inferential criteria


3. Results

3.1. LBA parameters


Posterior distributions for drift rate and threshold parameters are visualised in Figure 4 and Figure 5 and the medians and 95% quantile intervals are summarised in Table 3.

Threshold: Inspection of the posterior distribution shows that there is an effect of familiarity on the threshold parameter.

Drift rate: Inspection of the posterior distribution shows that there is a familiarity effect in drift rate difference. The quality of the evidence accumulation was greater for Novel faces compared to Learned faces.




(a) Threshold by response




(b) Threshold (novel - learned) contrast

Figure 4. Threshold estimates



(a) Drift rate (TRUE - FALSE) by condition



(b) Drift rate (novel - learned) contrast

Figure 5. Drift rate estimates

Table 3. Posterior median and 95% quantile intervals for threshold and drift rate parameters.

Parameter	Condition	Median	95% QI
Threshold	novel	2.25	[2.169, 2.323]
Threshold	learned	1.89	[1.822, 1.96]
Threshold contrast	novel - learned	0.35	[0.316, 0.394]
Drift rate	novel	1.15	[1.098, 1.199]
Drift rate	learned	0.15	[0.097, 0.195]
Drift rate contrast	novel - learned	1	[0.91, 1.094]

QI = quantile interval.

3.2. Correlations




Figure 1. Median threshold correlations with recognition ability




Figure 2. Median drift rate correlations with recognition ability

Point estimates correlations with recognition scores

We examined point-wise recognition ability linear relationship with point estimates (median) of the posterior distribution of each of the LBA parameters of interest. These relationships can be seen in Figure 6 for the face recognition ability. Visual inspections of these correlations seemed to show that the accumulation of evidence (drift rate) for learned and novel faces increases as face recognition ability increases. A similar conclusion could be drawn from the inspection of the response caution (threshold) towards the “Learned” response. However the strength of these relationship remains weak (the highest r value is 0.24) and we used a Bayesian plausible value correlational approach to determine the uncertainty linked to these associations.

3.3. Bayesian plausible value correlational analysis

To estimate the uncertainty linked to the relationships between LBA estimated parameters and face recognition ability, we used a Bayesian plausible value correlational analysis. Like described above (see Methods), instead of using a single point estimate to assess the strength of the relationship between our variables of interest, the posterior distribution of the LBA parameters allow us to use the entire sampling distribution to do it. We calculated the Person’s r between each sample value from our posterior distribution for each parameter of each subject and their face recognition ability. The posterior distributions of plausible correlation values and their contrast are shown in Figure 7 for threshold and Figure 8 for drift rate. Table 4 provides a summary of these distributions.

Threshold: There is a positive relationship between response caution for both learned and novel faces and recognition ability. Regarding face recognition ability, people with a higher face recognition ability have a higher response caution for learned faces whereas people with a higher car recognition ability have a higher threshold for both learned and novel faces.

Drift rate: A higher face recognition ability is associated with a greater drift rate for both novel and learned faces. However, a higher car recognition ability is only associated with an increase drift rate for novel faces.




Figure 6. Correlations between face recognition ability and LBA parameters

Pearson's correlations between the median of the posterior distribution of the LBA parameters of interest and face recognition ability (centred). The six upper panels illustrate the correlations between face recognition ability and the 6 estimated parameters for drift rate and the two lower panel between face recognition ability and the 2 estimated parameters for threshold.




Figure 7. Plausible correlation values distributions between threshold and recognition abilities. Points denote the median of the distribution and error bars represent 95% quantile intervals.




Figure 8. Plausible correlation values distributions between drift rate and recognition abilities. Points denote the median of the distribution and error bars represent 95% quantile intervals.

Text here

Table 4. Median r and 95% quantile intervals of the plausible value correlations between LBA parameters and recognition ability scores.

Parameter	Condition	Face		Car	
		median r_{Face}	95% QI_Face	median r_{Car}	95% QI_Car
Threshold	Learned	0.12	[0.06, 0.18]	0.13	[0.08, 0.19]
Threshold	Novel	0.06	[-0.00, 0.11]	0.18	[0.13, 0.24]
Threshold	Novel-Learned	-0.06	[-0.11, -0.02]	0.10	[0.05, 0.14]
Drift	Learned	0.14	[0.07, 0.21]	-0.01	[-0.08, 0.06]
Drift	Novel	0.20	[0.14, 0.27]	0.13	[0.07, 0.19]
Drift	Novel-Learned	0.05	[-0.02, 0.12]	0.08	[0.01, 0.15]

Blue indicates a 95% quantile interval entirely above zero; red indicates a 95% quantile interval entirely below zero.

3.4. Linear regression

4. Discussion

Paragraph 1: Quick summary of results Aim of the project: use evidence accumulation modelling to investigate the relationship between face recognition ability and the cognitive mechanisms involved in the face recognition process. Our results showed that individual difference in face recognition ability is associated with different latent computational processes. Face recognition

ability seems to be positively associated with the rate of evidence accumulation (drift rate parameter) as well as the response caution (threshold parameter) for both learned and novel faces recognition. In addition, this association (still holds) when accounting for object recognition ability.

By joining experimental psychology, individual differences approach and computational models, we bla bla bla.

Paragraph 2: Drift rate and threshold • Effect of individual differences on LBA parameters is multifaceted: effect on across several LBA parameters, not just one. • Drift rate: Face recognition ability predict an increase in the rate at which evidence accumulates for both novel and visually familiar faces, where people with a better face recognition ability accumulate more recognition signal (drift rate TRUE) and are more capable to ignore noise coming from the stimulus. - Finding in accordance with previous research that found that expertise effects are primarily due to a better information extraction (REF: fingerprints examiners (ref: Thompson, Tangen & McCarthy, 2013), medical images perception (van der Gijp et al., 2014, 2016; Litchfield and Donovan, 2017)). - Our results extend these effect that these effects are visible in the “normal” population as well, outside of group-level differences between experts and novice. • Threshold: Face recognition ability predict an increase in the response caution for both novel and visually familiar faces. - Threshold: higher threshold = more accurate but slower to respond / lower threshold = less accurate but quicker to respond - People with higher face recognition ability are more cautious, prioritizing accuracy over response time. However, the quality and speed of evidence accumulation is higher. - General metacognition -> people with higher abilities are more confident in their confidence judgement regarding this ability (ref: Lichtenstein & Fischhoff, 1977). Previous studies have shown that confidence is itself a decision variable that can regulate future behaviour -> can adjust their future caution to increase their performance (ref: Folke, Jacobsen, Fleming & De Martino, 2017; Fleming, van der Putten & Daw, 2018). Suggestion: People with higher face recognition ability are better at estimating the difficulty of the task, voluntarily increasing their threshold to ensure a better performance given the task demands. However future research would be required to confirm this proposal. • Overall: Our results suggest that not only does high face recognition ability predict a better ability to extract meaningful information for the recognition success but also predict the voluntary strategic decision of the subject to be more cautious.

Paragraph 3: Theoretical implications Our approach provides unusual insight into individual differences in latent computational processes in the domain of face recognition. These results have several theoretical implications not only for investigating individual differences and potentially expertise effects but also offer implications regarding models of face perception and memory.

- Implications for studying individual differences and expertise:

Most of investigations of individual differences in face recognition across the entire range of face processing abilities have used associations between different abilities performance scores (ref:), addressing potential association/dissociation of abilities. In this study we used traditional approach of an experimental manipulation in a large sample, extended the separate analysis of response times and accuracy to the estimation of latent variables through computational modelling that we then associated with face recognition ability. On a general level, the new insights obtained from evidence-accumulation modelling about individual differences in face recognition would not have been possible using the conventional analysis of response times and accuracy (Parker & Ramsey, 2023b). We propose that this approach could be applicable to other types of individual differences in expertise or abilities. - One key question in cognitive psychology concern the degree to which an expertise or an ability is domain-specific or domain-general. - (here find some examples in which we could apply our approach to other abilities/expertise)

- Theoretical implications about models of face perception and memory

- Bruce and Young model

- Individual differences in face recognition: observations from comparing group-levels difference between two different populations (ex: prosopagnosia and control/super-recognizer and control) / individual differences in typical range of face processing ability

❓ While Bruce and Young model describe the face perception process in general, there are some individual variabilities in the outcome of this process (outcome = performance)

and in other steps in this [?] With this study we also contribute to the extension of this model by showing that not only there are individual differences in the outcome, but that there is also individual differences in the cognitive processes that give rise to this outcome. [?] Future research could use an individual differences approach to investigate how some variations in the components in the Bruce and Young face recognition model could influence estimated latent variables and how are individuals differences in face recognition ability are related to the observed differences of latent variables of interest.

Paragraph 4: Mentioning the car correlations Even if main interest of this paper was to look into the CFMT, the exploratory analysis of the CCMT correlations with LBA parameters reveal interesting associations:

- Drift rate: Cambridge Car Memory score positive association only with Novel faces, not learned faces .
- Object recognition memory largely relies on featural information processing (REF). Does not capture (or should not capture) holistic processing.
- Since novel faces recognition processing relies more on feature information processing and matching, it would make sense that the CCMT score only correlate to drift rate (accumulation of evidence) for novel faces and not learned faces (combination of holistic processing and feature information processing).
- When looking at car recognition effect on drift rate: similar direction for TRUE and FALSE and for both type of faces: increased drift rate as the CCMT score increase. [?] CCMT does not predict the discrimination between TRUE and FALSE drift rate. Would expect that increased recognition ability lead to increase evidence accumulation when TRUE and decreased when FALSE, but not the case here - > especially regarding learned faces, seems that increased recognition ability for object predict an increased drift rate when participant are wrong and that pattern is different that observed in the prediction of the CFMT regarding learned faces. Suggestion: using visual information processing alone help to accumulate meaningful information for the recognition of faces but also contribute to the accumulation of information detrimental to the recognition process (noise). Whereas relying on both (visual information processing and holistic processing) seems to increase the accumulation of meaningful information while decreasing the noise coming from detrimental visual information to the recognition process.

Paragraph 5: Limitations

- Small effects size (correlations)
- Similar limitations to LBA parameter estimation than in the first paper
- Object recognition memory vs. Car recognition memory?

Paragraph 6: Conclusive paragraph

A1 Appendix content here

References

- Bobak, A. K., Hancock, P. J. B., & Bate, S. (2016). Super-recognisers in Action: Evidence from Face-matching and Face Memory Tasks. *Applied Cognitive Psychology*, 30(1), 81–91. <https://doi.org/10.1002/acp.3170>
- Brown, S. D., & Heathcote, A. (2008). The simplest complete model of choice response time: Linear ballistic accumulation. *Cognitive Psychology*, 57(3), 153–178. <https://doi.org/10.1016/j.cogpsych.2007.12.002>
- Burton, A. M., White, D., & McNeill, A. (2010). The Glasgow Face Matching Test. *Behavior Research Methods*, 42(1), 286–291. <https://doi.org/10.3758/BRM.42.1.286>
- Dennett, H. W., McKone, E., Edwards, M., & Susilo, T. (2012b). Face Aftereffects Predict Individual Differences in Face Recognition Ability. *Psychological Science*, 23(11), 1279–1287. <https://doi.org/10.1177/0956797612446350>
- Dennett, H. W., McKone, E., Tavashmi, R., Hall, A., Pidcock, M., Edwards, M., & Duchaine, B. (2012a). The Cambridge Car Memory Test: A task matched in format to the Cambridge Face Memory Test, with norms, reliability, sex differences, dissociations from face memory, and expertise effects. *Behavior Research Methods*, 44(2), 587–605. <https://doi.org/10.3758/s13428-011-0160-2>
- Dobel, C., Bolte, J., Aicher, M., & Schweinberger, S. (2007). Prosopagnosia Without Apparent Cause: Overview and Diagnosis of Six Cases. *Cortex*, 43(6), 718–733. [https://doi.org/10.1016/S0010-9452\(08\)70501-X](https://doi.org/10.1016/S0010-9452(08)70501-X)
- Donkin, C., Averell, L., Brown, S., & Heathcote, A. (2009). Getting more from accuracy and response time data: Methods for fitting the linear ballistic accumulator. *Behavior Research Methods*, 41(4), 1095–1110. <https://doi.org/10.3758/BRM.41.4.1095>
- Dowsett, A. J., & Burton, A. M. (2015). Unfamiliar face matching: Pairs out-perform individuals and provide a route to training. *British Journal of Psychology*, 106(3), 433–445. <https://doi.org/10.1111/bjop.12103>
- Duchaine, B., & Nakayama, K. (2006). The Cambridge Face Memory Test: Results for neurologically intact individuals and an investigation of its validity using inverted face stimuli and prosopagnosic participants. *Neuropsychologia*, 44(4), 576–585. <https://doi.org/10.1016/j.neuropsychologia.2005.07.001>
- Fysh, M. C., Stacchi, L., & Ramon, M. (2020). Differences between and within individuals, and subprocesses of face cognition: implications for theory, research and personnel selection. *Royal Society Open Science*, 7(9), 200233. <https://doi.org/10.1098/rsos.200233>
- Haines, N., Kvam, P. D., Irving, L. H., Smith, C., Beauchaine, T. P., Pitt, M., Ahn, W.-Y., & Turner, B. (n.d.). *Theoretically Informed Generative Models Can Advance the Psychological and Brain Sciences: Lessons from the Reliability Paradox*. <https://doi.org/10.31234/osf.io/xr7y3>
- Lewandowsky, S., & Oberauer, K. (2018). Computational Modeling in Cognition and Cognitive Neuroscience. In J. T. Wixted (Ed.), *Stevens' Handbook of Experimental Psychology and Cognitive Neuroscience* (1st ed., pp. 1–35). Wiley. <https://doi.org/10.1002/9781119170174.epcn501>
- Ly, A., Boehm, U., Heathcote, A., Turner, B. M., Forstmann, B., Marsman, M., & Matzke, D. (2017). A Flexible and Efficient Hierarchical Bayesian Approach to the Exploration of Individual Differences in Cognitive-model-based Neuroscience. In A. A. Moustafa (Ed.), *Computational Models of Brain and Behavior* (1st ed., pp. 467–479). Wiley. <https://doi.org/10.1002/9781119159193.ch34>
- Matzke, D., Ly, A., Selker, R., Weeda, W. D., Scheibehenne, B., Lee, M. D., & Wagenmakers, E.-J. (2017). Bayesian Inference for Correlations in the Presence of Measurement Error and Estimation Uncertainty. *Collabra: Psychology*, 3(1), 25. <https://doi.org/10.1525/collabra.78>
- McCaffery, J. M., Robertson, D. J., Young, A. W., & Burton, A. M. (2018). Individual differences in face identity processing. *Cognitive Research: Principles and Implications*, 3(1), 21. <https://doi.org/10.1186/s41235-018-0112-9>
- McConachie, H. R. (1976). Developmental Prosopagnosia. A Single Case Report. *Cortex*, 12(1), 76–82. [https://doi.org/10.1016/S0010-9452\(76\)80033-0](https://doi.org/10.1016/S0010-9452(76)80033-0)

- Noyes, E., Hill, M. Q., & O'Toole, A. J. (2018). Face recognition ability does not predict person identification performance: using individual data in the interpretation of group results. *Cognitive Research: Principles and Implications*, 3(1), 23. <https://doi.org/10.1186/s41235-018-0117-4>
- Ratcliff, R., Smith, P. L., Brown, S. D., & McKoon, G. (2016). Diffusion Decision Model: Current Issues and History. *Trends in Cognitive Sciences*, 20(4), 260–281. <https://doi.org/10.1016/j.tics.2016.01.007>
- Richler, J. J., Tomarken, A. J., Sunday, M. A., Vickery, T. J., Ryan, K. F., Floyd, R. J., & Sheinberg, D. (n.d.). *Individual Differences in Object Recognition*.
- Russell, R., Duchaine, B., & Nakayama, K. (2009). Super-recognizers: People with extraordinary face recognition ability. *Psychonomic Bulletin & Review*, 16(2), 252–257. <https://doi.org/10.3758/PBR.16.2.252>
- Simons, D., Shoda, Y., & Lindsay, D. (2017). Constraints on Generality (COG): A Proposed Addition to All Empirical Papers. *Perspectives on Psychological Science*, 12, 174569161770863. <https://doi.org/10.1177/1745691617708630>
- Stevenson, N., Donzallaz, M., Heathcote, A., & Miletic, S. (2026). *EMC2: Bayesian Hierarchical Analysis of Cognitive Models of Choice*. <https://doi.org/10.32614/CRAN.package.EMC2>
- Verhallen, R. J., Bosten, J. M., Goodbourn, P. T., Lawrance-Owen, A. J., Bargary, G., & Mollon, J. (2017). General and specific factors in the processing of faces. *Vision Research*, 141, 217–227. <https://doi.org/10.1016/j.visres.2016.12.014>
- White, C. N., & Kitchen, K. N. (2022). On the Need to Improve the Way Individual Differences in Cognitive Function Are Measured With Reaction Time Tasks. *Current Directions in Psychological Science*, 31(3), 223–230. <https://doi.org/10.1177/09637214221077060>
- White, C. N., Curl, R. A., & Sloane, J. F. (2016). Using Decision Models to Enhance Investigations of Individual Differences in Cognitive Neuroscience. *Frontiers in Psychology*, 7. <https://doi.org/10.3389/fpsyg.2016.00081>
- White, D., Kemp, R. I., Jenkins, R., Matheson, M., & Burton, A. M. (2014). Passport Officers' Errors in Face Matching. *Plos ONE*, 9(8), e103510. <https://doi.org/10.1371/journal.pone.0103510>
- Wilmer, J. B., Germine, L., Chabris, C. F., Chatterjee, G., Gerbasi, M., & Nakayama, K. (2012). Capturing specific abilities as a window into human individuality: The example of face recognition. *Cognitive Neuropsychology*, 29(5–6), 360–392. <https://doi.org/10.1080/02643294.2012.753433>
- Wilmer, J. B., Germine, L., Chabris, C. F., Chatterjee, G., Williams, M., Loken, E., Nakayama, K., & Duchaine, B. (2010). Human face recognition ability is specific and highly heritable. *Proceedings of the National Academy of Sciences*, 107(11), 5238–5241. <https://doi.org/10.1073/pnas.0913053107>
- Yarkoni, T. (2022). The generalizability crisis. *Behavioral and Brain Sciences*, 45, e1. <https://doi.org/10.1017/S0140525X20001685>