Notes 6: Linux File Management Commands

1. mkdir

Definition:
The `mkdir` command creates new directories (folders) in the file system.

Usage/Formula:
`mkdir [directory_name]`

Examples:

- `mkdir projects`
- `mkdir homework`
- `mkdir -p school/assignments/week6`

2. touch

Definition:
The `touch` command creates an empty file or updates the timestamp of an existing file.

Usage/Formula:
`touch [file_name]`

Examples:

- `touch notes.txt`
- `touch homework.md`
- `touch lab6.txt`2

3. rm

Definition:
The `rm` command removes files or directories from the file system.

Usage/Formula:
`rm [file_name]`

Examples:

- `rm oldfile.txt`
- `rm notes.txt`
- `rm -r old_folder`

4. cp

Definition:
The `cp` command copies files or directories from one location to another.

Usage/Formula:

```
cp [source] [destination]
```

Examples:

- `cp notes.txt backup.txt`
- `cp homework.txt Documents/`
- `cp -r projects/ backup/`

5. mv

Definition:

The `mv` command moves files or directories to another location or renames them.

Usage/Formula:

```
mv [source] [destination]
```

Examples:

- `mv notes.txt Documents/`
- `mv oldname.txt newname.txt`
- `mv homework/ Documents/`