```
aryan@LAPTOP-S5BAGLQR: ~                                                        —    □    ×

* Management:      https://landscape.canonical.com
* Support:         https://ubuntu.com/advantage

  System information as of Wed Mar  3 12:25:58 IST 2021

  System load:            0.52
  Usage of /home:         unknown
  Memory usage:           46%
  Swap usage:             0%
  Processes:              7
  Users logged in:        0
  IPv4 address for eth2:  192.168.56.1
  IPv4 address for wifi0: 192.168.29.39
  IPv6 address for wifi0: 2405:201:7000:9909:7198:7c20:4113:6163
  IPv6 address for wifi0: 2405:201:7000:9909:51a5:571e:6490:1122

1 update can be installed immediately.
0 of these updates are security updates.
To see these additional updates run: apt list --upgradable


The list of available updates is more than a week old.
To check for new updates run: sudo apt update


This message is shown once a day. To disable it please create the
/home/aryan/.hushlogin file.
aryan@LAPTOP-S5BAGLQR:~$ sudo service cron start
[sudo] password for aryan:
Sorry, try again.
[sudo] password for aryan:
 * Starting periodic command scheduler cron                              [ OK ]
aryan@LAPTOP-S5BAGLQR:~$ crontab -u
crontab: option requires an argument -- 'u'
crontab: usage error: unrecognized option
usage:  crontab [-u user] file
        crontab [ -u user ] [ -i ] { -e | -l | -r }
                (default operation is replace, per 1003.2)
        -e      (edit user's crontab)
        -l      (list user's crontab)
        -r      (delete user's crontab)
        -i      (prompt before deleting user's crontab)
aryan@LAPTOP-S5BAGLQR:~$ tty
/dev/tty1
aryan@LAPTOP-S5BAGLQR:~$
```

Scanned by TapScanner

```
# Edit this file to introduce tasks to be run by cron.
#
# Each task to run has to be defined through a single line
# indicating with different fields when the task will be run
# and what command to run for the task
#
# To define the time you can provide concrete values for
# minute (m), hour (h), day of month (dom), month (mon),
# and day of week (dow) or use '*' in these fields (for 'any').
#
# Notice that tasks will be started based on the cron's system
# daemon's notion of time and timezones.
#
# Output of the crontab jobs (including errors) is sent through
# email to the user the crontab file belongs to (unless redirected).
#
# For example, you can run a backup of all your user accounts
# at 5 a.m every week with:
# 0 5 * * 1 tar -zcf /var/backups/home.tgz /home/
#
# For more information see the manual pages of crontab(5) and cron(8)
#
# m h  dom mon dow   command
17 16 03 03 * echo "Hi i am aryan" >/dev/tty1
```

Save modified buffer?

 Y Yes
 N No   ^C Cancel

```
* Management:        https://landscape.canonical.com
* Support:           https://ubuntu.com/advantage

  System information as of Wed Mar  3 12:25:58 IST 2021

  System load:           0.52
  Usage of /home:        unknown
  Memory usage:          46%
  Swap usage:            0%
  Processes:             7
  Users logged in:       0
  IPv4 address for eth2:  192.168.56.1
  IPv4 address for wifi0: 192.168.29.39
  IPv6 address for wifi0: 2405:201:7000:9909:7198:7c20:4113:6163
  IPv6 address for wifi0: 2405:201:7000:9909:51a5:571e:6490:1122

1 update can be installed immediately.
0 of these updates are security updates.
To see these additional updates run: apt list --upgradable


The list of available updates is more than a week old.
To check for new updates run: sudo apt update


This message is shown once a day. To disable it please create the
/home/aryan/.hushlogin file.
aryan@LAPTOP-S5BAGLQR:~$ sudo service cron start
[sudo] password for aryan:
Sorry, try again.
[sudo] password for aryan:
 * Starting periodic command scheduler cron                               [ OK ]
aryan@LAPTOP-S5BAGLQR:~$ crontab -u
crontab: option requires an argument -- 'u'
crontab: usage error: unrecognized option
usage:  crontab [-u user] file
        crontab [ -u user ] [ -i ] { -e | -l | -r }
                (default operation is replace, per 1003.2)
        -e      (edit user's crontab)
        -l      (list user's crontab)
        -r      (delete user's crontab)
        -i      (prompt before deleting user's crontab)
aryan@LAPTOP-S5BAGLQR:~$ tty
/dev/tty1
aryan@LAPTOP-S5BAGLQR:~$ crontab -e
crontab: installing new crontab
aryan@LAPTOP-S5BAGLQR:~$ Welcome to srm
```

```
aryan@LAPTOP-S5BAGLQR: ~                                                                          —   □   ×

This message is shown once a day. To disable it please create the
/home/aryan/.hushlogin file.
aryan@LAPTOP-S5BAGLQR:~$ sudo service cron start
[sudo] password for aryan:
Sorry, try again.
[sudo] password for aryan:
 * Starting periodic command scheduler cron                                                              [ OK ]
aryan@LAPTOP-S5BAGLQR:~$ crontab -u
crontab: option requires an argument -- 'u'
crontab: usage error: unrecognized option
usage:  crontab [-u user] file
        crontab [ -u user ] [ -i ] { -e | -l | -r }
                (default operation is replace, per 1003.2)
        -e      (edit user's crontab)
        -l      (list user's crontab)
        -r      (delete user's crontab)
        -i      (prompt before deleting user's crontab)
aryan@LAPTOP-S5BAGLQR:~$ tty
/dev/tty1
aryan@LAPTOP-S5BAGLQR:~$ crontab -e
crontab: installing new crontab
aryan@LAPTOP-S5BAGLQR:~$ Welcome to srm
^C
aryan@LAPTOP-S5BAGLQR:~$ crontab -l
# Edit this file to introduce tasks to be run by cron.
#
# Each task to run has to be defined through a single line
# indicating with different fields when the task will be run
# and what command to run for the task
#
# To define the time you can provide concrete values for
# minute (m), hour (h), day of month (dom), month (mon),
# and day of week (dow) or use '*' in these fields (for 'any').
#
# Notice that tasks will be started based on the cron's system
# daemon's notion of time and timezones.
#
# Output of the crontab jobs (including errors) is sent through
# email to the user the crontab file belongs to (unless redirected).
#
# For example, you can run a backup of all your user accounts
# at 5 a.m every week with:
# 0 5 * * 1 tar -zcf /var/backups/home.tgz /home/
#
# For more information see the manual pages of crontab(5) and cron(8)
#
# m h  dom mon dow   command
31 12 03 03 * echo "Welcome to srm" >/dev/tty1


aryan@LAPTOP-S5BAGLQR:~$
```

GNU nano 4.8   /tmp/crontab.Ip8hcU/crontab   Modified

```
# Edit this file to introduce tasks to be run by cron.
#
# Each task to run has to be defined through a single line
# indicating with different fields when the task will be run
# and what command to run for the task
#
# To define the time you can provide concrete values for
# minute (m), hour (h), day of month (dom), month (mon),
# and day of week (dow) or use '*' in these fields (for 'any').
#
# Notice that tasks will be started based on the cron's system
# daemon's notion of time and timezones.
#
# Output of the crontab jobs (including errors) is sent through
# email to the user the crontab file belongs to (unless redirected).
#
# For example, you can run a backup of all your user accounts
# at 5 a.m every week with:
# 0 5 * * 1 tar -zcf /var/backups/home.tgz /home/
#
# For more information see the manual pages of crontab(5) and cron(8)
#
# m h  dom mon dow   command
31 12 03 03_ echo "Welcome to srm" >/dev/tty1
```

^G Get Help   ^O Write Out   ^W Where Is   ^K Cut Text   ^J Justify   ^C Cur Pos   M-U Undo   M-A Mark Text   M-] To Bracket   M-Q Previous   ^B Back   Prev Word
^X Exit   ^R Read File   ^\ Replace   ^U Paste Text   ^T To Spell   ^_ Go To Line   M-E Redo   M-6 Copy Text   ^Q Where Was   M-W Next   ^F Forward   Next Word

```
# For more information see the manual pages of crontab(5) and cron(8)
#
# m h  dom mon dow   command
31 12 03 03 * echo "Welcome to srm" >/dev/tty1


aryan@LAPTOP-S5BAGLQR:~$ crontab -l
# Edit this file to introduce tasks to be run by cron.
#
# Each task to run has to be defined through a single line
# indicating with different fields when the task will be run
# and what command to run for the task
#
# To define the time you can provide concrete values for
# minute (m), hour (h), day of month (dom), month (mon),
# and day of week (dow) or use '*' in these fields (for 'any').
#
# Notice that tasks will be started based on the cron's system
# daemon's notion of time and timezones.
#
# Output of the crontab jobs (including errors) is sent through
# email to the user the crontab file belongs to (unless redirected).
#
# For example, you can run a backup of all your user accounts
# at 5 a.m every week with:
# 0 5 * * 1 tar -zcf /var/backups/home.tgz /home/
#
# For more information see the manual pages of crontab(5) and cron(8)
#
# m h  dom mon dow   command
31 12 03 03 * echo "Welcome to srm" >/dev/tty1


aryan@LAPTOP-S5BAGLQR:~$ crontab -u
crontab: option requires an argument -- 'u'
crontab: usage error: unrecognized option
usage:  crontab [-u user] file
        crontab [ -u user ] [ -i ] { -e | -l | -r }
                (default operation is replace, per 1003.2)
        -e      (edit user's crontab)
        -l      (list user's crontab)
        -r      (delete user's crontab)
        -i      (prompt before deleting user's crontab)
aryan@LAPTOP-S5BAGLQR:~$ crontab -e
crontab: installing new crontab
aryan@LAPTOP-S5BAGLQR:~$ crontab -e
crontab: installing new crontab
aryan@LAPTOP-S5BAGLQR:~$ Hi i am aryan
```