Continuous-time Koopman autoencoder for transonic flow

Audit, fixes, redesign and benchmark against ACDM

Prepared for R. Grozavescu

22 October 2026

The short version

Question. Can the continuous-time, Mach-conditioned Koopman autoencoder (KAE) in `ocean_forecasting` be made to beat ACDM on the transonic cylinder benchmark (TRA) while keeping its continuous-time dynamics and zero-shot conditioning?

What I did.

1. **Audited** the original code, data and evaluation. I found 25 problems and fixed 18 of them, fully or partly; the other 7 are data or modelling issues, which are either addressed by the new model or listed as open. Several of them changed reported numbers (§2–3).
2. **Re-scored every baseline** with one verified scorer. This covers ACDM and all 13 official checkpoints from the ACDM paper (§4).
3. **Built a redesigned model** (CT-KAE) in a separate file and **tested it in 31 training runs**: 7 pilots, 5 final runs, a retrained legacy model, 4 representation tests (§5–6.7) and 14 follow-up runs (§7–10).

Main result (test set, MSE $\times 10^{-3}$, lower is better; "energy" is the share of the true fluctuation energy the forecast keeps, where 1 is ideal):

	Interpolation 60 steps	Extrapolation 60 steps	Long rollout 240 steps	Energy at step 58 (interp)	Correlation at step 58 (interp)
Original KAE (reproducible)	11.43	2.12	18.6	1.26	0.28
CT-KAE, 2 → 60 (3 seeds)	4.07 ± 0.29	2.18 ± 0.14	16.5 ± 2.0	0.77	0.62
CT-KAE, 2 → 8 (3 seeds)	**3.49** ± 0.15	**1.98** ± 0.31	**16.2** ± 0.6	**0.94**	**0.69**
ACDM (official)	2.81–3.02	1.99–2.22	22.5–22.8	1.10	0.73
U-Net (official, best)	1.53	1.42	22.4	1.08	0.85

Bottom line.

- The best new model (2 → 8) is **3.3× more accurate than the original** on interpolation. Its Mach conditioning now works and helps, and it predicts correctly at time steps it never saw.
- It is the best latent model on this benchmark: every latent model in the ACDM paper scores 6.4–7.4 on interpolation.
- It does **not** beat ACDM on interpolation. It is **level** with ACDM on extrapolation.
- It has lower error than ACDM on the 240-step rollout, but partly because it damps the oscillations. A constant mean field scores 15.8 on that case, so 240-step MSE is not good evidence of skill.
- The official stabilised U-Nets from the ACDM paper beat all models on the two 60-step cases.
- **Where the remaining gap comes from** (§10.1):
  - the reconstruction error at the first step is about 0.26, against 0.02–0.03 for the U-Net and ACDM. It explains about half of the gap to ACDM, but only an eighth of the gap to the U-Net;
  - the rest is error that grows with lead time: blurred or misplaced structure, harmonics, and late phase drift. The shedding frequency itself is accurate.

  Five targeted fixes did not close it under the 8-frame horizon rule (§10.3).

Update, 22 October (details in §10).

- **The first-step error is all reconstruction**, but it explains only half of the gap to ACDM and an eighth of the gap to the U-Net. The rest grows with lead time: blurred or misplaced structure, harmonics, and late phase drift. The shedding frequency itself is accurate.
- **Five fixes from a 47-paper literature review were tried; none helped.**
  - A detail latent cut the first-step error to ACDM's level (0.02), but collapsed after the 8-frame training window.
  - A harmonic-lattice generator and multi-start consistency both made the 60-step forecast worse.
- **The plain fair-horizon model remains the best.** Under the 8-frame horizon rule it appears to be close to the ceiling for a linear-latent model.

Update, 21 October (evening) (details in §9).

- **The original KAE's DA lead at df = 9 comes from checkpoint selection.** Its DA checkpoint (epoch 40) was picked on the trajectories DA is tested on. With its final checkpoint, as used for the new models and for its own forecast numbers, it scores 0.099–0.106 at df = 9. That is *worse* than the fair-horizon model (0.093–0.098, 3 seeds) and the curriculum model (0.094–0.100).
- At df = 1 the original and the curriculum model stay level and best. The fair-horizon model is about 1.5× worse on the window sweeps.
- A multiscale decoder did not lower the first-step error (0.260 vs 0.261). Decoder size and latent size are now both ruled out as its cause.

Update, 21 October: fair-horizon model (details in §8).

- Trained only for forecasting, end-to-end, on ACDM's data with the baselines' horizon (2 frames → 8 predicted), latent 256. This is **the best CT-KAE**: interp 3.49, extrap 1.98, long 16.2 (3 seeds). It keeps 94% of the oscillation energy at step 58, and its first-step error is 2.5× lower than the 60-step model's.
- Against ACDM it is still behind on interpolation (about 2.9) and level on extrapolation.
- **Data assimilation: the original model is still best** (df = 9: 0.093–0.098 vs 0.078–0.086). This holds after widening the learning-rate search, which the earlier runs had capped.

Update, 20 October (details in §7).

- **Training exactly as ACDM does** (2 frames → 1 predicted frame) makes this model much *worse*: interp 10.67, extrap 7.28, long 27.6. A linear latent model needs multi-step training; one-step training only sharpens its reconstruction.
- **The fixed point μ makes no measurable difference** and can be dropped. The model is then exactly $dz/dt = A(Ma)\, z$.
- **Data assimilation: your original model is still the best.** The best new model (a one-step-then-60-step curriculum) ties it at df = 1 and is 15–25% behind at df = 9. Both beat U-Net, FNO and ACDM by a wide margin at df = 9.

Correction to earlier figures. The original KAE numbers used in the earlier audit and in the paper drafts (6.37 / 1.59 / 16.91) come from saved prediction files that no checkpoint and no code in the repository can reproduce. Run with the repository code, the same checkpoint gives 11.43 / 2.12 / 18.62. Only reproducible numbers are used in this document.

Contents

1 Setting **4**

2 What was wrong with the original code **4**

3 What was fixed **5**

4 Verified baselines **5**

5 The new model (CT-KAE) **5**

6 Experiments **6**

6.1 Pilot runs: which ingredients matter? 6

6.2 Final runs and selection 6

6.3 Test results . . . 7
6.4 What helps on the test cases (single-seed analysis) . . . 7
6.5 Zero-shot generalisation . . . 7
6.6 Where the remaining gap comes from . . . 8
6.7 Representation experiments . . . 8

7 Follow-up (20 October): ACDM's training setting, μ, curriculum and data assimilation 9
7.1 Training exactly as ACDM does . . . 9
7.2 Does the fixed point $\mu(Ma)$ matter? . . . 10
7.3 Curriculum: one-step first, then 60 steps . . . 10
7.4 Data assimilation: new model vs original . . . 10

8 Follow-up (21 October): fair-horizon training ($2 \to 8$) 11
8.1 Forecasting . . . 12
8.2 Data assimilation . . . 12

9 Follow-up (21 October, evening): why the original wins DA, and a multiscale decoder 13
9.1 Was the curriculum model under-tuned? . . . 13
9.2 Does checkpoint selection explain the original's DA advantage? . . . 14
9.3 Why: how well do the observations pin down the initial state? . . . 14
9.4 Multiscale decoder . . . 15

10 Follow-up (22 October): where the remaining error comes from, and five attempts to reduce it 15
10.1 Diagnosis . . . 15
10.2 Literature . . . 16
10.3 Five attempts . . . 17
10.4 Conclusion . . . 17

11 Answers to the project's questions 17

12 What I would do next 18

A Where everything is 19

B How to reproduce 19

1 Setting

Data. The ACDM "Tra" benchmark: transonic flow past a cylinder on a 128×64 grid. There are four fields (velocity v_x, v_y, pressure p, density ρ), and the Mach number Ma varies between simulations. Frames are 0.1 time units apart, and one vortex-shedding period is about 25 frames.

Test cases (all from Mach numbers never seen in training, i.e. zero-shot in Ma):

- *Interpolation*: $Ma = 0.66$–0.68, inside a 0.06-wide gap in the training range. 6 sequences of 60 frames.
- *Extrapolation*: $Ma = 0.50$–0.52, below the training range (≥ 0.53). 6 sequences of 60 frames.
- *Long rollout*: $Ma = 0.64$–0.65. 4 sequences of 240 frames.

Every model receives the first two frames and predicts the rest.

Metrics.

- *MSE*: mean squared error in physical units, averaged over the four fields, the grid and the predicted frames, $\times 10^{-3}$. The obstacle is zeroed in both prediction and truth. This is the ACDM paper's metric, except that the paper also averages over the two given input frames, which makes its numbers about 3% lower.
- *Correlation* (ACC): how well the predicted pattern of deviations from the mean flow lines up with the true one. 1 is perfect; below about 0.6 the forecast is no longer useful.
- *Energy ratio*: predicted fluctuation energy divided by true fluctuation energy. Below 1 means the forecast is fading towards the mean flow, a known way to get a low MSE without real skill.

Compute. One RTX 4090, shared throughout with another of your jobs, so all times are pessimistic.

2 What was wrong with the original code

The most consequential problems, in plain terms. The full list, with file and line numbers, is in `audit_report/issues.json`.

ID	Severity	Problem and consequence
BUG-01	critical	The evaluation script compared each prediction with the *previous* true frame. Every recent KAE score was computed against the wrong frame.
BUG-02	critical	Mach conditioning never trained: the conditioning network started with both of its factors at zero, so its gradient was exactly zero. The encoder's conditioning path was not implemented and the decoder ignored Ma. Measured effect of changing Ma on the output: exactly 0.
DATA-01	critical	The QG test trajectories *are* the training trajectories for their first 500 steps, up to a rescaling (residual 6×10^{-8}). The QG configuration also validated on the test file.
REPRO-04	critical	The saved KAE predictions behind the reported numbers cannot be regenerated. Re-running the checkpoint gives 11.43 / 2.12 / 18.62, not 6.37 / 1.59 / 16.91.
STAB-01	high	The latent dynamics were not constrained to be stable. The QG model has 63 of 128 growing modes; the KS model has 7 growing modes and 80× transient amplification.
DYN-01	high	On TRA, the vortex-shedding modes decay in 36–41 steps, but real shedding never decays. Long forecasts faded to the mean: 27% of the true energy after 240 steps.
PERF-01	high	Debugging hooks were always on, making training 16.5× slower (4.62 s → 0.28 s per step once removed).
REPRO-01/05	high	The `.gitignore` hid 35 required configuration files and all result files, so a clean clone could not run an experiment.
BUG-03, 05, 06	medium	A stability penalty was detached and had no effect; QG normalisation crashed; padding and spectral-norm settings in configs were silently ignored.

One thing that was *not* a problem. The model steps its dynamics with a fourth-order Runge–Kutta (RK4) step instead of the exact matrix exponential. At the trained step the two agree to 1.6×10^{-4}, so this is not a source of error.

3 What was fixed

All fixes are on branch `impl/ct-kae`, built on `audit/kae-research-audit`; the original branch was not touched. Each fix is its own commit with a regression test. Every test fails on the original code and passes now (39 tests in total).

Fix	What changed
Evaluation alignment	Predictions are stitched after *all* input frames, so frame k is compared with true frame k.
Conditioning	Standard LoRA initialisation (one factor random, one zero): identical starting dynamics, but the gradient now flows.
Data splits	QG validates on an independent file. TRA has a new validation split ($Ma = 0.60$ and 0.75 held out of training) so that no test case is used for model selection. Normalisation statistics come from training data only.
Speed	Debugging hooks are opt-in (`training.debug_nan_checks=true`). Timings no longer force GPU synchronisation, and the model runs on CPU.
Reproducibility	Checkpoints store the full configuration and git commit. Missing checkpoints and evaluation errors are fatal instead of silently ignored. All configs and results are tracked.
Configuration honesty	Time step, frame dropping, loss type and conv settings are now real options. Defaults keep old checkpoints loading with bit-identical outputs (verified).

4 Verified baselines

All 13 baseline models from the ACDM paper exist locally as the official pretrained checkpoints (3 seeds each). I re-scored all of them with the same code. My ACDM interpolation score (2.81) matches the paper's 2.7 once the frame-averaging difference is accounted for. The paper reports *no* numbers for the long rollout, so all 240-step values are re-evaluations.

Model (official checkpoints)	Interp.	Extrap.	Long	Energy at 238 (long)
U-Net, unrolled training ("U-Net_ut")	**1.53**	1.66	22.4	1.17
U-Net, noise training ("U-Net_tn")	1.83	**1.42**	22.6	1.18
ACDM (two independent sampling runs)	2.81–3.02	1.99–2.22	22.5–22.8	1.11
FNO	5.72	4.98	21.0	0.97
Linear POD + linear dynamics (no neural net)	6.06	3.86	13.4	0.05
Constant training-mean field	16.76	17.39	**15.8**	0.17
Persistence (repeat last frame)	23.44	17.64	28.8	1.07

The last three rows matter for interpretation. A model that fades to the mean (energy $\ll 1$) scores well on 240-step MSE without predicting anything: the constant field beats every neural model there.

5 The new model (CT-KAE)

The new model keeps the framework (encoder, linear continuous-time latent dynamics, decoder, conditioning on Ma) and redesigns its components. It lives in its own file, `models/ct_kae.py`; the old model is untouched.

$$
\begin{aligned}
z_0 &= E\big(x_{t-1}, x_t;\, Ma\big) && \text{encode the last two frames} \\
z(t+\tau) &= \mu(Ma) + e^{\tau A(Ma)}\big(z_0 - \mu(Ma)\big) && \text{exact, for any } \tau \\
\hat{x}(t+\tau) &= D\big(z(t+\tau);\, Ma\big) && \text{decode}
\end{aligned}
$$

- **Generator $A(Ma)$.** A set of 2×2 oscillator blocks, each with a damping rate $\gamma_j \geq 0$ and a frequency ω_j. Both shift with Ma through a small network. Each block's exponential is just "decay $\times$ rotation", so propagation is exact, cheap and stable by construction: no mode can grow, but a mode may be perfectly persistent ($\gamma_j \to 0$), which shedding needs.
- **Fixed point $\mu(Ma)$.** The mean flow changes smoothly with Mach number (mean v_x rises from 0.44 to 0.72 across the range), so the latent dynamics oscillate around a Mach-dependent centre.
- **Conditioning** enters the encoder and decoder (feature-wise scaling, "FiLM"), the generator and the fixed point. Every conditional part starts at zero yet receives gradient, which avoids the bug in the original.
- **Encoder and decoder.** Convolutional, flattening to a 256-number latent. Unlike the original, there is no single-query attention pooling, no forced spectral norm and no dropout.

- **Training objective.** The model is trained on rollouts of up to 60 steps (the original used 8): reconstruction, prediction on randomly chosen lead times, latent consistency against the encoded truth, and an optional amplitude term that rewards keeping the size of each oscillation without forcing its phase. Training at several time steps (0.05, 0.1, 0.15) makes the dynamics genuinely continuous-time.
- **Two alternative generators** were also tested: a dense "Hurwitz" generator $A = J - R$ (stable, with mode coupling), and the original unconstrained form.

All new code is covered by 20 tests, including: exact propagation equals the matrix exponential to 10^{-9}; stepping t_1 then t_2 equals stepping t_1+t_2; the stable generators never grow; conditioning receives gradients and changes the output; and data windows are time-aligned.

6 Experiments

All model choices were made on the *validation* split (held-out $Ma = 0.60, 0.75$). The test cases were evaluated only after the final checkpoints were fixed.

6.1 Pilot runs: which ingredients matter?

Seven short runs (about 31 minutes each). Each changes one thing relative to the reference P0.




Figure 1: Best validation error of each pilot (single seed). Dashed line: linear POD baseline on the same windows.

- **Training horizon is the biggest lever.** Training on 10 steps instead of 60 makes 60-step error 30% worse, and the forecast fades towards the mean. This confirms that the original's 8-step objective caused its damping.
- **Stable generators beat the unconstrained one.** Ruling out growth costs no accuracy.
- The amplitude term and multiple time steps cost nothing measurable.
- Removing Mach conditioning barely matters *on validation*, because the validation Mach numbers sit 0.01 from training ones. It does matter on the wider test gaps (§6.4).

6.2 Final runs and selection

Five longer runs (12k steps, about 1 hour each), selected by validation error over 60 steps:

Configuration	Seeds	Val. error (60 steps)	First 10 steps
Block + amplitude term + multiple time steps	3	**4.04 / 4.33 / 4.09**	0.66–0.72
Hurwitz generator + multiple time steps	2	4.37 / 4.50	0.85–0.91
Linear POD baseline (same windows)	–	7.94	1.16

All three block seeds beat both Hurwitz seeds, so the block generator is the selected model.

6.3 Test results

Model	Interp.	Extrap.	Long	Energy at step 58	
				interp	long
CT-KAE, selected checkpoints (3 seeds)	**4.07** ± 0.29	**2.18** ± 0.14	16.5 ± 2.0	0.77	0.57
CT-KAE, final checkpoints (no early stop)	5.59 ± 0.29	2.56 ± 0.23	18.1 ± 0.5	1.11	0.88
CT-KAE, Hurwitz generator (2 seeds)	4.65	2.23	13.9	–	–
Original model retrained with all fixes	8.18	3.83	22.8	0.93	0.84
Original checkpoint (reproducible)	11.43	2.12	18.6	1.26	0.85
ACDM	2.81–3.02	1.99–2.22	22.5–22.8	1.10	1.01
U-Net (best official variant)	1.53	1.42	22.4	1.08	1.05

Reading the table.

- **Against the original:** the redesign is 2.8× better on interpolation, and much better at tracking the true flow. Correlation at step 58 is 0.62 vs 0.28 on interpolation and 0.46 vs 0.18 on the long case.
- **Against ACDM:**
  - worse on interpolation (4.07 vs about 2.9);
  - level on extrapolation, within the spread of ACDM's two sampling runs;
  - lower MSE on the long case. However, its correlation horizon is slightly shorter (43–48 vs 50–52 steps), and Fig. 3 shows it loses about half its energy between steps 60 and 150. That is not a win on long-horizon dynamics.
- **Damping is reduced, not removed.** The checkpoints chosen by MSE keep 57–77% of the energy at step 58. The final checkpoints keep about 100% but have higher MSE. This is the price MSE puts on keeping amplitude once the phase drifts. ACDM and the U-Nets avoid it because they re-anchor on their own predicted frame at every step.




Figure 2: Error at each forecast step (log scale). The new model starts high, which is the reconstruction floor, but grows slowly. At long lead times it matches ACDM on interpolation and is below ACDM on extrapolation.

6.4 What helps on the test cases (single-seed analysis)

These runs were scored on test *after* selection, only to understand the mechanisms.

Run (6k steps)	Interp.	Extrap.	Long	Reading
P0: block generator, single time step	4.40	1.71	15.6	reference
P3: P0 without Mach conditioning	5.43	2.04	18.9	conditioning helps: −19%, −16%
P5: P0 trained on 10-step horizon	5.18	2.44	15.9	long-horizon training helps

6.5 Zero-shot generalisation

Unseen Mach numbers. All three test cases use Mach numbers absent from training, so the table above *is* the zero-shot result. Fig. 4 shows that the forecast responds smoothly and monotonically when the Mach number given to the model is varied. Without conditioning the response is exactly zero.




Figure 3: Share of true fluctuation energy kept during the 240-step rollout. ACDM and U-Net stay near 1. The new model (bold: mean of 3 seeds; thin: individual seeds) dips to about 0.45 mid-rollout. The original fades steadily to 0.27.

Unseen time steps. P0 was trained only at $\Delta t = 0.1$. Asked for forecasts every 0.05 (half-steps it never saw), its error at the new half-step times equals its error at the trained times: 4.408 vs 4.400 on interpolation and 1.720 vs 1.707 on extrapolation. The exact continuous-time propagation generalises in time, which a discrete step-to-step model cannot do.




Figure 4: How much the forecast of an interpolation trajectory (true $Ma = 0.66$) changes when the model is told a different Mach number.

6.6 Where the remaining gap comes from

Fig. 2 locates it. At the first step the new model's error is 0.66 (interpolation), against 0.03 for ACDM and 0.02 for the U-Net, and it stays nearly flat for five steps. This is the error of encoding and decoding a frame through the 256-number latent, before any dynamics act. At late lead times the curves meet or cross. A linear POD with 128 modes reconstructs *better* (floor about 0.46) than this nonlinear autoencoder.

6.7 Representation experiments

Since the gap is a reconstruction floor, I tested the two most direct remedies on the selected configuration: a larger latent and a heavier reconstruction weight. These are four short runs (6k steps, one seed each), compared on validation only.

Run	Latent size	Best val. error (60 steps)	First-10-step error (end)	Energy kept (60)
R0 reference	256	4.48	0.58	0.97
R1 larger latent	512	4.12	0.56	0.99
R2 much larger latent	1024	4.50	**0.49**	0.97
R3 reconstruction ×5	256	4.40	0.53	0.95




Figure 5: Representation tests (single seed). Neither a 4× larger latent nor a 5× reconstruction weight changes the 60-step error beyond noise.

Result: neither remedy closes the gap.

- Quadrupling the latent lowers the early-step error by only about 15% (0.58 → 0.49). The overall 60-step error does not move beyond single-seed noise.
- Weighting reconstruction 5× helps by a similar small amount.
- The first-step gap to ACDM is 20–30×, so latent size is not the bottleneck.
- The likely causes are the encoder and decoder architecture themselves (they compress a $4 \times 64 \times 128$ field through one fully connected layer), and the joint training. The dynamics loss pulls the latent towards coordinates that are easy to propagate rather than easy to reconstruct.
- The next things to test are a multiscale (U-Net-style) decoder and pre-training the autoencoder alone before adding the dynamics.

7 Follow-up (20 October): ACDM's training setting, μ, curriculum and data assimilation

This section answers the three questions raised after the first version of the report. All runs use the same code, scorer and test cases as before.

7.1 Training exactly as ACDM does

ACDM's training script (`training_diffusion_tra.py`) uses `sequenceLength=[3, 2]`: 2 conditioning frames and **1** predicted frame at stride 2. I reproduced that setting exactly:

- the same 33 training simulations, adding simulation 40 (Ma 0.90), which was missing from `train.nc`, from the raw ACDM files;
- all 1,000 frames with random offsets;
- batch 64;
- no validation split, and the final checkpoint is used.

The only unmatched quantity is the epoch count, which is undocumented for the released ACDM models. Ours is 12k steps, about 140 epochs.

Test set, MSE $\times 10^{-3}$	interp	extrap	long	error at lead 1	error at lead 10
CT-KAE, ACDM setting (2 → 1)	10.67	7.28	27.6	**0.08**	3.08
CT-KAE, 60-step training (2 → 60)	**3.84**	2.23	15.0	0.66	**1.00**
ACDM	2.81–3.02	1.99–2.22	22.5–22.8	0.03	0.29

Result: the ACDM setting makes this model much worse (single seed; seeds 1–2 were dropped once this was clear).

- **Why.** ACDM conditions on its own last output at every step, so one-step training is enough for it. A Koopman model propagates the latent state forward in one go. Trained only on one-step pairs, its errors compound: by step 10 it is ten times worse than ACDM.
- **What it reveals.** With one-step training the reconstruction floor falls 8× (0.66 → 0.08, close to ACDM's 0.03). So the floor in the 60-step model comes from the multi-step objective *competing* with reconstruction. It does not come from latent size (§6.7).

7.2 Does the fixed point $\mu(Ma)$ matter?

μ does not make the model nonlinear. The dynamics are exactly linear in $z - \mu$, and in the augmented state $[z; 1]$:

$$\tfrac{d}{dt}[z; 1] = \begin{bmatrix} A & -A\mu \\ 0 & 0 \end{bmatrix} [z; 1]$$

Both forms are tested to 10^{-9}. Removing μ entirely gives plain $e^{\tau A} z$, which is also tested.

Measured effect (test, single seed per row):

Setting	Variant	interp	extrap	long	energy at step 58 (interp)
$2 \to 60$	with μ	3.84	2.23	14.96	0.74
$2 \to 60$	without μ	3.86	1.90	15.25	0.75
ACDM setting	with μ	10.67	7.28	27.6	0.59
ACDM setting	without μ	12.30	6.06	24.8	1.69

Result: no measurable difference. In the 60-step setting, both variants fall within the spread of the three μ seeds (interp 3.84–4.40, extrap 2.02–2.30). The model can therefore be used without μ, with purely linear latent dynamics $dz/dt = A(Ma)\, z$, at no cost.

7.3 Curriculum: one-step first, then 60 steps

The model trains one step at a time for the first 30% of steps (to learn sharp reconstructions), then ramps to 60-step rollouts.

Test, single seed	interp	extrap	long	error at lead 1	val. error (60 steps)
$2 \to 60$	**3.84**	2.23	14.96	0.66	4.04
Curriculum	4.45	**1.81**	**14.50**	0.49	**3.77**

The curriculum keeps only part of the sharp reconstruction: the lead-1 error falls from 0.66 to 0.49, but not to 0.08. Extrapolation improves (1.81, slightly better than ACDM's 1.99–2.22, but still behind U-Net_tn's 1.42). Interpolation is a little worse. One seed, so this is suggestive.

7.4 Data assimilation: new model vs original

Setup.

- The new model enters your existing 4D-Var code through an adapter. It is exposed in the shifted coordinates $z - \mu$, so the solver sees a purely linear $e^{K\tau}$ and runs unchanged. The adapter reproduces the model's own forecast to 1.5×10^{-4}.
- Both models run on the same DA code, and each learning rate is tuned the same way on `gt_extrap`.
- The original was re-run rather than reusing its saved numbers, which came from code that has since changed.
- The original DA checkpoint was selected on the regime DA is tested on, a small advantage for it.

Mean relative error of the analysis over each sweep's points (lower is better; 8 problems per point):

Sweep	Original KAE	CT-KAE curriculum	CT-KAE $2 \to 60$	CT-KAE ACDM setting
df = 9 (first observation 9 frames after the analysis time)				
window length δ_l	**0.085**	0.094	0.130	0.224
noise	**0.078**	0.094	0.129	0.215
sparsity	**0.086**	0.100	0.108	0.306
misspecified noise	**0.078**	0.099	0.132	0.216
number of observations	**0.079**	0.095	0.126	0.216
joint sparsity	**0.078***	0.100	0.110	0.276
df = 1 (canonical schedule)				
first-observation lead δ_f	**0.070**	0.074	0.094	0.194
single observation	**0.089**	0.091	0.105	0.190
window length δ_l	0.027	**0.027**	0.032	0.145
noise	**0.028**	0.028	0.033	0.147
sparsity	**0.031**	0.037	0.042	0.272
misspecified noise	**0.028**	0.029	0.034	0.147
number of observations	**0.026**	0.027	0.031	0.147
joint sparsity	**0.027**	0.028	0.034	0.227
Representation check (df = 9 default problem)				
decoder floor: decode(encode(truth))	0.041	0.032	0.041	**0.014**
4D-Var started from the true state	**0.074**	0.096	0.131	0.208
tuned learning rate	0.3	1.0†	1.0†	1.0†

* 3 of 5 points; the other two ran out of GPU memory. † Top of the search grid, so these models may still be slightly under-tuned. For context, your September runs give U-Net / FNO / ACDM about 0.27 / 0.29 / 0.25 at df = 9.

Result.

- **Your original model is still the best data-assimilation model.**
  - df = 1: the curriculum CT-KAE essentially ties it (within 0.001 on most sweeps).
  - df = 9: the curriculum CT-KAE is 15–25% behind.
  - Every KAE beats U-Net, FNO and ACDM by a wide margin at df = 9, except the ACDM-setting model.
- **The gap is not representation.** The new decoders represent the true state as well as or better than the original (floor 0.032–0.041 vs 0.041). It opens when 4D-Var must fit observations 9–25 steps ahead: started from the true state, the original drifts least (0.074 vs 0.096–0.131). So the difference lies in how the latent dynamics fit the observation window. Forecast accuracy and DA accuracy are not the same thing here.
- **Forecast training horizon drives DA quality.** Of the new models, the curriculum one, with the best multi-step dynamics, is best at DA; the one-step ACDM-setting model is worst.

Corrections made along the way.

- **Mislabelled schedule.** A first DA pass labelled some sweeps as df = 1 that were really df = 9: `exp_tra.py` defaults `--pin-delta-f` to 9. All numbers above set the schedule explicitly.
- **Out-of-memory crashes.** Several runs crashed with out-of-memory when DA and training shared the GPU. They were re-run alone; the gaps are marked.

8 Follow-up (21 October): fair-horizon training ($2 \to 8$)

The requirements for this round were:

- the model is trained **only for forecasting**, with no data-assimilation objective;
- it is trained **end-to-end**, with no frozen or staged parts;
- its training horizon is **comparable to the baselines**: 2 conditioning frames and 8 predicted frames, as in U-Net_ut's 8-frame unroll and the original KAE's $2 \to 8$;
- its latent size is accurate but affordable.

Setting (`configs/ctkae/fair_h8.yaml`):

- every one of the 8 predicted frames is supervised, at stride 2 only ($\Delta t = 0.1$, as ACDM);
- ACDM's 33 training simulations, all frames, batch 16, 20k steps, final checkpoint, no validation split;
- purely linear latent dynamics $dz/dt = A(Ma)\, z$, with no μ (§7.2).

Compared with the 60-step model of §6, this round also changes the training data (33 vs 30 simulations), the number of steps (20k vs 12k) and the supervision (every frame vs random frames). The gain below therefore cannot be credited to the short horizon alone.

8.1 Forecasting

Test, MSE $\times 10^{-3}$	interp	extrap	long	lead 1	energy at 58	corr. at 58
H8, latent 256 (3 seeds)	3.49 ± 0.15	1.98 ± 0.31	16.2 ± 0.6	0.26	**0.94**	0.69
H8, latent 128 (seed 0)	3.84	1.92	15.9	0.35	0.89	–
$2 \rightarrow 60$ (3 seeds, §6)	4.07 ± 0.29	2.18 ± 0.14	16.5 ± 2.0	0.66	0.77	0.62
ACDM (official)	2.81–3.02	1.99–2.22	22.5–22.8	0.03	1.10	0.73
U-Net (official, best variant)	1.53	1.42	22.4	0.02	1.08	0.85

Per seed, latent 256: interp 3.43 / 3.38 / 3.66, extrap 1.67 / 1.97 / 2.29, long 16.8 / 15.6 / 16.2.

Result.

- **This is the best CT-KAE so far.** Compared with the 60-step model:
  - interpolation error is 14% lower and extrapolation error 9% lower;
  - the first-step error is 2.5× lower (0.26 vs 0.66);
  - it keeps 94% of the oscillation energy at step 58 instead of 77%, so the mid-rollout damping is mostly gone.
- **Against ACDM:**
  - it is still behind on interpolation (3.49 vs about 2.9);
  - it is level on extrapolation (1.98 vs 1.99–2.22; seed spread 1.67–2.29);
  - it has lower 240-step error.

  The U-Nets remain better on both 60-step cases.
- **Latent size.** 256 beats 128 on interpolation, the first-step error, the energy at step 58 and every DA number. On extrapolation and the 240-step case the two are within the seed spread. 256 costs 24.7 M parameters against 16.3 M, at the same training time: about 1 hour and 12.3 GB on one GPU when not shared. 256 is the recommended size.
- **Zero-shot still holds.** Predictions at unseen half-steps are as accurate as those at whole steps (3.450 vs 3.434), and the response to Mach number is smooth.

8.2 Data assimilation

Setup.

- **Same pipeline as §7.4:** 4D-Var code, KAE slot, and learning rate tuned on `gt_extrap`.
- **Wider learning-rate grid.** The earlier grid (0.03–1.0) ended at its top value for the new models, while the error was still falling. So I widened it to 0.3–10. The optimum is now inside the grid at 3.0, for both latent sizes and all three seeds (tuning error 0.034 at 3.0, against 0.043 at 1.0 and 0.053 at 10).

Mean relative error over each sweep's points (8 problems per point; ± is the standard deviation over seeds):

Sweep	Original KAE	H8, 256 lr 3, 3 seeds	H8, 256 lr 1, seed 0	H8, 128 lr 1, seed 0	Curriculum lr 1
df = 9					
window length δ_l	**0.085**	0.096 ± 0.002	0.100	0.109	0.094
noise	**0.078**	0.094 ± 0.002	0.100	0.110	0.094
sparsity	**0.086**	0.098 ± 0.002	0.104	0.115	0.100
misspecified noise	**0.078**	0.093 ± 0.002	0.100	0.110	0.099
number of observations	**0.079**	0.095 ± 0.004	0.100	0.111	0.095
joint sparsity	**0.078***	0.097 ± 0.005	0.101	0.112	0.100
df = 1 (seed 0 only for H8)					
first-observation lead δ_f	**0.070**	0.076	0.083	0.093	0.074
single observation	0.089	**0.080**	0.088	0.093	0.091
window length δ_l	**0.027**	0.040	0.047	0.055	0.027
noise	**0.028**	0.041	0.049	0.058	0.028
sparsity	**0.031**	0.047	0.056	0.069	0.037
misspecified noise	**0.028**	0.041	0.049	0.058	0.029
number of observations	**0.026**	0.042	0.048	0.059	0.027
joint sparsity	**0.027**	0.043	0.050	0.062	0.028
Representation check (df = 9 default problem)					
decoder floor	0.041	**0.026**	0.027	0.031	0.032
4D-Var started from the true state	**0.074**	0.088	0.086	0.096	0.096

* 3 of 5 points. The curriculum model's learning rate (1.0) was later confirmed on the wider grid (§9).

Result.

- **Against the original's selected checkpoint, the original KAE is still the best data-assimilation model.** The like-for-like comparison follows in §9.2.
  - df = 9: the fair-horizon model is 13–24% behind it (0.093–0.098 vs 0.078–0.086). The gap is consistent across the three seeds.
  - df = 1: it is about 1.5× the original's error on the window sweeps, but slightly better on the single-observation sweep.
- **The fair-horizon model is level with the curriculum model at df = 9.** It is worse at df = 1.
- **Tuning mattered.** The wider learning-rate grid alone improved the new model by 7–10% at df = 9 and by 9–16% at df = 1 (seed 0).
- **The gap is not representation.** The new decoder reproduces the true state better than the original's (floor 0.026 vs 0.041). The gap opens when 4D-Var fits observations 9–25 steps ahead (0.088 vs 0.074 from the true state).
- **Forecast skill does not explain it either.** Over leads 9–25 the new model's forecast error is 3.4× lower than the original's on interpolation (1.14 vs 3.83) and 2.1× lower on extrapolation (0.66 vs 1.36). Two candidate causes were tested afterwards (§9):
  - *checkpoint selection:* the original DA checkpoint was selected on the trajectories DA is tested on. **Confirmed**: with its final checkpoint the original falls behind the new model at df = 9;
  - *conditioning of the inverse problem:* explains the difference between the original's two checkpoints, but not the rest.

  A DA-style training objective, which might close the gap, is excluded by design: the model is trained only for forecasting.

9 Follow-up (21 October, evening): why the original wins DA, and a multiscale decoder

Three questions were left open by §8. Every run in this section used the same DA code, problems and tuning procedure as before. Results are in `results/h8_summary.json`.

9.1 Was the curriculum model under-tuned?

No. On the widened learning-rate grid its optimum stays at 1.0, inside the grid (tuning error 0.022 / 0.019 / 0.021 / 0.031 at 0.3 / 1 / 3 / 10). Its DA numbers reproduced exactly, so the values in §7.4 stand.

9.2 Does checkpoint selection explain the original's DA advantage?

Background. Every DA result for your original KAE so far used `best_model.pth`. That checkpoint comes from epoch 40 and was picked by forecast loss on `gt_interp`, the same trajectories DA is tested on. The new models never see the test trajectories before testing:

- the fair-horizon model uses its final checkpoint;
- the curriculum model's checkpoint is picked on held-out Mach numbers.

I therefore re-ran the full DA suite on the original's *final* checkpoint (epoch 199). This is also the checkpoint behind its reproducible forecast numbers (11.43 / 2.12 / 18.62). Its tuned learning rate is unchanged at 0.3, inside the grid.

Sweep	Original KAE selected (ep. 40)	Original KAE final (ep. 199)	Curriculum	H8, 256 3 seeds	H8, 256 multiscale
df = 9					
window length δ_l	0.085	0.099	**0.094**	0.096	0.109
noise	0.078	0.101	**0.094**	**0.094**	0.105
sparsity	0.086	0.104	0.100	**0.098**	0.112
misspecified noise	0.078	0.102	0.099	**0.093**	0.106
number of observations	0.079	0.106	**0.095**	**0.095**	0.105
joint sparsity	0.078*	0.106	0.100	**0.097**	0.107
df = 1 (H8, 256: seed 0)					
first-observation lead δ_f	0.070	0.083	**0.074**	0.076	0.091
single observation	0.089	0.103	0.091	**0.080**	0.097
window length δ_l	0.027	0.028	**0.027**	0.040	0.051
noise	0.028	**0.028**	**0.028**	0.041	0.053
sparsity	0.031	**0.032**	0.037	0.047	0.062
misspecified noise	0.028	**0.029**	**0.029**	0.041	0.053
number of observations	0.026	0.028	**0.027**	0.042	0.054
joint sparsity	0.027	0.029	**0.028**	0.043	0.057
tuned learning rate	0.3	0.3	1.0	3.0	3.0

Bold: best among the models whose checkpoint never saw the test trajectories (all columns except the first). * 3 of 5 points.

Result: yes, at df = 9 the advantage comes from checkpoint selection.

- **df = 9:** the original's final checkpoint scores 0.099–0.106, *worse* than both new models. The fair-horizon model (3 seeds) is 3–10% better than it on every sweep.
- **df = 1:** selection barely matters on the window sweeps (0.026–0.031 vs 0.028–0.032). It does matter on the δ_f and single-observation sweeps (0.070 / 0.089 vs 0.083 / 0.103). On the window sweeps the original and the curriculum model are level and best. The fair-horizon model is about 1.5× worse on the window sweeps, but better on the single-observation sweep.
- **The fair comparison is therefore:** the new model is better at df = 9 and level or worse at df = 1, depending on the variant.

9.3 Why: how well do the observations pin down the initial state?

Method (`da_conditioning.py`). On the df = 9 default problem, each model is linearised around its best representation of the true state. Two Jacobians are compared:

- the map from latent to observations (what 4D-Var fits);
- the map from latent to the initial state (what the analysis is scored on).

Their generalised singular values (the "gains") measure, in each direction, how much the observations change per unit change of the initial state. The measure does not depend on how the latent is parametrised, so models with different latents are comparable. A small gain marks a part of the initial state that the observations barely see. The Jacobians use finite differences and agree with autograd to $< 10^{-3}$. Averages are over 8 problems.

	Original KAE ep. 40	Original KAE ep. 199	Curriculum	H8, 256	H8, 128	H8, 256 multiscale
analysis error (this problem)	0.079	0.107	0.102	0.093	0.111	0.112
weakest gain	0.10	**0.02**	0.13	0.11	0.15	0.11
10th-percentile gain	0.44	**0.14**	0.45	0.43	0.42	0.45
directions with gain $< 0.1 \times$ median	7.5%	**13.4%**	6.8%	6.6%	4.6%	6.4%
modes decaying before the first observation	0.8%	**15.6%**	0	0	0	0
condition number in latent coordinates	3×10^5	4×10^7	2×10^3	2×10^4	8×10^3	1×10^4
misfit at analysis / at encoded truth	0.20	0.24	0.55	0.83	0.84	0.88

Result.

- **It explains the two original checkpoints.** In the final checkpoint the weakly observed directions are three times weaker (10th-percentile gain 0.14 vs 0.44), and there are nearly twice as many of them. 16% of its modes decay before the first observation (frame 9). That information is lost before 4D-Var can see it, which is why it is worse at df = 9 and not at df = 1. The selected epoch-40 checkpoint happens to lack these modes.
- **It does not separate the selected original from the new models.** Their gain statistics are similar, and every new model has no fast-decaying modes and a far better latent condition number. What remains between them at df = 9 is not visible in these linear measures.
- **Every model fits the observations better than its own encoded truth does** (last row < 1). So the analysis error is limited by model error, not by optimisation, and more iterations would not help.

9.4 Multiscale decoder

Design (`z_inject` in `models/ct_kae.py`; `configs/ctkae/fair_h8_ms.yaml`).

- The latent z also writes 16 / 4 / 2 channels directly onto the decoder's 16×32 / 32×64 / 64×128 grids. This is a linear, POD-like path to the fine scales, motivated by POD's lower reconstruction error.
- The new path enters through zero-initialised layers, so training starts from the plain decoder.
- It is still a function of (z, Ma) only, so the dynamics stay exactly linear.
- It is trained end-to-end in the same $2 \to 8$ setting.
- Cost: 33.1 M parameters instead of 24.7 M, and 3% more time per step.

Rule fixed before the run: seeds 1–2 would follow only if seed 0's first-step error fell by at least 10% (below 0.235).

Seed 0, test	interp	extrap	long	lead 1	lead 10	energy at 58	DA df = 9
H8, 256	**3.43**	**1.67**	16.80	0.261	0.466	0.94	**0.091–0.095**
H8, 256, multiscale	3.67	1.97	**16.26**	0.260	**0.427**	0.94	0.105–0.112

Result: no gain.

- The first-step error is unchanged (0.260 vs 0.261), so the rule stopped the extra seeds.
- Interpolation and extrapolation are at the top of the plain model's seed spread (3.38–3.66 and 1.67–2.29).
- DA is worse.
- Zero-shot time stepping still holds (3.683 at half steps vs 3.672 at whole steps).
- **What this rules out.** Together with the latent-size test (§6.7), this rules out decoder capacity and latent size as the cause of the first-step error. The same decoder reaches 0.08 under one-step training (§7.1). The floor is therefore set by the trade-off in the training objective between reconstruction and multi-step prediction.

10 Follow-up (22 October): where the remaining error comes from, and five attempts to reduce it

This section asks why the fair-horizon model (§8) still trails the U-Net, and reports five attempts to fix it. All attempts keep the requirements: exactly linear latent dynamics, continuous time, Mach conditioning, forecasting-only end-to-end training, and the $2 \to 8$ horizon. Details are in `EXPERIMENT_RESULTS.md` §14 and `LITERATURE_REVIEW_V3.md`.

10.1 Diagnosis

The first-step error is all reconstruction. I split the one-step error on the test set into two parts: encoding and decoding the current frame, and the error added by one linear time step (`scripts/lead1_split.py`).

One-step error, interp ($\times 10^{-3}$)	reconstruction	added by the linear step	total
fair $2 \to 8$, latent 256	0.317	0.008	0.298
fair $2 \to 8$, latent 128	0.382	0.010	0.361
ACDM-setting training ($2 \to 1$)	0.092	0.022	0.088

But the first step explains only part of the gap. Gap in MSE to each baseline, by lead (interp):

	60-step average	lead 1	lead 10	lead 20	lead 30	lead 58
vs ACDM	0.47	0.23	0.18	0.54	0.92	0.03
vs U-Net	1.96	0.24	0.35	1.13	2.16	3.58

- Against ACDM, the reconstruction error is about half of the gap.
- Against the U-Net it is about one eighth. The rest grows with lead time.

What grows. I projected the error onto the true trajectory's own POD modes (`scripts/phase_drift.py`).

- The shedding frequency is accurate: within 0.2–1.5% on extrapolation, against ACDM 2.7% and U-Net 1.2%.
- Excess error over the U-Net at lead 30:
  - 49% lies outside the span of the true trajectory (blurred or misplaced structure);
  - 32% is in POD modes 3–10 (harmonics and secondary modes);
  - 8% is in the shedding pair.
- At lead 58 the shedding pair carries 33% (phase error 26–37° vs 14° for the U-Net), and the outside-span part 53%.

Checks on the trained model, at inference only (`scripts/infer_ablate.py`).

- **Damping helps.** Scaling every oscillator's damping by 1 / 0.5 / 0.25 / 0 gives interp 3.43 / 3.58 / 3.68 / 3.81. The damping hedges uncertain components, and the modes that carry most of the latent are already almost neutral.
- **The dynamics contain no harmonics.** At most 0.5% of the latent's temporal variance sits at or above twice the shedding frequency. Harmonics of the wake come only from the decoder.

The flow is only partly periodic (training data only; `scripts/shedding_freq.py`).

- Below Ma 0.875 the shedding frequency is 2.45 ± 0.16 per time unit. It scatters by 6.5% between neighbouring Mach numbers.
- Ma 0.88–0.89 is a separate regime at about 6.3.
- On average only 57% of the dominant mode's spectrum lies on the harmonic lattice.

10.2 Literature

Two source-verified reviews covered about 47 papers.

- **Most remedies target a problem this model does not have.** Pushforward, input noise, unrolling and test-time correction all target autoregressive drift. Here every lead is one exact matrix exponential from true input frames.
- **Evidence on Tra itself** (our re-scoring of the official checkpoints):
  - spectral refinement (PDE-Refiner) scores 7.50 / 5.61;
  - every latent model in the ACDM paper scores 6.4–7.4 on interpolation, so the CT-KAE is already the best latent model on this benchmark;
  - only the stabilised pixel-space U-Nets are ahead (1.53 / 1.66 unrolled, 1.83 / 1.42 with input noise).
- **The two constraint-compatible ideas both reviews ranked highest:**
  - a harmonic-lattice generator (Bagheri 2013; Lange et al. 2021);
  - multi-start temporal consistency (tcKAE, Nayak et al. 2024).

  No paper reports a linear-latent model reaching the stabilised U-Net under comparable constraints.

10.3 Five attempts

All runs used seed 0 and `last.pth`. The success criterion was fixed before the runs: interp ≤ 3.19 (two seed standard deviations below the plain model's mean) with extrap ≤ 2.29. DA is the range over the six df = 9 sweeps.

Seed 0	interp	extrap	long	lead 1	lead 58	DA df = 9
fair 2 → 8, latent 256 (reference)	**3.43**	**1.67**	16.80	0.261	**8.17**	**0.091–0.095**
+ detail latent, advection	8.85	5.53	16.98	**0.021**	15.8	0.142–0.176
+ detail latent, decay only	16.44	9.80	24.52	0.026	18.3	0.199–0.217
+ detail latent, advection, decay floor	12.79	5.99	24.73	0.030	21.5	0.292–0.306
harmonic lattice (64 of 128 pairs)	3.87	2.29	**15.35**	0.272	9.77	0.154–0.163
multi-start consistency	4.79	2.71	16.32	0.217	12.1	0.099–0.104

Result: none met the criterion.

- **Detail latent.**
  - *Design:* a spatial latent with a Fourier-diagonal advection and decay generator. It is exactly linear, which is tested against the dense matrix exponential to 10^{-9}.
  - *What it fixes:* the first step, to 0.02–0.03, as good as ACDM and the U-Net.
  - *What goes wrong:* the model moves the near-term dynamics into the detail latent. The oscillators go static or leave the shedding frequency, and the decoder never learns to forecast without the detail. Beyond the 8-frame window the forecast collapses, and a decay floor does not prevent it.
- **Harmonic lattice.**
  - The long rollout improves slightly; 15.35 is below all three reference seeds.
  - Interpolation and DA get worse.
  - This is consistent with the irregular, partly non-periodic shedding found above.
- **Multi-start consistency.**
  - The first step improves (0.217), and so do the DA tuning error and the encode-init floor.
  - The 60-step forecast and the df = 9 sweeps get worse.

10.4 Conclusion

- **The binding constraint is the 8-frame supervised window.** Every change that makes the near term sharper also gives the model a way to do well within 8 frames that does not carry beyond them. Nothing in a forecasting-only, 8-frame objective penalises that.
- **The plain fair-horizon model remains the best** of everything tried. It is the best latent model on Tra, level with ACDM on extrapolation, ahead of it on the 240-step rollout, and about 2.7× better than ACDM and the U-Net at df = 9 data assimilation.
- **What would still move the gap to the U-Net.** The one remaining lever with a clear mechanism is relaxing the horizon rule: the same 8 frames spread over a longer physical time span, which constrains frequencies and phases better. That is a decision about the comparison protocol, not a modelling fix.

11 Answers to the project's questions

1. **What was wrong?** Wrong-frame evaluation, dead conditioning, QG test–train overlap, unreproducible reported numbers, unconstrained dynamics with growing modes, over-damped shedding, a 16.5× training slowdown, and ignored settings (§2).
2. **Which affected reported performance?** The evaluation misalignment, the unreproducible prediction files (real numbers are 11.43 / 2.12 / 18.62), and the QG leakage. Dead conditioning means no reported result used Ma.
3. **What measurably improved things?**
   - 60-step training horizon instead of about 10: −25% on validation, −15% on interpolation test.
   - Working Mach conditioning: −19% interpolation, −16% extrapolation.

- Stable generator: better than unconstrained.
- The full redesign: 2.8× better than the reproducible original on interpolation, and 2.0× better than the original architecture retrained with all fixes on the same split.

4. **Best formulation?** 2×2 oscillator blocks with Mach-dependent damping and frequency, exact propagation, latent 256, purely linear dynamics $dz/dt = A(Ma)\, z$, trained end-to-end on $2 \to 8$ windows with every frame supervised (§8).
   - The fixed point μ can be dropped at no cost (§7.2), giving purely linear latent dynamics.
   - ACDM's one-step training setting is unsuitable for this model class (§7.1).
5. **Did it beat ACDM? No** on interpolation; **level** on extrapolation; lower 240-step MSE, but not better long-horizon dynamics.
6. **By how much?** With the fair $2 \to 8$ model: interpolation +20% worse than ACDM (3.49 vs about 2.9); extrapolation within noise (1.98 vs 1.99–2.22).
7. **Zero-shot?** Yes, demonstrated for unseen Mach numbers (all test cases) and unseen time steps (half-steps at no loss).
8. **Better or worse for data assimilation?** It depends on the checkpoint protocol (§9.2).
   - Like for like (no checkpoint chosen on the test trajectories): the fair-horizon model is 3–10% *better* than the original at df = 9, and about 1.5× worse on the df = 1 window sweeps. The curriculum model is level with the original at df = 1 and slightly better at df = 9.
   - Against the original's test-selected checkpoint, the original wins everywhere except the df = 1 single-observation sweep.
   - All KAEs beat U-Net, FNO and ACDM by a wide margin at df = 9.

   All of them except the ACDM-setting model beat U-Net, FNO and ACDM at df = 9 (§7.4).
9. **Physically meaningful long-horizon behaviour?** Partly. It tracks the true flow much longer than the original. The 60-step model damps oscillations mid-rollout (Fig. 3); the fair $2 \to 8$ model mostly does not (energy 0.94 at step 58).
10. **Cost?** One encoder pass, then all lead times at once in closed form; the decoder dominates. Training is about 0.31 s per step, 12.5 GB, about 1 hour per model. ACDM needs 20 denoising passes per step.
11. **Limitations.**
    - Single GPU shared with other work; 2–3 seeds.
    - No retraining of ACDM or the U-Nets on my split. They saw two more training Mach numbers, a small advantage for them.
    - QG and KS were not re-benchmarked, because the QG test set must be regenerated first.
12. **Strongest next step:** see §12.

12 What I would do next

1. **Close the reconstruction gap**, since it dominates the remaining forecast error.
   - A larger latent did not help (§6.7).
   - One-step training gives a sharp autoencoder, but poor dynamics (§7.1).
   - A one-step-then-60-step curriculum kept only part of it (§7.3).
   - Short-horizon training with every frame supervised brought it from 0.66 to 0.26 (§8).
   - A multiscale decoder did not help (§9.4).
   - A detail latent fixed the first step (0.02) but collapsed after the 8-frame window (§10.3).
   - Under the 8-frame rule the floor is set by the trade-off between reconstruction and multi-step prediction. The remaining lever is the horizon rule itself: the same 8 frames spread over a longer time span.

2. **Report DA like for like.** The original's df = 9 lead came from a checkpoint chosen on the DA test trajectories (§9.2). Any DA comparison should use checkpoints chosen without the test trajectories, and should report the gain statistics of §9.3 alongside, since fast-decaying latent modes predict poor df = 9 results.
3. **Do not remove the damping.** Setting it to zero at inference worsens MSE (interp 3.43 → 3.81, §10.1). It hedges uncertain components. Energy and correlation can still be reported alongside MSE for checkpoint selection.
4. **Report fairly.** Always show error-vs-lead, energy and correlation curves together with MSE, and include the U-Nets, not only ACDM.
5. **QG:** regenerate an independent test set before any QG claim.

A Where everything is

- **Branches.**
  - `audit/kae-research-audit`: the audit, worktree `/home/rg625/mnt/ocean_forecasting_audit`.
  - `impl/ct-kae`: fixes and the new model, worktree `/home/rg625/mnt/ocean_forecasting_impl`.
  - The original `rares/updated_model` checkout was not modified.
- **New model:** `koopman_autoencoder/models/ct_kae.py`, with data handling in `models/ct_data.py`.
- **Training and evaluation scripts:** `train_ctkae.py`, `eval_ctkae.py`.
- **Detailed write-ups** in `audit_report/`: `FINAL_AUDIT.md`, `ARCHITECTURE.md`, `EXPERIMENT_RESULTS.md`, `LITERATURE_REVIEW_V2.md`, `issues.json`, `experiments.yaml`.
- **Checkpoints and logs:** `koopman_autoencoder/model_outputs_ctkae/`.

B How to reproduce

```
cd /home/rg625/mnt/ocean_forecasting_impl/koopman_autoencoder
python -m pytest ../audit_report/tests -q                       # 39 tests
python train_ctkae.py --config=configs/ctkae/base.yaml \
   train.steps=12000 train.select=val_mse60 train.strides=[1,2,3] \
   model.generator=block train.w_amp=0.1 seed=0                 # final model
python eval_ctkae.py model_outputs_ctkae/<run> --dt_test --ma_sweep
python ../audit_report/scripts/benchmark_suite.py               # all baselines
```