

```
telnet@kali: ~ - ssh to 10.10.10.10
#include <stdio.h>
#include <pthread.h>
```

```
int counter = 0; // shared variable
```

```
void* increment(void* arg) {
    for (int i = 0; i < 1000000; i++) {
        counter++; // data race: multiple threads update at the same time
    }
    return NULL;
}
```

```
int main() {
    pthread_t t1, t2;
    pthread_create(&t1, NULL, increment, NULL);
    pthread_create(&t2, NULL, increment, NULL);
    pthread_join(t1, NULL);
    pthread_join(t2, NULL);

    printf("Final counter = %d \n", counter);
    return 0;
}
```

(END)

kolin@mosaic: ~/col7001/con

(base) kolin@mosaic:~/col7001/concurrency\$

(base) kolin@mosaic:~/col7001/concurrency\$

(base) kolin@mosaic:~/col7001/concurrency\$ less sync.c

(base) kolin@mosaic:~/col7001/concurrency\$ gcc sync.c

(base) kolin@mosaic:~/col7001/concurrency\$./a.out

Final counter = 1023471

(base) kolin@mosaic:~/col7001/concurrency\$./a.out

Final counter = 1018656

(base) kolin@mosaic:~/col7001/concurrency\$ less syncL.c

(base) kolin@mosaic:~/col7001/concurrency\$ gcc syncL.c

(base) kolin@mosaic:~/col7001/concurrency\$./a.out

Final counter = 2000000

(base) kolin@mosaic:~/col7001/concurrency\$ gcc -g sync.c

(base) kolin@mosaic:~/col7001/concurrency\$ gdb a.out

GNU gdb (Ubuntu 12.1-0ubuntu1~22.04) 12.1

Copyright (C) 2022 Free Software Foundation, Inc.

License GPLv3+: GNU GPL version 3 or later <<http://gnu.org/licenses/gpl.html>>

This is free software: you are free to change and redistribute it.

There is NO WARRANTY, to the extent permitted by law.

Type "show copying" and "show warranty" for details.

This GDB was configured as "x86_64-linux-gnu".

Type "show configuration" for configuration details.

For bug reporting instructions, please see:

<<https://www.gnu.org/software/gdb/bugs/>>.

Find the GDB manual and other documentation resources online at:

<<http://www.gnu.org/software/gdb/documentation/>>.

For help, type "help".

Type "apropos word" to search for commands related to "word"...

Reading symbols from a.out...

(gdb) list |

```

1  #include <stdio.h>
2  #include <pthread.h>
3
4  int counter = 0; // shared variable
5
6  void* increment(void* arg) {
7      for (int i = 0; i < 1000000; i++) {
8          counter++; // data race: multiple threads update at the same time
9      }
10     return NULL;

```

(gdb) p &counter

\$1 = (int *) 0x4014 <counter>

(gdb) disassemble increment

Dump of assembler code for function increment:

```

0x00000000000011a9 <+0>:    endbr64
0x00000000000011ad <+4>:    push    %rbp
0x00000000000011ae <+5>:    mov     %rsp,%rbp
0x00000000000011b1 <+8>:    mov     %rdi,-0x18(%rbp)
0x00000000000011b5 <+12>:   movl    $0x0,-0x4(%rbp)
0x00000000000011bc <+19>:   jmp     0x11d1 <increment+40>
0x00000000000011be <+21>:   mov     0x2e58(%rip),%eax    # 0x4014 <counter>
0x00000000000011c4 <+27>:   add     $0x1,%eax
0x00000000000011c7 <+30>:   mov     %eax,0x2e47(%rip)    # 0x4014 <counter>
0x00000000000011cd <+36>:   addl    $0x1,-0x4(%rbp)
0x00000000000011d1 <+40>:   cmpl    $0xf423f,-0x4(%rbp)
0x00000000000011d8 <+47>:   jle     0x11be <increment+21>
0x00000000000011da <+49>:   mov     $0x0,%eax
0x00000000000011df <+54>:   pop     %rbp
0x00000000000011e0 <+55>:   ret

```

End of assembler dump.

(gdb) q


```

7      for (int i = 0; i < 1000000; i++) {
8          counter++; // data race: multiple threads update at the same time
9      }
10     return NULL;

```

(gdb) p &counter

\$1 = (int *) 0x4014 <counter>

(gdb) disassemble increment

Dump of assembler code for function increment:

```

0x0000000000011a9 <+0>:      endbr64
0x0000000000011ad <+4>:      push    %rbp
0x0000000000011ae <+5>:      mov     %rsp,%rbp
0x0000000000011b1 <+8>:      mov     %rdi,-0x18(%rbp)
0x0000000000011b5 <+12>:     movl    $0x0,-0x4(%rbp)
0x0000000000011b8 <+19>:     jmp     0x11d1 <increment+48>
0x0000000000011be <+21>:     mov     0x2e50(%rip),%eax      # 0x4014 <counter>
0x0000000000011c4 <+27>:     add     $0x1,%eax
0x0000000000011c7 <+30>:     mov     %eax,0x2e47(%rip)      # 0x4014 <counter>
0x0000000000011cd <+36>:     addl    $0x1,-0x4(%rbp)
0x0000000000011d1 <+40>:     cmpl    $0xf423f,-0x4(%rbp)
0x0000000000011d3 <+47>:     jle     0x11be <increment+21>
0x0000000000011d9 <+49>:     mov     $0x0,%eax
0x0000000000011df <+54>:     pop     %rbp
0x0000000000011e0 <+55>:     ret

```

End of assembler dump.

(gdb) quit

(base) kolin@mosaic:~/col7001/concurrency\$ gcc -g -O6 sync.c

(base) kolin@mosaic:~/col7001/concurrency\$./a.out

Final counter = 2000000

(base) kolin@mosaic:~/col7001/concurrency\$./a.out

Final counter = 2000000

(base) kolin@mosaic:~/col7001/concurrency\$ gcc syncL.c

There is NO WARRANTY, to the extent permitted by law.
Type "show copying" and "show warranty" for details.
This GDB was configured as "x86_64-linux-gnu".
Type "show configuration" for configuration details.
For bug reporting instructions, please see:
<<https://www.gnu.org/software/gdb/bugs/>>.
Find the GDB manual and other documentation resources online at:
<<http://www.gnu.org/software/gdb/documentation/>>.

For help, type "help".
Type "apropos word" to search for commands related to "word"....
Reading symbols from ./a.out...

(gdb) list

```
1      #include <stdio.h>
2      #include <pthread.h>
3
4      int counter = 0; // shared variable
5
6      void* increment(void* arg) {
7          for (int i = 0; i < 1000000; i++) {
8              counter++; // data race: multiple threads update at the same time
9          }
10         return NULL;
11     }
```

(gdb) disassemble increment

Dump of assembler code for function increment:

```
0x0000000000001253 <+0>:    endbr64
0x0000000000001254 <+4>:    addl    $0xf4240,0x2db6(%rip)    # 0x4014 <counter>
0x000000000000125e <+14>:   xor     %eax,%eax
0x0000000000001260 <+16>:   ret
```

End of assembler dump.


(gdb)






Search





Constant Folding
Dead code Elim.





Constant Folding
Dead Code Elim.

for $2 = 1$ — ~~✓~~
 $Count = Count + 1$
 $Count = Count + N$




CPU



Memory Model


Consistency

Ordering



False Sharing

CPU



Stored {

Int a

Char b

{ xyz

xyz

xyz(0)	00 ✓
xyz(1)	01 ✓
xyz(2)	20
	21 →
	30
	31

abc[10]

Consistency

Coherence

x = 10

A(1)

A(2)

A(3)

A(4)

Block/Line


```
#include <stdio.h>
#include <pthread.h>

int x = 0, y = 0;
int r1, r2;

void* thread1(void* arg) {
    x = 1;           // write x
    r1 = y;          // read y
    return NULL;
}

void* thread2(void* arg) {
    y = 1;           // write y
    r2 = x;          // read x
    return NULL;
}

int main() {
    for (int i = 0; i < 1000000; i++) {
        x = y = 0; r1 = r2 = 0;
        pthread_t t1, t2;
        pthread_create(&t1, NULL, thread1, NULL);
        pthread_create(&t2, NULL, thread2, NULL);
        pthread_join(t1, NULL);
        pthread_join(t2, NULL);
        printf("r1=%d\r2=%d\n", r1, r2);
    }
}
```

reorder.c (END)



Q Search



▷

```
(base) kolin@mosaic:~/col7001/concurrency$ ls
```

```
(base) kolin@mosaic:~/col7001/concurrency$ gcc reorderWithComm.c
```

Reordering observed!


```
r1=0    r2=1
r1=0    r2=1
r1=0    r2=1
r1=0    r2=1
r1=0    r2=1
r1=0    r2=1
r1=0    r2=1
r1=0    r2=1
r1=0    r2=1
r1=0    r2=1
r1=1    r2=0
```

^C

(base) kolin@mosaic:~/col7001/concurrency\$ ls

```
a.out      cacheSharing.c  fs-v2.c      reorderF.c      reorderWithComm.c  sync.c      syncM.c
cacheC.c   fs.c            reorder.c    reorderSeqCons.c  syncB.c            syncL.c
```

(base) kolin@mosaic:~/col7001/concurrency\$ less reorderF.c

(base) kolin@mosaic:~/col7001/concurrency\$ less reorderWithComm.c

(base) kolin@mosaic:~/col7001/concurrency\$ gcc reorderWithComm.c

(base) kolin@mosaic:~/col7001/concurrency\$./a.out

Reordering observed!

(base) kolin@mosaic:~/col7001/concurrency\$ less reorderF.c

(base) kolin@mosaic:~/col7001/concurrency\$ gcc reorderF.c

(base) kolin@mosaic:~/col7001/concurrency\$./a.out

Reordering observed! in 161107th Iteration

(base) kolin@mosaic:~/col7001/concurrency\$./a.out

Reordering observed! in 84865th Iteration

(base) kolin@mosaic:~/col7001/concurrency\$

```
void* thread2(void* arg) {
    atomic_store_explicit(&y, 1, memory_order_seq_cst);
    r2 = atomic_load_explicit(&x, memory_order_seq_cst);
    return NULL;
}

int main() {
    for (int i = 0; i < 10000000; i++) {
        atomic_store(&x, 0);
        atomic_store(&y, 0);
        r1 = r2 = 0;

        pthread_t t1, t2;
        pthread_create(&t1, NULL, thread1, NULL);
        pthread_create(&t2, NULL, thread2, NULL);
        pthread_join(t1, NULL);
        pthread_join(t2, NULL);

        if (r1 == 0 && r2 == 0) {
            printf("Reordering observed (i=%d)\n", i);
            break;
        }
    }
    return 0;
}
```

(END)


```
r1=0    r2=1
r1=0    r2=1
r1=0    r2=1
r1=0    r2=1
r1=0    r2=1
r1=1    r2=0
```

^C

(base) kolin@mosaic:~/col7001/concurrency\$ ls

```
a.out      cacheSharing.c  fs-v2.c      reorderF.c      reorderWithComm.c  sync.c      syncM.c
cacheC.c   fs.c            reorder.c     reorderSeqCons.c  syncB.c            syncL.c
```

(base) kolin@mosaic:~/col7001/concurrency\$ less reorderF.c

(base) kolin@mosaic:~/col7001/concurrency\$ less reorderWithComm.c

(base) kolin@mosaic:~/col7001/concurrency\$ gcc reorderWithComm.c

(base) kolin@mosaic:~/col7001/concurrency\$./a.out

Reordering observed!

(base) kolin@mosaic:~/col7001/concurrency\$ less reorderF.c

(base) kolin@mosaic:~/col7001/concurrency\$ gcc reorderF.c

(base) kolin@mosaic:~/col7001/concurrency\$./a.out

Reordering observed! in 161107th Iteration

(base) kolin@mosaic:~/col7001/concurrency\$./a.out

Reordering observed! in 84865th Iteration

(base) kolin@mosaic:~/col7001/concurrency\$ less reorder

```
reorder.c      reorderF.c      reorderSeqCons.c  reorderWithComm.c
```

(base) kolin@mosaic:~/col7001/concurrency\$ less reorderSeqCons.c

(base) kolin@mosaic:~/col7001/concurrency\$ gcc reorderSeqCons.c

(base) kolin@mosaic:~/col7001/concurrency\$./a.out

```
#include <stdio.h>
#include <pthread.h>
#include <time.h>

#define N 1000000000

// --- Case 1: False Sharing ---
struct {
    int a;    // updated by thread 1
    int b;    // updated by thread 2
} shared;

// --- Case 2: Fixed with Padding ---
struct {
    int a;
    char pad1[64]; // avoid same cache line
    int b;
    char pad2[64];
} shared_padded;

void* t1(void* arg) {
    int mode = *(int*)arg;
    for (int j=0; j<N/10; j++){
        if (mode == 0) {
            for (int i = 0; i < N; i++) shared.a++;
        } else {
```



```
    }  
    }  
    return NULL;  
}  
  
void* t2(void* arg) {  
    int mode = *(int*)arg;  
    if (mode == 0) {  
        for (int i = 0; i < N; i++) shared.b++;  
    } else {  
        for (int i = 0; i < N; i++) shared_padded.b++;  
    }  
    return NULL;  
}  
  
double run_test(int mode) {  
    struct timespec start, end;  
    pthread_t x, y;  
  
    clock_gettime(CLOCK_MONOTONIC, &start);  
  
    pthread_create(&x, NULL, t1, &mode);  
    pthread_create(&y, NULL, t2, &mode);  
    pthread_join(x, NULL);  
    pthread_join(y, NULL);  
}
```

```
kolin@mosaic: ~/col7001/con x + v
(base) kolin@mosaic:~/col7001/concurrency$ gcc fs.c
(base) kolin@mosaic:~/col7001/concurrency$ ./a.out
^C
```

```
fs.c: in function 't1':
fs.c:23:22: error: lvalue required as increment operand
23 |     for (int j=0;j<1j++){
    |                  ^~
```

```
fs.c:23:24: error: expected ';' before ')' token
23 |     for (int j=0;j<1j++){
    |                  ^
```

```
(base) kolin@mosaic:~/col7001/concurrency$ vi fs.c
(base) kolin@mosaic:~/col7001/concurrency$ gcc fs.c
(base) kolin@mosaic:~/col7001/concurrency$ ./a.out
False sharing time: 3.665 sec
Fixed (padded) time: 1.867 sec
(base) kolin@mosaic:~/col7001/concurrency$
```

