



RGA SOUND IMAGE

ELEVATING AUDIO EXPERIENCES SINCE 1995

STONENEWATER® OFFICIAL DISTRIBUTOR AP & TELANGANA

SPEAKER CATALOGUE

WALLMOUNT SPEAKERS

QUBE 3 | SATELLITE SPEAKER



ATOM 3 | SATELLITE SPEAKER



Commercial Sound | SPEAKERS ZETA 3.5 | ZETA 3.5T

Speaker 2 Way with 3.5" woofer and 13mm Dome tweeter

The Zeta 3.5 is an elegant looking two way speaker system that provides extended and smooth response. With admirable power handling packaged in a convenient size, these are extremely well suited for cafes and restaurants.

Outstanding value for your money!

| SPECIFICATION

Output	: 100W
Nominal Rating	: 25W RMS
Magnet	: Ferrite
Speaker	: 2 way with 3.5" Woofer
Tweeter	: 13mm Soft Dome
SPL	: 86 db
Frequency Response	: 90 hz-20khz
Available Colours	: Black and White
Dimensions (mm)	: 140 (W) x 185 (H) x 115 (D)
LMT Taps	: 100V/ 20W / 10W / 5W / 2.5W
Impedance	: 8 Ω
Net Weight	: 1.41 Kg 1.8 Kg

100

Commercial Sound | SPEAKERS ELEMENT 5 | 5T

Wall Mount Speaker

Weather resistant, wall mount speaker. The weather resistant Element-5 is perfectly comfortable with both indoor and outdoor. Silky smooth highs coupled with a solid Low-Mid performance make it suitable for a wide range of applications where high quality audio is needed in a limited space. Restaurants, bars, retail stores etc.

| SPECIFICATION

Continuous program Power	: 80W
Nominal Rating	: 40W AES
Impedance	: 8 Ω Nominal
Speaker LF	: 1 x 5.25" (125mm) / 1" Voice Coil
Tweeter HF	: 1 x 1" (25mm) Silk Dome Tweeter
Sensitivity 1watt/ 1metre	: 89 db : 60 hz-20khz
Power Taps	: Available only on ELEMENT 5T (30W, 15W, 7.5W, 3.75W)
Net Weight	: 3.3 3.7 Kg
Dimensions (mm)	: 190 (W) x 275 (H) x 180 (D)



Professional Audio | SPEAKERS AQUA6

Two-Way Full Range Loudspeaker

The AQUA 6 is a highly weather-resistant, single 6" 2-way full range loudspeaker. The system conforms to IP46 international standard.

| SPECIFICATIONS

Drivers	: 1 x 1" (25mm) / 1.4" voice coil HF 1 x 6" (150mm) / 1.5" voice coil LF
Frequency Response (-3dB)	: 60Hz-18kHz
Sensitivity	: 89 dB 1W/ 1M
Maximum SPL	: 110 dB continuous, 116 dB peak
Impedance	: 8 Ω nominal
Dispersion (-6dB)	: 90° (H) x 60° (V)
Crossover	: 2.4kHz passive
Rated Power	: 80W RMS, 320W peak
Dimensions (mm)	: 182 (W) x 362 (H) x 224 (D)
Net Weight	: 6.4 Kg/pc



CEILING SPEAKERS



Commercial Sound | SPEAKERS CS-8PP

Ceiling Mount Speaker

The CS-8PP offers an ideal balance between cost and performance. A good bandwidth and clean sound reproduction characteristics applicable for that specific range of commercial applications which requires good quality sound with an extra low end and power.

| SPECIFICATION

Output	: 150W
Nominal Rating	: 75W
Woofer Magnet	: Ferrite
Cone	: Black Fiber Glass Cone with rubber edge
Tweeter	: 25mm Cat Eye Silk Dome
Crossover	: 2 Way
SPL	: 88 dB
Frequency	: 59 hz-20khz
Impedance	: 8 Ω
Cut out Diameter	: 244mm
Net Weight	: 2.5 Kg



Commercial Sound | SPEAKERS CS-6PP

Ceiling Mount Speaker

The CS-6PP offers an ideal balance between cost and performance. A good bandwidth and clean sound reproduction characteristics make it a smart choice for a wide range of commercial applications that require good quality sound.

| SPECIFICATION

Output	: 100W
Nominal Rating	: 50W RMS
Woofer Magnet	: Ferrite
Cone	: Black Fiberglass Cone with Rubber Edge
Tweeter	: 25mm Pivoting Cat Eye Silk Dome Tweet with Ferro fluid
Crossover	: 2 way
Frequency	: 61 hz – 20 Khz
Impedance	: 8 Ω
SPL	: 89 dB
Cut out Diameter	: 203mm
Net Weight	: 1.5 Kg



Commercial Sound | SPEAKERS CS-4LM

Ceiling Mount Speaker

The CS-4LM offers an ideal balance between cost and performance. A good bandwidth and clean sound reproduction characteristics make it a smart choice for a wide range of commercial applications that require good quality sound.

| SPECIFICATION

Output	: 12W
Nominal Rating	: 6W RMS
Woofer Magnet	: Ferrite
Cone	: Full Paper Dual Cone
Frequency	: 61 hz – 20 Khz
Impedance	: 8 Ω
SPL	: 89 dB
Cut out Diameter	: 147mm
Net Weight	: 1.5 Kg



Commercial Sound | SPEAKERS CS-6LM | CS-6LE

Ceiling Mount Speaker

The CS-6LE | CS-6LE is a “Value for Money” product that offers class leading performance and high SPL, at an affordable budget.

It takes care of all basics of audio engineering without any expensive frills. It is also available with a built-in LMT under the model name CS-6LE | CS-6LE .

| SPECIFICATION

Output	: 80W
Nominal Rating	: 40W RMS
Woofer Magnet	: Ferrite
Cone	: Polypropylene
Tweeter	: PEI Dome
SPL	: 89 dB@1w/ 1m
Frequency	: 65 hz – 20 Khz
Impedance	: 8 ohms
LMT Tappings	: 100V / 2.5W, 5W, 10W
Cut out Diameter	: 205mm
Net Weight	: 1.4 Kg 1.1 Kg

PENDANT SPEAKERS



Commercial Sound | SPEAKERS PT- 5

Pendant Speaker

The core design concept behind PT- 5 is freedom and flexibility. The initiative is to open up brand new pathways for wall mount speakers design where user have more freedom on where and how they can install the speaker units.

The PT- 5 is a IPX66 Waterproof Certified. It is ideal for outdoor applications also.

| SPECIFICATION

Output	: 50W
Nominal Rating	: 30W
Woofer Magnet	: Ferrite
Cone	: Graphite
Tweeter	: 1" Silk Soft Dome
Crossover	: 2 Way
SPL	: 87 dB
Frequency	: 118 hz-20 khz
Impedance	: 8 Ω
Power Taps	: 3.7W / 7.5W / 15W / 30W
Net Weight	: 2.4 Kg
Dimensions	: 240 x 170 x 170mm



Commercial Sound | SPEAKERS PT- 4

Pendant Speaker

The core design concept behind PT- 4 is freedom and flexibility. The initiative is to open up brand new pathways for wall mount speakers design where user have more freedom on where and how they can install the speaker units.

The PT- 4 is a IPX66 Waterproof Certified. It is ideal for outdoor applications also.

| SPECIFICATION

Output	: 40W
Nominal Rating	: 20W
Woofer Magnet	: Ferrite
Cone	: Graphite
Tweeter	: 1" Silk Soft Dome
Crossover	: 2 Way
SPL	: 85 dB
Frequency	: 129 hz-20 khz
Impedance	: 8 Ω
Power Taps	: 2.5W / 5W / 10W / 20W
Net Weight	: 1.6 Kg
Dimensions	: 190 x 138 x 138mm

PROFESSIONAL SPEAKER



Professional Audio | SPEAKERS AQUA6

Two-Way Full Range Loudspeaker

The AQUA 6 is a highly weather-resistant, single 6" 2-way full range loudspeaker.
The system conforms to IP46 international standard.

| SPECIFICATIONS

Drivers	: 1 x 1" (25mm) / 1.4"voice coil HF 1 x 6" (150mm) / 1.5"voice coil LF
Frequency Response (-3dB)	: 60Hz-18kHz
Sensitivity	: 89 dB 1W/ 1M
Maximum SPL	: 110 dB continuous, 116 dB peak
Impedance	: 8 Ω nominal
Dispersion (-6dB)	: 90° (H) x 60° (V)
Crossover	: 2.4kHz passive
Rated Power	: 80W RMS, 320W peak
Dimensions (mm)	: 182 (W) x 362 (H) x 224 (D)
Net Weight	: 6.4 Kg/pc

WATER RESISTANT SPEAKERS



Professional Audio | SPEAKERS AQUA8

Two-Way Full Range Loudspeaker

The AQUA 8 is a highly weather-resistant, single 8" 2-way full range loudspeaker.
The system conforms to IP46 international standard.

| SPECIFICATIONS

Drivers	: 1 x 1" (25mm) / 1.4"voice coil HF 1 x 8" (150mm) / 2"voice coil LF
Frequency Response (-3dB)	: 60Hz-18kHz
Sensitivity	: 94 dB 1W/ 1M
Maximum SPL	: 116 dB continuous, 122 dB peak
Impedance	: 8 Ω nominal
Dispersion (-6dB)	: 90° (H) x 60° (V)
Crossover	: 2.4kHz passive
Rated Power	: 150W RMS, 600W Peak
Dimensions (mm)	: 241 (W) x 450 (H) x 285 (D)
Net Weight	: 8.6 Kg/pc



Professional Audio | SPEAKERS AQUA12

12" Two-Way Loudspeaker System

The AQUA 12 is a compact, 12" coaxial, 2-way, highly weather-resistant full range loudspeaker with high SPL.
The system confirms to IP56 international standard.

FEATURES

- Highly Weather-resistant IP56 Rating
- High SPL

| SPECIFICATIONS

Drivers	: 1 x 12" (300mm) / 3"voice coil LF 1 x 1"(25mm)/1.7"voice coil HF
Frequency Response (-3dB)	: 55Hz-18kHz
Sensitivity	: 98 dB 1 watt / 1 meter
Maximum SPL	: 123 dB continuous, 129 dB peak
Impedance	: 8 Ω nominal
Dispersion (-6dB)	: 80°(H) x 80°(V)
Crossover	: 2.2kHz passive
Rated Power	: 300W RMS, 1200W peak
Dimensions (mm)	: 407 (W) x 443 (H) x 411 (D)
Net Weight	: 15.2 Kg/pc