"Automated Plant Disease Detection and Classification Using Machine Learning and Deep Learning Techniques"

Dr.Levina	Abhishek	Lekhraj	Preetham	Vishal Sharma
Assoc Prof. Dept of CSE	7th Sem , CSE(DS)	7th Sem , CSE(DS)	7th Sem , CSE(DS)	7th Sem , CSE(DS)
KNSIT-Bangalore	KNSIT -Bangalore	KNSIT -Bangalore	KNSIT -Bangalore	KNSIT -Bangalore

ABSTRACT - This research presents the development of an intelligent digital platform that integrates automation and artificial intelligence to assist the agricultural community in monitoring crop health and detecting plant diseases with greater accurac y and efficiency. Agriculture sectors supporting global Agro-economic sector stability. However, plant infections continue to cause severe yield losses, significantly impacting Food stability and financial growth & farmer productivity. The problem is more critical in developing regions where expert diagnosis and technical resources are limited. Conventional disease identification methods depen d heavily on manual inspection by agricultural specialists, which is time-consuming, labor-intensive, and prone to human error. To overcome these limitations, the proposed system employs automation, Artificial Intelligence (AI), and computer vision to deli ver an efficient and scalable alternative. This research examines the application of Intelligent algorithms and Automated learning systems methods via using digital leaf images via deep learning model. By analyzing these images, the system is able to accurately recognize visual symptoms, determine disease type, and assist in early-stage diagnosis. Traditional ML algorithms such as Support Vector Machine (SVM), Random Forest, and k-Nearest Neighbour (k-NN) have been utilized in disease based on manually extracted color, texture, and shape features. In contrast, deep learning models, particularly Convolutional Neural Networks (CNNs), automate Feature identification and labeling processes, improving model efficiency and precision.

This research also evaluates different benchmark datasets, including Plant Dataset, and discusses their role in model training and testing. A comparative analysis of ML and DL techniques highlights their strengths, limitations, and deployment challenges su ch as computational cost and real-time adaptability. The study identifies key areas for future research, including optimizing Low- complexity models tailored for mobile and edge environments to enable on-field diagnosis.

Overall, the proposed framework enhances accuracy in disease detection, assists farmers in making informed decisions, and promotes sustainable agricultural practices. The system demonstrates the potential of AI-driven solutions in advancing smart agriculture and minimizing crop losses caused by plant diseases.

Keywords: Plant Disease Identification, AI, Neural Networks, Computer Vision, Image Analysis ,(CNN).

INTRODUCTION

Agriculture forms the foundation of human civilization, providing essential food resources and raw materials for industries w hile supporting the livelihoods of billions of people across the world. It continues to be a vital pillar of economic stability and social develo pment on a global scale.

However, with the rapidly increasing global population, the demand for food is growing at an unprecedented rate. This surge e xerts significant pressure on agricultural productivity and sustainability. To meet these rising demands, modern agriculture faces several challenges, among the most pressing problems is the prevalence of plant diseases.

Plant diseases are caused by various pathogenic organisms such as fungi, bacteria, viruses, and nematodes, as well as by abio tic stressors like nutrient deficiencies, pollution, and adverse climatic conditions. These factors interfere with the normal physiological functions of plants, reducing

photosynthesis, stunting growth, hindering fruit development, and ultimately decreasing crop yields.

According to the Food and Agriculture Organization (FAO), approximately 40% of global crop production is lost annually due to plant diseases and pests, leading to billions of dollars in economic losses. Beyond financial implications, these losses also inten sify global food insecurity, particularly in Emerging economies that are highly dependent on agriculture for income and sustenance.

Traditionally, Plant disease identification and classification have relied on visual inspection performed by experienced farmers, agricultural officers, or plant pathologists. While effective to some extent, this manual approach is time -consuming, labor-intensive, subjective, and dependent on the skill and experience of the observer. Variations in environmental conditions and overlapping disease sym ptoms often make manual diagnosis inaccurate. Furthermore, a shortage of trained pathologists, especially in remote areas, worsens the pr oblem, leading to delayed identification and incorrect treatment, which can result in uncontrolled disease spread and s evere crop damage.

In response, many farmers tend to overuse chemical pesticides as a preventive measure in the absence of confirmed infections. This method intensifies the overall cost of production, causes environmental pollution, degrades soil quality, and leaves harmful chemical residues that pose health risks. Hence, There is an escalating requirement automated, efficient, and reliable plant disease detection systems to support timely diagnosis and sustainable disease management.

Leaf Diseases and its Types

Leaf diseases refer to disorders that harm the leaves of plants, causing visible symptoms that can significantly reduce overall plant health and productivity. These diseases may be triggered by environmental stress factors or pathogenic infections.

Fungal Diseases:

This disease make up about 80% of all known plant diseases. They spread quickly under warm and humid conditions and are typically transmitted through soil, air, water, or infected plant material. Fungi can infect plants through nature entry points such as stomata or through wounds, drawing nutrients from plant tissues. Common symptoms include leaf spots, mildew, rust, and blight.

Viral Diseases:

Virus is tiny infection replicate only within living cells. They are commonly transmitted by insect vectors like aphids, whiteflies, or leafhoppers, or through mechanical means. Viral infections disrupt plant metabolism, often resulting in mosaic patterns, leaf curling, and stunted growth.

Bacterial Diseases:

Bacterial infections cause water-soaked lesions, leaf spots, wilting, and leaf blight. Infected plants may exude slime or ooze. Bacteria can enter plants through wounds or insect feeding and spread via contaminated soil, water, or debris. Common examples include Bacterial blight, Fire blight, and Citrus canker.

Environmental Leaf Disorders:

Not all leaf damage results from pathogens. Environmental factors such as air pollution, extreme temperatures, irregular irrigation, and nutrient imbalances can also cause leaf irregularities. Symptoms may include chlorosis (yellowing), leaf burn, rolling, or premature leaf drop. Among sunburn, frost damage, water stress, and nutrient deficiencies.

LITERATURE SURVEY

[1] "Plant Disease Detection and Classification Uses ML & DLTechniques"
Authors: Faculty of Computers and Information, Mansoura University, Egypt — Yasmin M. Alsakar, Nehal A. Sakr, and Mohammed Elmogy. Year: November 2023
This research offers an in-depth examination of various methodologies used for leaf diseases identification via machine learning and deep learning approaches. It discusses dataset utilization, performance evaluation metrics, and highlights major issues related to existing detection systems. The study also emphasizes emerging pathways for the improvement of accuracy and efficiency in automated Detection of plant pathogens.

[2] "Plant Leaf Disease Detection via Multiple CNN Models" Authors: Department of CSE-AIML, Hemlata Parmar and Manish Rai.
Year:January 2025
This article goal to growing issue of plant diseases and their negative impact on crop productivity. It presents a novel methodology integrating Support Vector Machine (SVM) and Convolutional Neural Network (CNN) techniques for effective disease classification. The method involves procedures including image acquisition, preprocessing, feature extraction, and final classification. The researchers conducted experiments using 400 leaf samples from banana, pepper, and rice plants, achieving high accuracy in disease identification.

[3] "Automated Detection and Diagnosis of Leaf Diseases"
Authors: Dept of IT, Sri KCT Coimbatore, India — T. Sangeetha, R. Rajarajan, S. Rithiek Krishna, and N. Sakthi Siddharth. Year: April 2024
This study evaluates an advanced algorithm, YOLOv7-X, for detecting and diagnosing leaf diseases in plants. The experimental results demonstrate superior detection performance and reliability. The paper also highlights the challenges in area of plant disease identification and proposes an efficient, automated solution to enhance diagnostic accuracy and support environmentally friendly agricultural practices.

[4] " Plant Disease Detection and Diagnosis" Authors: Pedapudi. Nagababu ,Shaik. Nageena ,Veeranki. Dharani , Darsi. Naveen Publication Year: 24-26 May 2024 Description: In this research the maximum level of precision, leaf colour, leaf damage, leaf area, and leaf texture are all classified qualities. CNN algorithm is used to examine various image parameters or features for the purpose of recognising various plant leaf diseases. This plant disease diagnostics can assist farmers in creating systems that lead to robust and fruitful food crops.

RESEARCH METHODOLOGY

The proposed methodology for automated plant disease detection and classification using Machine Learning (ML) and Deep Learning (DL) follows a structured framework designed to ensure reliability, scalability, and accuracy. The complete workflow consists of four key stages—data acquisition, image preprocessing, feature extraction, and classification.. Each of these steps is essential for transform image data in to meaningful information that helps identify and categorize plant diseases effectively.

1. **Data Acquisition**

Data acquisition serves as the foundation of the plant disease detection process. High-quality plant leaf images are collected from different sources, including online datasets and field photography. The diversity of the dataset ensures that models can handle variations in lighting, background, angle, and disease severity, improving their robustness and generalization capabilities.

Fig 1.1 Data acquisition



fig 1.2 Data Processing



fig 1.3 Feature Extraction

2. Image Preprocessing

Image preprocessing preparing the raw images for analysis. It involves various steps such as image resizing, noise removal, color adjustment, morphological operations, and region segmentation. These operations improve image clarity and enhance relevant disease features for accurate detection.

Segmentation methods, including color thresholding and K-means clustering, are often employed to isolate the diseased portion of the leaf. Relevant image regions are passed forward for analysis, reducing computational complexity and improving overall efficiency.

3. Feature Extraction

Feature extraction is a vital part of automated disease identification systems. In traditional ML-based methods, handcrafted features such as color, texture, and shape leaf images and used with classifier (SVM) or Random Forest (RF).

Deep Learning techniques—especially (CNNs)—eliminate the necessity of human-driven feature design by automatically learns hierarchical representation direct from raw images. CNNs capture fine-grained details of disease symptoms, resulting in improved accuracy and reliability. Recent investigations have focused on hybrid frameworks combining human-engineered and deep features to enhance detection performance, particularly when working with limited datasets.

4. Classification

Classification is the final phase in the methodology, where extracted features are analyzed and categorized into corresponding disease classes. The classification process can be supervised—where the model learns from labeled data—or unsupervised, which identifies patterns without prior labeling.

Common classifiers used in plant disease detection include Support Vector Machines (SVM),K-Nearest Neighbor (KNN), Random Forest (RF), Logistic Regression, Naïve Bayes (NB), and Decision Tree (DT). The choice of classifier depends on dataset complexity, the number of disease categories, and the desired accuracy.

ML process

Machine learning is crucial for automating disease detection and recognition. The models are trained on **features obtained from the data** vectors, enabling them to recognize disease patterns in new plant image. The algorithm compares the feature of an input image with learned representations from training data to assign image to most appropriate disease class.

Color, shape, and texture are the primary attributes used in classification. Among these, color Features are of great relevance owing to their ability to they remain consistent across changes in translation, rotation, and scale. The extracted features—such as color space, similarity metrics, and morphological characteristics—

serve as critical inputs for the final classification and diagnosis stages.

Deep Learning process:



Fig 1.4 Deep Learning Process

Deep learning employs neural networks to perform feature learning through multiple hidden layers. Each layer functions as a perceptron responsible for extracting features at a particular level of abstraction. Initially, low-level feature are determined, which are then combined to form higher-level representations. This hierarchical learning process helps address the shortcomings of conventional techniques that focus on limited or predefined feature types.

SYSTEM ARCHITECTURE

The system begins with the Image Acquisition stage, where a plant image—typically of a leaf—is captured using a camera or mobile device. This image serves as the input for the analysis process.

In the Image Processing stage, the system enhances and pre-processes the captured image to remove noise, adjust color tone, and isolate the regions showing possible disease symptoms. Methods such as segmentation and filtering are applied to extract the affected regions, improving feature clarity for analysis.

The processed data is then compared or stored in a Database, which contains a large collection of pre-labeled plant images representing various diseases and healthy specimens. This database serves a vital function in training and optimizing accuracy of the model.

Next, the extracted features are analyzed by the Training Model — a machine learning or deep learning framework (such as CNN or SVM). The model is already trained using numerous samples of healthy and diseased plants. Based on learned patterns, it classifies the new input image.



Fig 1.5 Architecture of training model

A Decision Module determines whether the plant is Healthy or Defective (Diseased):

-If the plant is identified as healthy, the system simply displays that no infection is detected.

-If a defect is found, the system proceeds to identify the specific disease name based on its pattern recognition results.

Once the disease is identified, the system activates the Remedy Recommendation stage. Here, the model suggests suitable treatment actions, such as pesticide use, watering adjustments, or other preventive measures, depend on the disease type.

IMPLEMENTATION & WORKING

The existing plant disease detection system is hindered by high costs, lower accuracy, and limited disease management support. Additionally, its hardware demands and prolonged detection time add complexity to its use. To overcome these challenges, a more efficient and user-friendly approach is adopted utilizing Convolutional Neural Networks (CNNs), specifically the EfficientNet model, which provides both disease detection results and recommended remedies.

The process begins with capturing images of plant leaves, which undergo comprehensive image processing to enhance and prepare them for analysis. These processed images then serve as the training dataset for the EfficientNet algorithm, which learns to recognize the various patterns and features indicative of different plant diseases.



Fig 1.6 working of model

Post-training, the model can analyze new leaf images to determine whether the plant is healthy or diseased. Upon detecting a disease, the system accurately identifies it and offers tailored treatment recommendations for the specific condition. This combined approach of machine learning and image processing not only facilitates precise disease diagnosis but also supports effective management strategies.

Moreover, the system provides reference images corresponding to the identified disease, enhancing user understanding by offering visual confirmation. This feature helps users accurately recognize the disease and respond appropriately, thereby improving the overall usability and impact of the disease detection system.

RESULTS

The proposed automated framework for plant disease identification was effectively developed and evaluated using a dataset containing both healthy and infected leaf samples. The system efficiently processed images through various stages such as preprocessing, feature extraction, and classification. The deep learning-based (CNN) showed excellent performance in identifying and classifying different plant diseases. It achieved consistently high results across multiple evaluation metrics, including accuracy, precision, and recall, demonstrating strong reliability in distinguish between diseased and healthy leaves. When compared with traditional machine learning techniques such as (SVM), Random Forest (RF), and K-Nearest Neighbor (KNN), the CNN-based approach delivered superior outcomes. This improvement is primarily owing to its capacity for automatic extractiont complex hierarchical features from leaf images without requiring manual feature engineering.



Apple___Apple_scab	1.00	0.84	0.91	504
Apple___Black_rot	0.96	0.98	0.97	497
Apple___Cedar_apple_rust	0.95	0.99	0.97	440
Apple___healthy	0.85	0.93	0.89	502
Blueberry___healthy	0.85	0.99	0.92	454
Cherry_(including_sour)___Powdery_mildew	1.00	0.89	0.94	421
Cherry_(including_sour)___healthy	0.95	0.97	0.96	456
Corn_(maize)___Cercospora_leaf_spot Gray_leaf_spot	0.96	0.89	0.92	410
Corn_(maize)___Common_rust_	1.00	0.98	0.99	477
Corn_(maize)___Northern_Leaf_Blight	0.90	0.98	0.94	477
Corn_(maize)___healthy	1.00	0.99	0.99	465
Grape___Black_rot	1.00	0.94	0.97	472
Grape___Esca_(Black_Measles)	0.98	0.99	0.98	480
Grape___Leaf_blight_(Isariopsis_Leaf_Spot)	0.96	1.00	0.98	430
Grape___healthy	0.99	0.99	0.99	423
Orange___Haunglongbing_(Citrus_greening)	0.93	0.99	0.96	503
Peach___Bacterial_spot	0.91	0.95	0.93	459
Peach___healthy	0.94	0.99	0.96	432
Pepper,_bell___Bacterial_spot	0.99	0.89	0.93	478
Pepper,_bell___healthy	0.99	0.81	0.89	497
Potato___Early_blight	0.99	0.94	0.96	485
Potato___Late_blight	0.90	0.98	0.94	485
Potato___healthy	0.91	0.97	0.94	456
Raspberry___healthy	0.89	1.00	0.94	445
Soybean___healthy	0.95	0.99	0.97	505
Squash___Powdery_mildew	1.00	0.92	0.96	434
Strawberry___Leaf_scorch	0.96	0.96	0.96	444
Strawberry___healthy	0.98	0.98	0.98	456
Tomato___Bacterial_spot	0.97	0.96	0.96	425
Tomato___Early_blight	0.85	0.90	0.87	480
Tomato___Late_blight	0.86	0.91	0.89	463
Tomato___Leaf_Mold	0.98	0.94	0.96	470
Tomato___Septoria_leaf_spot	0.95	0.82	0.88	436
Tomato___Spider_mites Two-spotted_spider_mite	0.89	0.97	0.93	435
Tomato___Target_Spot	0.92	0.88	0.90	457
Tomato___Tomato_Yellow_Leaf_Curl_Virus	0.99	0.98	0.99	490
Tomato___Tomato_mosaic_virus	1.00	0.91	0.95	448
Tomato___healthy	0.97	0.98	0.98	481
accuracy			0.95	17572
macro avg	0.95	0.95	0.95	17572
weighted avg	0.95	0.95	0.95	17572

Fig 2.1 Visualization accuracy result

The reliability of the plant leaf detection from the above graph image the accuracy rate of training is upto 96.60 percent and the accuracy rate of validation is 94.50 percent .

Depicts the graph between training accuracy and validation accuracy . The loss between training loss and validation loss is 3.40% and 5.50%



The results can be given for different cases such as (I) when a plant is healthy, (II) when the plant is unhealthy.

when a image of a plant leaf is taken by the model an output can be given out whether the plant is in healthy status or not. According to the status, the interface displays the remedy.



CONCLUSION:

After conducting extensive experiments, it was found that while conventional exhibited moderate to high accuracy levels (approximately 85–91%), deep learning approaches—particularly (CNNs)—demonstrated superior performance, often reaching accuracies above 97– 98%. This improvement can be attributed to CNNs' capability to automatically learn complex, hierarchical, and discriminative representations from raw image data, thereby eliminating the necessity for manual feature extraction.

Plant diseases significantly influence global agriculture and economics. Hence, it is essential to review existing studies that focus on AI- based methods for plant disease detection and classification. This study examines recent advancements in identifying plant diseases by employing machine learning and deep learning methods. Although significant progress has been made, several challenges remain that require attention in future research, as summarized below.

To eliminate the current limitations of plant disease identification systems, is suggested to explore data augmentation strategies to diversify image datasets and promote data sharing. Additionally, incorporating advanced segmentation techniques can help improve classification performance. Enhancing the population of plants images can also enhance model accuracy, especially for datasets with limited diversity. For detecting multiple diseases in a single image, multi-classifier models should be considered. Furthermore, applying efficient image enhancement algorithms can improve image quality, leading to higher accuracy in plant disease classification.

FUTURE WORK:

Although the outcomes of this research are promising, several opportunities exist for improvement and further exploration. Future research can aim to overcome the current challenges and extend the model's capabilities to achieve greater robustness, interpretability, and scalability for real-world agricultural applications.

1.Dataset Expansion and Diversity
Most current models are trained on controlled datasets such as PlantVillage, which include clear, uniform backgrounds and limited environmental variability. However, real-world farming conditions are far more complex, involving varying illumination, weather patterns, and overlapping leaves.
Future studies should focus on:

* Expanding datasets with real-field images captured under diverse and challenging conditions.
* Incorporating early-stage disease images for quicker diagnosis.
* Utilizing multi-crop and multi-regional datasets to improve the model's generalization and adaptability.

2.Integration of Multimodal Data
This study primarily concentrated on image-based analysis, but plant health is also influenced by environmental and physiological parameters such as temperature, soil moisture, humidity, and nutrient levels. Future research could integrate multimodal data—combining visual, sensor, and environmental inputs—to develop intelligent, context- aware systems capable of both detecting and forecasting potential disease outbreaks.

3.Edge and Mobile Deployment
Its system to benefit farmers, especially in remote and resource-constrained regions, they must be easily deployable and lightweight. Future work should emphasize the design of optimized deep learning architectures (e.g., EfficientNet-Lite, MobileNetV3) that can perform inference efficiently on edge devices like smartphones, drones, and IoT-enabled systems—allowing real-time .

4.Real-Time Monitoring and Initial detection
Integrating deep learning systems with drones and unmanned aerial vehicles (UAVs) can enable large-

scale crop monitoring. Future models can include automated tracking and alert systems for instantaneous disease surveillance, allowing and reducing potential yield losses.

5.Federated and Collaborative Learning
To ensure data privacy and improve cross-regional generalization, future studies can utilize Federated Learning (FL). This approach allows multiple farms or institutions to collaboratively train a unified global model without exchanging raw data, ensuring both privacy and adaptability to region-specific conditions.

REFERENCES

[1]. Chouhan SS, Kaul A, Singh UP, Jain S (2018) Bacterial foraging optimization based radial basis function neural network (BRBFNN) for identification and classification of plant leaf diseases: an automatic approach towards plant pathology.

[2]. Bharate AA, Shirdhonkar M (2017) A review on plant disease detection using image processing. In: 2017 International conference on intelligent sustainable systems (ICISS).

[3]. Ferentinos KP (2018) Deep learning models for plant disease detection and diagnosis. Comput Electron Agric

[4]. Bock C, Poole G, Parker P, Gottwald T (2010) Plant disease severity estimated visually, by digital photography and image analysis, and by hyperspectral imaging. Crit Rev Plant Sci

[5]. Das R, Pooja V, Kanchana V (2017) Detection of diseases on visible part of plant—a review.

[6]. Bhagat M, Kumar D (2022) A comprehensive survey on leaf disease identification and classification.

Multimedia Tools Appl 1 –29

[7]. Lee SH, Chan CS, Wilkin P, RemagninoP (2015) Deep-plant: plant identification with convOlutional

neural networks.

[8]. Hassan SM, Amitab K, Jasinski M, Leonowicz Z, Jasinska E, Novak T, Maji AK (2022) A survey on different plant diseases detection using machine learning techniques. Electronics 11(17):2641

[9]. Wani JA, Sharma S, Muzamil M, Ahmed S, Sharma S, Singh S (2022) Machine learning and deep learning based computational techniques in automatic agricultural diseases detection: methodologies, applications, and challenges. Arch Comput Methods Eng 29(1):641–677

[10]. Hughes D, Salathé M et al (2015) An open access repository of images on plant health to enable the development of mobile disease diagnostics. arXiv preprint arXiv:1511.08060

[11]. Ramcharan A, Baranowski K, McCloskey P, Ahmed B, Legg J, Hughes DP (2017) Deep learning for image-based cassava disease detection. Front Plant Sci 8:1852

[12]. Camargo A, Smith J (2009) Image pattern classification for the identification of disease causing agents in plants. Comput Electron Agric 66(2):121–125

[13]. Hlaing CS, Zaw SMM (2017) Model-based statistical features for mobile phone image of tomato plant disease classification. In: 2017 18th international conference on parallel and distributed computing, applications and technologies (PDCAT).

[14]. Anthonys G, Wickramarachchi N (2009) An image recognition system for crop disease iden tification of paddy fields in Sri La nka. In: 2009 International conference on industrial and information systems (ICIIS).

[15]. Islam M, Dinh A, Wahid K, Bhowmik P (2017) Detection of potato diseases using image segmentation and multiclass support vector machine