## PHYS 229 - Ryan Kaufmann/Experiment 3/Cooling Prelab

SIGNED by Ryan Kaufmann Apr 10, 2018 @02:40 PM PDT

Ryan Kaufmann Apr 08, 2018 @02:26 PM PDT

## **Cooling 0 Prelab Questions**

Ryan Kaufmann Apr 08, 2018 @02:32 PM PDT

Let us first look at the convection equation of the rod. We can set up our differential equation as so:

Ryan Kaufmann Apr 09, 2018 @01:19 PM PDT

$$egin{split} rac{dQ}{dt} &= -hA(T-T_0) \ rac{dQ}{dt} &= -1.32Arac{1}{D^{1/4}}(T-T_0)^{5/4} \ 
ho VCrac{dT}{dt} &= -1.32Arac{1}{D^{1/4}}(T-T_0)^{5/4} \ rac{dT}{dt} &= -1.32rac{A}{
ho CV}rac{1}{D^{1/4}}(T-T_0)^{5/4} \end{split}$$

Ryan Kaufmann Apr 09, 2018 @07:49 PM PDT

We can then apply our constant conditions of the properties of the rod and the temperature of the lab. Our constants from the rod are set up such that we have the following:

Ryan Kaufmann Apr 09, 2018 @07:53 PM PDT

$$D = 0.0246m \pm 0.0001m$$
  $L = 0.305m \pm 0.001m$   $ho = 2700kg/m^3 \pm 2kg/m^3$   $C = 904J/(kgK) \pm 2J/(kgK)$   $T_c = 293.0K \pm 0.5K$ 

Ryan Kaufmann Apr 09, 2018 @07:49 PM PDT

Solving the differential equation gives us the following:

1 of 4 04/10/2018, 2:41 PM

Ryan Kaufmann Apr 09, 2018 @08:08 PM PDT

$$egin{aligned} rac{dT}{dt} &= -1.32 rac{A}{
ho CV} rac{1}{D^{1/4}} (T-T_0)^{5/4} \ & rac{dT}{dt} &= -1.32 rac{0.02457}{2700*904*0.0001456} rac{1}{0.02465^{1/4}} (T-293)^{5/4} \ & (T-293)^{-5/4}*dT &= -0.0002304dt \ & rac{4}{(T-293)^{1/4}} - rac{4}{(T_c-293)^{1/4}} &= -0.0002304t \end{aligned}$$

Ryan Kaufmann Apr 08, 2018 @03:17 PM PDT

where Tc is the starting temperature of the rod (i.e. the temperature at t=0). We can then solve for both t when Tc is 363 and T is 303K and for the equation of T in terms of Tc and t:

Ryan Kaufmann Apr 09, 2018 @08:07 PM PDT

$$egin{aligned} rac{4}{(T-293)^{1/4}} - rac{4}{(T_c-293)^{1/4}} &= -0.0002304t \ rac{4}{(T-293)^{1/4}} &= -0.0002304t - rac{4}{(T_c-293)^{1/4}} \ rac{1}{(T-293)^{1/4}} &= -0.00005761t - rac{1}{(T_c-293)^{1/4}} \ (T-293)^{1/4} &= rac{1}{-0.00005761t - rac{1}{(T_c-293)^{1/4}}} \ (T-293) &= (rac{1}{-0.00005761t - rac{1}{(T_c-293)^{1/4}}})^4 \ T(t,T_c) &= (rac{1}{-0.00005761t - rac{1}{(T_c-293)^{1/4}}})^4 + 293 \end{aligned}$$

Ryan Kaufmann Apr 09, 2018 @08:06 PM PDT

$$egin{aligned} rac{4}{(T-293)^{1/4}} + rac{-4}{(T_c-293)^{1/4}} &= -0.0002304t \ rac{4}{(363-293)^{1/4}} + rac{-4}{(303-293)^{1/4}} &= -0.0002304t \ rac{4}{(70)^{1/4}} + rac{-4}{(10)^{1/4}} &= -0.0002304t \ rac{4}{2.893} + rac{-4}{1.778} &= -0.0002304t \ 1.383 - 2.250 &= -0.0002304t \ -0.867 &= -0.0002304t \ t &= 3762.57s \end{aligned}$$

Ryan Kaufmann Apr 09, 2018 @08:06 PM PDT

Thus we have that it would take around 3,760 seconds for the rod to cool using convection.

Ryan Kaufmann Apr 08, 2018 @03:59 PM PDT

Applying the same differential equation techniques to the radiation formula gives us the following set up:

Ryan Kaufmann Apr 09, 2018 @01:32 PM PDT

$$egin{aligned} rac{dQ}{dt} &= Ae\sigma T_0^4 - Ae\sigma T^4 \ 
ho VCrac{dT}{dt} &= Ae\sigma T_0^4 - Ae\sigma T^4 \ rac{dT}{dt} &= rac{Ae\sigma}{
ho VC}T_0^4 - rac{Ae\sigma}{
ho VC}T^4 \end{aligned}$$

Ryan Kaufmann Apr 08, 2018 @04:09 PM PDT

Then applying our constants, we have:

Ryan Kaufmann Apr 09, 2018 @08:27 PM PDT

$$\frac{dT}{dt} = \frac{0.02457\sigma}{2700*904*0.0001456} * (293)^4 - \frac{0.02457\sigma}{2700*904*0.0001456} * T^4$$

$$\frac{1}{(293^4 - T^4)} \frac{dT}{dt} = 9.899*10^{-12}$$

$$\ln(293+T_c)-2\arctan(293/T_c)-\ln(293+T)+2\arctan(293/T)=0.0009960t$$

Ryan Kaufmann Apr 08, 2018 @11:14 PM PDT

While this is unsolvable for a analytical solution of T in terms of Tc and t, we can plug in values of T and Tc to find the cooling time:

Ryan Kaufmann Apr 09, 2018 @08:30 PM PDT

$$\ln(293+363)-2\arctan(293/363)-\ln(293+303)+2\arctan(293/303)=0.0009960t$$
 
$$1.6709=0.0009960t$$
 
$$t=1677.7s$$

Ryan Kaufmann Apr 09, 2018 @08:30 PM PDT

Which gives us a shorter around 1,678 seconds for the rod to cool using radiation.