

Setting up an R development environment on github

RG Thomas

2024-12-25

Table of contents

| | | |
|----------|--|----------|
| 0.1 | Introduction | 1 |
| 0.2 | The Problem/Data | 2 |
| 0.2.1 | Step 1: Initial Repo Setup | 2 |
| 1 | Debugging workflow | 4 |
| 2 | Debugging Workflow from chatGPT | 6 |
| 2.1 | Reproducibility | 7 |
| 2.2 | Next Steps | 8 |
| 2.3 | References | 8 |

0.1 Introduction

Its often the case that a data scientist needs to share an R function with a co-worker or a student. This post describes a step by step methodology for wrapping the function in a package, that includes a number of support files, and sharing it either via github or CRAN. This may seem like overkill but over time a not having to address the many technical issues that can arise when sharing a function in a more ad hoc manner may be appreciated.



Figure 1: purrr

0.2 The Problem/Data

The end goal of this terminal is to create a directory (or repository) that contains the package contents. The top level elements of the package are the `DESCRIPTION` file, the `NAMESPACE` file, the `R` directory, the `tests` directory, and the `man` directory. Other files such as a `README.md`, a `LICENSE` file are optional but recommended. The `DESCRIPTION` file contains metadata about the package such as the package name, the version number, the author, and the license. The `NAMESPACE` file contains the export and import declarations. The `R` directory contains the R functions. The `tests` directory contains the unit tests.

0.2.1 Step 1: Initial Repo Setup

Start by using the various helpful tools in the `devtools` and `usethis` packages to facilitate the repository building process.

Open R from the shell prompt in your development directory. and run the command `usethis::create_package("my_package")` to create the package directory and the `DESCRIPTION` and `NAMESPACE` files. Assuming the package will be named `my_package`.

```
install.packages("devtools")
library(devtools)
usethis::create_package("my_package")
```

This creates the following directory structure.

```
my_package  tree --charset=ascii
.
|-- DESCRIPTION
|-- NAMESPACE
`-- R

my_package  more DESCRIPTION
Package: my_package
Title: What the Package Does (One Line, Title Case)
```

```

Version: 0.0.0.9000
Authors@R:
  person("First", "Last", , "first.last@example.com", role = c("aut", "cre"),
    comment = c(ORCID = "YOUR-ORCID-ID"))
Description: What the package does (one paragraph).
License: `use_mit_license()`, `use_gpl3_license()` or friends to pick a
  license
Encoding: UTF-8
Roxygen: list(markdown = TRUE)
RoxygenNote: 7.3.2

```

Next use the `usethis` package tools to generate repository support files.

```

usethis::use_git()
usethis::use_github()
use_gpl_license(version = 3, include_future = TRUE)
usethis::use_readme_md()
usethis::use_code_of_conduct("rgthomas@ucsd.edu")
usethis::use_tidy_contributing()

```

Next copy the R file containing the function to the R directory and add a `#'` roxygen comment block to the top of the file. Then call `devtools::document()` to generate the `man` directory containing the help page.

```
devtools::document()
```

At this point the directory structure looks like this.

```

julia dev/my_package  tree --charset=ascii
.
|-- DESCRIPTION      # package Metadata
|-- NAMESPACE       # Exports and imports declarations
|-- R                # R functions
|   `-- my_package.R
|-- man              # Documentation for the functions
|   `-- my_package.Rd

```

The next step is to set up testing.

```
usethis::use_testthat()
```

```
call inside R
usethis::use_test("my_package")
```

This open an editor. Enter the unit tests using the `test_that` function.

```
# Test: Empty dataframe error
test_that("t2f throws an error for empty dataframe", {
  empty_df <- data.frame()
  expect_error(my_package(empty_df, filename = "empty_table"), "`df` must not be empty")
})
```

Set up a new repository on github.

```
git init
git add .
git commit -m "Initial commit"
```

Add each dependency (e.g. `kableExtra`) (e.g. `kableExtra`) (e.g. `kableExtra`)

```
usethis::use_package("kableExtra", type = "Imports")
```

Finally do a full check using `devtools::check()`. This reflects the checks that CRAN will perform when you submit the package.

```
devtools::build()
devtools::install()
devtools::test()
devtools::check()
```

1 Debugging workflow

```
git checkout -b fix-bug
```

Debug locally and isolate the issue.

- Create a local branch (fix-bug) for the fix.
- `git checkout -b fix-bug`
- Make and test the changes.
- Run `devtools::test()` to confirm all tests pass.
- Use `devtools::check()` to validate the package.
- `git add .`
- `git commit -m "Fix issue with my__package function"`
- `git push`
- Merge the branch into the main branch and clean up.
- `git checkout main`
- `git merge fix-bug`
- `git branch -d fix-bug`
- `git push`
- Open a Pull Request.
- Update the version number
- `usethis::use_version("patch")`
- and push the final changes.
- `git push`

2 Debugging Workflow from chatGPT

Follow these steps to debug and fix issues in your R package:

1. Debug Locally

- Isolate the issue using R debugging tools like `browser()`, `traceback()`, or `debug()`.

2. Create a Local Git Branch

- Create a branch for the fix to isolate your changes:

```
git checkout -b fix-bug
```

3. Make and Test Changes

- Modify your code to fix the issue and add or update unit tests as needed.
- Run tests to confirm functionality:

```
devtools::test() # Confirm all tests pass  
devtools::check() # Validate the package complies with CRAN standards
```

4. Commit Your Changes

- Stage and commit your changes:

```
git add .  
git commit -m "Fix issue with my_package function"
```

5. Push the Branch

- Push the branch to GitHub for collaboration or to prepare for merging:

```
git push origin fix-bug
```

6. Open a Pull Request

- Open a Pull Request (PR) on GitHub to merge the fix into the main branch. Include a clear description of the changes.

7. Merge and Clean Up

- After review and approval, merge the branch into the main branch:

```
git checkout main
git merge fix-bug
```

- Delete the branch locally and remotely:

```
git branch -d fix-bug
git push origin --delete fix-bug
```

8. Test the Main Branch

- Ensure the main branch passes all tests:

```
devtools::test() # Confirm functionality
devtools::check() # Validate compliance
```

9. Update the Version Number

- Increment the package version using `usethis::use_version()`:

```
usethis::use_version("patch") # Use "patch", "minor", or "major"
```

- Commit and push the version update:

```
git add DESCRIPTION
git commit -m "Bump version to 1.0.1"
git push
```

2.1 Reproducibility

```
# Print session info for reproducibility
sessionInfo()
```

```
R version 4.4.2 (2024-10-31)
Platform: aarch64-apple-darwin20
Running under: macOS Sequoia 15.2
```

```
Matrix products: default
```

```
BLAS: /Library/Frameworks/R.framework/Versions/4.4-arm64/Resources/lib/libRblas.0.dylib
```

LAPACK: /Library/Frameworks/R.framework/Versions/4.4-arm64/Resources/lib/libRlapack.dylib; LA

locale:

[1] en_US.UTF-8/en_US.UTF-8/en_US.UTF-8/C/en_US.UTF-8/en_US.UTF-8

time zone: America/Los_Angeles

tzcode source: internal

attached base packages:

[1] stats graphics grDevices datasets utils methods base

other attached packages:

| | | | | |
|--------------------|-----------------|----------------|------------------|--------------|
| [1] here_1.0.1 | shiny_1.9.1 | styler_1.10.3 | quarto_1.4.4 | pacman_0.5.1 |
| [11] dplyr_1.1.4 | purrr_1.0.2 | readr_2.1.5 | tidyr_1.3.1 | tibble_3.2.1 |
| [21] janitor_2.2.0 | datapasta_3.1.0 | ggthemes_5.1.0 | conflicted_1.2.0 | DT_0.33 |

loaded via a namespace (and not attached):

| | | | | |
|-----------------------|-------------------|-------------------|----------------|-------------------|
| [1] tidyselect_1.2.1 | viridisLite_0.4.2 | R.utils_2.12.3 | fastmap_1.2.0 | promises_1.3.2 |
| [11] processx_3.8.4 | magrittr_2.0.3 | compiler_4.4.2 | rlang_1.1.4 | tools_4.4.2 |
| [21] pkgload_1.4.0 | miniUI_0.1.1.1 | R.cache_0.16.0 | withr_3.0.2 | R.oo_1.27.0 |
| [31] colorspace_2.1-1 | scales_1.3.0 | cli_3.6.3 | generics_0.1.3 | remotes_2.5.0 |
| [41] vctr_0.6.5 | jsonlite_1.8.9 | hms_1.1.3 | visdat_0.6.0 | systemfonts_1.1.0 |
| [51] munsell_0.5.1 | pillar_1.9.0 | htmltools_0.5.8.1 | R6_2.5.1 | rprojroot_2.0.4 |
| [61] Rcpp_1.0.13-1 | svglite_2.1.3 | xfun_0.49 | fs_1.6.5 | pkgconfig_2.0.3 |

2.2 Next Steps

- Suggest areas for further exploration
- Mention potential improvements
- Invite reader engagement

2.3 References

- Cite your sources
- Link to relevant documentation
- Credit other contributors

Tags: R, your-topic-tags Category: R