

Working example for generating multiple plots inside a map2 call

Ronald (Ryy) Glenn Thomas

2024-02-07

Table of contents

| | | |
|---|--|---|
| 1 | Introduction | 1 |
| 2 | Plots for every variable and each species map inside map see ref 2 below | 3 |
| 3 | combine plots in a upper triangular grid with correlation coefs | 3 |
| 4 | Code | 3 |
| 5 | References | 4 |

1 Introduction

Consider the problem of running a data analysis requiring a separate analysis for each of `n` strata. For example consider an effort to model the relationship between `Bill length` and `Flipper length` across three different species of penguins.

We can work with the dataset `penguins` included in the package `palmerpenguins`




Figure 1: purrr

```
library(palmerpenguins)
```

One naive approach is to split the dataset and do three separate analyses:

```
df1 = split(penguins, penguins$species)
```

The R package `purrr` provides a straightforward method to conduct the analyses with a single command. Assume the set of data tables are contained in a list of dataframes. Also assume the analysis is a simple visualization of a potential linear association between two features,




Figure 2: Scatterplot for species: Adelie




Figure 3: Scatterplot for species: Chinstrap




Figure 4: Scatterplot for species: Gentoo

**2 Plots for every variable and each species
map inside map see ref 2 below**

**3 combine plots in a upper triangular grid
with correlation coefs**

4 Code

```
1 library(pacman)
2 p_load(palmerpenguins, tidyverse, knitr)
3
4 opts_chunk$set(
5   warning = FALSE, message = FALSE, echo = FALSE, fig.width = 4,
6   fig.height = 2.1, results = "asis", dev = "pdf")
7
8 df1 = split(penguins, penguins$species)
9
10 foo <- function (df, z) {
11   # df is the data frame, z is the name of the species
```

```

12 df |> ggplot(aes(x = bill_length_mm, y = flipper_length_mm))+
13   geom_point(aes(color = island), alpha = .5) +
14   geom_smooth() +
15   scale_color_manual(values = c("purple","green","red")) +
16   theme_bw() +
17   labs(title = paste(z, " Penguin Anatomy Comparison"), x = "Flipper length",
18         y = "Bill length", color = "Island")
19 plotfile_name = paste0(z,".pdf")
20 ggsave(plotfile_name)
21 cat(paste0("\\includegraphics[]{" ,plotfile_name,"}"), "\n")
22 cat(paste0("\\captionof{figure}{Scatterplot for species: ",z,"}"), "\n")
23 cat("\\vspace{1cm}", "\n")
24 }
25
26 bar = df1 |> map2(names(df1), foo)

```

5 References

[principal components analysis](#)

[Automating exploratory plots with ggplot2 and purrr](#)