Configure the tiling window manager yabai for macos

Ronald (Ryy) Glenn Thomas 2024-02-07

Table of contents

1	Introduction	1
2	skhd	Į

1 Introduction

Yabai is a tiling window manager for macOS.

From the wiki Home · koekeishiya/yabai Wiki · GitHub

"It automatically modifies your window layout using a binary space partitioning algorithm interface allows you to control and query windows, spaces and displays to enable powerful integration with tools like skhd to allow you to work more efficiently with macOS."

Requirements: (from the WIKI)

• In the Desktop & Dock tab, inside the Mission Control pane, the setting "Displays have separate Spaces" must be enabled.



Figure 1: quarto

- System Settings (macOS 13.x, 14.x) In the Desktop & Dock tab, inside the Mission Control pane, the setting "Automatically rearrange Spaces based on most recent use" should be disabled for commands that rely on the ordering of spaces to work reliably.
- System Settings (macOS 14.x) In the Desktop & Dock tab, inside the Desktop & Stage Manager pane, the setting "Show Items On Desktop" should be enabled for display and space focus commands to work reliably in multidisplay configurations.
- System Settings (macOS 14.x) In the Desktop & Dock tab, inside the Desktop & Stage Manager pane, the setting "Click wallpaper to reveal Desktop" should be set to "Only in Stage Manager" for display and space focus commands to work reliably.

```
brew install koekeishiya/formulae/yabai
# start yabai
yabai --start-service
```

Sample configuration files can be found in the examples directory. Refer to the documentation or the wiki for further information.

Keyboard shortcuts can be defined with skhd or any other suitable software you may prefer. ## yabairc

```
gaps["left"]="4"
gaps["right"]="4"
gaps["inner"]="4"
color["focused"]="0xE0808080"
color["normal"]="0x00010101"
color["preselect"]="0xE02d74da"
# Uncomment to refresh ubersicht widget on workspace change
# Make sure to replace WIDGET NAME for the name of the ubersicht widget
#ubersicht_spaces_refresh_command="osascript -e 'tell application id \"tracesOf.Uebersicht\" to
# ===== Loading Scripting Additions ========
# See: https://github.com/koekeishiya/yabai/wiki/Installing-yabai-(latest-release)#macos-big-s
sudo yabai --load-sa
yabai -m signal --add event=dock_did_restart action="sudo yabai --load-sa"
# ===== Tiling setting ===========
yabai -m config layout
                                            bsp
                                            "${gaps["top"]}"
yabai -m config top_padding
                                            "${gaps["bottom"]}"
yabai -m config bottom_padding
                                            "${gaps["left"]}"
yabai -m config left_padding
yabai -m config right_padding
                                            "${gaps["right"]}"
                                            "${gaps["inner"]}"
yabai -m config window_gap
yabai -m config mouse_follows_focus
                                            off
yabai -m config focus_follows_mouse
                                            off
yabai -m config window_topmost
                                            off
yabai -m config window_opacity
                                            off
yabai -m config window_shadow
                                            float
yabai -m config window_border
                                            on
yabai -m config window_border_width
yabai -m config active_window_border_color
                                            "${color["focused"]}"
yabai -m config normal_window_border_color
                                            "${color["normal"]}"
yabai -m config insert_feedback_color
                                            "${color["preselect"]}"
```

```
yabai -m config active_window_opacity
                                            1.0
yabai -m config normal_window_opacity
                                            0.90
yabai -m config split_ratio
                                            0.50
yabai -m config auto_balance
                                            on
yabai -m config mouse modifier
                                            fn
yabai -m config mouse_action1
                                            move
yabai -m config mouse_action2
                                            resize
# ===== Rules ==============================
yabai -m rule --add label="Finder" app="^Finder$" title="(Co(py|nnect)|Move|Info|Pref)" manage
yabai -m rule --add label="Safari" app="^Safari$" title="^(General|(Tab|Password|Website|Extension
yabai -m rule --add label="macfeh" app="^macfeh$" manage=off
yabai -m rule --add label="System Preferences" app="^System Preferences$" title=".*" manage=of:
yabai -m rule --add label="App Store" app="^App Store$" manage=off
yabai -m rule --add label="Activity Monitor" app="^Activity Monitor$" manage=off
yabai -m rule --add label="KeePassXC" app="^KeePassXC$" manage=off
yabai -m rule --add label="Calculator" app="^Calculator$" manage=off
yabai -m rule --add label="Dictionary" app="^Dictionary$" manage=off
yabai -m rule --add label="mpv" app="^mpv$" manage=off
yabai -m rule --add label="Software Update" title="Software Update" manage=off
yabai -m rule --add label="About This Mac" app="System Information" title="About This Mac" man
# ===== Signals ============================
yabai -m signal --add event=application_front_switched action="${ubersicht_spaces_refresh_comm
yabai -m signal --add event=display_changed action="${ubersicht_spaces_refresh_command}"
yabai -m signal --add event=space_changed action="${ubersicht_spaces_refresh_command}"
yabai -m signal --add event=window_created action="${ubersicht_spaces_refresh_command}"
yabai -m signal --add event=window_destroyed action="${ubersicht_spaces_refresh_command}"
yabai -m signal --add event=window_focused action="${ubersicht_spaces_refresh_command}"
yabai -m signal --add event=window_title_changed action="${ubersicht_spaces_refresh_command}"
set +x
printf "yabai: configuration loaded...\\n"
```

2 skhd

```
# opens iTerm2
alt - return : "${HOME}"/bin/open_iterm.sh
# Navigation
alt - h : yabai -m window --focus west
alt - j : yabai -m window --focus south
alt - k : yabai -m window --focus north
alt - 1 : yabai -m window --focus east
# Moving windows
shift + alt - h : yabai -m window --warp west
shift + alt - j : yabai -m window --warp south
shift + alt - k : yabai -m window --warp north
shift + alt - 1 : yabai -m window --warp east
# Move focus container to workspace
shift + alt - m : yabai -m window --space last; yabai -m space --focus last
shift + alt - p : yabai -m window --space prev; yabai -m space --focus prev
shift + alt - n : yabai -m window --space next; yabai -m space --focus next
shift + alt - 1 : yabai -m window --space 1; yabai -m space --focus 1
shift + alt - 2 : yabai -m window --space 2; yabai -m space --focus 2
shift + alt - 3 : yabai -m window --space 3; yabai -m space --focus 3
shift + alt - 4 : yabai -m window --space 4; yabai -m space --focus 4
# Resize windows
lctrl + alt - h : yabai -m window --resize left:-50:0; \
                  yabai -m window --resize right:-50:0
lctrl + alt - j : yabai -m window --resize bottom:0:50; \
                  yabai -m window --resize top:0:50
lctrl + alt - k : yabai -m window --resize top:0:-50; \
                  yabai -m window --resize bottom:0:-50
lctrl + alt - 1 : yabai -m window --resize right:50:0; \
                  yabai -m window --resize left:50:0
# Equalize size of windows
lctrl + alt - e : yabai -m space --balance
```

```
# Enable / Disable gaps in current workspace
lctrl + alt - g : yabai -m space --toggle padding; yabai -m space --toggle gap
# Rotate windows clockwise and anticlockwise
alt - r : yabai -m space --rotate 270
shift + alt - r : yabai -m space --rotate 90
# Rotate on X and Y Axis
shift + alt - x : yabai -m space --mirror x-axis
shift + alt - y : yabai -m space --mirror y-axis
# Float / Unfloat window
shift + alt - space : \
   yabai -m window --toggle float; \
    yabai -m window --toggle border
# Restart Yabai
shift + lctrl + alt - r : \
    /usr/bin/env osascript <<< \
        "display notification \"Restarting Yabai\" with title \"Yabai\""; \
    launchctl kickstart -k "gui/${UID}/homebrew.mxcl.yabai"
# Make window native fullscreen
               : yabai -m window --toggle zoom-fullscreen
shift + alt - f : yabai -m window --toggle native-fullscreen
```