

# Constructing a medium complexity shiny app for power analysis

Ronald (Ryy) Glenn Thomas

10/12/23

## Table of contents

1	Introduction	1
2	- Code	1

## 1 Introduction

## 2 - Code

```
library(pacman)
p_load(ggplot2, pwr)

ui <- fluidPage(
  fluidRow(
    column(
      2,
      sliderInput("N", "Total Sample Size:", min = 0, max = 500, value = 100),
      # verbatimTextOutput("sizes"),
      sliderInput("dropout", "Dropout Rate:", min = 0, max = .40, value = .10),
      hr(),
      selectInput(
        "deltamethod", "Method for Delta (Effect Size) Specification",
```

```

c( "Standard Deviation Units (Cohen)" = "std",
  "difference in change scores between groups" = "diff",
  "percent reduction/increase in active
    change score from placebo" = "pct",
  "change in active group" = "active"
)
),
conditionalPanel(
  condition = "input.deltamethod == 'std'",
  sliderInput("del", "Range for delta",
    min = 0.0,
    max = 1.5, value = c(0, 1)
  ),
),
conditionalPanel(
  condition = "input.deltamethod == 'diff' |
input.deltamethod == 'pct' |input.deltamethod == 'active' ",
  numericInput("placebosd", "Placebo Change Score Standard Deviation:",
    10.0,
    min = 1, max = 100, value = 1
  ),
  numericInput("placebo", "Placebo Change Score:", 10,
    min = -100,
    max = 100
  ),
),
conditionalPanel(
  condition = "input.deltamethod == 'diff'",
  sliderInput("diff", "Diff in change scores",
    min = 0,
    max = 30, value = c(0, 25)
  ),
),
conditionalPanel(
  condition = "input.deltamethod == 'pct'",
  sliderInput("pct", "Percent Reduction",
    min = 1,
    max = 100, value = c(10, 90)
  ),
),

```

```

),
conditionalPanel(
  condition = "input.deltamethod == 'active'",
  sliderInput("active", "Treatment group change",
    min = 1,
    max = 50, value = c(1, 50)
  )
),
checkboxInput("choice", "Additional parameter settings"),
conditionalPanel(
  condition = "input.choice == 1",
  numericInput("type1", "Type one error:",
    min = 0.001, max = .2,
    value = .05, step = .005
  ),
  numericInput("ratio", "Ratio of active to control subjects:",
    min = .5,
    max = 5.0, value = 1, step = .5
  ),
  htmlOutput("sizes"),
  sliderInput("dropin", "Drop-in rate:", min = 0, max = .4, value = 0),
  htmlOutput("dropoutsizes"),
),
),
column(2,
  align = "center", plotOutput("plot"),
  verbatimTextOutput("eff0"),
  verbatimTextOutput("eff"),
  verbatimTextOutput("eff2")
),
tags$head(tags$style("#eff{color:gray; font-size:12px;
font-style:italic; text-align:left;
max-height: 130px; background: ghostwhite;}")),
  column(8, DT::dataTableOutput("df"), ),
)
)
server <- function(input, output, session) {
  N <- reactive(input$N)
  R <- reactive(input$ratio)

```

```

type1 <- reactive(input$type1)
dropin <- reactive(input$dropin)
dropout <- reactive(input$dropout)
del <- reactive(input$del)
diff <- reactive(input$diff)
pct <- reactive(input$pct)
placebo <- reactive(input$placebo)
active <- reactive(input$active)
placebosd <- reactive(input$placebosd)
deltamethod <- reactive(input$deltamethod)
delv <- reactive(seq(del()[1], del()[2], (del()[2] - del()[1]) / 30))
diffv <- reactive(seq(diff()[1], diff()[2], (diff()[2] - diff()[1]) / 30))
pctv <- reactive(seq(pct()[1], pct()[2], (pct()[2] - pct()[1]) / 30))
pctv2 <- reactive(placebo() * seq(
  pct()[1] / 100, pct()[2] / 100,
  (pct()[2] - pct()[1]) / 2000
))
activev <- reactive(seq( active()[1], active()[2],
  (active()[2] - active()[1]) / 30 ))
activev2 <- reactive(placebo() - activev())
# placebosdrange <- reactive(input$placebosdrange)
n1 <- reactive(R() * N() / (R() + 1) * ((1 - (dropin() + dropout()))))
n2 <- reactive(N() / (R() + 1) * ((1 - (dropin() + dropout()))))

deltav <- reactive({
  if (input$deltamethod == "diff") {
    deltav <- diffv() / placebosd()
  }
  else if (input$deltamethod == "std") {
    deltav <- delv()
    diffv <- delv()*placebosd()
    pctv = NA
  }
  else if (input$deltamethod == "pct") {
    deltav <- ((pct() / 100) * placebo()) / placebosd()
  }
  return(deltav)
})

```

```

pow <- reactive(sapply(
  deltav(),
  function(x) pwr.t2n.test(n1(), n2(), sig.level = type1(), d = x)$power
))
powdiff <- reactive(sapply(
  diffv(),
  function(x) {
    pwr.t2n.test(n1(), n2(),
      sig.level = type1(),
      d = x / placebosd()
    )$power
  }
))
powpct <- reactive(sapply(
  pctv(),
  function(x) {
    pwr.t2n.test(n1(), n2(),
      sig.level = type1(),
      d = ((x / 100) * placebo()) / placebosd()
    )$power
  }
))

observeEvent(input$N, {
  print(paste0("N: ", input$N))
})
observeEvent(input$deltamethod, {
  print(paste0("deltamethod: ", input$deltamethod))
})
out <- reactive(data.frame(cbind(
  N = input$N,
  SD = input$placebosd,
  Pl = input$placebo,
  deltav = round(deltav(), 3),
  diffv = round(diffv(), 3),
  pctv = round(pctv(), 3),
  powdiff = round(powdiff(), 3),
  powpct = round(powpct(), 3),
  power = round(pow(), 3)
)))

```

```

output$df <- DT::renderDataTable(out(),
  server = FALSE,
  filter = "top", extensions = "Buttons",
  options = list(
    paging = FALSE, scrollCollapse = TRUE,
    buttons = c("copy", "csv", "pdf"),
    dom = "Bt", scrollX = 300, scrollY = 200
  )
)
xaxistext <- "test"
output$plot <- renderPlot(ggplot(out(), aes(x = diffv, y = power)) +
  geom_line() +
  geom_hline(yintercept = 0.8, color = "red") +
  geom_vline(xintercept = pwr.t2n.test(n1(), n2(),
    sig.level = type1(), power = .8
  )$d, color = "blue") +
  # scale_x_continuous(name=xaxistext, sec.axis = dup_axis(),
  scale_x_continuous(
    name = xaxistext, sec.axis = sec_axis(~ . / placebosd(),
    name = "standard deviation units"
  ),
  limits = c(input$del[[1]], input$del[[2]])
) +
scale_y_continuous(
  name = "Power", limits = c(0, 1.0),
  breaks = seq(0, 1, .1)
) +
theme_bw())

effsize <- renderText(round(pwr.t2n.test(n1(), n2(),
  sig.level = type1(), power = .8
)$d, 3))
output$sizes <- renderText(paste0(
  "ITT analysis per group sample size: N<sub>active</sub> = ",
  round(N() * (R() / (1 + R()))), 0), ", N<sub>control</sub> = ",
  round(N() / (1 + R())), 0)

```

```

))
output$dropoutsizes <- renderText(paste0(
  "Expected number of completers: N<sub>active</sub> = ",
  round(n1(), 0), ", N<sub>control</sub>= ", round(n2(), 0)
))
output$eff <- renderText(paste0(
  "\ntype 1 error = ", type1(),
  "\ndropout rate = ", dropout(),
  "\ndropin rate = ", dropin(),
  "\nactive to placebo ratio = ", R()
))
output$eff0 <- renderText(
  paste0("In summary, given the parameters: ")
)
output$eff2 <- renderText(
  paste0(
    "A sample size of ", N(), " has 80% power to detect an effect of ",
    effsize()
  )
)
}

shinyApp(ui, server)

```