workflow_mini

July 22, 2025

ZZCOLLAB Mini Workflow Guide

Solo Developer: Complete Analysis Workspace

Single Developer Setup (Complete Environment)

For solo developers who want a complete, reproducible analysis environment:

```
# Option A: Two-step approach (recommended for flexibility)

# Step 1: Create team images (builds all variants: shell, rstudio, verse)
zzcollab -i -t rgt47 -p c275 -B all -S

# Step 2: Create full project with personal workspace
mkdir c275 && cd c275
zzcollab -t rgt47 -p c275 -F -d ~/dotfiles --github -I shell
```

What this creates: - [CHECKMARK] Complete Docker environment: All variants (shell, rstudio, verse) available - [CHECKMARK] Personal workspace: Your dotfiles integrated - [CHECKMARK] Private GitHub repository: https://github.com/rgt47/c275 with CI/CD - [CHECKMARK] Ready-to-code: Start immediately with make docker-zsh

Alternative: One-command setup

```
# Single command for complete solo setup
zzcollab -t rgt47 -p c275 -F -d ~/dotfiles --github -I shell
Build modes: -F (Fast), -S (Standard), -C (Comprehensive)
Interfaces: -I shell (vim/tmux), -I rstudio (web), -I verse (publishing)
```

Daily Workflow

```
make docker-zsh  # Start development
# ... analysis work ...
exit  # Exit container
git add . && git commit -m "Add analysis" && git push
```

Developer 1: Team Lead Project Initialization

Two-Step Process for Team Lead (Fixed -i Flag Behavior)

```
# Step 1: Create and push team Docker images ONLY
# Navigate to projects directory first
cd ~/projects # or your preferred projects directory
# Create team images with selective base image building
# Choose one approach based on team needs:
# Option A: Build only shell variant (fastest - recommended for command-line teams)
zzcollab -i -t rgt47 -p png1 -B r-ver -S
# Option B: Build only RStudio variant (for GUI-focused teams)
zzcollab -i -t rgt47 -p png1 -B rstudio -S
# Option C: Build only verse variant (for publishing-focused teams)
zzcollab -i -t rgt47 -p png1 -B verse -S
# Option D: Build all variants (traditional approach - takes longer)
zzcollab -i -t rgt47 -p png1 -B all -S
# Step 2: Create full project structure (run separately)
mkdir png1 && cd png1 # or git clone if repo exists
zzcollab -t rgt47 -p png1 -I shell # Full project setup (use appropriate interface)
# Note: Step 1 (-i flag) now stops after team image creation
# Step 2 creates the actual project structure and GitHub repository
```

What Each Step Does:

Step 1 (-i flag): 1. **Builds team Docker images**: Creates and pushes to Docker Hub as rgt47/pnglcore-shell:latest (and/or other variants) 2. **Stops after image creation**: Provides guidance for next steps

Step 2 (separate project setup): 1. Creates project directory: png1/2. Initializes zzcollab project structure: Complete R package with analysis framework 3. Creates private GitHub repository: https://github.com/rgt47/png1 4. Sets up automated CI/CD: GitHub Actions for team image management 5. Enables team collaboration: Dev 2 and Dev 3 can join immediately

Required: Invite Team Members

After completing both steps, Dev 1 must invite collaborators:

```
# Invite team members to the private GitHub repository
gh repo invite rgt47/png1 dev2-github-username
gh repo invite rgt47/png1 dev3-github-username

# Alternative: Via GitHub web interface
# 1. Go to https://github.com/rgt47/png1/settings/access
# 2. Click "Invite a collaborator"

# 3. Add dev2-github-username and dev3-github-username with "Write" access
```

For Dev 2 and Dev 3 to Join:

1. Accept GitHub collaboration invitation

Check email for invitation from rgt47/png1 repository

```
# OR visit: https://github.com/rgt47/png1/invitations
# Click "Accept invitation"

# 2. Clone the project
git clone https://github.com/rgt47/png1.git
cd png1

# 3. Join with available interface (they'll get helpful errors if variant unavailable)
zzcollab -t rgt47 -p png1 -I shell -d ~/dotfiles  # If shell variant available
zzcollab -t rgt47 -p png1 -I rstudio -d ~/dotfiles  # If RStudio variant available
zzcollab -t rgt47 -p png1 -I verse -d ~/dotfiles  # If verse variant available
```

Key Benefits of This Approach:

- [CHECKMARK] **No local workspace for Dev 1**: Team infrastructure created without personal development setup
- [CHECKMARK] Faster initialization: Only builds needed variants, not all three
- [CHECKMARK] **Immediate team access**: Dev 2 & 3 can join as soon as GitHub repo is created
- [CHECKMARK] **Flexible team scaling**: Can add more variants later with zzcollab -V rstudio
- [CHECKMARK] **Error guidance**: Team members get helpful messages if requesting unavailable variants

If Team Needs Multiple Interfaces Later:

Developer 1 can add variants incrementally:

```
cd png1
zzcollab -V rstudio # Add RStudio variant
zzcollab -V verse # Add verse variant for publishing
```

This approach optimizes for **team coordination** while minimizing **setup overhead** for the team lead! [ROCKET]

Developer 2: Development Completion Workflow

When **Developer 2** finishes their development work, here's the complete workflow:

1. Final Testing & Validation (Inside Container)

```
# Still in development container (make docker-zsh)
R
# Run final tests
devtools::load_all()  # Load all package functions
devtools::test()  # Run unit tests
testthat::test_dir("tests/integration")  # Run integration tests
source("scripts/my_analysis.R")  # Test your analysis script
quit()
```

```
2. Exit Container & Validate Dependencies

# Exit the development container
exit

# Validate all dependencies are properly tracked
make docker-check-renv-fix  # Auto-fix any dependency issues
make docker-test  # Run all tests in clean environment
make docker-render  # Ensure reports render correctly

3. Git Workflow - Commit Changes

# Check what you've changed
git status
git diff

# Stage and commit your work
qit add .
```

qit commit -m "Add [feature description] with comprehensive tests

- [Describe what you implemented]
- [List any new packages added]
- [Mention test coverage]
- All tests passing and dependencies validated"

```
# Push to your feature branch (if using feature branches - recommended)
git push origin feature/my-analysis
```

```
# OR push directly to main (if using simple workflow)
git push origin main
```

4. Create Pull Request (Recommended Team Workflow)

- [x] All unit tests pass
- [x] Integration tests pass
- [x] Analysis scripts run without errors
- [x] Report renders successfully
- [x] Dependencies validated

Impact

- [Describe how this affects the project]
- [Any breaking changes or requirements for other devs]"

5. What Happens Next (Automated)

When Dev 2 pushes changes:

1. GitHub Actions automatically:

- [CHECKMARK] Runs R package validation
- [CHECKMARK] Executes all tests
- [CHECKMARK] Renders analysis reports
- [CHECKMARK] Detects if new packages were added

2. If new packages detected:

- [CHECKMARK] **Rebuilds team Docker image** with new packages
- [CHECKMARK] **Pushes updated image** to Docker Hub (rgt47/png1core-*:latest)
- [CHECKMARK] **Notifies team** via commit comment with update instructions

3. Team gets notification:

```
[WHALE] Team Docker Image Updated

New packages detected: tidymodels, plotly

Team members: Update your environment with:
git pull
docker pull rgt47/png1core-shell:latest
make docker-zsh
```

6. Team Synchronization (Dev 1 & Dev 3)

Other team members sync automatically:

```
# Dev 1 and Dev 3 run when they see the notification:
git pull  # Get latest code changes
docker pull rgt47/png1core-shell:latest # Get updated team environment
make docker-zsh  # Continue development with new packages
```

Alternative: Simple Direct Push Workflow

If not using pull requests:

```
# After validation (steps 1-2 above)
git add .
git commit -m "Add my analysis with tests - all dependencies validated"
git push origin main  # Direct push triggers team image rebuild
```

Key Benefits of This Workflow:

- [CHECKMARK] **Zero manual image management**: GitHub Actions handles Docker rebuilds
- [CHECKMARK] **Automatic team notification**: Everyone knows when environment updates
- [CHECKMARK] **Dependency validation**: Prevents environment drift before commit
- [CHECKMARK] Professional quality: Tests, validation, and documentation required
- [CHECKMARK] **Team coordination**: Clear communication about changes and impacts

Dev 2's Work is Done! [PARTY]

Once Dev 2 pushes their changes: - **Code is integrated** into the main project - **Team environment is updated** automatically

- Other developers are notified and can sync - Dev 2 can start next feature or analysis

This workflow ensures **zero-friction collaboration** while maintaining **enterprise-grade quality standards**! [ROCKET]

Developer 1: Reacting to Team Contributions & Adding Own Work

Here are the commands **Developer 1 (Team Lead)** uses to react to Dev 2 and Dev 3's additions and then add their own code:

1. Sync with Team Changes

2. Review Team Contributions (Optional)

```
# Review specific team member changes
git log --author="dev2" --oneline -5  # See Dev 2's recent commits
git log --author="dev3" --oneline -5  # See Dev 3's recent commits

# Look at specific files that changed
git show HEAD~1  # Show last commit details
git diff HEAD~2..HEAD scripts/  # See script changes
git diff HEAD~2..HEAD R/  # See function changes
```

3. Start Development Environment with Updated Team Packages

4. Explore Team's New Code (Inside Container)

```
# Create branch for your new work
git checkout -b feature/dev1-integration
# OR work directly on main (simpler workflow)
# git checkout main
```

6. Add Your Own Code (Inside Container)

```
# Still in development container
vim scripts/04_advanced_modeling.R  # Create your analysis

# Example: Build on team's work
vim R/integration_functions.R  # Add functions that use team's work

# Write tests for your additions
vim tests/testthat/test-integration_functions.R
vim tests/integration/test-04_advanced_modeling.R

# Test your new code
R
devtools::load_all()  # Load all functions (yours + team's)
source("scripts/04_advanced_modeling.R")  # Test your script
devtools::test()  # Run all tests
quit()
```

7. Exit Container & Validate Complete Integration

```
# Exit development container
exit
# Validate entire project works together
make docker-check-reny-fix
                                         # Ensure dependencies are tracked
make docker-test
                                          # Run all tests (team's + yours)
make docker-render
                                          # Ensure reports still render
# Test end-to-end workflow
make docker-zsh
# Run complete analysis pipeline
source("scripts/01_data_import.R") # Original work
source("scripts/dev2_analysis.R") # Dev 2's contra
                                         # Dev 2's contribution
source("scripts/dev3 visualization.R") # Dev 3's contribution
source("scripts/04 advanced modeling.R") # Your new integration
quit()
exit
8. Commit Your Integration Work
# Check what you've added
git status
git diff
# Commit your work
git add .
git commit -m "Add advanced modeling integration building on team contributions
- Integrate Dev 2's analysis patterns with advanced modeling
- Extend Dev 3's visualization framework for model results
- Add comprehensive integration tests for complete pipeline
- All team code compatibility maintained and tested"
# Push to feature branch
git push origin feature/dev1-integration
# OR push directly to main
# git push origin main
```

9. Create Pull Request for Team Review

```
# Create PR for team feedback
gh pr create --title "Add advanced modeling integration" \
    --body "## Summary
- Built advanced modeling on top of Dev 2's analysis framework
- Extended Dev 3's visualization tools for model interpretation
- Added comprehensive integration testing
## Integration Testing
- [x] All existing team code runs without modification
- [x] New code integrates seamlessly with team contributions
- [x] Complete analysis pipeline tested end-to-end
- [x] All dependencies validated
## Team Impact
```

- Enhances existing analysis without breaking changes
- Provides advanced modeling capabilities for future work
- Maintains all existing functionality"

10. Alternative: Quick Integration (Direct Push)

```
# For simple additions, skip PR process
git add .
git commit -m "Add modeling integration - builds on team's excellent foundation"
git push origin main
                                         # Triggers automatic team image rebuild
```

Key Benefits of This Workflow:

- [CHECKMARK] **Seamless integration**: Dev 1 builds on team work without conflicts
- [CHECKMARK] Automatic environment sync: GitHub Actions handled package updates
- [CHECKMARK] Code compatibility: Testing ensures nothing breaks
- [CHECKMARK] Team coordination: PR process enables feedback and discussion
- [CHECKMARK] Professional quality: Integration testing validates entire pipeline

What Happens Next:

1. GitHub Actions automatically:

- [CHECKMARK] Tests complete integration (all team code + Dev 1's additions)
- [CHECKMARK] Rebuilds team image if new packages added
- [CHECKMARK] Notifies team of updated environment

2. Team members sync:

```
git pull # Get Dev 1's integration work

docker pull rgt47/png1core-shell:latest # Get any env updates

make docker-zsh # Continue with enhanced codebase
```

This workflow ensures **Dev 1 can lead and integrate** while **building on the team's excellent contributions**! [ROCKET]