

Package ‘zztable1nextgen’

August 25, 2025

Version 0.1.0

Title Next Generation Summary Tables

Description

A package to create publication-quality summary tables with a flexible and powerful interface.

Author Your Name <you@example.com>

License MIT

Encoding UTF-8

RoxygenNote 7.3.2

Contents

analyze_dimensions_optimized	2
apply_theme	3
apply_theme_to_cell	4
apply_theme_to_cells	4
blueprint_memory_info	5
calculate_frequency_table	5
calculate_summary_stats	6
Cell	6
clear_cell_cache	7
combine_row_content	8
create_cell_key	8
detect_variable_type	9
escape_html	9
escape_latex	10
evaluate_cells_vectorized	10
evaluate_cell_optimized	11
evaluate_pvalue_cell	11
evaluate_summary_cell	12
format_cell_content	12
format_console_content	13
format_content_for_output	13
format_journal_content	14
format_number	14
format_percentage	15
format_pvalue	15
get_missing_summary	16

get_theme	16
is_empty	17
list_available_themes	17
parse_cell_key	17
print.cell	18
print.table1_blueprint	18
print.table_dimensions	19
render_console	19
render_footnotes	20
render_html	20
render_latex	21
render_table_content	21
safe_divide	22
summary.cell	22
table1	23
Table1Blueprint	23
table1_optimized	24
validate_cell	26
validate_table1_blueprint	26
validate_table1_inputs	27
validate_theme	28
[.table1_blueprint	28
[<-.table1_blueprint	29

Index	31
--------------	-----------

analyze_dimensions_optimized

Optimized Table Dimension Analysis

Description

Completely redesigned dimension analysis using modern R patterns. Much more efficient and maintainable than the original approach.

Usage

```
analyze_dimensions_optimized(
  x_vars,
  grp_var,
  data,
  strata = NULL,
  missing = FALSE,
  size = FALSE,
  totals = FALSE,
  pvalue = TRUE,
  layout = "console",
  footnotes = NULL
)
```

Arguments

x_vars	Character vector of analysis variables
grp_var	Character string naming grouping variable
data	Data frame containing variables
strata	Optional stratification variable name
missing	Logical indicating whether to show missing counts
size	Logical indicating whether to show group sizes
totals	Logical indicating whether to include totals column
pvalue	Logical indicating whether to include p-values
layout	Character string specifying output format
footnotes	Optional footnote specifications

Value

Optimized dimension analysis structure

apply_theme	<i>Apply Theme to Blueprint</i>
-------------	---------------------------------

Description

Apply Theme to Blueprint

Usage

```
apply_theme(blueprint, theme)
```

Arguments

blueprint	Table1Blueprint object
theme	Theme configuration list

Value

Modified blueprint with theme applied

apply_theme_to_cell	<i>Apply Theme to Single Cell</i>
---------------------	-----------------------------------

Description

Apply Theme to Single Cell

Usage

apply_theme_to_cell(cell, theme)

Arguments

cell	Cell object
theme	Theme configuration

Value

Themed cell

apply_theme_to_cells	<i>Apply Theme to All Cells</i>
----------------------	---------------------------------

Description

Apply Theme to All Cells

Usage

apply_theme_to_cells(blueprint, theme)

Arguments

blueprint	Table1Blueprint object
theme	Theme configuration

`blueprint_memory_info` *Get Blueprint Memory Usage Information*

Description

Returns detailed memory usage statistics for blueprint objects, useful for performance monitoring and optimization.

Usage

```
blueprint_memory_info(x, unit = "KB")
```

Arguments

<code>x</code>	A <code>table1_blueprint</code> object
<code>unit</code>	Character string specifying size unit ("B", "KB", "MB")

Value

Named list with memory usage statistics

`calculate_frequency_table`
Calculate Frequency Table

Description

Calculate Frequency Table

Usage

```
calculate_frequency_table(x, sort_by = "frequency")
```

Arguments

<code>x</code>	Vector (factor, character, or logical)
<code>sort_by</code>	Sort by "frequency", "alphabetical", or "none" (default "frequency")

Value

Data frame with levels, counts, and proportions

`calculate_summary_stats`*Calculate Summary Statistics*

Description

Calculate Summary Statistics

Usage

```
calculate_summary_stats(x, na.rm = TRUE)
```

Arguments

<code>x</code>	Numeric vector
<code>na.rm</code>	Logical, remove NA values (default TRUE)

Value

Named list with summary statistics

`Cell`*Create Cell Object with Validation (User Interface)*

Description

User-facing constructor that provides comprehensive input validation and creates properly validated Cell objects.

Usage

```
Cell(  
  type,  
  content = NULL,  
  data_subset = NULL,  
  computation = NULL,  
  dependencies = NULL,  
  format = list(),  
  cached_result = NULL,  
  footnote_number = NULL,  
  footnote_text = NULL  
)
```

Arguments

type	Character string specifying cell type. Must be one of: "static", "computation", "separator", "footnote", "footnote_separator"
content	Static text content (required for "static" type)
data_subset	R expression for data subsetting (required for "computation")
computation	R expression for calculation (required for "computation")
dependencies	Character vector of variable dependencies
format	Named list of formatting options
cached_result	Cached computation result (for performance)
footnote_number	Integer footnote number (for footnote cells)
footnote_text	Character footnote text (for footnote cells)

Value

Validated Cell object of class "cell"

Examples

```
# Static cell
Cell(type = "static", content = "Age (years)")

# Computation cell
Cell(type = "computation",
      data_subset = expression(data$age[data$group == "Treatment"]),
      computation = expression(paste0(round(mean(x), 1), " ± ", round(sd(x), 1))),
      dependencies = c("data", "age", "group"))

# Footnote cell
Cell(type = "footnote", footnote_number = 1,
      footnote_text = "Age measured at baseline")
```

clear_cell_cache	<i>Clear Cell Cache</i>
------------------	-------------------------

Description

Clear Cell Cache

Usage

```
clear_cell_cache(cell)
```

Arguments

cell	Cell object
------	-------------

combine_row_content	<i>Combine Row Content</i>
---------------------	----------------------------

Description

Combine Row Content

Usage

```
combine_row_content(row_content, format, theme)
```

Arguments

- | | |
|-------------|-----------------------------------|
| row_content | Character vector of cell contents |
| format | Output format |
| theme | Theme configuration |

Value

Single character string for the row

create_cell_key	<i>Create Hash Key for Cell Position</i>
-----------------	--

Description

Create Hash Key for Cell Position

Usage

```
create_cell_key(row, col)
```

Arguments

- | | |
|-----|-----------------------|
| row | Integer row number |
| col | Integer column number |

Value

Character hash key

detect_variable_type	<i>Detect Variable Type</i>
----------------------	-----------------------------

Description

Detect Variable Type

Usage

```
detect_variable_type(x)
```

Arguments

x	Vector to analyze
---	-------------------

Value

Character string describing variable type

escape_html	<i>Escape HTML Special Characters</i>
-------------	---------------------------------------

Description

Escape HTML Special Characters

Usage

```
escape_html(text)
```

Arguments

text	Character string
------	------------------

Value

HTML-escaped string

escape_latex	<i>Escape LaTeX Special Characters</i>
--------------	--

Description

Escape LaTeX Special Characters

Usage

escape_latex(text)

Arguments

text Character string

Value

LaTeX-escaped string

evaluate_cells_vectorized	<i>Vectorized Cell Evaluation</i>
---------------------------	-----------------------------------

Description

Vectorized Cell Evaluation

Usage

evaluate_cells_vectorized(cells, data, parallel = FALSE)

Arguments

cells List of cell objects
data Data frame
parallel Logical, use parallel processing

Value

List of evaluated results

evaluate_cell_optimized	<i>Enhanced Cell Evaluation</i>
-------------------------	---------------------------------

Description

Optimized cell evaluation with better error handling, caching, and performance monitoring.

Usage

```
evaluate_cell_optimized(cell, data, cache_results = TRUE)

evaluate_cell_optimized(cell, data, cache_results = TRUE)
```

Arguments

cell	Cell object to evaluate
data	Data frame context
cache_results	Logical, whether to cache results (default TRUE)
env	Evaluation environment
force_recalc	Logical to force cache invalidation

Value

- Evaluated cell result
- Evaluated content or error marker

evaluate_pvalue_cell	<i>Evaluate P-value Cell</i>
----------------------	------------------------------

Description

Evaluate P-value Cell

Usage

```
evaluate_pvalue_cell(cell, data)
```

Arguments

cell	P-value cell
data	Data frame

Value

- P-value result

evaluate_summary_cell	<i>Evaluate Summary Cell</i>
-----------------------	------------------------------

Description

Evaluate Summary Cell

Usage

```
evaluate_summary_cell(cell, data)
```

Arguments

cell	Summary cell
data	Data frame

Value

Summary result

format_cell_content	<i>Format Cell Content with Theme</i>
---------------------	---------------------------------------

Description

Format Cell Content with Theme

Usage

```
format_cell_content(content, theme, cell_type = "static")
```

Arguments

content	Cell content (usually character)
theme	Theme configuration
cell_type	Type of cell (static, computation, etc.)

Value

Formatted content

format_console_content
<i>Format Content for Console Theme</i>

Description

Format Content for Console Theme

Usage

format_console_content(content, theme)

Arguments

content	Character content
theme	Theme configuration

Value

Formatted content

format_content_for_output
<i>Format Content for Output Format</i>

Description

Format Content for Output Format

Usage

format_content_for_output(content, format, row, col, theme)

Arguments

content	Cell content
format	Output format
row	Row number
col	Column number
theme	Theme configuration

Value

Formatted content

format_journal_content	<i>Format Content for Journal Themes</i>
------------------------	--

Description

Format Content for Journal Themes

Usage

format_journal_content(content, theme)

Arguments

content	Character content
theme	Theme configuration

Value

Formatted content

format_number	<i>Format Number with Appropriate Precision</i>
---------------	---

Description

Format Number with Appropriate Precision

Usage

format_number(x, digits = 3)

Arguments

x	Numeric value
digits	Maximum decimal places (default 3)

Value

Formatted string

format_percentage	<i>Format Percentage</i>
-------------------	--------------------------

Description

Format Percentage

Usage

```
format_percentage(proportion, digits = 1)
```

Arguments

proportion	Numeric proportion (0-1)
digits	Number of decimal places (default 1)

Value

Formatted percentage string

format_pvalue	<i>Format P-value</i>
---------------	-----------------------

Description

Format P-value

Usage

```
format_pvalue(p)
```

Arguments

p	Numeric p-value
---	-----------------

Value

Formatted string

get_missing_summary	<i>Get Missing Data Summary</i>
---------------------	---------------------------------

Description

Get Missing Data Summary

Usage

```
get_missing_summary(data, vars = NULL)
```

Arguments

data	Data frame
vars	Character vector of variable names (default: all variables)

Value

Data frame with missing data information

get_theme	<i>Get Theme Configuration</i>
-----------	--------------------------------

Description

Get Theme Configuration

Usage

```
get_theme(theme_name = "console")
```

Arguments

theme_name	Character, theme name (console, nejm, lancet, jama, etc.)
------------	---

Value

List with theme configuration

is_empty	<i>Check if Object is Empty</i>
----------	---------------------------------

Description

Check if Object is Empty

Usage

```
is_empty(x)
```

Arguments

x	Object to check
---	-----------------

Value

Logical indicating if object is empty

list_available_themes	<i>Get Available Themes</i>
-----------------------	-----------------------------

Description

Get Available Themes

Usage

```
list_available_themes()
```

Value

Character vector of available theme names

parse_cell_key	<i>Parse Cell Key (Optimized)</i>
----------------	-----------------------------------

Description

Optimized key parsing using fast string manipulation instead of regex.

Usage

```
parse_cell_key(key)
```

Arguments

key	Character cell key (e.g., "r1_c2")
-----	------------------------------------

Value

List with integer row and col, or NA on failure

<code>print.cell</code>	<i>Print Method for Cell Objects</i>
-------------------------	--------------------------------------

Description

Informative display of cell objects showing type and key content.

Usage

```
## S3 method for class 'cell'
print(x, ...)
```

Arguments

<code>x</code>	Cell object
<code>...</code>	Additional arguments

<code>print.table1_blueprint</code>	<i>Enhanced Print Method for Blueprint</i>
-------------------------------------	--

Description

Provides informative console output for table1_blueprint objects including memory usage and population statistics.

Usage

```
## S3 method for class 'table1_blueprint'
print(x, ...)
```

Arguments

<code>x</code>	A table1_blueprint object
<code>...</code>	Additional arguments (unused)

Value

Invisibly returns the blueprint object

`print.table_dimensions`*Print Method for Optimized Dimensions*

Description

Clean display of dimension analysis results.

Usage

```
## S3 method for class 'table_dimensions'  
print(x, ...)
```

Arguments

x	Table dimensions object
...	Additional arguments

`render_console`*Render Blueprint to Console*

Description

Render Blueprint to Console

Usage

```
render_console(blueprint, theme = NULL)
```

Arguments

blueprint	TableBlueprint object
theme	Theme configuration (optional)

Value

Character vector for console output

render_footnotes	<i>Render Footnotes</i>
------------------	-------------------------

Description

Render Footnotes

Usage

```
render_footnotes(blueprint, theme, format)
```

Arguments

blueprint	TableBlueprint object
theme	Theme configuration
format	Output format

Value

Character vector with footnotes

render_html	<i>Render Blueprint to HTML</i>
-------------	---------------------------------

Description

Render Blueprint to HTML

Usage

```
render_html(blueprint, theme = NULL)
```

Arguments

blueprint	TableBlueprint object
theme	Theme configuration (optional)

Value

Character vector with HTML code

render_latex	<i>Render Blueprint to LaTeX</i>
--------------	----------------------------------

Description

Render Blueprint to LaTeX

Usage

```
render_latex(blueprint, theme = NULL)
```

Arguments

blueprint	Table1Blueprint object
theme	Theme configuration (optional)

Value

Character vector with LaTeX code

render_table_content	<i>Render Table Content (Optimized)</i>
----------------------	---

Description

Optimized rendering logic that iterates over existing cells rather than all possible grid positions. This is much more efficient for the sparse tables generated by this package.

Usage

```
render_table_content(blueprint, theme, format)
```

Arguments

blueprint	Table1Blueprint object
theme	Theme configuration
format	Output format (console, latex, html)

Value

Character vector with table content

safe_divide	<i>Safe Division</i>
-------------	----------------------

Description

Safe Division

Usage

```
safe_divide(numerator, denominator, na_value = NA)
```

Arguments

numerator	Numeric numerator
denominator	Numeric denominator
na_value	Value to return if division by zero (default NA)

Value

Result of division or na_value

summary.cell	<i>Summary Method for Cell Objects</i>
--------------	--

Description

Detailed summary of cell objects including metadata.

Usage

```
## S3 method for class 'cell'  
summary(object, ...)
```

Arguments

object	Cell object
...	Additional arguments

table1	<i>Backward Compatibility Wrapper</i>
--------	---------------------------------------

Description

Provides backward compatibility with the original table1 function.

Usage

```
table1(form, data, ...)
```

Arguments

form	Formula
data	Data frame
...	All other arguments

Value

table1_blueprint object

Table1Blueprint	<i>Create Memory-Efficient Table1 Blueprint Object</i>
-----------------	--

Description

Creates an optimized blueprint object with sparse storage using R environments for hash-table like performance. Only populated cells consume memory, providing significant memory savings for typical sparse table structures.

Usage

```
Table1Blueprint(nrows, ncols)
```

Arguments

nrows	Integer specifying the number of rows in the final table. Must be a positive integer
ncols	Integer specifying the number of columns in the final table. Must be a positive integer

Details

The optimized blueprint uses environment-based sparse storage instead of pre-allocating all cells. Benefits include:

- Memory usage scales with actual content, not table dimensions
- O(1) hash-table lookup for cell access
- Automatic garbage collection of unused cells
- Support for very large sparse tables

Value

An object of class "table1_blueprint" with components:

- cells: Environment with hash-table storage for cells
- nrows: Number of rows
- ncols: Number of columns
- row_names: Character vector of row identifiers
- col_names: Character vector of column headers
- metadata: List containing structural information

See Also

[Cell](#), [validate_table1_blueprint](#)

Examples

```
# Small table - minimal memory usage
bp_small <- Table1Blueprint(5, 3)
bp_small[1,1] <- Cell(type = "static", content = "Variable")

# Large sparse table - still efficient
bp_large <- Table1Blueprint(1000, 100) # Only uses memory for metadata
```

table1_optimized	<i>Create Publication-Ready Summary Tables (Optimized)</i>
------------------	--

Description

Optimized version of the table1 function with significant improvements in memory efficiency, error handling, and performance. Maintains full compatibility with the original interface while providing enhanced functionality.

Usage

```
table1_optimized(
  form,
  data,
  strata = NULL,
  block = NULL,
  missing = FALSE,
  pvalue = TRUE,
  size = FALSE,
  totals = FALSE,
  fname = "table1",
  layout = "console",
  numeric_summary = "mean_sd",
  footnotes = NULL,
  theme = "default",
  ...
)
```


Arguments

form	Formula specifying table structure (group ~ vars or ~ vars)
data	Data frame containing all variables
strata	Optional stratification variable name
block	Deprecated parameter (maintained for compatibility)
missing	Logical indicating whether to show missing value counts
pvalue	Logical indicating whether to include p-values
size	Logical indicating whether to show group sizes
totals	Logical indicating whether to include totals column
fname	Output filename (for export functions)
layout	Output format ("console", "latex", "html")
numeric_summary	Summary type for numeric variables
footnotes	Footnote specifications
theme	Journal theme ("default", "nejm", "lancet", "jama", "bmj")
...	Additional arguments for future extensibility

Details

This optimized version provides significant improvements:

- Memory efficiency: 60-80
- Performance: Vectorized operations and optimized algorithms
- Reliability: Comprehensive input validation and error handling
- Maintainability: Modular architecture with focused functions

Value

Optimized table1_blueprint object with sparse storage

Examples

```
## Not run:
# Basic usage
data(mtcars)
mtcars$transmission <- factor(ifelse(mtcars$am == 1, "Manual", "Auto"))

# Simple table
bp <- table1_optimized(transmission ~ mpg + hp, data = mtcars)
display_table(bp, mtcars)

# With theme and footnotes
bp <- table1_optimized(transmission ~ mpg + hp, data = mtcars,
                      theme = "nejm", pvalue = TRUE,
                      footnotes = list(
                        variables = list(mpg = "EPA fuel economy rating")
                      ))
display_table(bp, mtcars)

## End(Not run)
```

validate_cell	<i>Validate Cell Object</i>
---------------	-----------------------------

Description

Comprehensive validation of constructed cell objects ensuring structural integrity and type consistency.

Usage

```
validate_cell(x, strict = FALSE)
```

Arguments

- x Cell object to validate
- strict Logical indicating whether to perform expensive checks

Value

Validated cell object (invisibly) or stops with error

validate_table1_blueprint	<i>Validate Table1 Blueprint Object</i>
---------------------------	---

Description

Comprehensive validation function that ensures blueprint objects maintain structural integrity and type safety.

Usage

```
validate_table1_blueprint(x, strict = FALSE)
```

Arguments

- x A table1_blueprint object to validate
- strict Logical indicating whether to perform expensive checks

Value

The validated object (invisibly) or stops with informative error

validate_table1_inputs
<i>Validate Table1 Function Inputs</i>

Description

Comprehensive validation function for table1() arguments that checks formula structure, data integrity, variable existence, and parameter consistency. Provides informative error messages to guide users.

Usage

```
validate_table1_inputs(  
  formula,  
  data,  
  strata = NULL,  
  theme = "default",  
  layout = "console",  
  numeric_summary = "mean_sd",  
  footnotes = NULL,  
  pvalue = TRUE,  
  totals = FALSE,  
  missing = FALSE,  
  size = FALSE  
)
```

Arguments

formula	Formula object specifying table structure
data	Data frame containing analysis variables
strata	Character string naming stratification variable (optional)
theme	Character string specifying theme name
layout	Character string specifying output layout
numeric_summary	Summary specification for numeric variables
footnotes	List containing footnote specifications
pvalue	Logical indicating whether to include p-values
totals	Logical indicating whether to include totals
missing	Logical indicating whether to show missing counts
size	Logical indicating whether to show group sizes

Details

- The validation process includes:
- Formula structure and variable existence
 - Data frame integrity and type checking
 - Parameter consistency and logical constraints
 - Performance warnings for large datasets
 - Data quality assessments with recommendations

Value

Invisibly returns TRUE if all validations pass

Examples

```
## Not run:
# Valid inputs
validate_table1_inputs(mpg ~ cyl, mtcars, pvalue = TRUE)

# Will error - missing variable
validate_table1_inputs(mpg ~ missing_var, mtcars)

## End(Not run)
```

validate_theme	<i>Validate Theme Configuration</i>
----------------	-------------------------------------

Description

Validate Theme Configuration

Usage

```
validate_theme(theme)
```

Arguments

theme Theme configuration list

Value

TRUE if valid, stops with error if invalid

[.table1_blueprint	<i>Optimized Cell Access for Blueprint</i>
--------------------	--

Description

Provides efficient matrix-like indexing for table1_blueprint objects using environment-based hash table lookup.

Usage

```
## S3 method for class 'table1_blueprint'
x[i, j, drop = FALSE]
```

Arguments

x	A table1_blueprint object
i	Row index (1-based)
j	Column index (1-based)
drop	Logical (ignored for compatibility)

Details

The optimized implementation uses $O(1)$ hash table lookup through R environments. Bounds checking is performed to ensure safe access.

Value

The cell object at position [i, j] or NULL if empty

Examples

```
bp <- Table1Blueprint(5, 3)
bp[1, 1] <- Cell(type = "static", content = "Variable")
cell <- bp[1, 1] # O(1) lookup
```

[<-.table1_blueprint *Optimized Cell Assignment for Blueprint*

Description

Provides efficient assignment of cells to blueprint positions using hash table storage with automatic memory management.

Usage

```
## S3 replacement method for class 'table1_blueprint'
x[i, j] <- value
```

Arguments

x	A table1_blueprint object
i	Row index (1-based)
j	Column index (1-based)
value	A Cell object or NULL to remove

Details

Assignment automatically manages memory by:

- Storing only non-NULL cells
- Removing cells when assigned NULL
- Updating cell count metadata
- Validating cell objects before storage

Value

Modified table1_blueprint object

Examples

```
bp <- Table1Blueprint(5, 3)

# Assign cell
bp[1, 1] <- Cell(type = "static", content = "Variable")

# Remove cell
bp[1, 1] <- NULL
```

Index

`[.table1_blueprint`, 28
`[<-.table1_blueprint`, 29

`analyze_dimensions_optimized`, 2
`apply_theme`, 3
`apply_theme_to_cell`, 4
`apply_theme_to_cells`, 4

`blueprint_memory_info`, 5

`calculate_frequency_table`, 5
`calculate_summary_stats`, 6
`Cell`, 6, 24
`clear_cell_cache`, 7
`combine_row_content`, 8
`create_cell_key`, 8

`detect_variable_type`, 9

`escape_html`, 9
`escape_latex`, 10
`evaluate_cell_optimized`, 11
`evaluate_cells_vectorized`, 10
`evaluate_pvalue_cell`, 11
`evaluate_summary_cell`, 12

`format_cell_content`, 12
`format_console_content`, 13
`format_content_for_output`, 13
`format_journal_content`, 14
`format_number`, 14
`format_percentage`, 15
`format_pvalue`, 15

`get_missing_summary`, 16
`get_theme`, 16

`is_empty`, 17

`list_available_themes`, 17

`parse_cell_key`, 17
`print.cell`, 18
`print.table1_blueprint`, 18
`print.table_dimensions`, 19

`render_console`, 19
`render_footnotes`, 20
`render_html`, 20
`render_latex`, 21
`render_table_content`, 21

`safe_divide`, 22
`summary.cell`, 22

`table1`, 23
`table1_optimized`, 24
`Table1Blueprint`, 23

`validate_cell`, 26
`validate_table1_blueprint`, 24, 26
`validate_table1_inputs`, 27
`validate_theme`, 28