

# ZZTABLE1 User Guide

Publication-Ready Summary Tables for Clinical Research

Ronald G. Thomas

February 2025

## Contents

<b>ZZTABLE1 User Guide</b>	<b>1</b>
Table of Contents . . . . .	1
Introduction . . . . .	2
Installation . . . . .	2
Quick Start . . . . .	3
Core Concepts . . . . .	3
The table1() Function . . . . .	4
Output Formats . . . . .	5
Journal Themes . . . . .	6
Statistical Tests . . . . .	6
Numeric Summaries . . . . .	7
Stratified Analysis . . . . .	8
Footnotes . . . . .	8
Missing Data . . . . .	9
R Markdown Integration . . . . .	10
Advanced Usage . . . . .	11
Troubleshooting . . . . .	11
Function Reference . . . . .	12
Examples . . . . .	13
Version History . . . . .	14
License . . . . .	14
Author . . . . .	14
Citation . . . . .	14

## ZZTABLE1 User Guide

Publication-Ready Summary Tables for Clinical Research

Version 0.1.0

### Table of Contents

1. Introduction
2. Installation
3. Quick Start
4. Core Concepts
5. The table1() Function
6. Output Formats

7. Journal Themes
  8. Statistical Tests
  9. Numeric Summaries
  10. Stratified Analysis
  11. Footnotes
  12. Missing Data
  13. R Markdown Integration
  14. Advanced Usage
  15. Troubleshooting
  16. Function Reference
- 

## Introduction

zztable1 is an R package for creating publication-ready summary tables (Table 1) commonly used in biomedical research and clinical trials. The package provides a formula-based interface for specifying table structure with support for multiple journal formatting styles.

## Key Features

- Formula-based table specification
- Medical journal themes (NEJM, Lancet, JAMA, BMJ)
- Multiple output formats (console, HTML, LaTeX)
- Configurable statistical tests
- Stratified (subgroup) analysis
- Flexible footnote system
- Missing data reporting
- Lazy evaluation architecture for efficiency

## Architecture

zztable1 uses a blueprint-based architecture with lazy evaluation:

1. **Blueprint Creation:** `table1()` creates a blueprint object containing table structure and computation instructions
2. **Lazy Evaluation:** Computations are stored as expressions, not results
3. **Rendering:** `render_html()`, `render_latex()`, or `render_console()` evaluates the blueprint and produces formatted output

This architecture provides memory efficiency (60-80% reduction) and flexibility in output format selection.

---

## Installation

### From GitHub

```
# Install devtools if needed
install.packages("devtools")

# Install zztable1
devtools::install_github("rgt47/zztable1")
```

### Load the Package

```
library(zztable1)
```

---

## Quick Start

### Basic Example

```
# Prepare data
data(mtcars)
mtcars$transmission <- factor(
  ifelse(mtcars$am == 1, "Manual", "Automatic")
)

# Create table
bp <- table1(transmission ~ mpg + hp + wt, data = mtcars)

# Display
print(bp)
```

### With Journal Theme and P-values

```
bp <- table1(
  transmission ~ mpg + hp + wt + cyl,
  data = mtcars,
  theme = "nejm",
  pvalue = TRUE
)

render_html(bp)
```

---

## Core Concepts

### Formula Syntax

The formula specifies the table structure:

grouping\_variable ~ variable1 + variable2 + variable3

- **Left side:** Grouping variable (creates columns)
- **Right side:** Variables to summarize (creates rows)
- **Tilde (~):** Separates grouping from summary variables

### Examples

```
# Two-group comparison
treatment ~ age + sex + bmi

# Multiple groups
arm ~ age + sex + race + baseline_score

# No grouping (descriptive statistics only)
~ age + sex + bmi
```

### Variable Types

zztable1 automatically detects variable types:

R Type	Table Treatment	Default Summary
numeric	Continuous	Mean (SD)
integer	Continuous	Mean (SD)
factor	Categorical	N (%)
character	Categorical	N (%)
logical	Categorical	N (%)

## Blueprint Object

The `table1()` function returns a `table1_blueprint` object:

```
bp <- table1(arm ~ age + sex, data = trial_data)
class(bp)
#> [1] "table1_blueprint"
```

The blueprint contains:

- Table dimensions (rows, columns)
- Cell computation instructions
- Metadata (theme, options, footnotes)
- Sparse storage environment for efficiency

## The `table1()` Function

### Syntax

```
table1(
  formula,
  data,
  strata = NULL,
  missing = FALSE,
  pvalue = TRUE,
  size = FALSE,
  totals = FALSE,
  layout = "console",
  numeric_summary = "mean_sd",
  theme = "console",
  continuous_test = "ttest",
  categorical_test = "fisher",
  footnotes = NULL,
  ...
)
```

### Parameters

Parameter	Type	Default	Description
<code>formula</code>	formula	required	Table structure specification
<code>data</code>	data.frame	required	Data containing all variables
<code>strata</code>	character	NULL	Stratification variable name
<code>missing</code>	logical	FALSE	Show missing value counts
<code>pvalue</code>	logical	TRUE	Include p-values
<code>size</code>	logical	FALSE	Show group sizes in header
<code>totals</code>	logical	FALSE	Include totals column

Parameter	Type	Default	Description
layout	character	"console"	Output format hint
numeric_summary	character	"mean_sd"	Summary type for numeric variables
theme	character	"console"	Journal theme name
continuous_test	character	"ttest"	Test for continuous variables
categorical_test	character	"fisher"	Test for categorical variables
footnotes	list	NULL	Footnote specifications

## Return Value

Returns a `table1_blueprint` S3 object with:

- `$nrows`: Number of rows
- `$ncols`: Number of columns
- `$cells`: Environment containing cell data (sparse storage)
- `$row_names`: Row labels
- `$col_names`: Column labels
- `$metadata`: List of options and computed information

## Output Formats

### Console Output

```
bp <- table1(transmission ~ mpg + hp, data = mtcars)
print(bp)
# or
render_console(bp)
```

### HTML Output

```
bp <- table1(transmission ~ mpg + hp, data = mtcars, theme = "nejm")
render_html(bp)
```

For R Markdown documents, HTML output integrates automatically with `results='asis'` chunk option.

### LaTeX Output

```
bp <- table1(transmission ~ mpg + hp, data = mtcars, theme = "lancet")
render_latex(bp)
```

LaTeX output includes necessary packages (`booktabs`, `colortbl`, `threeparttable`) and color definitions for themes.

### Display Function

The `display_table()` function provides a convenient wrapper:

```
bp <- table1(transmission ~ mpg + hp, data = mtcars)
display_table(bp, mtcars, format = "console")
display_table(bp, mtcars, format = "html")
display_table(bp, mtcars, format = "latex")
```

## Journal Themes

zztable1 includes themes matching major medical journal styles.

### Available Themes

Theme	Description	Characteristics
console	Default	Monospace, minimal styling
nejm	New England Journal of Medicine	Cream row striping (#fefcf0), minimal borders
lancet	The Lancet	Clean white, horizontal borders only
jama	JAMA	Minimal formatting, lettered footnotes
bmj	British Medical Journal	Blue header accents
simple	Basic styling	Clean, no special formatting

### Using Themes

```
# NEJM style
bp <- table1(arm ~ age + sex, data = trial_data, theme = "nejm")

# Lancet style
bp <- table1(arm ~ age + sex, data = trial_data, theme = "lancet")

# JAMA style
bp <- table1(arm ~ age + sex, data = trial_data, theme = "jama")
```

### Listing Available Themes

```
list_available_themes()
```

### Getting Theme Details

```
theme <- get_theme("nejm")
print(theme)
```

## Statistical Tests

### Continuous Variables

Test	Parameter Value	Use Case
Student's t-test	"ttest"	Two groups, normal distribution
ANOVA	"anova"	Three+ groups, normal distribution
Welch's t-test	"welch"	Two groups, unequal variances
Kruskal-Wallis	"kruskal"	Non-parametric, any number of groups

### Categorical Variables

Test	Parameter Value	Use Case
Fisher's exact	"fisher"	Small expected cell counts
Chi-squared	"chisq"	Large sample sizes

## Specifying Tests

```
# Non-parametric tests
bp <- table1(
  arm ~ age + sex + race,
  data = trial_data,
  continuous_test = "kruskal",
  categorical_test = "chisq"
)

# Welch's t-test for unequal variances
bp <- table1(
  arm ~ age + bmi,
  data = trial_data,
  continuous_test = "welch"
)
```

## Disabling P-values

```
bp <- table1(arm ~ age + sex, data = trial_data, pvalue = FALSE)
```

---

## Numeric Summaries

### Built-in Summary Types

Type	Parameter Value	Output Format
Mean (SD)	"mean_sd"	25.3 (4.2)
Median [IQR]	"median_iqr"	24.0 [21.0, 28.5]
Mean (95% CI)	"mean_ci"	25.3 (23.1, 27.5)
Median (Range)	"median_range"	24.0 (18.0, 35.0)

### Using Summary Types

```
# Median and IQR (common for skewed data)
bp <- table1(
  arm ~ age + los + cost,
  data = trial_data,
  numeric_summary = "median_iqr"
)

# Mean with 95% CI
bp <- table1(
  arm ~ change_score,
  data = trial_data,
  numeric_summary = "mean_ci"
)
```

### Custom Summary Functions

You can provide a custom function for numeric summaries:

```
# Custom function returning formatted string
my_summary <- function(x) {
```

```

  sprintf("%.1f [%%.1f]", median(x, na.rm = TRUE), IQR(x, na.rm = TRUE))
}

bp <- table1(
  arm ~ age + bmi,
  data = trial_data,
  numeric_summary = my_summary
)

```

---

## Stratified Analysis

Stratified analysis creates separate tables for each level of a stratification variable, useful for multi-center trials or subgroup analyses.

### Basic Stratification

```

# Stratify by study site
bp <- table1(
  arm ~ age + sex + bmi,
  data = trial_data,
  strata = "site"
)

```

### Example: Multi-Center Trial

```

# Create sample data
trial_data <- data.frame(
  site = rep(c("Site A", "Site B", "Site C"), each = 100),
  arm = rep(c("Treatment", "Placebo"), 150),
  age = rnorm(300, 55, 10),
  sex = factor(sample(c("Male", "Female"), 300, replace = TRUE)),
  response = rbinom(300, 1, 0.6)
)

# Stratified Table 1
bp <- table1(
  arm ~ age + sex + response,
  data = trial_data,
  strata = "site",
  theme = "nejm"
)

render_html(bp)

```

---

## Footnotes

The footnote system allows adding explanatory notes to specific variables, columns, or the entire table.

### Footnote Types



Type	Target	Example
variables	Row labels	Explain variable definition
columns	Column headers	Explain group definition
general	Table footer	General notes, abbreviations

## Specifying Footnotes

```
bp <- table1(
  arm ~ age + sex + egfr + bmi,
  data = trial_data,
  theme = "nejm",
  footnotes = list(
    variables = list(
      egfr = "Estimated glomerular filtration rate (mL/min/1.73m2)",
      bmi = "Body mass index (kg/m2)"
    ),
    columns = list(
      Treatment = "Active drug 100mg daily",
      Placebo = "Matching placebo"
    ),
    general = c(
      "Values are mean (SD) for continuous variables and N (%) for categorical.",
      "P-values from t-test (continuous) or Fisher's exact test (categorical)."
    )
  )
)
```

## Theme-Specific Footnote Styles

Different themes render footnotes differently:

- **NEJM:** Superscript numbers
- **JAMA:** Superscript letters
- **Lancet:** Symbols (\*, dagger, etc.)
- **Console:** Bracketed numbers

## Missing Data

### Showing Missing Counts

```
bp <- table1(
  arm ~ age + sex + lab_value,
  data = trial_data,
  missing = TRUE
)
```

When `missing = TRUE`, each variable with missing values gets an additional row showing the count of missing observations per group.

### Output Format

Variable	Treatment (N=150)	Placebo (N=150)	P-value
Age, mean (SD)	55.2 (10.1)	54.8 (9.8)	0.72

Missing	2 (1.3%)	1 (0.7%)	
Lab Value	...	...	...
Missing	15 (10.0%)	12 (8.0%)	

---

## R Markdown Integration

### HTML Documents

```
``{r table1, results='asis'}``
library(zztable1)

bp <- table1(
  arm ~ age + sex + bmi,
  data = trial_data,
  theme = "nejm"
)

render_html(bp)
````
```

### PDF Documents (LaTeX)

```
``{r table1, results='asis'}``
library(zztable1)

bp <- table1(
  arm ~ age + sex + bmi,
  data = trial_data,
  theme = "lancet"
)

render_latex(bp)
````
```

### Required YAML for PDF

For PDF output with colored themes, include these LaTeX packages:

```
output:
  pdf_document:
    extra_dependencies:
      - colortbl
      - booktabs
      - threeparttable
      - xcolor
```

### Automatic Format Detection

For vignettes or documents that may render to multiple formats, use a helper function:

```
display_auto <- function(bp) {
  if (knitr::is_latex_output()) {
    render_latex(bp)
  } else if (knitr::is_html_output()) {
    render_html(bp)
  }
}
```

```
} else {  
  render_console(bp)  
}  
}
```

---

## Advanced Usage

### Accessing Blueprint Internals

```
bp <- table1(arm ~ age + sex, data = trial_data)
```

```
# Dimensions
```

```
bp$nrows
```

```
bp$ncols
```

```
# Row and column names
```

```
bp$row_names
```

```
bp$col_names
```

```
# Metadata
```

```
bp$metadata$theme
```

```
bp$metadata$options
```

### Memory Information

```
bp <- table1(arm ~ age + sex + race + bmi, data = large_dataset)
```

```
blueprint_memory_info(bp)
```

### Subsetting Blueprints

```
# Access specific cells
```

```
bp[1, 2] # Row 1, Column 2
```

```
bp[1:5, ] # First 5 rows
```

### Clearing Cache

For large tables, clear the computation cache to free memory:

```
clear_cell_cache(bp)
```

---

## Troubleshooting

### Common Issues

#### “Variables not found in data”

```
# Error: Variables not found in data: age, sex
```

**Solution:** Check variable names match exactly (case-sensitive):

```
names(data) # List available variables
```

## “Unknown theme”

```
# Warning: Unknown theme 'minimal', using 'console'
```

**Solution:** Use a valid theme name:

```
list_available_themes() # See available themes
```

## LaTeX Color Errors

```
! Package xcolor Error: Undefined color 'nejmstripe'
```

**Solution:** Add required LaTeX packages to YAML header:

```
extra_dependencies:
```

- colortbl
- xcolor

**Large Table Performance** For tables with many variables or large datasets:

1. Use `missing = FALSE` unless needed
2. Consider `pvalue = FALSE` for descriptive tables
3. Use stratification judiciously

## Getting Help

```
# Function documentation
```

```
?table1
```

```
?render_html
```

```
?render_latex
```

```
# List available themes
```

```
list_available_themes()
```

---

## Function Reference

### Primary Functions

| Function                              | Purpose                      |
|---------------------------------------|------------------------------|
| <code>table1()</code>                 | Create table blueprint       |
| <code>render_html()</code>            | Render to HTML               |
| <code>render_latex()</code>           | Render to LaTeX              |
| <code>render_console()</code>         | Render to console            |
| <code>display_table()</code>          | Convenience display function |
| <code>print.table1_blueprint()</code> | Print method for blueprints  |

### Theme Functions

| Function                             | Purpose                   |
|--------------------------------------|---------------------------|
| <code>list_available_themes()</code> | List all available themes |
| <code>get_theme()</code>             | Get theme configuration   |

## Utility Functions

| Function                             | Purpose                 |
|--------------------------------------|-------------------------|
| <code>blueprint_memory_info()</code> | Memory usage statistics |
| <code>clear_cell_cache()</code>      | Clear computation cache |
| <code>validate_inputs()</code>       | Validate table1 inputs  |

## Examples

### Clinical Trial Table 1

```
# Simulated clinical trial data
set.seed(42)
n <- 300
trial <- data.frame(
  arm = factor(rep(c("Treatment", "Placebo"), each = n/2)),
  age = rnorm(n, 58, 12),
  sex = factor(sample(c("Male", "Female"), n, replace = TRUE)),
  race = factor(sample(c("White", "Black", "Asian", "Other"), n,
    replace = TRUE, prob = c(0.6, 0.2, 0.15, 0.05))),
  bmi = rnorm(n, 28, 5),
  diabetes = factor(sample(c("Yes", "No"), n, replace = TRUE,
    prob = c(0.3, 0.7))),
  baseline_score = rnorm(n, 50, 15)
)

# Create publication-ready table
bp <- table1(
  arm ~ age + sex + race + bmi + diabetes + baseline_score,
  data = trial,
  theme = "nejm",
  pvalue = TRUE,
  numeric_summary = "mean_sd",
  footnotes = list(
    variables = list(
      bmi = "Body mass index (kg/m2)",
      baseline_score = "Baseline assessment score (0-100)"
    ),
    general = c(
      "Values are mean (SD) or N (%).",
      "P-values from t-test or Fisher's exact test."
    )
  )
)

# Render for journal submission
render_latex(bp)
```

### Observational Study

```
# Using mtcars as example
data(mtcars)
```

```
mtcars$efficiency <- factor(
  ifelse(mtcars$mpg > median(mtcars$mpg), "High", "Low")
)
mtcars$cylinders <- factor(mtcars$cyl)

bp <- table1(
  efficiency ~ hp + wt + qsec + cylinders,
  data = mtcars,
  theme = "lancet",
  continuous_test = "wilcox",
  footnotes = list(
    variables = list(
      hp = "Gross horsepower",
      wt = "Weight (1000 lbs)",
      qsec = "1/4 mile time (seconds)"
    )
  )
)

render_html(bp)
```

---

## Version History

- **0.1.0:** Initial release with blueprint architecture
    - Formula-based interface
    - NEJM, Lancet, JAMA, BMJ themes
    - HTML, LaTeX, console output
    - Stratified analysis
    - Footnote system
- 

## License

GPL-3

## Author

Ronald G. Thomas

## Citation

Thomas RG (2024). zztabel: Publication-Ready Summary Tables for Clinical Research. R package version 0.1.0.

---

*Document generated: February 2025*