

Key Mappings

<localleader> r	Create terminal
<localleader> w	Vertical split
<localleader> W	Horizontal split
<localleader> q	Quit session
<localleader> c	Interrupt

Code

CR	Smart submit
<localleader> sf	Force function
<localleader> sl	Force line
<localleader> sa	Smart auto

R Markdown

<localleader> j	Next chunk
<localleader> k	Previous chunk
<localleader> l	Execute chunk
<localleader> t	All previous

Inspect

<localleader> h	head()
<localleader> u	tail()
<localleader> s	str()
<localleader> d	dim()
<localleader> p	print()
<localleader> n	names()
<localleader> f	length()
<localleader> g	glimpse()
<localleader> b	dt()
<localleader> y	help()

Workspace

<localleader> ’	Overview
<localleader> i	Inspect obj
<localleader> o	Insert pipe

Ex Commands

Core	
:ROpenTerminal	Create term
:RSendLine	Send line
:RSendSelection	Send select
:RSendFunction	Send func
:RSendSmart	Smart
:RSend {code}	Execute

Chunks

:RNextChunk	Next
:RPrevChunk	Previous
:RSendChunk	Execute
:RSendPreviousChunks	All prev

Analysis

:RHead [obj]	head()
:RTail [obj]	tail()
:RStr [obj]	str()
:RDim [obj]	dim()
:RPrint [obj]	print()
:RNames [obj]	names()
:RLength [obj]	length()
:RGlimpse [obj]	glimpse()
:RSummary [obj]	summary()
:RHelp [topic]	help()

Session

:RQuit	Quit R
:RInterrupt	Interrupt
:RGetwd	Show dir
:RSetwd [dir]	Set dir
:RLs	List objs
:RRm	Clear

Packages

:RLibrary {pkg}	Load pkg
:RInstall {pkg}	Install
:RSource {file}	Source
:RInstallDplyr	dplyr

Data/Terminal

:RLoad {file}	Load RDS
:RSave {obj} {file}	Save RDS
:RShowTerminal	Show term
:RListTerminals	List terms
:RSwitchToTerminal	Jump term
:ROpenSplit [type]	Split term
:RWorkspace	Overview
:RInspect [obj]	Inspect

Config Variables

g:zzvim_r_disable_mappings	0
g:zzvim_r_terminal_width	100
g:zzvim_r_terminal_height	15
g:zzvim_r_command	R
g:zzvim_r_chunk_start	````{
g:zzvim_r_chunk_end	````

Smart Detection

- **Functions:** function() complete
- **Control:** if/for/while block
- **Multi-line:** () [] balanced
- **Pipes:** %>% |> chain
- **Lines:** assignments current
- **Debug:** inside functions single

Tips

- LocalLeader = space key (shown as <localleader>), Leader = ,
- Each buffer = isolated R session
- Uses .zzvim_r_temp.R for clean output
- Visual mode: CR sends selection
- Object inspection: cursor word or argument
- Terminal per file for workflow isolation