



1. What is Observer Pattern?

It defines a **one-to-many dependency** between objects so that when **one object changes state**, **all its dependents** are notified **automatically**.



Real-Life Analogy

Scenario: YouTube Notifications

- You **subscribe** to a YouTube channel (Observer).
 - When the channel **uploads a new video** (Subject state changes), all subscribers are **notified**.
 - You can **unsubscribe** anytime.
-



Structure

```
Subject (Publisher)
├─ attach(Observer)
├─ detach(Observer)
└─ notifyObservers()
```

```
Observer (Subscriber)
└─ update()
```



2. JDK Built-in Support: `java.util.Observable` and `Observer` (❌ Deprecated in Java 9)

Example:

```
class NewsAgency extends Observable {
    void setNews(String news) {
        setChanged();           // must call this before notify
        notifyObservers(news);
    }
}

class NewsChannel implements Observer {
    public void update(Observable o, Object arg) {
        System.out.println("News update: " + arg);
    }
}

NewsAgency agency = new NewsAgency();
NewsChannel channel = new NewsChannel();

agency.addObserver(channel);
agency.setNews("Election Results Declared!");
```

❌ Problems with JDK Observable/Observer:

Problem	Explanation
❌ Inheritance-based	Observable is a class , so it forces single inheritance.
❌ setChanged()	You must manually call setChanged() or it won't notify. Easy to forget.
❌ Obsolete design	Lacks flexibility, extensibility; was deprecated in Java 9.



3. Custom Observer Pattern in Java (Best Practice)

Step-by-step:



Subject (Observable)

```
interface Subject {  
    void addObserver(Observer o);  
    void removeObserver(Observer o);  
    void notifyObservers(String message);  
}
```



Observer (Subscriber)

```
interface Observer {  
    void update(String message);  
}
```



Concrete Subject

```
class NewsAgency implements Subject {  
    private List<Observer> observers = new ArrayList<>();  
  
    public void addObserver(Observer o) {  
        observers.add(o);  
    }  
  
    public void removeObserver(Observer o) {  
        observers.remove(o);  
    }  
  
    public void notifyObservers(String message) {  
        for (Observer o : observers) {  
            o.update(message);  
        }  
    }  
  
    public void setNews(String news) {  
        System.out.println("Agency: " + news);  
        notifyObservers(news);  
    }  
}
```



Concrete Observers

```
class EmailSubscriber implements Observer {  
    public void update(String message) {  
        System.out.println("Email received: " + message);  
    }  
}  
  
class SMSSubscriber implements Observer {  
    public void update(String message) {
```

```

        System.out.println("SMS received: " + message);
    }
}

```

Demo

```

java
CopyEdit
NewsAgency agency = new NewsAgency();
Observer email = new EmailSubscriber();
Observer sms = new SMSSubscriber();

agency.addObserver(email);
agency.addObserver(sms);

agency.setNews("Java 21 Released!");

```

4. Observer Pattern in Frameworks

Spring Events (Observer Pattern under the hood)

```

// 1. Define Event
public class OrderPlacedEvent extends ApplicationEvent {
    public OrderPlacedEvent(Object source) {
        super(source);
    }
}

// 2. Publisher
@Component
public class OrderService {
    @Autowired
    ApplicationEventPublisher publisher;

    public void placeOrder() {
        // business logic...
        publisher.publishEvent(new OrderPlacedEvent(this));
    }
}

// 3. Observer
@Component
public class OrderEmailListener {
    @EventListener
    public void onOrderPlaced(OrderPlacedEvent event) {
        System.out.println("Sending email confirmation...");
    }
}

```

Spring manages this using **Observer pattern internally**.

5. RxJS / RxJava – Push-based Observer

```

// RxJS example
const observable = Rx.Observable.of("Video1", "Video2");

```

```
observable.subscribe(video => console.log("Got notification:", video));
```

Reactive Programming is an advanced evolution of Observer Pattern where:

- Data is **pushed** to observers asynchronously.
- Observers can transform/filter/merge streams.

RxJS / RxJava uses **Observer + Observable + Scheduler + Subscription** for complete control.



Summary Table

Topic	Traditional Observer	RxJS / RxJava
Push model	Yes	Yes
Async	No	Yes
Stream-based	No	Yes
Built-in in JDK?	Deprecated	External libs
Spring Event model	Yes	Internally Observer



Use Cases

Use Case	Description
UI updates	e.g., text boxes auto-updating
Messaging systems	RabbitMQ, Kafka consumers
Notification services	Emails/SMS on triggers
Event-driven microservices	With Spring Events, Kafka
Reactive streams	RxJava, Project Reactor

Spring Boot app using the **Observer pattern via Spring's event system**, which is a production-grade implementation of the Observer pattern.



Scenario: E-Commerce – Order Placement Notification System

When an order is placed:

- Email notification is sent
- SMS notification is sent
- Admin dashboard is updated

All these are observers reacting to the same event.

Project Structure

```
com.example.observerdemo
├── ObserverDemoApplication.java
├── event
│   └── OrderPlacedEvent.java
├── publisher
│   └── OrderService.java
└── listener
    ├── EmailNotificationListener.java
    ├── SMSNotificationListener.java
    └── DashboardUpdateListener.java
```

Step-by-Step Code

1 OrderPlacedEvent.java

```
package com.example.observerdemo.event;

import org.springframework.context.ApplicationEvent;

public class OrderPlacedEvent extends ApplicationEvent {
    private final String orderId;

    public OrderPlacedEvent(Object source, String orderId) {
        super(source);
        this.orderId = orderId;
    }

    public String getOrderId() {
        return orderId;
    }
}
```

2 OrderService.java (Publisher)

```
package com.example.observerdemo.publisher;

import com.example.observerdemo.event.OrderPlacedEvent;
import org.springframework.beans.factory.annotation.Autowired;
import org.springframework.context.ApplicationEventPublisher;
import org.springframework.stereotype.Service;

@Service
public class OrderService {

    @Autowired
    private ApplicationEventPublisher publisher;

    public void placeOrder(String orderId) {
        System.out.println("✅ Order placed: " + orderId);

        // publish the event
        publisher.publishEvent(new OrderPlacedEvent(this, orderId));
    }
}
```

```
}
```

3 Listeners (Observers)

EmailNotificationListener.java

```
package com.example.observerdemo.listener;

import com.example.observerdemo.event.OrderPlacedEvent;
import org.springframework.context.event.EventListener;
import org.springframework.stereotype.Component;

@Component
public class EmailNotificationListener {

    @EventListener
    public void onOrderPlaced(OrderPlacedEvent event) {
        System.out.println("✉️ Sending email for order: " + event.getOrderId());
    }
}
```

SMSNotificationListener.java

```
package com.example.observerdemo.listener;

import com.example.observerdemo.event.OrderPlacedEvent;
import org.springframework.context.event.EventListener;
import org.springframework.stereotype.Component;

@Component
public class SMSNotificationListener {

    @EventListener
    public void onOrderPlaced(OrderPlacedEvent event) {
        System.out.println("📱 Sending SMS for order: " + event.getOrderId());
    }
}
```

DashboardUpdateListener.java

```
package com.example.observerdemo.listener;

import com.example.observerdemo.event.OrderPlacedEvent;
import org.springframework.context.event.EventListener;
import org.springframework.stereotype.Component;

@Component
public class DashboardUpdateListener {

    @EventListener
    public void onOrderPlaced(OrderPlacedEvent event) {
        System.out.println("📊 Updating dashboard for order: " +
event.getOrderId());
    }
}
```

4 ObserverDemoApplication.java

```
package com.example.observerdemo;

import com.example.observerdemo.publisher.OrderService;
import org.springframework.beans.factory.annotation.Autowired;
import org.springframework.boot.CommandLineRunner;
import org.springframework.boot.SpringApplication;
import org.springframework.boot.autoconfigure.SpringBootApplication;

@SpringBootApplication
public class ObserverDemoApplication implements CommandLineRunner {

    @Autowired
    private OrderService orderService;



    public static void main(String[] args) {
        SpringApplication.run(ObserverDemoApplication.class, args);
    }

    @Override
    public void run(String... args) {
        orderService.placeOrder("ORDER123");
    }
}
```

✓ Output

- ✓ Order placed: ORDER123
- ▣ Sending email for order: ORDER123
- ▣ Sending SMS for order: ORDER123
- ▣ Updating dashboard for order: ORDER123

You've Built:

- ✓ **Observer Pattern**
-  Fully decoupled: Listeners don't know about each other.
-  Easily extendable: Add more listeners anytime.

✓ 1. What is Spring's Event Mechanism?

Spring's **application event system** is a **lightweight Observer Pattern** implementation built into the framework.

- A component (publisher) triggers an event.
 - One or more listeners (observers) **automatically react** to that event.
 - You can make it **synchronous (default)** or **asynchronous (via @Async)**.
-

✓ 2. Real-Life Use Case

🎯 Use Case: Order Processing in E-Commerce

When a user places an order:

- ◆ Send an email
- ◆ Send an SMS
- ◆ Update dashboard
- ◆ Record in analytics

These are **side effects** and should be decoupled from the core business logic.

✗ Without Events (Tight Coupling – Not Ideal)

```
public void placeOrder(Order order) {  
    saveToDb(order);  
    emailService.sendEmail(order);  
    smsService.sendSms(order);  
    dashboardService.update(order);  
}
```

Drawbacks:

- All side-effects are tightly bound
 - Hard to test
 - Hard to extend (Open/Closed Principle violated)
 - Adding/removing logic = code change
-

✓ With Events (Loose Coupling – Ideal)

```
public void placeOrder(Order order) {  
    saveToDb(order);  
    publisher.publishEvent(new OrderPlacedEvent(order));  
}
```

All the side effects move to listeners:

```
@EventListener  
public void handleEmail(OrderPlacedEvent event) { ... }
```

```
@EventListener  
public void handleSms(OrderPlacedEvent event) { ... }
```

✓ Now it's extensible, testable, and decoupled!

✓ 3. Why Use @Async?

By default, Spring event listeners run **synchronously**, meaning:

- Order processing **waits** for all listeners to finish.

But:

- Email sending
- SMS delivery
- Dashboard update

...don't need to block the order confirmation.

✅ With @Async

```
@Async
@EventListener
public void sendEmail(OrderPlacedEvent event) { ... }
```

Benefits:

- Core order processing returns faster
- Side effects handled **in parallel**
- Higher throughput
- Still loosely coupled

To enable:

```
@EnableAsync
@SpringBootApplication
public class MyApp {}
```

✅ 4. Spring Events vs Messaging (Kafka, RabbitMQ)

Feature	Spring Events	Messaging Systems (Kafka, RabbitMQ)
Scope	In-process (same JVM)	Cross-service / distributed
Speed	Fast (in-memory)	Slower (network, serialization)
Reliability	Not durable	Durable & fault-tolerant
Async Support	Via @Async	Built-in
Use When	Components in same app	Microservices or cross-system comm

So:

- Use **Spring events** for internal app-level decoupling.
 - Use **Kafka/RabbitMQ** for **inter-service communication** or **system integration**.
-

✅ Summary

Component	Purpose
ApplicationEventPublisher	Fires the event
@EventListener	Subscribes and reacts

Component	Purpose
@Async	Makes listener run in background thread
Messaging (Kafka/RabbitMQ)	For durable, distributed messaging

✓ When to Use Spring Events

- Decoupling layers (Service → Notification, Audit, etc.)
 - Modular monoliths
 - Plugin/event-driven apps
 - Not worth full messaging system yet
-

Let me know if you want:

- Full implementation with @Async
- REST API to trigger order
- Comparison with Kafka/RabbitMQ
- Real analytics integration

Would you like to convert this to a full architecture diagram?

You said:

@Async

i i remember it is something to do with an feature added to servlet api 3.x ..the thread that was assigned for client request give request further to a background thread so that original thread ready for request processing again

ChatGPT said:

You're **spot on** — what you're recalling is the **Servlet 3.0 asynchronous processing** feature, which is indeed **related to freeing up the request thread** for reuse, **but not the same as @ASYNC in Spring**.

Let me clarify both for you:

✓ 1. Servlet 3.0 Async Processing (Low-level Servlet API)

Introduced in **Servlet 3.0 (Java EE 6)**, this lets you **start async processing** within a servlet so that the **original HTTP request thread can be released** back to the thread pool **while background work continues**.

🔧 How It Works:

```
@WebServlet(asyncSupported = true)
public class AsyncServlet extends HttpServlet {
    protected void doGet(HttpServletRequest request, HttpServletResponse
response) {
```

```

        AsyncContext asyncContext = request.startAsync();

        asyncContext.start(() -> {
            // Background thread
            doLongRunningTask();
            asyncContext.complete(); // Marks async response complete
        });
    }
}

```

✓ Benefits:

- Non-blocking servlet threads
- Higher scalability for long-running operations (I/O, DB calls)

✓ 2. Spring's @Async (General-Purpose Background Task Execution)

@Async in Spring is a **higher-level abstraction**, not directly tied to HTTP/Servlets. It tells Spring to run the annotated method in a **separate thread**, managed by a **TaskExecutor**.

```

@Async
public void sendEmail(Order order) {
    // Runs in background thread
}

```

✨ When Spring Uses It:

- Any service-layer background work
- @EventListener to make event handling async
- **Can also be used inside controllers**, but **must combine with Callable<>**, **WebAsyncTask**, or **DeferredResult** to fully integrate with Servlet 3 async behavior.

✓ ↺ How They're Related

Aspect	Servlet 3.0 Async	Spring @Async
Thread handling	Frees servlet request thread	Runs method in background thread
Purpose	Async HTTP processing	Async method execution
API Level	Low-level (HttpServlet)	High-level (Spring Bean methods)
Returns control to client	Yes, eventually	Depends — needs integration with async web return types
Spring MVC support	Yes (with Callable, DeferredResult, etc.)	Yes (with task executors)

✓ Combine Both (Best Practice in Spring MVC)

If you're doing long-running processing **in a controller**, combine:

```
@GetMapping("/long-process")
public Callable<String> longProcess() {
    return () -> {
        // Background thread via Servlet 3
        Thread.sleep(5000);
        return "Done!";
    };
}
```

Or:

```
@GetMapping("/long")
public DeferredResult<String> handle() {
    DeferredResult<String> result = new DeferredResult<>();

    taskExecutor.execute(() -> {
        // Long running task
        result.setResult("Done!");
    });

    return result;
}
```

✓ Summary

Feature	Servlet 3.0 Async	Spring @Async
Introduced in	Servlet API 3.0	Spring 3.0
Manages HTTP thread?	✓ Yes	✗ Not directly
Goal	Async response handling	Async business logic
Uses thread pool?	Usually container-managed	Spring-managed TaskExecutor
Can be used together?	✓ Yes	✓ Yes

Would you like a **Spring Boot project** combining all these:

- ✓ Async REST Controller
- ✓ Background processing with @Async
- ✓ Spring Event + Async
- ✓ Logging of thread names to visualize?

Let me know — I'll scaffold it for you.

You said:

is airsole based body audor is allowed in domestic flight in india

ChatGPT said:

Yes, you're remembering correctly—and you're also on the mark. Let's break it down clearly:

🧠 What You Remember: Servlet 3.0 Async

Your memory is accurate—**Servlet 3.0** introduced native support for **asynchronous request processing**. In this model:

- The servlet calls `request.startAsync()`.
- The original servlet thread is **released immediately**, returning it to the thread pool.
- Long-running work continues on a **background thread**.
- When done, invoking `asyncContext.complete()` sends the response **later**, freeing up the servlet thread early.

This improves performance and scalability, especially under high concurrency.

How It's Related to Spring's @Async

@Async in Spring works at the **method level** within beans:

```
java
CopyEdit
@Async
public void doBackgroundWork() { ... }
```

- Spring uses a `TaskExecutor` to run it on a background thread.
 - The original caller (e.g. service layer) **does not wait** for this method to finish.
 - Commonly used for email notifications, logging, cleanup tasks—not for handling HTTP requests.
-

Combining Both for HTTP

When executing **long-running controller tasks**, you'd typically combine both:

```
@GetMapping("/process")
public Callable<String> process() {
    return () -> {
        // This runs on a background thread managed via Servlet 3 async
        service.doLongProcess();
        return "done";
    };
}
```

or using `DeferredResult`:

```
@GetMapping("/defer")
public DeferredResult<String> defer() {
    DeferredResult<String> dr = new DeferredResult<>();
    asyncService.longWork(dr);
    return dr; // servlet thread freed immediately
}
```

Spring's underlying mechanism uses **Servlet 3.0 async support**, so the servlet request thread is **not blocked**.

Note

- **Servlet 3.0 async** = frees up the **HTTP request thread**, hands off to a background task, returns later.
- **Spring @Async** = background execution of bean methods using a thread pool, but doesn't manage HTTP threads directly.
- **Together**, they allow both **non-blocking HTTP handling** and **asynchronous business logic**.