




Spring MVC 5.x

Rajeev Gupta MTech CS
Java Trainer

Spring mvc:



Spring MVC

is a imp of mvc design pattner build on top of servlet api

problem in servlet api:

1. it is not pojo based

```
class MyServlet extends HttpServlet {  
    ...  
}
```

it is very diff to do unit/inte testing with servlet

spring provide u pojo based controller

```
@Controller / @RestController
```

```
class MyController {  
    @Autowired  
    private BankFacade bankFacade;  
}
```

it is easy to do unit/inte testing with spring mvc controller as they are pojo based


Spring 5 MVC

- Spring MVC basic Architecture
- Hello world configuration
- Spring MVC annotations
- Form processing
- Form validation
- PRG pattern
- Flush attribute

Spring 5 MVC

- **Spring MVC basic Architecture**
- Hello world configuration
- Spring MVC annotations
- Form processing
- Form validation
- PRG pattern
- Flush attribute

Spring MVC basic Architecture



issues in servlet jsp:

servlet need to extract data one by one
data conversion
data validation
data buffering is also a problem

Spring MVC : form bean?
it is a pojo

```
class User{  
    String username;  
    String password;  
    Address address address;  
}
```

form bean

A diagram of an HTML form represented as a rectangle. Inside, there are five input fields, each followed by a label: 'isbn', 'title', 'price', 'author', and an empty field. Red lines connect these labels to the corresponding labels in the 'form bean' diagram to the right.

isbn
title
price
author

}

```
class Address{  
    String city;  
    String pin;  
}
```

~~html tags~~

mvc form bean tags:

we can write the logic
of form valition with pojo

declerative logic


JSR 303: validation api
hibernate validator

get: u need to bind a form bean with a jsp

post

form processing in spring mvc:

```
@GetMapping("/addbook")
public String getAddBook(ModelMap map) {
    map.addAttribute("book", new Book());
    return "addbook";
}
```



form bean

```
<%@ taglib prefix="form" uri="http://www.springframework.org/tags/form" %>
```

```
<form:form action="addbook" method="post" modelAttribute="book">
    isbn: <form:input path="isbn"/><br>
    title: <form:input path="title"/><br>
    author: <form:input path="author"/><br>
    price: <form:input path="price"/><br>
    <input type="submit" value="Add" />
</form:form>
```


```
public class Book {
    private int id;
    private String isbn;
    private String title;
    private String author;
    private double price;

    //getter and setter

}
```

```
@PostMapping("/addbook")
public String postAddBook
( @ModelAttribute(name = "book") Book book)
{
    System.out.println(book);
    return "addbook";
}
```

Spring MVC request flow



Spring MVC request flow

- **DispatcherServlet** receives the request for a URL in the application.
- The **Locale Resolver** component will look for the the Locale information in the request header or session or Cookie as the configuration. The Locale is used to pick the resource files based on the language of the user. This Locale Resolver plays a key role in internationalization of the application.
- The **Theme Resolver** is bound to the request to make the views determine which theme/CSS needs to be applied.
- The **Multipart Resolver** component is invoked to check if the request is for a file upload and then wraps the request to facilitate the file upload functionality.
- The **Handler mapping** component is invoked on the request to get the respective controller which is responsible to handle this request.
- The **DispatcherServlet** then invokes the HandlerChain which will execute the following:
 - Checks if there are any interceptors mapped and invokes the Pre Processing logic.
 - The controllers handler method will be invoked where the request is processed and the result is returned.
 - The mapped interceptors post processing logic will be invoked
- The **DispatcherServlet** based on the result returned by the Controllers handlers method, the ResultToViewNameTranslator component is invoked to generate the view name.
- The **view resolver** will then decide on what view needs to be rendered (JSP/XML/PDF/VELOCITY etc.,) and then the result will be dispatched to the client.

Spring 5 MVC

- Spring MVC basic Architecture
- **Hello world configuration**
- Understanding Controller, Model and view in details
- Form processing
- Form validation
- PRG pattern
- Flush attribute

Spring MVC Configuration

- **Step 1:** Configure the web.xml with DispatcherServlet and details of the application context file location.

```
<servlet>
  <servlet-name>dispatcher</servlet-name>
  <servlet-class>org.springframework.web.servlet.DispatcherServlet</servlet-class>
  <load-on-startup>1</load-on-startup>
</servlet>
<servlet-mapping>
  <servlet-name>dispatcher</servlet-name>
  <url-pattern>*.htm</url-pattern>
</servlet-mapping>

<context-param>
  <param-name>contextConfigLocation</param-name>
  <param-value>/WEB-INF/dispatcher-servlet.xml</param-value>
</context-param>

<listener>
  <listener-class>
    org.springframework.web.context.ContextLoaderListener
  </listener-class>
</listener>
```

Spring MVC Configuration

□ **Step 2:** Configure the dispatcher-servlet.xml

```
<beans xmlns="http://www.springframework.org/schema/beans"
       xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance" xmlns:p="http://www.springframework.org/schema/p"
       xmlns:context="http://www.springframework.org/schema/context"
       xsi:schemaLocation="http://www.springframework.org/schema/beans
http://www.springframework.org/schema/beans/spring-beans-3.0.xsd
http://www.springframework.org/schema/context
http://www.springframework.org/schema/context/spring-context-3.0.xsd">

    <context:component-scan base-package="com.controller" />

    <bean id="viewResolver"
          class="org.springframework.web.servlet.view.InternalResourceViewResolver">
        <property name="prefix">
            <value>/WEB-INF/views/</value>
        </property>
        <property name="suffix">
            <value>.jsp</value>
        </property>
    </bean>
</beans>
```

Spring MVC Configuration

□ **Step 3:** Create hello world controller

```
import org.springframework.stereotype.Controller;

@Controller
public class HelloWorld {
    @RequestMapping("/helloworld")
    public ModelAndView helloWord() {
        String message = "Hello World, Spring 3.0!";
        return new ModelAndView("helloworld", "message", message);
    }
}
```

```
@Controller
@RequestMapping("/welcome")
public class HelloController {

    @RequestMapping(method = RequestMethod.GET)
    public String printWelcome(ModelMap model) {

        model.addAttribute("message", "Spring 3 MVC Hello World");
        return "hello";
    }
}
```

Spring MVC Configuration

□ **Step 4:** Create view

```
<meta http-equiv="Content-Type" content:
<title>Insert title here</title>
</head>
<body>
  ${message}
</body>
</html>
```

Spring 5 MVC

- Spring MVC basic Architecture
- Hello world configuration
- **Spring MVC annotations**
- Understanding Controller, Model and view in details
- Form processing
- Form validation
- PRG pattern

Annotations in Spring MVC

- @Controller
- @RequestMapping
- @PathVariable
- @RequestParam
- @RequestHeader
- @ModelAttribute

@Controller

- This annotation is used at the class level.
- Denotes that the marked class acts as a controller.

```
import org.springframework.stereotype.Controller;  
@Controller  
public class StudentController {  
}
```

@RequestMapping

- This annotation can be used at the class level and method level.
- This annotation accepts the following as its parameters.
- Note that all the arguments are optional
 - **String[] values** - Represents an array of URLs which tells that the controller should be invoked for the request which arrive with the list of URLs mentioned. Eg: `@RequestMapping(value={"/welcome", "/test"})`.
 - **RequestMethod[] methods** - An array of HTTP methods. This is optional parameter and when not mentioned, the default method is HTTP GET. If specifically mentioned like POST, TRACE etc., then the method or controller will be invoked only when the request comes with the mentioned method. Eg: `@RequestMapping(method=RequestMethod.GET)`.
 - **String[] Params** - An array of Request Parameters and their values which can be used to validate if a particular request parameter has a value. Eg. `@RequestMapping(params="myParam=myValue")`
 - **String[] headers** - An array of headers which can be used to validate the values that the headers carry in request object. This is used for validation purposes same as the Params[] discussed earlier.
 - Eg. `@RequestMapping(headers = "content-type=text/*")`

@RequestMapping Examples

@Controller

@RequestMapping("/student/*")

public class StudentController{

@RequestMapping("add", method=RequestMethod.POST)

public String addStudent(){} - /appcontext/student/add

@RequestMapping("delete", method=RequestMethod.GET)

public String deleteStudent(){} - /appcontext/student/delete

@RequestMapping("details") –By default the method is GET

public String studentDetails(){} - /appcontext/student/details

@PathVariable

- ❑ Can only be used at method parameter level
- ❑ Used to mention that value should be retrieve from url
- ❑ Most important to support RESTful URL

```
@Controller
```

```
@RequestMapping("/student/*")
```

```
public class StudentController{
```

```
    @RequestMapping("delete/{studentNumber}",  
        method=RequestMethod.GET)
```

```
    public String deleteStudent(@PathVariable("studentNumber") int number)  
    { ...}
```

```
}
```

```
URL - /appcontext/student/delete/320
```

@RequestParam

- ❑ Used at the method parameter level
- ❑ Used to check for a parameter in the request and assign its values to a method argument


```
public String  
    login(@RequestParam("username")String  
          username, @RequestParam("pwd")String  
          pwd){  
}
```

Spring 5 MVC

- Spring MVC basic Architecture
- Hello world configuration
- Spring MVC annotations
- **Form processing**
- Form validation
- PRG pattern

Html form vs. web applications

- Html forms gives a place to enter data but do not provide space for web app to put such data




Html form vs. web applications

- What happens when form submitted?
 - The browser send the data up to the server as a list of name value pair
 - Everything is going to be transferred to the web app as a String
- **HTTP/HTML does not provide a components that can buffer, validate and convert input coming from a form**
 - That is the way HTTP and HTML work, web applications can not control this



The best I can do is to send you everything as a list of Strings...

What? This means that I have to do all the data processing by myself



Html form vs. web applications

- But, what if...
 - A field has to be interpreted as something different than a `String` (e.g., as a `Date`)? Conversion
 - The user forgets to provide a mandatory field? does he have to re-type everything from scratch? Buffering
 - We want to check that a field respects a given pattern? Validation
- When trying to solve these problems, HTML and HTTP are of **no use** to us


Account Sign up example: Conversion

- What is the best way to move request parameter to the account object? (backing bean)

```
<spring:url value="/account" var="account"/>
<form action="${account}" method="post">
    Name:      <input type="text" name="name"/>    <br/>
    Surname:   <input type="text" name="surname"/> <br/>
    Email:     <input type="text" name="email"/>    <br/>
    Birthday:  <input type="text" name="birthday"/><br/>
               <input type="submit" value="Sign-up"/>
</form>
```

| HTTP Request | |
|--------------|---|
| header | POST /account HTTP/1.1 Host: myserver.com User-Agent: ... Accept-Encoding: ... |
| body | name=John& surname=Smith& email=john@smith.com& birthday=10-1-1956 |

list of Strings



```
public class Account {

    private String name;
    private String surname;
    private String email;
    private Date birthday;

    // getters and setters


}
```

Account object

Data binding

- Data binding is the process of "binding" the request parameters to a so called form bean/backing bean
- All we need to do is to declare an account object as a method parameter.

```
@RequestMapping("/account")  
public String addAccountFromForm(Account account) {  
    ...  
}
```



account will be automatically populated from the request parameters

- The following sequence of operations occurs:
 1. A new form bean is instantiated
 2. the form bean is added to the model
 3. the form bean is populated from the request parameters

Account Sign up example: Data buffering (Pre populated values)

□ Setting a default value for the form bean

- Assume that we want to ask the user for the permission of sending marketing e-mails
- To this end we add a marketingOk property in the Account form bean
- By default we want marketingOk to be checked
- We would like the registration page to use properties coming from a prepopulated Account bean

```
public class Account {  
  
    private String name;  
    private String surname;  
    private String email;  
    private Date birthday;  
    private boolean marketingOk = true;  
  
    // getters and setters  
}
```

We are prepopulating the Account bean

The diagram shows a registration form on the left and an 'Account bean' object on the right. A blue arrow points from the 'Account bean' to the form, indicating data prepopulation. The form contains the following elements:

- Name:
- Surname:
- Date:
- ☒ Please send me product updates via e-mail
-

Revised registration form

- To deal with pre-populated form beans, Spring provides a set of data binding aware tags
- To use the tags from the form library, following directives need to be added to the top of JSP

```
<%@ taglib prefix="form"
      uri="http://www.springframework.org/tags/form" %>
```

modelAttribute binds the form to the account bean placed into the model

```
<form:form modelAttribute="account">
  Name:      <form:input path="name" />      <br/>
  Surname:   <form:input path="surname" />    <br/>
  Email:     <form:input path="email" />      <br/>
  Birthday:  <form:input path="birthday" />   <br/>

  <form:checkbox path="marketingOk" />
  Please send me product updates via e-mail <br/>

  <input type="submit" value="Sign-up" />
</form:form>
```

Each path attribute reference the property of the account bean

Spring 5 MVC

- Spring MVC basic Architecture
- Hello world configuration
- Spring MVC annotations
- Form processing
- **Form validation**
- PRG pattern
- Flush attribute

Account Sign up example: Data validation

- To detect user's errors, we need to validate the form data that are encapsulated in the form bean
- Example: the email property should respect the pattern `foo@provider.com`

```
public class Account {  
  
    private String name;  
    private String surname;  
    private String email;  
    private Date birthday;  
    private boolean marketingOk = true;  
  
    // getters and setters  
}
```

- The **Bean Validation API (JSR-303)** is a specification that defines a metadata model and API for JavaBean validation
- Using this API, it is possible to **annotate** bean properties with **declarative validation constraints**
- **Examples:** `@NotNull`, `@Pattern`, `@Size`

Adding constraints to the Account bean

```
public class Account {  
  
    @Pattern(regexp="^[A-Z]{1}[a-z]+$")  
    @Size(min=2, max=50)  
    private String name;  
  
    @Pattern(regexp="^[A-Z]{1}[a-z]+$")  
    @Size(min=2, max=50)  
    private String surname;  
  
    @NotBlank  
    @Email  
    private String email;  
  
    @NotNull  
    private Date birthday;  
    ...  
}
```

name and
surname should
start with a capital
letter and have at
least one
additional
lowercase letter

email must respect the
username@provider.tld
pattern

As with any other JEE API, the standard defines only the API specification

We are going to use **Hibernate Validator**, which is the reference implementation of the JSR-303 specification


Checking for validation errors

- together with the form bean, the handler method can now receive the result of the validation process



BindingResult is the part of the model

- To this end the bindingResult object is automatically inserted into the model and send back to the view



<form:errors>

<form:errors>

Spring provides a <spring:errors> tag as part of the Spring's form tag library

The tag renders **error message** taken from the BindingResult object within a HTML tag

```
<form:form modelAttribute="account">
Name:    <form:input path="name"/>    <form:errors path="name"/>    <br/>
Surname: <form:input path="surname"/> <form:errors path="surname"/> <br/>
Email:   <form:input path="email"/>   <form:errors path="email"/>   <br/>
...
</form:form>
```

```
public class Account {

    ...
    @NotNull(message = "the email address cannot be empty")
    @Email(message = "please provide a valid e-mail address")
    private String email;

    ...
}
```

Resource Bundle

- A better alternative is to store the error messages in a separate file called the resource bundle
- By doing so, error messages can be updated independently from the source code (loose coupling)

Resource bundle:

```
NotBlank.account.email=the email address cannot be empty  
Email.account.email=please provide a valid e-mail address  
NotNull.account.birthdate=The date cannot be empty
```

Spring's convention dictates the following syntax for messages:

```
[ConstraintName].[ClassName].[FieldName]=[Message]
```

- We need to declare ReloadableResourceBundleMessageSource bean in order to load messages from a resource bundle

frontcontroller]-servlet.xml:

```
<bean id="messageSource"
      class="org.springframework.context.support.ReloadableResourceBundleMessageSource">
    <property name="basename" value="classpath:validationMessages" />
</bean>
```

- The Spring DI Container will load the MessageSource

- **Remember:** the MessageSource bean **must** have the id equal to messageSource

We can now specify the **message code**, rather than the message itself


```
public class Account {
    ...
    @NotBlank(message = "{NotBlank.account.email}")
    @Email(message = "{Email.account.email}")
    private String email;
    ...
}
```

Spring 5 MVC

- Spring MVC basic Architecture
- Hello world configuration
- Spring MVC annotations
- Form processing
- Form validation
- **PRG pattern**
- Flush attribute


Handling User input PRG pattern

- Web form are submitted to the server through http POST
- What if user press **refresh** on the browser?
- Double form submission



The Post/Redirect/Get design pattern

- The PRG pattern solve the duplicate submission problem
 - According to the PRG pattern, the POST operation should not return web page directly, instead a redirect will be casted, causing an new GET operation to be executed
 - Upside: if the user refreshes the page, the GET request will be send, instead of original HTTP POST



RedirectView **redirect:prefix**

- To force a redirect, a controller can return RedirectView instance
- RedirectView is a special view which redirects the user to a different URL, rather than rendering the view itself
- To return a RedirectView, it is sufficient to prefix the view name with label redirect

```
@RequestMapping(method=RequestMethod.POST)
public String addAccountFromForm(@Valid Account account,
                                BindingResult bindingResult) {

    if (bindingResult.hasErrors())
        return "account/edit";

    return "redirect:/account/thanks";
}
```

redirect: is a special indication that a redirect is needed

The rest of the view name is treated as the **redirect URL**


RedirectView **redirect:prefix**

- **Remember : what follows the redirect:prefix is considered a url, not a view name**
- **that is /account/thanks will cause a GET request to http://myserver.com/webapp/account/thanks**
- hence we need a controller to handle the /account/thanks mapping
- The sole purpose of such a controller would be to return the /account/thanks view name
- That will cause the viewResolver to finally resolve the view name to /WEB-INF/account/thanks.jsp
- **Starting from Spring 3, it is possible to declarative set up controller whose unique purpose is to return a view name in FC-servlet.xml**

```
<mvc:view-controller path="/account/thanks"  
                    view-name="account/thanks"/>
```

PRG pattern: Model attributes

- As the model contains the data to be rendered by the view, its lifetime is limited by the request/response lifecycle



- In other words, a new Model Object is created for each request that hits the DispatcherServlet

Problem: A redirect creates a new request, hence causing the model attributes to be discarded

What if we want to retain some model attributes?

Spring 5 MVC

- Spring MVC basic Architecture
- Hello world configuration
- Spring MVC annotations
- Form processing
- Form validation
- PRG pattern
- **Flush attribute**

The flash Scope

- What if we want to retain some model attributes?
- **Solution?**
 - store attribute of interest in the flash scope

The **flash scope** works similarly to the session scope

The difference is that **flash attributes** are kept solely for the **subsequent request**

Flash attributes are stored before the redirect and made available as **model attributes** after the redirect

An handler method can declare an argument of type `RedirectAttributes`...

```
@RequestMapping(method=RequestMethod.POST)
public String addAccountFromForm(@Valid Account account,
                                BindingResult bindingResult,
                                RedirectAttributes redirectAttributes) {
```

...and use its `addFlashAttribute()` method to add attributes in the flash scope

```
@RequestMapping(method=RequestMethod.POST)
public String addAccountFromForm(@Valid Account account,
                                BindingResult bindingResult,
                                RedirectAttributes redirectAttributes) {

    if (bindingResult.hasErrors())
        return "account/edit";

    redirectAttributes.addFlashAttribute("name", account.getName());
    redirectAttributes.addFlashAttribute("surname", account.getSurname());
    return "redirect:/account/thanks";
}
```

name and surname will be automatically placed into the model object of the next request

they have been automatically inserted into the model

```
<html>
<head>
    <title>Thanks</title>
</head>
<body>
    Hi, ${name} ${surname}.
    You have been successfully registered. <br/>
</body>
</html>
```

Spring amvc Java Configuration

Step 1: cnfiguration for spring mvc bootstrap

```
1 package com.demo;
2
3 import org.springframework.web.servlet.support.AbstractAnnotationConfigDispatcherServletInitializer;
4
5 public class WebInit extends AbstractAnnotationConfigDispatcherServletInitializer{
6
7     @Override
8     protected Class<?>[] getRootConfigClasses() {
9         return null;
10    }
11
12    @Override
13    protected Class<?>[] getServletConfigClasses() {
14        return new Class[] {MvcConfig.class};
15    }
16
17    @Override
18    protected String[] getServletMappings() {
19        return new String[] {"/"};
20    }
21
22 }
```



```
import org.springframework.web.servlet.view.InternalResourceViewResolver;
```

Step 2: Configure viewresolver

```
@Configuration
```

```
@EnableWebMvc
```

```
@ComponentScan(basePackages = {"com.demo"})
```

```
public class MvcConfig extends WebMvcConfigurerAdapter{
```

```
    @Bean
```

```
    public InternalResourceViewResolver getInternalResourceViewResolver() {  
        InternalResourceViewResolver resolver = new InternalResourceViewResolver();  
        resolver.setPrefix("/WEB-INF/views/");  
        resolver.setSuffix(".jsp");  
        return resolver;  
    }
```

```
    @Override
```

```
    public void addResourceHandlers(ResourceHandlerRegistry registry) {  
        // Don't forget the ending "/" for location or you will hit 404.  
        registry.addResourceHandler("/resources/**").addResourceLocations("/resources/");  
    }
```

```
}
```

Step 3: Hello world controller

```
@Controller
```


```
public class HelloController {
```

```
    @GetMapping(path = "hello")
```

```
    public ModelAndView hello(ModelAndView mv) {  
        mv.addObject("key", "hello to spring mvc");  
        mv.setViewName("demo");  
        return mv;  
    }
```

```
}
```


Understanding Spring Web config



WebApplicationContext vs applicationContext

The `WebApplicationContext` is an extension of the plain `ApplicationContext` that has some extra features necessary for web applications. It differs from a normal `ApplicationContext` in that it is capable of resolving themes (see [Using themes](#)), and that it knows which `Servlet` it is associated with (by having a link to the `ServletContext`). The `WebApplicationContext` is bound in the `ServletContext`, and by using static methods on the `RequestContextUtils` class you can always look up the `WebApplicationContext` if you need access to it. Cited from [Spring web framework reference](#)

By the way servlet and root context are **both** `webApplicationContext`:



webappcontext vs applicationcontext

