API Documentation

Référence complète des endpoints REST.

BASE URL	`http://localhost:8000/api`
AUTH	Bearer token (Sanctum) — header `Authorization: Bearer <token>`
AUTEURS	Wassim RHILANE & Ilyasse DBIZA

---

01 · AUTHENTICATION

POST `/api/register`

REQUEST

```
{ "name": "Alice", "email": "a@a.com", "password": "secret123", "password_confirmatio
n": "secret123" }
```

RESPONSE 201

```
{ "user": { "id": 3, "name": "Alice", "email": "a@a.com", "role": "user" }, "token":
"1|abc..." }
```

POST `/api/login`

REQUEST

```
{ "email": "...", "password": "..." }
```

RESPONSE 200

```
{ "user": { "id": 1, "name": "...", "email": "...", "role": "user" }, "token": "..."
}
```

FAILURE 422

```
{ "message": "Validation failed", "errors": { "email": ["Invalid credentials."] } }
```

POST `/api/logout` auth

RESPONSE 200

```
{ "message": "Logged out" }
```

GET **/api/me** auth

RESPONSE 200

```
{ "user": { "id": 1, "name": "...", "email": "...", "role": "user" } }
```

02 · ANALYSE IA

POST **/api/analyze** auth

REQUEST

```
{ "text": "Great product!" }
```

RESPONSE 200

```
{ "sentiment": "positive", "score": 0.98, "topics": ["product"] }
```

Toujours une réponse valide même si l'API Hugging Face est inaccessible (fallback basé sur des règles).

03 · REVIEWS (CRUD)

Tous les endpoints nécessitent l'authentification. Utilisateurs normaux : leurs avis uniquement. Admins : tous les avis.

GET **/api/reviews** auth

RESPONSE 200

```
{ "data": [
  { "id": 1, "user_id": 2, "content": "...", "sentiment": "positive", "score": 0.95,
    "topics": ["delivery","quality"], "created_at": "2026-04-18T10:00:00.000000Z",
    "user": { "id": 2, "name": "Demo User", "email": "user@example.com" } }
] }
```

POST **/api/reviews** auth

REQUEST

```
{ "content": "The service was excellent and fast." }
```

RESPONSE 201

```
{ "id": 6, "user_id": 2, "content": "...", "sentiment": "positive",
  "score": 0.97, "topics": ["service"], "created_at": "...", "updated_at": "..." }
```

L'analyse (sentiment, score, topics) est déclenchée automatiquement à la création.

GET **/api/reviews/{id}** auth

Retourne l'objet avis. 404 si introuvable, 403 si ni propriétaire ni admin.

PUT **/api/reviews/{id}** auth

REQUEST

```
{ "content": "updated text..." }
```

Relance l'analyse et met à jour sentiment / score / topics.

DELETE **/api/reviews/{id}** auth

RESPONSE 200

```
{ "message": "Deleted" }
```

04 · DASHBOARD

GET **/api/dashboard/stats** auth

RESPONSE 200

```
{
  "total": 5,
  "positive_count": 3, "negative_count": 1, "neutral_count": 1,
  "positive_percent": 60.0, "negative_percent": 20.0, "neutral_percent": 20.0,
  "average_score": 0.7123
}
```

GET **/api/dashboard/recent-reviews** auth

5 avis les plus récents, avec le même filtrage par rôle que `GET /api/reviews`.

GET **/api/dashboard/topics** auth

RESPONSE 200

```
{ "data": [
  { "topic": "delivery", "count": 4 },
  { "topic": "quality",  "count": 3 },
  { "topic": "price",    "count": 2 }
] }
```

05 · FORMAT DES ERREURS

Tous les endpoints `/api/*` retournent des erreurs en JSON :

STATUS	CORPS DE LA RÉPONSE
401	`{ "message": "Unauthenticated" }`
403	`{ "message": "Forbidden" }`
404	`{ "message": "Not found" }`
422	`{ "message": "Validation failed", "errors": { "field": ["..."] } }`
500	`{ "message": "Server error", "error": "..." }`

06 · GUIDE DE TEST

Avec curl

```
TOKEN=$(curl -s -X POST http://localhost:8000/api/login \
  -H 'Content-Type: application/json' \
  -d '{"email":"user@example.com","password":"password"}' | jq -r .token)

curl -X POST http://localhost:8000/api/reviews \
  -H "Authorization: Bearer $TOKEN" -H 'Content-Type: application/json' \
  -d '{"content":"absolutely terrible, broke in one day"}'
# → sentiment: "negative", topics include "quality"
```

Avec Postman

1. Créer une variable d'environnement `token`.
2. Envoyer `POST {{base}}/login` — dans l'onglet Tests : `pm.environment.set("token", pm.response.json().token)`.
3. Sur les autres requêtes, ajouter le header `Authorization: Bearer {{token}}`.

Vérifier l'intégration Hugging Face

- Premier appel peut prendre 5–15 s (cold start). Les suivants sont rapides.
- `storage/logs/laravel.log` enregistre un avertissement si l'API HF échoue.
- Vider `HUGGINGFACE_API_TOKEN` pour tester le fallback — le sentiment est quand même retourné.