Showing results for http | W3C CSS Validator resu | CSS Shrink | PNG to PDF – Convert P

Secure | https://validator.w3.org/nu/?doc=https%3A%2F%2Fbobbi.ivytech.edu%2F~rhurd7%...

Apps | Dashboard | https://attendee.got | Google Testing Tool | Netflix | In what order should | YouTube | Other bookmarks

Checker Input

Show source outline image report Options...

Check by address

https://bobbi.ivytech.edu/~rhurd7/project/finalVersion/services.html

Check

Use the Message Filtering button below to hide/show particular messages, and to see total counts of errors and warnings.

Message Filtering

1. **Error** Element `figure` not allowed as child of element `span` in this context. (Suppressing further errors from this subtree.)
   From line 177, column 6; to line 177, column 31
   `or">··· <figure class="alignleft">···`
   Contexts in which element `figure` may be used:
   Where flow content is expected.
   Content model for element `span`:
   Phrasing content.

2. **Error** Element `p` not allowed as child of element `span` in this context. (Suppressing further errors from this subtree.)
   From line 185, column 31; to line 185, column 52
   `"founder"><p class="alignright">Don Bl`
   Contexts in which element `p` may be used:
   Where flow content is expected.
   Content model for element `span`:
   Phrasing content.

3. **Error** Element `p` not allowed as child of element `span` in this context. (Suppressing further errors from this subtree.)
   From line 188, column 37; to line 188, column 59
   `tAddress"><p class="alignright1"><a hre`
   Contexts in which element `p` may be used:
   Where flow content is expected.
   Content model for element `span`:
   Phrasing content.

4. **Error** End tag `p` implied, but there were open elements.
   From line 195, column 32; to line 195, column 54
   `elephone"><p class="alignright2">(574)`

5. **Error** Unclosed element `span`.
   From line 195, column 5; to line 195, column 31
   `> ···<··· <span itemprop="telephone">cp cla`

6. **Error** Element `p` not allowed as child of element `span` in this context. (Suppressing further errors from this subtree.)
   From line 195, column 32; to line 195, column 54
   `elephone"><p class="alignright2">(574)`
   Contexts in which element `p` may be used:
   Where flow content is expected.
   Content model for element `span`:
   Phrasing content.

7. **Error** Element `p` not allowed as child of element `span` in this context. (Suppressing further errors from this subtree.)
   From line 196, column 5; to line 196, column 22
   `span>··· <p class="report">a hre`
   Contexts in which element `p` may be used:
   Where flow content is expected.
   Content model for element `span`:
   Phrasing content.

8. **Error** End tag `footer` seen, but there were open elements.
   From line 197, column 4; to line 197, column 12
   `a></p>··· </footer>··· </d`

9. **Error** Unclosed element `span`.
   From line 187, column 5; to line 187, column 82
   `span>··· <span itemprop="address" itemtype="http://schema.org/PostalAddress" itemscope>···`

10. **Error** Unclosed element `span`.
    From line 175, column 5; to line 175, column 63
    `cope>··· <span itemprop="https://schema.org/Organization" itemscope>···`

Document checking completed.

Used the HTML parser. Externally specified character encoding was UTF-8.

Total execution time 182 milliseconds.