



Sherpa Elephant V6 Tool Head - Ender 3 V2 Neo



LH

[VIEW IN BROWSER](#)

updated 19. 4. 2023 | published 19. 4. 2023

Summary

Tool Head design for the Ender 3 V2 Neo based on the E3D V6 and Sherpa Mini direct drive extruder by Annex Engineering

[3D Printers](#) > [3D Printers - Upgrades](#)

Tags: [extruder](#) [dragon](#) [bmg](#) [bondtech](#) [e3d](#) [hotend](#) [v6](#)
[stepper](#) [creality](#) [ender](#) [v2](#) [drive](#) [noctua](#) [ender3](#)
[4020](#) [direct](#) [5015](#) [dragonfly](#) [neo](#) [bmo](#) [revo](#)
[toolhead](#) [sherpa](#) [phaetus](#) [ender3v2neo](#)

Tool Head design for the **Ender 3 V2 Neo** based on the E3D V6 (or Revo 6, Dragon SF, HF, Dragonfly BMO) and Sherpa Mini direct drive extruder by Annex Engineering

https://github.com/Annex-Engineering/Sherpa_Mini-Extruder

Features:

- Weight balanced compact and modular design using components as structural parts
- Print weight: 57g
- Direct/no gear reduction direct drive assembly using a Creality 42-40 stepper motor

- Tested at 22mm³/s flow rate on a stock E3D V6 0.4mm nozzle (G1 E100 F550 - PETG @ 240C)
- Clears the Z uprights and doesn't require modifications for the endstops

Update:

v1.02

- Added optional hotend duct insert module
(Requires 3mm longer screws for the axial fan mount, and re-routing the fans cables)

v1.01

- New improved part cooling nozzle design

Print settings:

- 0.2 mm layer height
- 3 perimeters, 100% infill
- Supports, 30 degrees Snug (includes sacrificial bridges, but some supports needed for safety; check examples)
- Detect thin walls OFF
- Classic perimeter preferred
- Printed in PETG

Designed at 0.2 fit tolerance (0.1 per side)

Please consult the F3D for assembly

Parts Required:

- E3D V6 Hot End / Revo 6 /Dragon SF, HF / Dragonfly BMO
- BMG Extruder Kit / Parts (Stepper gear, idler gear, idler bearings, two 3x20mm shafts)
(I used parts from the cheap RED all metal dual gear extruder and custom cut two 20mm x 3mm shafts)
- Creality stock extruder spring (if not using BMG kit. Others might work)
- Creality 42-40 (Stock Ender 3 extruder stepper motor, or other with similar dimensions)
- Stepper Extension Cable (If still using the stock bowden setup)
- 5015 Blower Fan - (Designed for a Creality 5015. Others should work, check nozzle fit)
- 4020/4010 Axial Fan - (Designed for a Noctua NF-A4x20. Others should work)

Hardware:

Screws:

Button Head

-M3 5mm 2x

-M3 8mm 7x

-M3 10mm 4x

-M3 12mm 5x

-M3 15mm 4x

-M3 20mm 1x

-M3 25mm 2x

-M3 25mm Flat head (if using the Creality stock extruder spring)

Optional Hotend Cooling Duct:

Button Head

-M3 15mm 3x

Nuts

-M3 Hex Nuts 15x

Optional: Side box for cable management/board/connectors + Cable guide

Bowden Length: ~55.5mm

Post Print:

Remove supports and break through sacrificial bridges

- File flat joining areas for good fitting

- Test blower fan nozzle fit

- Insert Hex nuts

- Assemble it in three parts:

a. Main carriage mount with hotend, right small axial fan carriage mount, cable duct and hotend cooling fan

b. Extruder

c. Front frame with blower fan and CR Touch.

-Fit everything together, but don't overtighten the screws risking the hex nuts to break away from their fit and spin freely.

- Consult image or f3d for screw lengths.

Extruder motor direction needs to be reversed in firmware (eg. Klipper: dir_pin: !PB3), or with cabling.

Probe Offset: x -25, y -7
- Filament Load Length: 65.0, Prime: 35.0
- Filament Unload Length: 160.0

Enjoy!

This remix is based on



GitHub - Annex-Engineering/Sherpa_Mini-Extruder: A smaller version of the sherpa extruder, direct and bowden supported

Model files



F3D

1 file



sherpa-elephant-v6-ender-3-v2-neo-v102.f3d



3MF

4 files




se-black-mount-and-extruder.3mf



se-red-frame-v101.3mf



se-optional-cable-box.3mf



se-optional-hotend-duct.3mf




STL

16 files



se-red-fan-nozzle-v101.stl



se-sherpa-mount.stl



se-sherpa-arm.stl



se-sherpa-face.stl




se-sherpa-knob.stl



se-sherpa-spring-guide.stl



se-v6-front-clamp.stl



se-v6-main-carriage-mount.stl



se-cable-holder-hotend-lead.stl



se-cable-holder-arm.stl



se-red-fan-holder-right.stl



se-red-blower-support-mount.stl



se-red-blower-and-bl-frame.stl



se-optional-box-inner.stl




se-optional-box-outer.stl



se-optional-hotend-fan-duct.stl

Other files



annex-engineering-license-agreement.txt

License

This work is licensed under a
[Creative Commons \(4.0 International License\)](#)



Attribution

- ✗ | Sharing without ATTRIBUTION
- ✓ | Remix Culture allowed
- ✓ | Commercial Use
- ✓ | Free Cultural Works
- ✓ | Meets Open Definition