# Who is the best connected scientist? A study of scientific coauthorship networks

M. E. J. Newman

Santa Fe Institute, 1399 Hyde Park Road, Santa Fe, NM 87501 Center for Applied Mathematics, Cornell University, Rhodes Hall, Ithaca, NY 14853

Using data from computer databases of scientific papers in physics, biomedical research, and computer science, we have constructed networks of collaboration between scientists in each of these disciplines. In these networks two scientists are considered connected if they have coauthored one or more papers together. We have studied many statistical properties of our networks, including numbers of papers written by authors, numbers of authors per paper, numbers of collaborators that scientists have, typical distance through the network from one scientist to another, and a variety of measures of connectedness within a network, such as closeness and betweenness. We further argue that simple networks such as these cannot capture the variation in the strength of collaborative ties and propose a measure of this strength based on the number of papers coauthored by pairs of scientists, and the number of other scientists with whom they coauthored those papers. Using a selection of our results, we suggest a variety of possible ways to answer the question "Who is the best connected scientist?"

#### I. INTRODUCTION

A social network [1,2] is a set of people or groups each of which has connections of some kind to some or all of the others. In the language of social network analysis, the people or groups are called "actors" and the connections "ties." Both actors and ties can be defined in different ways depending on the questions of interest. An actor might be a single person, a team, or a company. A tie might be a friendship between two people, a collaboration or common member between two teams, or a business relationship between companies.

Social network analysis has a history stretching back at least half a century, and has produced many results concerning social influence, social groupings, inequality, disease propagation, communication of information, and indeed almost every topic that has interested twentieth century sociology. This paper, however, is a physics paper. Why should a physicist be interested in social networks? There has, in fact, been a substantial surge of interest in social networks within the physics community recently, as evidenced by the large body of papers on the topic—see Refs. [3] through [23] and references therein. The techniques of statistical physics in particular turn out to be well suited to the study of these networks. Profitable use has been made of a variety of physical modeling techniques [4,5,6], exact solutions [7,8,9,10,11,12], Monte Carlo simulation [13,14,15,16], scaling and renormalization group methods [14,15,16], mean-field theory [17,18], percolation theory [19,20,21], the replica method [22], generating functions [19,21,23], and a host of other techniques familiar to physicists.

This paper makes use of some of these techniques in the study of some specific examples of social networks. However, the subject matter of this paper will be of interest to physicists for another reason: it's about them. In this paper, we study collaboration networks in which the actors are scientists, and the ties between them are scientific collaborations, as documented in the papers that they write.

#### II. COLLABORATION NETWORKS

Traditional investigations of social networks have been carried out through field studies. Typically one looks at a fairly self-contained community such as a business community [24,25,26], a school [27,28], a religious or ethnic community [29], and so forth, and constructs the network of ties by interviewing participants, or by circulating questionnaires. A study will ask respondents to name those with whom they have the closest ties, probably ranked by subjective closeness, and may optionally call for additional information about those people or about the nature of the ties.

Studies of this kind have revealed much about the structure of communities, but they suffer from two substantial problems which make them poor sources of data for the kinds of quantitative approach to network analysis that physics has adopted. First, the data they return are not numerous. Collecting and compiling data from these studies is an arduous process and most data sets contain no more than a few tens or hundreds of actors. It is a rare study that exceeds a thousand actors. This makes the statistical accuracy of many results poor, a particular difficulty for the large-system-size methods adopted by statistical physics. Second, they contain significant and uncontrolled errors as a result of the subjective nature of the respondents' replies. What one respondent considers to be a friendship or acquaintance, for example, may be completely different from what another respondent does. In studies of school-children [27,28], for instance, it is found that some children will claim friendship with every single one of their hundreds of schoolmates, while

others will name only one or two friends. Clearly these respondents are employing different definitions of friendship.

In response to these inadequacies, many researchers have turned instead to other, better documented networks, for which reliable statics can be collected. Examples include the world-wide web [13,30,31], power grids [4], telephone call graphs [32], and airline timetables [33]. These graphs are certainly interesting in their own right, and furthermore might loosely be regarded as social networks, since their structure clearly reflects something about the structure of the society that built them. However, their connection to the "true" social networks discussed here is tenuous at best and so, for our purposes, they cannot offer a great deal of insight.

A more promising source of data is the affiliation network. An affiliation network is a network of actors connected by common membership in groups of some sort, such as clubs, teams, or organizations. Examples which have been studied in the past include women and the social events they attend [34], company CEOs and the clubs they frequent [25], company directors and the boards of directors on which they sit [24,35], and movie actors and the movies in which they appear [4,33]. Data on affiliation networks tend to be more reliable than those on other social networks, since membership of a group can often be determined with a precision not available when considering friendship or other types of acquaintance. Very large networks can be assembled in this way as well, since in many cases group membership can be ascertained from membership lists, making time-consuming interviews or questionnaires unnecessary. A network of movie actors, for example, has been compiled using the resources of the Internet Movie Database [36], and contains the names of nearly half a million actors—a much better sample on which to perform statistics than most social networks, although it is unclear whether this particular network has any real social interest.

In this paper we construct affiliation networks of scientists in which a link between two scientists is established by their coauthorship of one or more scientific papers. Thus the groups to which scientists belong in this network are the groups of coauthors of a single paper. This network is in some ways more truly a social network than many affiliation networks; it is probably fair to say that most pairs of people who have written a paper together are genuinely acquainted with one another, in a way that movie actors who appeared together in a movie may not be. There are exceptions—some very large collaborations, for example in high-energy physics, will contain coauthors who have never even met—and we will discuss these at the appropriate point. By and large, however, the network reflects genuine professional interaction between scientists, and may be the largest social network ever studied [37].

The idea of constructing a network of coauthorship is not new. Many readers will be familiar with the concept of the Erdös number, named after Paul Erdös, the Hungarian mathematician, one of the founding fathers of graph theory amongst other things [38]. At some point, it became a popular cocktail party pursuit for mathematicians to calculate how far removed they were in terms of publication from Erdös. Those who had published a paper with Erdös were given a Erdös number of 1, those who had published with one of those people but not with Erdös, a number of 2, and so forth. In the jargon of social networks, vour Erdös number is the geodesic distance between you and Erdös in the coauthorship network. In recent studies [39,40], it has been found that the average Erdös number is about 4.7, and the maximum known finite Erdös number (within mathematics) is 15. These results are probably influenced to some extent by Erdös' prodigious mathematical output: he published at least 1401 papers, more than any other mathematician ever except possibly Leonhard Euler. However, quantitatively similar, if not quite so impressive, results are in most cases found if the network is centered on other mathematicians. (On the other hand, fifth-most published mathematician, Lucien Godeaux, produced 644 papers, on 643 of which he was the sole author. He has no finite Erdös number [39]. Clearly sheer size of output is not a sufficient condition for high connectedness.)

There is also a substantial body of work in bibliometrics (a specialty within information science) on extraction of collaboration patterns from publication data—see Refs. [41,42,43,44,45] and references therein. However, these studies have not so far attempted to reconstruct actual collaboration networks from bibliographic data, concentrating more on organization and institutional aspects of collaboration [46].

In this paper, we study networks of scientists using bibliographic data drawn from four publicly available databases of papers. The databases are:

- 1. Los Alamos e-Print Archive: a database of unrefereed preprints in physics, self-submitted by their authors, running from 1992 to the present. This database is subdivided into specialties within physics, such as condensed matter and high-energy physics.
- 2. MEDLINE: a database of articles on biomedical research published in refereed journals, stretching from 1961 to the present. Entries in the database are updated by the database's maintainers, rather than papers' authors, giving it relatively thorough coverage of its subject area. The inclusion of biomedicine is crucial in a study such as this one. In most countries biomedical research easily dwarfs civilian research on any other topic, in terms of both expenditure and human effort. Any study which omitted it would be leaving out the largest part of current scientific research.
- 3. SPIRES: a database of preprints and published papers in high-energy physics, both theoretical and

experimental, from 1974 to the present. The contents of this database are also professionally maintained. High energy physics is an interesting case socially, having a tradition of much larger experimental collaborations than any other discipline.

4. NCSTRL: a database of preprints in computer science, submitted by participating institutions and stretching back about ten years.

We have constructed networks of collaboration for each of these databases separately, and analyzed them using a variety of techniques, some standard, some invented for the purpose. The outline of this paper is as follows. In Section III we discuss some basic statistics, to give a feel for the shape of our networks. Among other things we discuss the typical numbers of authors, numbers of papers per author, authors per paper, and number of collaborators of scientists in the various disciplines. In Section IV we look at a variety of measures concerned with paths between scientists on the network. In Section V we extend our networks to include a measure of the strength of collaborative ties between scientists and examine measures of connectedness in these weighted networks. In Section VI we give our conclusions. A brief report of some of the work described here has appeared previously as Ref. [47].

#### III. BASIC RESULTS

For this study, we constructed collaboration networks using data from a five year period from 1995 to 1999 inclusive, although data for much longer periods were available in some of the databases. There were several reasons for using this fairly short time window. First, older data are less complete than newer for all databases. Second, we wanted to study the same time period for all databases, so as to be able to make valid comparisons between collaboration patterns in different fields. The coverage provided by both the Los Alamos Archive and the NCSTRL database is relatively poor before 1995, and this sets a limit on how far back we can look. Third, networks change over time, both because people enter and leave the professions they represent and because practices of scientific collaboration and publishing change. In this particular study we have not examined time evolution in the network, although this is certainly an interesting topic for research and indeed is currently under investigation by others [48]. For our purposes, a short window of data is desirable, to ensure that the collaboration network is roughly static during the study.

The raw data for the networks described here are computer files containing lists of papers, including authors names and possibly other information such as title, abstract, date, journal reference, and so forth. Construction of the collaboration networks is straightforward. The files are parsed to extract author names and as names

are found a list is maintained of the ones seen so farvertices already in the network—so that recurring names can be correctly assigned to extant vertices. Edges are added between each pair of authors on each paper. A naive implementation of this calculation, in which names are stored in a simple array, would take time O(pn), where p is the total number of papers in the database and n the number of authors. This however turns out to be prohibitively slow for large networks since p and n are of similar size and may be a million or more. Instead therefore, we store the names of the authors in an ordered binary tree, which reduces the running time to  $O(p \log n)$ , making the calculation tractable, even for the largest databases studied here.

In Table I we give a summary of some of the basic results for the networks studied here. We discuss these results in detail in the rest of this section.

#### A. Number of authors

The size of the databases varies considerably from about a million authors for MEDLINE to about ten thousand for NCSTRL. In fact, it is difficult to say with precision how many authors there are. One can say how many distinct names appear in a database, but the number of names is not the same as the number of authors. A single author may report their name differently on different papers. For example, F. L. Wright, Francis Wright, and Frank Lloyd Wright could all be the same person. Also two authors may have the same name. Grossman and Ion [39] point out that there are two American mathematicians named Norman Lloyd Johnson, who are known to be distinct people and who work in different fields, but between whom computer programs such as ours cannot hope to distinguish. Even additional clues such as home institution or field of specialization cannot be used to distinguish such people, since many scientists have more than one institution or publish in more than one field. The present author, for example, has addresses at the Santa Fe Institute and Cornell University, and publishes in both statistical physics and paleontology.

In order to control for these biases, we constructed two different versions of each of the collaboration networks studied here, as follows. In the first, we identify each author by his or her surname and first initial only. This method is clearly prone to confusing two people for one, but will rarely fail to identify two names which genuinely refer to the same person. In the second version of each network, we identify authors by surname and all initials. This method can much more reliably distinguish authors from one another, but will also identify one person as two if they give their initials differently on different papers. Indeed this second measure appears to overestimate the number of authors in a database substantially. Networks constructed in these two different fashions therefore give upper and lower bounds on the number of authors, and

		I	los Alamos e-I				
	MEDLINE	complete	astro-ph	cond-mat	hep-th	SPIRES	NCSTRL
total papers	2163923	98502	22029	22016	19085	66652	13169
total authors	1520251	52909	16706	16726	8361	56627	11994
first initial only	1090584	45685	14303	15451	7676	47445	10998
mean papers per author	6.4(6)	5.1(2)	4.8(2)	3.65(7)	4.8(1)	11.6(5)	2.55(5)
mean authors per paper	3.754(2)	2.530(7)	3.35(2)	2.66(1)	1.99(1)	8.96(18)	2.22(1)
collaborators per author	18.1(1.3)	9.7(2)	15.1(3)	5.86(9)	3.87(5)	173(6)	3.59(5)
size of giant component	1395693	44337	14845	13861	5835	49002	6396
first initial only	1019418	39709	12874	13324	5593	43089	6706
as a percentage	92.6(4)%	85.4(8)%	89.4(3)	84.6(8)%	71.4(8)%	88.7(1.1)%	57.2(1.9)%
2nd largest component	49	18	19	16	24	69	42
clustering coefficient	0.066(7)	0.43(1)	0.414(6)	0.348(6)	0.327(2)	0.726(8)	0.496(6)
mean distance	4.6(2)	5.9(2)	4.66(7)	6.4(1)	6.91(6)	4.0(1)	9.7(4)
maximum distance	24	20	14	18	19	19	31

TABLE I. Summary of results of the analysis of seven scientific collaboration networks. Numbers in parentheses are standard errors on the least significant figures.

hence also give bounds on many of the other quantities studied here. In Table I we give numbers of authors in each network using both methods, but for many of the other quantities we give only an error estimate based on the separation of the bounds.

#### B. Number of papers per author

The average number of papers per author in the various subject areas is in the range of around three to six over the five year period. The only exception is the SPIRES database, covering high-energy physics, in which the figure is significantly higher at 11.6. One possible explanation for this is that SPIRES is the only database which contains both preprints and published papers. It is possible that the high figure for papers per author reflects duplication of papers in both preprint and published form. However, the maintainers of the database go to some lengths to avoid this [49], and a more probable explanation is perhaps that publication rates are higher for the large collaborations favored by high-energy physics, since a large group of scientists has more person-hours available for the writing of papers.

In addition to the average numbers of papers per author in each database, it is interesting to look at the distribution  $p_k$  of numbers k of papers per author. In 1926, Alfred Lotka [50] showed, using a dataset compiled by hand, that this distribution followed a power law, with exponent approximately -2, a result which is now referred to as Lotka's Law of Scientific Productivity. In other words, in addition to the many authors who publish only a small number of papers, one expects to see a "fat tail" consisting of a small number of authors who publish a very large number of papers. In Fig. 1 we show on logarithmic scales histograms for each of our four databases of the numbers of papers




FIG. 1. Histograms of the number of papers written by authors in MEDLINE (circles), the Los Alamos Archive (squares), and NCSTRL (triangles). The dotted lines are fits to the data as described in the text. Inset: the equivalent histogram for the SPIRES database.

published. (These histograms and all the others shown here were created using the "all initials" versions of the collaboration networks.) For the MEDLINE and NC-STRL databases these histograms follow a power law quite closely, at least in their tails, with exponents of -2.86(3) and -3.41(7) respectively—somewhat steeper than those found by Lotka, but in reasonable agreement with other more recent studies [41,51,52]. For the Los Alamos Archive the pure power law is a poor fit. An exponentially truncated power law does much better:

$$p_k = Ck^{-\tau} e^{-k/\kappa}, \tag{1}$$

	number of papers		number of co-workers		betweenness $(\times 10^6)$		collaboration weight		
astro-ph	112	Fabian, A.C.	360	Frontera, F.	2.33	Kouveliotou, C.	16.5	Moskalenko, I.V./Strong, A.W.	
	101	van Paradijs, J.	353	Kouveliotou, C.	2.15	van Paradijs, J.	15.0	Hernquist, L./Heyl, J.S.	
	81	Frontera, F.	329	van Paradijs, J.	1.80	Filippenko, A.V.	14.0	Mathews, W.G./Brighenti, F.	
	80	Hernquist, L.	299	Piro, L.	1.57	Beaulieu, J.P.	13.4	Labini, F.S./Pietronero, L.	
	79	Gould, A.	296	Costa, E.	1.52	Nomoto, K.	12.2	Piran, T./Sari, R.	
	78	Silk, J.	291	Feroci, M.	1.52	Pian, E.	11.8	Zaldarriaga, M./Seljak, U.	
	78	Klis, M.V.D.	284	Pian, E.	1.49	Frontera, F.	11.4	Hernquist, L./Katz, N.	
	73	Kouveliotou, C.	284	Hurley, K.	1.35	Silk, J.	11.1	Avila-Reese, V./Firmani, C.	
	70	Ghisellini, G.	244	Palazzi, E.	1.33	Kamionkowski, M.	10.9	Dai, Z.G./Lu, T.	
	66	Piro, L.	244	Heise, J.	1.28	McMahon, R.G.	10.8	Ostriker, J.P./Cen, R.	
cond-mat	116	Parisi, G.	107	Uchida, S.	4.11	MacDonald, A.H.	22.3	Belitz, D./Kirkpatrick, T.R.	
	79	Scheffler, M.	103	Ueda, Y.	3.96	Bishop, A.R.	17.0	Shrock, R./Tsai, S.	
	75	Das Sarma, S.	96	Revcolevschi, A.	3.36	Das Sarma, S.	15.0	Yukalov, V.I./Yukalova, E.P.	
	74	Stanley, H.E.	94	Eisaki, H.	2.96	Tosatti, E.	14.7	Martín-Delgado, M.A./Sierra, G.	
	70	MacDonald, A.H.	84	Cheong, S.	2.52	Wang, X.	14.3	Krapivsky, P.L./Ben-Naim, E.	
	68	Sornette, D.	83	Isobe, M.	2.38	Revcolevschi, A.	14.1	Beenakker, C.W.J./Brouwer, P.W.	
	60	Volovik, G.E.	78	Stanley, H.E.	2.30	Uchida, S.	13.8	Weng, Z.Y./Sheng, D.N.	
Ū	56	Beenakker, C.W.J.	76	Shirane, G.	2.21	Sigrist, M.	13.7	Sornette, D./Johansen, A.	
	53	Dagotto, E.	76	Scheffler, M.	2.19	Cheong, S.	13.6	Rikvold, P.A./Novotny, M.A.	
	50	Helbing, D.	76	Menovsky, A.A.	2.18	Stanley, H.E.	13.0	Scalapino, D.J./White, S.R.	
hep-th	78	Odintsov, S.D.	50	Ambjorn, J.	0.98	Odintsov, S.D.	34.0	Lu, H./Pope, C.N.	
	73	Lu, H.	44	Ferrara, S.	0.88	Ambjorn, J.	29.0	Odintsov, S.D./Nojiri, S.	
	72	Pope, C.N.	43	Vafa, C.	0.88	Kogan, I.I.	18.7	Lee, H.W./Myung, Y.S.	
	69	Cvetic, M.	39	Odintsov, S.D.	0.84	Henneaux, M.	18.3	Schweigert, C./Fuchs, J.	
	68	Ferrara, S.	39	Kogan, I.I.	0.73	Douglas, M.R.	14.7	Ovrut, B.A./Waldram, D.	
	65	Vafa, C.	36	Proeyen, A.V.	0.67	Ferrara, S.	14.7	Kleihaus, B./Kunz, J.	
	65	Tseytlin, A.A.	35	Fre, P.	0.63	Vafa, C.	12.9	Mavromatos, N.E./Ellis, J.	
	65	Mavromatos, N.E.	35	Ellis, J.	0.60	Khare, A.	12.4	Kachru, S./Silverstein, E.	
	63	Witten, E.	35	Douglas, M.R.	0.58	Tseytlin, A.A.	11.7	Kakushadze, Z./Tye, S.H.H.	
	54	Townsend, P.K.	34	Lu, H.	0.58	Townsend, P.K.	11.6	Arefeva, I.Y./Volovich, I.V.	

TABLE II. The authors with the highest numbers of papers, numbers of coauthors, and betweenness, and strongest collaborations in astrophysics, condensed matter physics, and high-energy theory. The figures for betweenness have been divided by  $10^6$ . Full lists of the rankings of all the authors in these databases can be found on the world-wide web [53].

where  $\tau$  and  $\kappa$  are constants and C is fixed by the requirement of normalization—see Fig. 1. (The probability  $p_0$  of having zero papers is taken to be zero, since the names of scientists who have not written any papers do not appear in the database.) The exponential cutoff we attribute to the finite time window of five years used in this study which prevents any one author from publishing a very large number of papers. Lotka and subsequent authors who have confirmed his law have not usually used such a window.

It is interesting to speculate why the cutoff appears only in physics and not in computer science or biomedicine. Surely the five year window limits everyone's ability to publish very large numbers of papers, regardless of their area of specialization? For the case of MEDLINE one possible explanation is suggested by a brief inspection of the names of the most published authors. It turns out that most of the names of highly published authors in MEDLINE are Japanese (with a sprinkling of Chinese names among them). The top ten, for example, are Suzuki, T., Wang, Y., Suzuki, K., Takahashi, M., Nakamura, T., Tanaka, K., Tanaka, T.,

Wang, J., Suzuki, Y., and Takahashi, T. This may reflect differences in author attribution practices in Japanese biomedical research, but more probably these are simply common names, and these apparently highly published authors are each several different people who have been conflated in our analysis. Thus it is possible that there is not after all any fat tail in the distribution for the MEDLINE database, only the illusion of one produced by the large number of scientists with commonly occurring names. (This doesn't however explain why the tail appears to follow a power law.) This argument is strengthened by the sheer numbers of papers involved. T. Suzuki published, it appears, 1697 papers, or about one paper a day, including weekends and holidays, every day for the entire course of our five year study. This seems to be an improbably large output.

Interestingly, no national bias is seen in any of the other databases, and the names which top the list in physics and computer science are not common ones. (For example, the most published authors in the other three databases are Shelah, S. (Los Alamos Archive), Wolf, G. (SPIRES), and Bestavros, A. (NCSTRL).) Thus it is still

unclear why the NCSTRL database should have a powerlaw tail, though this database is small and it is possible that it does possess a cutoff in the productivity distribution which is just not visible because of the limits of the dataset.

For the SPIRES database, which is shown separately in the inset of the figure, neither pure nor truncated power law fits the data well, the histogram displaying a significant bump around the 100-paper mark. A possible explanation for this is that a small number of large collaborations published around this number of papers during the time-period studied. Since each author in such a collaboration is then credited with publishing a hundred papers, the statistics in the tail of the distribution can be substantially skewed by such practices.

In the first column of Table II, we list the most frequent authors in three subject-specific subdivisions of the Los Alamos Archive: astro-ph (astro-physics), cond-mat (condensed matter physics), and hep-th (high-energy theory). Although there is only space to list the top ten winners in this table, the entire list (and the corresponding lists for the other tables in this paper) can be found by the curious reader on the world-wide web [53].

### C. Numbers of authors per paper

Grossman and Ion [39] report that the average number of authors on papers in mathematics has increased steadily over the last sixty years, from a little over 1 to its current value of about 1.5. Higher numbers still seem to apply to current studies in the sciences. Purely theoretical papers appear to be typically the work of two scientists, with high-energy theory and computer science showing averages of 1.99 and 2.22 in our calculations. For databases covering experimental or partly experimental subject areas the averages are, not surprisingly, higher: 3.75 for biomedicine, 3.35 for astrophysics, 2.66 for condensed matter physics. The SPIRES high-energy physics database however shows the most startling results, with an average of 8.96 authors per paper, obviously a result of the presence of papers in the database written by very large collaborations. (Perhaps what is most surprising about this result is actually how small it is. The hundreds strong mega-collaborations of CERN and Fermilab are sufficiently diluted by theoretical and smaller experimental groups, that the number is only 9, and not 100.)

Distributions of numbers of authors per paper are shown in Fig. 2, and appear to have power-law tails with widely varying exponents of -6.2(3) (MEDLINE), -3.34(5) (Los Alamos Archive), -4.6(1) (NCSTRL), and -2.18(7) (SPIRES). The SPIRES data, which are again shown in a separate inset, also display a pronounced peak in the distribution around 200–500 authors. This peak presumably corresponds to the large experimental collaborations which dominate the upper end of this histogram.

The largest number of authors on a single paper was




FIG. 2. Histograms of the number of authors on papers in MEDLINE (circles), the Los Alamos Archive (squares), and NCSTRL (triangles). The dotted lines are the best fit power-law forms. Inset: the equivalent histogram for the SPIRES database, showing a clear peak in the 200 to 500 author range.

1681 (in high-energy physics, of course).

#### D. Numbers of collaborators per author

The differences between the various disciplines represented in the databases are emphasized still more by the numbers of collaborators that a scientist has, the total number of people with whom a scientist wrote papers during the five-year period. The average number of collaborators is markedly lower in the purely theoretical disciplines (3.87 in high-energy theory, 3.59 in computer science) than in the wholly or partly experimental ones (18.1 in biomedicine, 15.1 in astrophysics). But the SPIRES high-energy physics database takes the prize once again, with scientists having an impressive 173 collaborators, on average, over a five-year period. This clearly begs the question whether the high-energy coauthorship network can be considered an accurate representation of the highenergy physics community at all; it seems unlikely that an author could know 173 colleagues well.

The distributions of numbers of collaborators are shown in Fig. 3. In all cases they appear to have long tails, but only the SPIRES data (inset) fit a power-law distribution well, with a low measured exponent of -1.20. Note also the small peak in the SPIRES data around 700—presumably again a result of the presence of large collaborations.

For the other three databases, the distributions show some curvature. This may, as we have previously suggested [47], be the signature of an exponential cutoff, produced once again by the finite time window of the




FIG. 3. Histograms of the number of collaborators of authors in MEDLINE (circles), the Los Alamos Archive (squares), and NCSTRL (triangles). The dotted lines show how power-law distributions with exponents -2 and -3 would look on the same axes. Inset: the equivalent histogram for the SPIRES database, which is well fit by a single power law (dotted line).

study. (Redner [54] has suggested an alternative origin for the cutoff using growth models of networks—see Ref. [9].) An alternative possibility has been suggested by Barabási [55], based on models of the collaboration process. In one such model [48], the distribution of the number of collaborators of an author follows a power law with slope -2 initially, changing to slope -3 in the tail, the position of the crossover depending on the length of time for which the collaboration network has been evolving. We show slopes -2 and -3 as dotted lines on the figure, and the agreement with the curvature seen in the data is moderately good, particularly for the MEDLINE data. (For the Los Alamos and NCSTRL databases, the slope in the tail seems to be somewhat steeper than -3.)

Column 2 of Table II shows the authors in astro-ph, cond-mat, and hep-th with the largest numbers of collaborators. The winners in this race tend to be experimentalists, who conduct research in larger groups, though there are exceptions. The high-energy theory database of course contains only theorists, and the smaller numbers of collaborators reflects this.

#### E. Size of the giant component

In the theory of random graphs [23,56,57,58] it is known that there is a continuous phase transition with increasing density of edges in a graph at which a "giant component" forms, i.e., a connected subset of vertices whose size scales extensively. Well above this transition, in the region where the giant component exists, the giant

component usually fills a large portion of the graph, and all other components (i.e., connected subsets of vertices) are small, typically of size  $O(\log n)$ , where n is the total number of vertices. We see a situation reminiscent of this in all of the graphs studied here: a single large component of connected vertices which fills the majority of the volume of the graph, and a number of much smaller components filling the rest. In Table I we show the size of the giant component for each of our databases. both as total number of vertices and as a fraction of system size. In all cases the giant component fills around 80\% or 90\% of the total volume, except for high-energy theory and computer science, which give smaller figures. A possible explanation of these two anomalies may be that the corresponding databases give poorer coverage of their subjects. The hep-th high-energy database is quite widely used in the field, but overlaps to a large extent with the longer established SPIRES database, and it is possible that some authors neglect it for this reason [49]. The NCSTRL computer science database differs from the others in this study in that the preprints it contains are submitted by participating institutions, of which there are about 160. Preprints from institutions not participating are mostly left out of the database, and its coverage of the subject area is, as a result, incomplete.

The figure of 80–90% for the size of the giant component is a promising one. It indicates that the vast majority of scientists are connected via collaboration, and hence via personal contact, with the rest of their field. Despite the prevalence of journal publishing and conferences in the sciences, person-to-person contact is still of paramount importance in the communication of scientific information, and it is reasonable to suppose that the scientific enterprise would be significantly hindered if scientists were not so well connected to one another.

#### F. Clustering coefficients

An interesting idea circulating in social network theory currently is that of "transitivity," which, along with its sibling "structural balance," describes symmetry of interaction amongst trios of actors. "Transitivity" has a different meaning in sociology from its meaning in mathematics and physics, although the two are related. It refers to the extent to which the existence of ties between actors A and B and between actors B and C implies a tie between A and C. The transitivity, or more precisely the fraction of transitive triples, is that fraction of connected triples of vertices which also form "triangles" of interaction. Here a connected triple means an actor who is connected to two others. In the physics literature, this quantity is usually called the clustering coefficient C [4], and can be written

$$C = \frac{3 \times \text{ number of triangles on the graph}}{\text{number of connected triples of vertices}}.$$
 (2)

The factor of three in the numerator compensates for the fact that each complete triangle of three vertices contributes three connected triples, one centered on each of the three vertices, and ensures that C = 1 on a completely connected graph. On all unipartite random graphs  $C = O(n^{-1})$  [4,23], where n is the number of vertices, and hence goes to zero in the limit of large graph size. In social networks it is believed that the clustering coefficient will take a non-zero value even in very large networks, because there is a finite (and probably quite large) probability that two people will be acquainted if they have another acquaintance in common. This is a hypothesis we can test with our collaboration networks. In Table I we show values of the clustering coefficient C, calculated from Eq. (2), for each of the databases studied, and as we see, the values are indeed large, as large as 0.7 in the case of the SPIRES database, and around 0.3 or 0.4 for most of the others.

There are a number of possible explanations for these high values of C. First of all, it may be that they indicate simply that collaborations of three or more people are common in science. Every paper which has three authors clearly contributes a triangle to the numerator of Eq. (2) and hence increases the clustering coefficient. This is, in a sense, a "trivial" form of clustering, although it is by no means socially uninteresting.

In fact it turns out that this effect can account for some but not all of the clustering seen in our graphs. One can construct a random graph model of a collaboration network which mimics the trivial clustering effect, and the results indicate that only about a half of the clustering which we see is a result of authors collaborating in groups of three or more [23]. The rest of the clustering must have a social explanation, and there are some obvious possibilities:

- A scientist may collaborate with two colleagues individually, who may then become acquainted with one another through their common collaborator, and so end up collaborating themselves. This is the usual explanation for transitivity in acquaintance networks [1].
- 2. Three scientists may all revolve in the same circles—read the same journals, attend the same conferences—and, as a result, independently start up separate collaborations in pairs, and so contribute to the value of C, although only the workings of the community, and not any specific person, is responsible for introducing them.
- 3. As a special case of the previous possibility—and perhaps the most likely case—three scientists may all work at the same institution, and as a result may collaborate with one another in pairs.

Interesting studies could no doubt be made of these processes by combining our network data with data on, for instance, institutional affiliations of scientists. Such studies are, however, perhaps better left to social scientists and the social science journals.

The clustering coefficient of the MEDLINE database is worthy of brief mention, since its value is far smaller than those for the other databases. One possible explanation of this comes from the unusual social structure of biomedical research, which, unlike the other sciences, has traditionally been organized into laboratories, each with a "principal investigator" supervising a large number of postdocs, students, and technicians working on different projects. This organization produces a tree-like hierarchy of collaborative ties with fewer interactions within levels of the tree than between them. A tree has no loops in it, and hence no triangles to contribute to the clustering coefficient. Although the biomedicine hierarchy is certainly not a perfect tree, it may be sufficiently tree-like for the difference to show up in the value of C. Another possible explanation comes from the generous tradition of authorship in the biomedical sciences. It is common, for example, for a researcher to be made a coauthor of a paper in return for synthesizing reagents used in an experimental procedure. Such a researcher will in many cases have a less than average likelihood of developing new collaborations with their collaborators' friends, and therefore of increasing the clustering coefficient.

# IV. DISTANCES AND CENTRALITY

The basic statistics of the previous section are certainly of importance, particularly for the construction of models such as those of Refs. [4,12,13,23], but there is much more that we can do with our collaboration networks. In this section, we look at some simple but useful measures of network structure, concentrating on measures having to do with paths between vertices in the network. In Section V we discuss some shortcomings of these measures, and construct some new and more complex measures which may better reflect true collaboration patterns.

#### A. Shortest paths

A fundamental concept in graph theory is the "geodesic," or shortest path of vertices and edges which links two given vertices. There may not be a unique geodesic between two vertices: there may be two or more shortest paths, which may or may not share some vertices. The geodesic(s) between two vertices i and j can be calculated in time O(m), where m is the number of edges in the graph, using the following algorithm, which is a modified form of the standard breadth-first search [59].

1. Assign vertex j distance zero, to indicate that it is zero steps away from itself, and set  $d \leftarrow 0$ .




FIG. 4. The geodesics, or shortest paths, in the collaboration network of physicists between Duncan Watts and Laszlo Barabási.

- 2. For each vertex k whose assigned distance is d, follow each attached edge to the vertex l at its other end and if l has not already been assigned a distance, assign it distance d+1. Declare k to be a predecessor of l.
- 3. If l has already been assigned distance d + 1, then there is no need to do this again, but k is still declared a predecessor of l.
- 4. Set  $d \leftarrow d + 1$ .
- 5. Repeat from step (2) until there are no unassigned sites left.

Now the shortest path (if there is one) from i to j is the path you get by stepping from i to its predecessor, and then to the predecessor of each successive site until j is reached. If a site has two or more predecessors, then there are two or more shortest paths, each of which must be followed separately if we wish to know all shortest paths from i to j.

In Fig. 4 we show the shortest paths of known collaborations between two of the author's colleagues, Duncan Watts (Columbia) and Laszlo Barabási (Notre Dame), both of whom work on social networks of various kinds. It is interesting to note that, although the two scientists in question are well acquainted both personally and with one another's work, the shortest path between them does not run entirely through other collaborations in the field. (For example, the connection between the present author and Juan Pedro Garrahan results from our coauthorship of a paper on spin glasses.) Although this may at first sight appear odd, it is probably in fact a good sign. It indicates that workers in the field come from different

scientific "camps," rather than all descending intellectually from a single group or institution. This presumably increases the likelihood that those workers will express independent opinions on the open questions of the field, rather than merely spouting slight variations on the same underlying doctrine.

A database which would allow one conveniently and quickly to extract shortest paths between scientists in this way might have some practical use. Kautz et al. [60] have constructed a web-based system which does just this for computer scientists, with the idea that such a system might help to create new professional contacts by providing a "referral chain" of intermediate scientists through whom contact may be established.

#### B. Betweenness and funneling

A quantity of interest in many social network studies is the "betweenness" of an actor i, which is defined as the total number of shortest paths between pairs of actors which pass through i. This quantity is an indicator of who are the most influential people in the network, the ones who control the flow of information between most others. The vertices with high betweenness also result in the largest increase in typical distance between others when they are removed [1].

Naively, one might think that betweenness would take time of order  $O(mn^2)$  to calculate for all vertices, since there are  $O(n^2)$  shortest paths to be considered, each of which takes time O(m) to calculate, and standard network analysis packages such as UCInet [61] indeed use  $O(mn^2)$  algorithms at present. However, since breadth-first search algorithms can calculate n shortest paths in time O(m), it seems possible that one might be able to calculate betweenness for all vertices in time O(mn). Here we present a simple new algorithm which performs this calculation. Being enormously faster than the standard packages, it makes possible exhaustive calculation of betweenness on the very large graphs studied here. The algorithm is as follows.

- 1. The shortest paths from a vertex i to every other vertex are calculated using breadth-first search as described above, taking time O(m).
- 2. A variable  $b_k$ , taking the initial value 1, is assigned to each vertex k.
- 3. Going through the vertices k in order of their distance from i, starting from the furthest, the value of  $b_k$  is added to the corresponding variable on the predecessor vertex of k. If k has more than one predecessor, then  $b_k$  is divided equally between them. This means that if there are two shortest paths between a pair of vertices, the vertices along those paths are given betweenness of  $\frac{1}{2}$  each.

4. When we have gone through all vertices in this fashion, the resulting values of the variables  $b_k$  represent the number of geodesic paths to vertex i which run through each vertex on the lattice, with the end-points of each path being counted as part of the path. To calculate the betweenness for all paths, the  $b_k$  are added to a running score maintained for each site and the entire calculation is repeated for each of the n possible values of i. The final running scores are precisely the betweenness of each of the n vertices.

In column 3 of Table II we show the ten highest betweennesses in the astro-ph, cond-mat, and hep-th subdivisions of the Los Alamos Archive. While we leave it to the knowledgeable reader to decide whether the scientists named are indeed pivotal figures in their respective fields, we do notice one interesting feature of the results. The betweenness measure gives very clear winners in the competition: the individuals with highest betweenness are well ahead of those with second highest, who are in turn well ahead of those with third highest, and so on. This same phenomenon has been noted in other social networks [1].

Strogatz [62] has raised another interesting question about social networks which we can address using our betweenness algorithm: are all of your collaborators equally important for your connection to the rest of the world, or do most paths from others to you pass through just a few of your collaborators? One could certainly imagine that the latter might be true. Collaboration with just one or two senior or famous members of one's field could easily establish short paths to a large part of the collaboration network, and all of those short paths would go through those one or two members. Strogatz calls this effect "funneling." Since our algorithm, as a part of its operation, calculates the vertices through which each geodesic path to a specified actor i passes, it is a trivial modification to calculate also how many of those geodesic paths pass through each of the immediate collaborators of that actor, and hence to use it to look for funneling.

Our collaboration networks, it turns out, show strong funneling. For most people, their top few collaborators lie on most of the paths between themselves and the rest of the network. The rest of their collaborators, no matter how numerous, account for only a small number of paths. Consider, for example, the present author. Out of the 44 000 scientists in the giant component of the Los Alamos Archive collaboration network, 31 000 paths from them to me, about 70%, pass through just two of my collaborators, Chris Henley and Juanpe Garrahan. Another 13 000, most of the remainder, pass through the next four collaborators. The remaining five account for a mere 1% of the total.

To give a more quantitative impression of the funneling effect, we show in Fig. 5 the average fraction of paths that pass through the top 10 collaborators of an author, averaged over all authors in the giant component of the




FIG. 5. The average percentage of paths from other scientists to a given scientist which pass through each collaborator of that scientist, ranked in decreasing order. The plot is for the Los Alamos Archive network, although similar results are found for other networks.

Los Alamos database. The figure shows for example that on average 64% of one's shortest paths to other scientists pass through one's top-ranked collaborator. Another 17% pass through the second-ranked one. The top 10 shown in the figure account for 98% of all paths.

That one's top few acquaintances account for most of one's shortest paths to the rest of the world has been noted before in other contexts. For example, Stanley Milgram, in his famous "small world" experiment [63], noted that most of the paths he found to a particular target person in an acquaintance network went through just one or two acquaintances of the target. He called these acquaintances "sociometric superstars."

# C. Average distances

Breadth-first search allows to us calculate exhaustively the lengths of the shortest paths from every vertex on a graph to every other (if such a path exists) in time O(mn). We have done this for each of the networks studied here and averaged these distances to find the average distance between any pair of (connected) authors in each of the subject fields studied. These figures are given in the penultimate row of Table I. As the table shows, these figures are all quite small: they vary from 4.0 for SPIRES to 9.7 for NCSTRL, although this last figure may be artificially inflated by the poor coverage of this database discussed in Section IIIE. At any rate, all the figures are very small compared to the number of vertices in the corresponding databases. This "small world" effect, first described by Milgram [63], is, like the existence of the giant component, probably a good sign for




FIG. 6. The point in the center of the figure represents the author of the paper you are reading, the first ring his collaborators, and the second ring their collaborators. Collaborative ties between members of the same ring, of which there are many, have been omitted from the figure for clarity.

science; it shows that scientific information—discoveries, experimental results, theories—will not have far to travel through the network of scientific acquaintance to reach the ears of those who can benefit by them. Even the maximum distances between scientists in these networks, shown in the last row of the table, are not very large, the longest path in any of the networks being just 31 steps long, again in the NCSTRL database, which may have poorer coverage than the others.

The explanation of the small world effect is simple. Consider Fig. 6, which shows all the collaborators of the present author (in all subjects, not just physics), and all the collaborators of those collaborators—all my first and second neighbors in the collaboration network. As the figure shows, I have 26 first neighbors, but 623 second neighbors. The "radius" of the whole network around me is reached when the number of neighbors within that

radius equals the number of scientists in the giant component of the network, and if the increase in numbers of neighbors with distance continues at the impressive rate shown in the figure, it will not take many steps to reach this point.

This simple idea is borne out by theory. In almost all networks, the number of kth-nearest neighbors of a typical vertex increases exponentially with k, and hence the average distance between pairs of vertices  $\ell$  scales logarithmically with n the number of vertices. In a standard random graph [56,57], for instance,  $\ell = \log n/\log z$ , where z is the average degree of a vertex, the average number of collaborators in our terminology. In the more general class of random graphs in which the distribution of vertex degrees is arbitrary [58], rather than Poissonian as in the standard case, the equivalent expression is [23]




FIG. 7. Average distance between pairs of scientists in the various networks, plotted against average distance on a random graph of the same size and degree distribution. The dotted line shows where the points would fall if measured and predicted results agreed perfectly. The solid line is the best straight-line fit to the data.

$$\ell = \frac{\log(n/z_1)}{\log(z_2/z_1)} + 1,\tag{3}$$

where  $z_1$  and  $z_2$  are the average numbers of first and second neighbors of a vertex. It is in fact quite difficult to find a network which does not show logarithmic behavior—such networks are a set of measure zero in the limit of large n. Thus the presence of the small world effect is hardly a surprise to anyone familiar with graph theory. However, it would be nice to demonstrate explicitly the presence of logarithmic scaling in our networks. Figure 7 does this in a crude fashion. In this figure we have plotted the measured value of  $\ell$ , as given in Table I, against the value given by Eq. (3) for each of our four databases, along with separate points for nine of the subject-specific subdivisions of the Los Alamos Archive. As the figure shows, the correlation between measured and predicted values is quite good. A straight-line fit has  $R^2 = 0.86$ , rising to  $R^2 = 0.95$  if the NCSTRL database, with its incomplete coverage, is excluded (the downwardpointing triangle in the figure).

Figure 7 needs to be taken with a pinch of salt. Its construction implicitly assumes that the different networks are statistically similar to one another and to random graphs with the same distributions of vertex degree, an assumption which is almost certainly not correct. In practice, however, the measured value of  $\ell$  seems to follow Eq. (3) quite closely. Turning this observation around, our results also imply that it is possible to make a good prediction of the typical vertex–vertex distance in a network by making only local measurements of the average numbers of neighbors that vertices have. If this result ex-




FIG. 8. Scatter plot of the mean distance from each physicist in the giant component of the Los Alamos Archive data to all others as a function of number of collaborators. Inset: the same data averaged vertically over all authors having the same number of collaborators.

tends beyond coauthorship networks to other social networks, it could be of some importance for empirical work, where the ability to calculate global properties of a network by making only local measurements could save large amounts of effort.

We can also trivially use our breadth-first search algorithm to calculate the average distance from a single vertex to all other vertices in the giant component. This average is essentially the same as the quantity known as "closeness" to social network analysts. Like betweenness it is also a measure, in some sense, of the centrality of a vertex—authors with low values of this average will, it is assumed, be the first to learn new information, and information originating with them will reach others quicker than information originating with other sources. Average distance is thus a measure of centrality of an actor in terms of their access to information, unlike betweenness which is a measure of an actor's control over information flowing between others.

Calculating average distance for many networks returns results which look sensible to the observer. Calculations for the network of collaborations between movie actors, for instance, gives small average distances for actors who are famous—ones many of us will have heard of. Interestingly, however, performing the same calculation for our scientific collaboration networks does not return sensible results. For example, one finds that the people at the top of the list are always experimentalists. This, you might think, is not such a bad thing: perhaps the experimentalists are better connected people? In a sense, in fact, it turns out that they are. In Fig. 8 we show the average distance from scientists in the Los Alamos Archive to all others in the giant component as a function of their number of collaborators. As the figure shows, there is a

trend towards shorter average distance as the number of collaborators becomes large. This trend is clearer still in the inset, where we show the same data averaged over all authors who have the same number of collaborators. Since experimentalists work in large groups, it is not surprising to learn that they tend to have shorter average distances to other scientists.

But this brings up an interesting question, one that we touched upon in Section II: while most pairs of people who have written a paper together will know one another reasonably well, there are exceptions. On a high-energy physics paper with 1000 coauthors, for instance, it is unlikely that every one of the 499 500 possible acquaintanceships between pairs of those authors will actually be realized. Our closeness measure does not take into account the tendency for collaborators in large groups not to know one another, or to know one another less well. In the next section we study a more sophisticated form of collaboration network which does do this.

#### V. WEIGHTED COLLABORATION NETWORKS

There is more information present in the databases used here than in the simple networks we have constructed from them, which tell us only whether scientists have collaborated or not [64]. In particular, we know on how many papers each pair of scientists has collaborated during the period of the study, and how many other coauthors they had on each of those papers. We can use this information to make an estimate of the strength of collaborative ties.

First of all, it is probably the case, as we pointed out at the end of the previous section, that two scientists whose names appear on a paper together with many other coauthors know one another less well on average than two who were the sole authors of a paper. The extreme case of a very large collaboration which we discussed illustrates this point forcefully, but it probably applies to smaller collaborations too. Even on a paper with four or five authors, the authors probably know one another less well on average than authors from a smaller collaboration. To account for this effect, we weight collaborative ties inversely according to the number of coauthors as follows. Suppose a scientist collaborates on the writing of a paper which has n authors in total, i.e., he or she has n-1 coauthors on that paper. Then we assume that he or she is acquainted with each coauthor 1/(n-1) times as well, on average, as if there were only one coauthor. One can imagine this as meaning that the scientist divides his or her time equally between the n-1 coauthors. This is obviously only a rough approximation: in reality a scientist spends more time with some coauthors than with others. However, in the absence of other data, it is the obvious first approximation to make [65].

Second, authors who have written many papers together will, we assume, know one another better on aver-




FIG. 9. Authors A and B have coauthored three papers together, labeled 1, 2, and 3, which had respectively four, two, and three authors. The tie between A and B accordingly accrues weight  $\frac{1}{3}$ , 1, and  $\frac{1}{2}$  from the three papers, for a total weight of  $\frac{11}{6}$ .

age than those who have written few papers together. To account for this, we add together the strengths of the ties derived from each of the papers written by a particular pair of individuals [66]. Thus, if  $\delta_i^k$  is one if scientist i was a coauthor of paper k and zero otherwise, then our weight  $w_{ij}$  representing the strength of the collaboration (if any) between scientists i and j is

$$w_{ij} = \sum_{k} \frac{\delta_i^k \delta_j^k}{n_k - 1},\tag{4}$$

where  $n_k$  is the number of coauthors of paper k and we explicitly exclude from our sums all single-author papers. (They do not contribute to the coauthorship network, and their inclusion in Eq. (4) would make  $w_{ij}$  ill-defined.) We illustrate this measure for a simple example in Fig. 9.

Note that the equivalent of vertex degree for our weighted network—i.e., the sum of the weights for each of an individual's collaborations—is now just equal to the number of papers they have coauthored with others:

$$\sum_{j(\neq i)} w_{ij} = \sum_{k} \sum_{j(\neq i)} \frac{\delta_i^k \delta_j^k}{n_k - 1} = \sum_{k} \delta_i^k.$$
 (5)

In Fig. 10 we show as an example collaborations between Gerard Barkema (one of the present author's frequent collaborators), and all of his collaborators in the Los Alamos Archive for the past five years. Lines between points represent collaborations, with their thickness proportional to the weights  $w_{ij}$  of Eq. (4). As the figure shows, Barkema has collaborated closely with myself and with Normand Mousseau, and less closely with a number of others. Also, two of his collaborators, John Cardy and Gesualdo Delfino have collaborated quite closely with one another.




FIG. 10. Gerard Barkema and his collaborators, with lines representing collaborations whose thickness is proportional to our estimate, Eq. (4), of the strength of the corresponding tie.

In the last column of Table II we show the pairs of collaborators who have the strongest collaborative ties in three subdivisions of the Los Alamos Archive.

We have used our weighted collaboration graphs to calculate distances between scientists. In this simple calculation we assumed that the distance between authors is just the inverse of the weight of their collaborative tie. Thus if one pair of authors know one another twice as well as another pair, the distance between them is half as great. Calculating minimum distances between vertices on a weighted graph such as this cannot be done using the breadth-first search algorithm of Section IV A, since the shortest weighted path may not be the shortest in terms of number of steps on the unweighted network. Instead we use Dijkstra's algorithm [67], which calculates all distances from a given starting vertex i as follows.

- 1. Distances from vertex i are stored for each vertex and each is labeled "exact," meaning we have calculated that distance exactly, or "estimated," meaning we have made an estimate of the distance, but that estimate may be wrong. We start by assigning an estimated distance of  $\infty$  to all vertices except vertex i to which we assign an estimated distance of zero. (We know the latter to be exactly correct, but for the moment we consider it merely "estimated.")
- 2. From the set of vertices whose distances from *i* are currently marked "estimated," choose the one with the lowest estimated distance, and mark this "exact."
- 3. Calculate the distance from that vertex to each of its immediate neighbors in the network by adding

to its distance the length of the edges leading to those neighbors. Any of these distances which is shorter than a current estimated distance for the same vertex supersedes that current value and becomes the new estimated distance for the vertex.

4. Repeat from step (2), until no "estimated" vertices remain.

A naive implementation of this algorithm takes time O(mn) to calculate distances from a single vertex to all others, or  $O(mn^2)$  to calculate all pairwise distances. One of the factors of n, however, arises because it takes time O(n) to search through the vertices to find the one with the smallest estimated distance. This operation can be improved by storing the estimated distances in a binary heap (a partially ordered binary tree with its smallest entry at its root). We can find the smallest distance in such a heap in time O(1), and add and remove entries in time  $O(\log n)$ . This speeds up the operation of the algorithm to  $O(mn\log n)$ , making the calculation feasible for the large networks studied here.

It is in theory possible to generalize any of the calculations of Section IV to the weighted collaboration graph using this algorithm and variations on it. For example, we can find shortest paths between specified pairs of scientists, as a way of establishing referrals. We can calculate the weighted equivalent of betweenness by a simple adaption of our fast algorithm of Section IVB—we use Dijkstra's algorithm to establish the hierarchy of predecessors of vertices and then count paths through vertices exactly as before. We can also study the weighted version of the "funneling" effect using the same algorithm. Here we carry out just one calculation explicitly to demonstrate the idea; we calculate the weighted version of the distance centrality measure of Section IVC, i.e., the average weighted distance from a vertex to all others. In Table III we show the winners in this particular popularity contest, along with their numbers of collaborators and papers in the database. Many of the scientists who score highly here do indeed appear to be well connected individuals. For example, number 1 best connected astrophysicist, Martin Rees, is the Astronomer Royal of Great Britain. (On being informed of this latest honor, Prof. Rees is reported as replying, "I'm certainly relieved not to be the most disconnected astrophysicist" [68].)

What is interesting to note however (apart from non-chalantly checking to see if one has made it into the top 10) is that sheer number of collaborators is no longer a necessary prerequisite for being well-connected in this sense (although some of the scientists listed do have a large number of collaborators). The case of D. Youm is particularly startling, since Youm has only three collaborators listed in the database, but nonetheless is fifth best connected high-energy theorist (out of eight thousand), because those three collaborators are themselves very well connected, and because their ties to Youm are very strong. Experimentalists no longer dominate

	rank	name	co-workers	papers
astro-ph:	1	Rees, M. J.	31	36
	2	Miralda-Escude, J.	36	34
	3	Fabian, A. C.	156	112
	4	Waxman, E.	15	30
	5	Celotti, A.	119	45
	6	Narayan, R.	65	58
	7	Loeb, A.	33	64
	8	Reynolds, C. S.	45	38
	9	Hernquist, L.	62	80
	10	Gould, A.	76	79
cond-mat:	1	Fisher, M. P. A.	21	35
	2	Balents, L.	24	29
	3	MacDonald, A. H.	64	70
	4	Senthil, T.	9	13
	5	Das Sarma, S.	51	75
	6	Millis, A. J.	43	37
	7	Ioffe, L. B.	16	27
	8	Sachdev, S.	28	44
	9	Lee, P. A.	24	34
	10	Jungwirth, T.	27	17
hep-th:	1	Cvetic, M.	33	69
	2	Behrndt, K.	22	41
	3	Tseytlin, A. A.	22	65
	4	Bergshoeff, E.	21	39
	5	Youm, D.	3	30
	6	Lu, H.	34	73
	7	Klebanov, I. R.	29	47
	8	Townsend, P. K.	31	54
	9	Pope, C. N.	33	72
	10	Larsen, F.	11	27

TABLE III. The ten best connected individuals in three of the communities studied here, calculated using the weighted distance measure described in the text.

the field, although the well-connected amongst them still score highly.

Note that the number of papers for each of the well-connected scientists listed is high. Having written a large number of papers is, as it rightly should be, always a good way of becoming well connected. Whether you write many papers with many different authors, or many with a few, writing many papers will put you in touch with your peers.

#### VI. CONCLUSIONS

In this paper we have studied social networks of scientists in which the actors are authors of scientific papers, and a tie between two authors represents coauthorship of one or more papers. Drawing on the lists of authors in four databases of papers in physics, biomedical research, and computer science, we have constructed explicit networks for papers appearing between the begin-

ning of 1995 and the end of 1999. We have cataloged a large number of basic statistics for our networks, including typical numbers of papers per author, authors per paper, and numbers of collaborators per author in the various fields. We also note that the distributions of these quantities roughly follow a power-law form, although there are some deviations which may be due to the finite time window used for the study.

We have also looked at a variety of non-local properties of our networks. We find that typical distances between pairs of authors through the networks are small—the networks form a "small world" in the sense discussed by Milgram—and that they scale logarithmically with total number of authors in a network, in reasonable agreement with the predictions of random graph models. We have introduced a new algorithm for counting the number of shortest paths between vertices on a graph which pass through each other vertex, which is one order of system size faster than previous algorithms, and used this to calculate the so-called "betweenness" measure of centrality on our graphs. We also show that for most authors the bulk of the paths between them and other scientists in the network go through just one or two or their collaborators, an effect which Strogatz has dubbed "funneling."

We have suggested a measure of the closeness of collaborative ties which takes account of the number of papers a given pair of scientists have written together, as well as the number of other coauthors with whom they wrote them. Using this measure we have added weightings to our collaboration networks to represent closeness and used the resulting networks to find those scientists who have the shortest average distance to others. Generalization of the betweenness and funneling calculations to these weighted networks is also straightforward.

The calculations presented in this paper inevitably represent only a small part of the investigations which could be conducted using large network datasets such as these. Indeed, to a large extent, the purpose of this paper is simply to alert other researchers to the presence of a valuable source of network data in bibliometric databases, and to provide a first demonstration of the kind of results which can be derived from them. We hope, given the high current level of interest in network phenomena, that others will find many further uses for collaboration network data.

## ACKNOWLEDGEMENTS

The author would particularly like to thank Paul Ginsparg for his invaluable help in obtaining the data used for this study. The data used were generously made available by Oleg Khovayko, David Lipman, and Grigoriy Starchenko (MEDLINE), Paul Ginsparg and Geoffrey West (Los Alamos E-print Archive), Heath O'Connell (SPIRES), and Carl Lagoze (NCSTRL). The Los Alamos E-print Archive is funded by the NSF under grant num-

ber PHY-9413208. NCSTRL is funded through the DARPA/CNRI test suites program under DARPA grant N66001-98-1-8908.

The author also would like to thank Steve Strogatz for suggesting the "funneling effect" calculation of Section IV B, Laszlo Barabási for making available an early version of Ref. [48], and Dave Alderson, Laszlo Barabási, Sankar Das Sarma, Paul Ginsparg, Rick Grannis, Jon Kleinberg, Laura Landweber, Vito Latora, Hazel Muir, Sid Redner, Ronald Rousseau, Steve Strogatz, Duncan Watts, and Doug White for many useful comments and suggestions. This work was funded in part by a grant from Intel Corporation to the Santa Fe Institute's Network Dynamics Program.

Note added: After this work was completed the author learned of a recent preprint by Brandes [69] in which an algorithm for calculating betweenness similar to ours is described. The author is grateful to Rick Grannis for bringing this to his attention.

- S. Wasserman and K. Faust, Social Network Analysis, Cambridge University Press, Cambridge (1994).
- [2] J. Scott, Social Network Analysis: A Handbook, 2nd Edition, Sage Publications, London (2000).
- [3] M. E. J. Newman, "Models of the small world," J. Stat. Phys. 101, 819–841 (2000).
- [4] D. J. Watts and S. H. Strogatz, "Collective dynamics of 'small-world' networks," *Nature* 393, 440–442 (1998).
- [5] A.-L. Barabási and R. Albert, "Emergence of scaling in random networks," Science 286, 509-512 (1999).
- [6] R. Kumar, P. Raghavan, S. Rajagopalan, D. Sivakumar, A. Tomkins, E. Upfal, "Stochastic models for the web graph," in Proceedings of the IEEE Symposium on Foundations of Computer Science (2000).
- [7] C. F. Moukarzel, "Spreading and shortest paths in systems 10nwith sparse long-range connections," *Phys. Rev. E* 60, 6263–6266 (1999).
- [8] S. N. Dorogovtsev and J. F. F. Mendes, "Exactly solvable small-world network," *Europhys. Lett.* 50, 1–7 (2000).
- [9] P. L. Krapivsky, S. Redner, and F. Leyvraz, "Connectivity of growing random networks," *Phys. Rev. Lett.* 85, 4629– 4632 (2000).
- [10] S. N. Dorogovtsev, J. F. F. Mendes, and A. N. Samukhin, "Structure of growing networks with preferential linking," *Phys. Rev. Lett.* 85, 4633–4636 (2000).
- [11] R. V. Kulkarni, E. Almaas, and D. Stroud, "Exact results and scaling properties of small-world networks," *Phys. Rev.* E 61, 4268–4271 (2000).
- [12] J. M. Kleinberg, "Navigation in a small world," *Nature* 406, 845 (2000)
- [13] R. Albert, H. Jeong, and A.-L. Barabási, "Diameter of the world-wide web," *Nature* 401, 130–131 (1999).
- [14] M. Barthélémy and L. A. N. Amaral, "Small-world networks: Evidence for a crossover picture," Phys. Rev. Lett.

- 82, 3180-3183 (1999).
- [15] M. E. J. Newman and D. J. Watts, "Renormalization group analysis of the small-world network model," *Phys. Lett.* A 263, 341–346 (1999); "Scaling and percolation in the small-world network model," *Phys. Rev. E* 60, 7332–7342 (1999).
- [16] M. A. de Menezes, C. F. Moukarzel, and T. J. P. Penna, "First-order transition in small-world networks," *Euro-phys. Lett.* 50, 574–579 (2000).
- [17] A.-L. Barabási, R. Albert, and H. Jeong, "Mean-field theory for scale-free random networks," *Physica* 272, 173–187 (1999).
- [18] M. E. J. Newman, C. Moore and D. J. Watts, "Mean-field solution of the small-world network model," *Phys. Rev. Lett.* 84, 3201–3204 (2000).
- [19] C. Moore and M. E. J. Newman, "Epidemics and percolation in small-world networks," *Phys. Rev. E* 61, 5678–5682 (2000); "Exact solution of site and bond percolation on small-world networks," *Phys. Rev. E* 62, 7059–7064 (2000).
- [20] R. Cohen, K. Erez, D. ben-Avraham, and S. Havlin, "Resilience of the Internet to random breakdowns," *Phys. Rev. Lett.* 85, 4626–4628 (2000).
- [21] D. S. Callaway, M. E. J. Newman, S. H. Strogatz, and D. J. Watts, "Network robustness and fragility: Percolation on random graphs," *Phys. Rev. Lett.*, in press.
- [22] A. Barrat and M. Weigt, "On the properties of small-world network models," Eur. Phys. J. B 13, 547–560 (2000).
- [23] M. E. J. Newman, S. H. Strogatz, and D. J. Watts, "Random graphs with arbitrary degree distribution and their applications," cond-mat/0007235/.
- [24] P. Mariolis, "Interlocking directorates and control of corporations: The theory of bank control," *Social Science Quarterly* **56**, 425–439 (1975).
- [25] J. Galaskiewicz and P. V. Marsden, "Interorganizational resource networks: Formal patterns of overlap," *Social Sci*ence Research 7, 89–107 (1978).
- [26] J. F. Padgett and C. K. Ansell, "Robust action and the rise of the Medici, 1400–1434," American Journal of Sociology 98, 1259–1319 (1993).
- [27] C. C. Foster, A. Rapoport, and C. J. Orwant, "A study of a large sociogram: Elimination of free parameters," Behavioural Science 8, 56–65 (1963).
- [28] T. J. Fararo and M. Sunshine, A Study of a Biased Friendship Network, Syracuse University Press, Syracuse (1964).
- [29] H. R. Bernard, P. D. Kilworth, M. J. Evans, C. Mc-Carty, and G. A. Selley, "Studying social relations crossculturally," *Ethnology* 2, 155–179 (1988).
- [30] A. Broder, R. Kumar, F. Maghoul, P. Raghavan, S. Rajagopalan, R. Stata, A. Tomkins, and J. Wiener, "Graph structure in the web," *Computer Networks* 33, 309–320 (2000).
- [31] R. Albert, H. Jeong, and A.-L. Barabási, "Error and attack tolerance of complex networks," *Nature* 406, 378–382 (2000).
- [32] J. Abello, A. Buchsbaum, and J. Westbrook, "A functional approach to external graph algorithms," in *Proceedings of the Sixth European Symposium on Algorithms* (1998).
- [33] L. A. N. Amaral, A. Scala, M. Barthélémy, and H. E. Stanley, "Classes of small-world networks," *Proc. Natl. Acad.*

- Sci. 97, 11149-11152 (2000).
- [34] A. Davis, B. B. Gardner, and M. R. Gardner, Deep South, University of Chicago Press, Chicago (1941).
- [35] G. F. Davis and H. R. Greve, "Corporate elite networks and governance changes in the 1980s," *American Journal* of Sociology 103, 1–37 (1997).
- [36] http://www.imdb.com/
- [37] If one considers the world-wide web to be a social network (an issue of some debate—see B. Wellman, J. Salaff, D. Dimitrova, L. Garton, M. Gulia and C. Haythorn-thwaite, "Computer networks as social networks," *Annual Review of Sociology* 22, 213–238 (1996)), then it certainly dwarfs the networks studied here, having, it is estimated, about a billion vertices at the time of writing.
- [38] P. Hoffman, The Man Who Loved Only Numbers, Hyperion, New York (1998).
- [39] J. W. Grossman and P. D. F. Ion, "On a portion of the well-known collaboration graph," Congressus Numerantium 108, 129–131 (1995).
- [40] V. Batagelj and A. Mrvar, "Some analyses of Erdös collaboration graph," Social Networks 22, 173–186 (2000)
- [41] L. Egghe and R. Rousseau, *Introduction to Informetrics*, Elsevier, Amsterdam (1990).
- [42] O. Persson and M. Beckmann, "Locating the network of interacting authors in scientific specialties," *Scientometrics* 33, 351–366 (1995).
- [43] G. Melin and O. Persson, "Studying research collaboration using co-authorships," Scientometrics 36, 363–377 (1996).
- [44] H. Kretschmer, "Bekannte Regeln—kristallisiert im Koautorschaftsnetzwerk," Zeitschrift für Sozialpsychologie 29, 307–324 (1998).
- [45] Y. Ding, S. Foo, and G. Chowdhury, "A bibliometric analysis of collaboration in the field of information retrieval," *International Information and Library Review* 30, 367–376 (1999).
- [46] There has been a considerable amount of work on networks of citations between papers, both in information science (see Ref. [41], for instance), and more recently in physics (see S. Redner, "How popular is your paper? An empirical study of the citation distribution," Eur. Phys. J. B 4, 131–134 (1998)). In these networks, the actors are papers and the (directed) ties between them are citations of one paper by another. However, while citation data are plentiful and many results are known, citation networks are not true social networks since the authors of two papers need not be acquainted for one of them to cite the other's work. On the other hand, citation probably does imply a certain congruence in the subject matter of the two papers, which although not a social relationship, may certainly be of interest for other reasons.
- [47] M. E. J. Newman, "The structure of scientific collaboration networks," *Proc. Natl. Acad. Sci.*, in press.
- [48] A.-L. Barabási, H. Jeong, R. Ravasz, Z. Néda, T. Vicsek, and A. Schubert, "On the topology of scientific collaboration networks," preprint, Notre Dame (2000).
- [49] H. B. O'Connell, "Physicists thriving with paperless publishing," physics/0007040.
- [50] A. J. Lotka, "The frequency distribution of scientific production," J. Wash. Acad. Sci. 16, 317–323 (1926).
- [51] H. Voos, "Lotka and information science," Journal of the

- American Society for Information Science, July-August 1974, pp. 270–272.
- [52] M. L. Pao, "An empirical examination of Lotka's law," Journal of the American Society for Information Science, January 1986, pp. 26–33.
- [53] Complete tables of results for authors in the Los Alamos Archive can be found on the world-wide web at http://www.santafe.edu/~mark/collaboration/.
- [54] S. Redner, personal communication.
- [55] A.-L. Barabási, personal communication.
- [56] P. Erdös and A. Rényi, "On the evolution of random graphs," Publications of the Mathematical Institute of the Hungarian Academy of Sciences 5, 17–61 (1960).
- [57] B. Bollobás, Random Graphs, Academic Press, New York (1985).
- [58] M. Molloy and B. Reed, "A critical point for random graphs with a given degree sequence," Random Structures and Algorithms 6, 161–179 (1995); "The size of the giant component of a random graph with a given degree sequence," Combinatorics, Probability and Computing 7, 295–305 (1998).
- [59] R. Sedgewick, Algorithms, Addison-Wesley, Reading (1988).
- [60] H. Kautz, B. Selman, and M. Shah, "ReferralWeb: Combining social networks and collaborative filtering," Comm. ACM 40, 63–65 (1997).
- [61] http://www.analytictech.com/.
- [62] S. H. Strogatz, personal communication.
- [63] S. Milgram, "The small world problem," Psychology Today 2, 60–67 (1967).
- [64] A complete description of a collaboration network, or indeed any affiliation network, requires us to construct a bipartite graph or hypergraph of actors and the groups to which they belong [1,23]. For our present purposes however, such detailed representations are not necessary.
- [65] One can imagine using a measure of connectedness which weights authors more or less heavily depending on the order in which their names appear on a publication. We have not adopted this approach here however, since it will probably discriminate against those authors with names falling towards the end of the alphabet, who tend to find themselves at the ends of purely alphabetical author lists.
- [66] A weighted network of collaborations between movie actors, taking into account frequency of collaboration but not number of coworkers, has been studied in M. Marchiori and V. Latora, "Harmony in the small-world," *Physica A* 285, 539–546 (2000).
- [67] R. K. Ahuja, T. L. Magnanti, and J. H. Orlin, Network Flows: Theory, Algorithms, and Applications, Prentice Hall, Englewood Cliffs (1993).
- [68] H. Muir, "Let's do lunch," New Scientist, November 25, 2000, p. 10.
- [69] U. Brandes, "Faster evaluation of shortest-path based centrality indices," preprint, University of Konstanz (2000).