

WebSphere Cartridge Installation Guide

PREPARED FOR - FRIT

Table of Contents

1. Synopsis	1
2. OpenShift 2 WebSphere Gear Creation	2
2.1. Creating WebSphere Application Via the OpenShift Console	2
2.1.1. Login to the OpenShift Console	2
2.1.2. Click on "Create Your First Application Now"	2
2.1.3. Complete the Application Form	3
2.1.4. Create the Application & Access the WebSphere Console	4
2.2. Creating WebSphere Application with OpenShift Red Hat Client Tools	5
2.2.1. Creating WebSphere Application without a Database Add-On	5
2.2.2. Creating WebSphere Application with a Database Add-On	5

1. Synopsis

The purpose of this document is to present how OpenShift 2 users can interact with the WebSphere 8.5.5.1 OpenShift Enterprise V2.2 cartridge. By the end of this document users that have the WebSphere cartridge enabled for them will be able to provision WebSphere servers in a matter of minutes.

The end result of their OpenShift 2 WebSphere gear provisioning would be a WebSphere console that gives them full administrative rights over their WebSphere servers.

Each WebSphere server is contained in an OpenShift gear which means that collocated WebSphere users are segregated from one another. The figure below shows the WebSphere administrative console that every users will obtain.




Figure 1: WebSphere Administration Console in OpenShift

2. OpenShift 2 WebSphere Gear Creation

There are two ways to create a WebSphere gear in OpenShift 2:

1. Via the OpenShift Console
2. Via the OpenShift Client Tools

The following sections will present how each of these methods can be used to create a WebSphere gear in OpenShift 2

2.1. Creating WebSphere Application Via the OpenShift Console

The steps to create a WebSphere gear via the OpenShift console are very straightforward:

2.1.1. Login to the OpenShift Console



OpenShift can be configured with various identity stores. Check with your organization's administrator to find out your login credentials.




Figure 2: OpenShift Login Page

2.1.2. Click on "Create Your First Application Now"



This step assumes that the user has already created a namespace, and has setup his public key in his OpenShift account.

The next page that is displayed should show the list of all the cartridges that are available. The name of the cartridge might be different between this document and what you are seeing, therefore make sure that you select the one that hints to WebSphere.



OpenShift can be configured with various identity stores. Check with your organization's administrator to find out your login credentials.




Figure 3: OpenShift Available Cartridges Menu

2.1.3. Complete the Application Form

On the next page you will be presented with a form that has a few fields to be completed:

1. The Public URL: This is the name your application will be registered with in DNS. It will have the formate **application_name-namespace.Enterprise_Domain**
2. Source Code: If your application code is stored in a Git repository, you may provide the Git URL and OpenShift will clone the code into the Gear so that the application is built and ready on gear creation - Not frequently used.
3. Gears: This is the size in memory, disk and CPU that will be given to the application. Each cartridge may be associated wiht one or more gear types. Check your OpenShift administrator to find out what gear size to choose for the WebSphere cartridge
4. Scaling:

There are two options that you may choose from:

- **No Scaling:** This means that OpenShift will not attempt to spin up identical gears of your applicaiton when its being "hit" with a lot of web traffic
- **Scaling:** Allows OpenShift to create more gears as web traffic increases to your application. This is horizontal scaling. Once the web traffic is reduced, the additional gears are destroyed and resources are released back to the system.

Figure 4: OpenShift Application Form

2.1.4. Create the Application & Access the WebSphere Console

Once you are done completing the form above, click on **"Create Application"** button. The page will show that it is "working". It will take about a few minutes before the WebSphere gear is created.

The OpenShift console will then echo out the details of the WebSphere Administration Console as per the image below.

put image here

The WebSphere Administration Console can be access in two ways:

- Option 1: Preferred - After you have created your gear, do an `rhc port-forward <GEAR_NAME>` and open a browser with the following URL:

```
https://<YOUR_LOCAL_IP>:9043/ibm/console
```

- Option 2: The Admin Console is also exposed via a separate external port that can be determined as follows:

```
rhc ssh <GEAR_NAME>
export | grep WC_ADMINHOST_SECURE_PROXY_PORT
```

Now point your browser to the following URL:

`https://<GEAR_DNS>:<WC_ADMINHOST_SECURE_PROXY_PORT>/ibm/console/logon.jsp` and enter your credentials. Unfortunately the Admin Console tries to redirect us to the local port **9043**.

Now manually change port **9043** back to **WC_ADMINHOST_SECURE_PROXYPORT** and change **login.jsp** to **login.do** so that the URL looks like follows:

https://<GEAR_DNS>:<WC_ADMINHOST_SECURE_PROXY_PORT>/ibm/console/login.do?action=secure.

The Admin Console should then appear.

2.2. Creating WebSphere Application with OpenShift Red Hat Client Tools

The second mechanism by why a WebSphere application may be created is via the OpenShift Red Hat client tools that could be installed on your computer. The commands below assume that a domain space **test** has already been created.

2.2.1. Creating WebSphere Application without a Database Add-On

In a terminal window run the below command to create the application **myapp** with the WebSphere cartridge **frb-websphere-8.5.5.1**

```
rhc app create myapp frb-websphere-8.5.5.1
```

The output below should be seen:

```
[ose@node01 ~]$ rhc app create myapp frb-websphere-8.5.5.1
Application Options
-----
Domain:      test
Cartridges:  frb-websphere-8.5.5.1
Gear Size:   default
Scaling:     no

Creating application 'myapp' ...
```

2.2.2. Creating WebSphere Application with a Database Add-On

In the previous section we did not include a database for our application. In this section we demonstrate how this can be done from the command line... To be continued