Where does it come from and where does it go? Fast, open-source flow tracing for MODFLOW 6 models

Article Impact Statement: Open-source code turns saved MODFLOW 6 flows into contributing areas, water sources and travel times for any well or stream, in steady-state or transient flow, fast enough for ensembles.

Abstract: Groundwater studies often ask where water comes from and where it goes. Which land feeds a well, spring or stream? How much of a well's water is river water? Where does recharge under a polluted field end up? We present open-source code, `gwsource`, that answers such questions from the flows a MODFLOW 6 model saves. The code treats the water in each cell as fully mixed, like earlier methods. It computes the share of each cell's water that ends at a well, a stream or another outlet. The same trace splits a well's water by source and gives mean travel times. The code extends the method to every MODFLOW 6 grid type, stream network and linked model. It handles weak sinks. It carries tagged water through storage between time steps, forward and backward in time. Every result is checked against the flow model's water budget. The paper presents ten worked examples. Each checks an output a practitioner would use against other commonly used approaches. Results matched MODFLOW 6 transport to its solver tolerance with the same water volumes. They matched particle tracking in totals and mean travel times, not cell by cell at area edges. On a regional model of 1.68 million cells, tracing nine well groups took 2–3 s. That is small next to the model run itself. Tracing is cheap enough to include in history matching and similar analyses. Full-mixing areas are wider than particle-tracked areas. Particle tracking remains better where a sharp edge or first arrival matters.

Key words: flow tracing; full mixing; MODFLOW 6; contributing area; sources of water; travel time; transient tracking; ensemble; source protection

1. Introduction

Groundwater studies often ask where water comes from and where it goes. Which land feeds a supply well, a spring or a stream? How much of a well's water comes from a river? Practitioners also need to know how the answers change through the year and how sure they can be of them.

Methods that answer these questions from a groundwater flow model fall into four families. Particle tracking follows particles of water along flow paths. It is the standard tool for mapping a well's contributing area. This is the land where water enters the aquifer and later reaches the well. In MODFLOW models it runs in MODPATH (Pollock 2016) or in the particle-tracking model of MODFLOW 6 (PRT; Langevin et al. 2026). Transport with tagged water gives the water from one source a concentration of 1 and all other water a concentration of 0 (Bedekar et al. 2024). In MODFLOW 6 it runs in the Groundwater Transport (GWT) Model, with one model for each source (Langevin et al. 2022). Adjoint and age methods solve transport equations of their own (Neupauer and Wilson 1999; Goode 1996). Full-mixing flow tracing splits each cell's mixed water among its outflows.

But particles need a rule at weak sinks. Sink terms are the boundaries that remove water from a cell, such as a pumping well or a gaining stream. A weak sink is a cell whose sink terms take only part of the cell's outflow. A particle cannot split. It must either stop at a weak sink or pass on. If it stops, all its water is

counted as reaching the sink. If it passes, none of it is. The rule chosen changes the contributing area (Section 5).

Under full mixing, a weak sink takes its share of the cell's water. The rest passes on to the neighbouring cells. FlowSource (Foley and Black 2013; Black and Foley 2013) uses this method to draw source protection zones in England (Environment Agency 2019). It counts all the water passing through a weak-sink well's cell as the well's water. We refer to this as net accounting. For transient models, it traces each time step as a steady-state flow field. We refer to such a trace as a snapshot. MODALL (Potter et al. 2008) applies full mixing to steady-state MODFLOW-88 models. At a weak-sink well it counts only the water the well pumps. We refer to this as gross accounting. As published, neither program reads MODFLOW 6 output. All these methods are compared in Supporting Information, Table S1.

This paper presents open-source code, `gwsource`, that extends the full-mixing method of FlowSource to MODFLOW 6. It reads every MODFLOW 6 grid type, stream networks and linked models. It uses gross accounting by default. It checks every result against the water budget. In transient models, it carries tagged water through storage, forward and backward in time. It is fast enough for risk-based studies, which run an ensemble of model versions that fit the measurements about equally well (Fienen et al. 2022).

2. Method in brief

The derivations and the solution of the equations are given in Supporting Information, Text S1.

2.1 Full mixing and the backward and forward fractions

Full mixing treats each active model cell as one well-mixed volume of water. Its water leaves through each outflow in proportion to the size of that outflow. The code reads the cell-to-cell flows and the source and sink terms, such as recharge, wells and rivers, from the MODFLOW 6 budget file.

A backward trace follows water to a destination, such as one well or a wellfield. The backward fraction F_i is the share of the water leaving cell i that later leaves the model through the destination. All outflows of a fully mixed cell carry the same water. So

$$F_i = \sum_j \frac{q_{ij}}{O_i} F_j + \frac{d_i}{O_i}, \tag{1}$$

where q_{ij} is the flow from cell i to its neighbour j. The total outflow of the cell is O_i. Its outflow through the destination is d_i. In words: the share of a cell's water that reaches the destination is the share that leaves directly through it plus the outflow-weighted mean of the shares of its downstream neighbours. An eight-cell example is worked through in Supporting Information, Figure S1. The code solves Eq. (1) for all cells at once, in the order the water flows. A contributing area is the set of cells where F exceeds a chosen threshold, such as one half.

A forward trace follows water from a source, such as recharge. The forward fraction G_i is the share of the water entering cell i that came from the source. The sum over all cells of F times each cell's inflow from source terms splits the destination's water by source.

2.2 Gross and net accounting

At a weak sink, Eq. (1) needs a rule for how much of the cell's water to attribute to the sink. By default the code uses gross accounting. Each sink term then takes its share of the cell's outflow, as in a transport model. Net accounting attributes to a sink all the water that passes through its cell.

2.3 Water-budget checks and mean travel time

Each trace comes with checks that the traced volumes agree with the saved flows. For example, the source water traced to a well must add up to its pumping. The checks test the solution, not the flow model or the assumption of full mixing. With a porosity, the code also gives mean travel times (Supporting Information, Text S1). A mean travel time is not a first-arrival time.

2.4 Transient flow: snapshots and transient tracking

A snapshot treats storage terms as source and sink terms. It therefore assumes that water reaches the well in the same step it entered. It cannot say where the water released from storage came from.

Transient tracking extends full mixing through time. Water from the chosen sources is tagged, as a tracer would be. The tagged water is carried through storage from step to step. Each step is solved as in GWT, without dispersion (Langevin et al. 2022). Transient tracking needs porosity and the budget of every time step. The water in the model at the start can be tagged as its own group. We refer to it as initial water. Backward tracking in time solves the backward counterpart of each step, from the end of the simulation to its start. It gives the share of the water in each cell that leaves through the destination before the simulation ends. A map of this share is a time-limited contributing area (Section 4.2).

3. Software and cost

The method is implemented in `gwsource`. It is an open-source Python package (MIT licence). It reads the binary grid file and the budget file of a MODFLOW 6 Groundwater Flow (GWF) model, on any grid type. Stream reaches, lakes and multi-aquifer wells can be traced as extra cells from their own budget files. GWF models joined by exchanges are read as one system. Destinations and sources are chosen by package, boundname, cells or zone. Outputs export to netCDF and GeoPackage files. The code can also run MODFLOW 6 PRT on the same flows. The inputs, selections and outputs are listed in Supporting Information, Table S2.

On the regional model of Section 5, with 1.68 million cells, a trace of nine destination groups took 2–3 s. Its memory peaked at 2.5 GB. Each further group added about 0.19 GB. The MODFLOW 6 run of that model takes 44 s (Supporting Information, Table S3). The package is tested on ten small test models and two published examples (Supporting Information, Figure S2).

4. Worked examples

Three of ten worked examples follow. Section 4.4 summarises the rest. All start from one small example model. It is a single unconfined layer of 40×40 cells of 50 m. Recharge of 5×10^{-4} m/d falls on every cell.

A constant head along the west edge brings in regional groundwater. A river runs north–south 100 m east of a supply well that pumps 800 m^3/d. Every example model is described in Supporting Information, Text S2.

4.1 Where does the well's water come from?

A protection zone starts from the land whose water reaches the well. Fig. 1a maps F. Cells with $F > 0.5$ cover 1.143 km^2. Cells with $F > 0.1$ cover 1.575 km^2. Between the two contours, full mixing spreads the area's edge over a few cells. The same trace splits the 800 m^3/d pumped into 71 % recharge, 15 % inflow at the west edge and 14 % river leakage (Fig. 1c). The traced sources add up to the pumping, as the closure check requires.




Figure 1. Where the well's water comes from (Section 4.1). (a) F, with white lines at $F = 0.1$ (dashed) and $F = 0.5$ (solid). (b) Particle share of each release cell, with the $F = 0.5$ line of (a). (c) The well's water by source. Star: well. Blue cells: river.

PRT tests the edge of the area on the same flows. Particles start from every source term in cells with $F > 0$, each weighted by a share of the term's flow. A particle loses weight at every other sink it passes, in proportion to the flow that sink takes. Visser et al. (2009) and Winston et al. (2018) reduce particle weights at sinks in similar ways. We refer to these as weight-losing particles. They deliver 799.9 of the 800 m^3/d pumped, as any method that conserves water must. The particle share of a cell is the share of the weight released there that reaches the well. Cells with a particle share above 0.5 cover 1.168 km^2. The $F > 0.5$ area is 2.1 % smaller. The $F > 0.1$ area is 35 % larger. It holds every cell of the particle area. In the 372 cells with F between 0.05 and 0.95, the particle share and F differ by 0.164 on average (Fig. 1b). In those cells, most particles either reach the well or miss it. Full mixing gives the cell an in-between value.

Accounting matters only at weak sinks. In a three-layer version of the model, a small well pumps 5 m^3/d from a cell that carries 33.7 m^3/d. Net accounting attributes all 33.7 m^3/d to the well. This is 6.7 times what the well pumps. Net accounting also reproduces the worked example of Foley and Black (2013) to 1×10^{-14} (Supporting Information, Text S3).

4.2 How much of the pumped water arrived since the start?

A manager may ask how much of the water pumped over the coming decades is already in the aquifer today. This example makes the model transient, with seasonal recharge and pumping. It runs for 30 years, with one time step per season. The run starts from a steady state in which the well already pumps. Each flow step is split into four transport sub-steps (Supporting Information, Text S1).

On average over time, snapshots give the well's water as about 60 % recharge and 15 % storage release (Fig. 2a). With transient tracking, the well's water in the last season of year 30 is 51.6 % initial water, 32.9 % recharge and 15.5 % river water (Fig. 2b). Of all the water pumped in the first 10 years, 81 % was initial water. New recharge mixes into a large volume of older water, because a column of this aquifer holds about 64 years of recharge. A layered model may give other shares.

Backward tracking in time shows that only the water near the well and along the main flow path reaches the well within 30 years (Fig. 2d–f). Most of the water in the steady-state contributing area (Fig. 2c) is still on its way at the end. With GWT's water volumes and one transport step per flow step, transient tracking matched a GWT run with tagged recharge to 9.8×10^{-14} in every cell and step (Supporting Information, Text S4).




Figure 2. The seasonal model over 30 years (Section 4.2). The well's water by source from (a) snapshots and (b) transient tracking. Dashed line: initial water's share of all water pumped so far. (c) Steady-state F for the first step. (d–f) Shares of each cell's water at the start that leave through the well or the river within 30

years, or stay stored.

4.3 How sure can we be of the contributing area?

Many sets of parameters can fit the measured heads about equally well. We refer to each set as a realisation. A set of realisations is an ensemble. Here 50 realisations of the example model each have a random hydraulic conductivity field. No measurements have shaped these fields. We refer to such an ensemble as a prior. The probability of contribution of a cell is the share of realisations in which $F > 0.5$.

History matching adjusts a model's parameters until it fits measurements. PEST++ IES does this for every realisation of an ensemble (White 2018; White et al. 2020). Here it fits heads in 40 cells of a separate synthetic true aquifer (Supporting Information, Text S5). The result is the posterior ensemble. History matching narrows the probability of contribution (Fig. 3). The probability lies between 0.1 and 0.9 over 1.10 km² in the prior and 0.35 km² in the posterior. The middle 90 % of river shares narrows from 0–33 % to 5–13 %. The true share is 9.4 %.




Figure 3. Probability of contribution (Section 4.3). It is the share of realisations with $F > 0.5$ in a cell. (a) Prior. (b) After history matching. Black lines: 0.1, 0.5 and 0.9. Red dashed line: $F = 0.5$ in the true model. White circles: head measurements. (c) River share of the pumped water in each realisation. Red dashed line: true share.

A narrower posterior is not necessarily a correct one. The posterior gives a probability of at least 0.5 to 93 % of the true $F > 0.5$ area, against 79 % for the prior. One synthetic case cannot show how reliable posteriors are in general.

4.4 Further examples

The other seven examples are in the Supporting Information. A forward trace sends all 113 m³/d that the river loses to the well (Supporting Information, Text S6). On a Voronoi grid, F falls from 0.5 to 0.1 over 186 m north of the well, against 121 m on the regular grid (Supporting Information, Text S7). In seasonal snapshots, the $F > 0.5$ area grows from 0.59 km² in the wet season to 1.35 km² in the dry season (Supporting Information, Text S8). Weight-losing particles give a mean travel time to the well of 45.7 years, against 45.9

years for full mixing (Supporting Information, Text S9). Tracing stream reaches as cells turns 32 % of the well's water from stream leakage into upstream inflow and recharge (Supporting Information, Text S10). Transient tracking gives the source shares of the unit-concentration example of Bedekar et al. (2024) after 25 years as 48.2 %, 29.2 % and 22.5 %, against the published 48 %, 29 % and 23 % (Supporting Information, Text S11).

5. A regional model: Neversink

This section tests the method on a published regional model. The USGS Neversink/Rondout model (Fienen et al. 2022; Corson-Dosch et al. 2022) is a steady-state model of 1.68 million cells, with 12,316 SFR reaches. The published study mapped the contributing areas of eight priority wells with MODPATH 7 (Pollock 2016). One particle started in the uppermost active cell of each column near the wells. The published contributing cells are the 980 of these start cells whose particle ends in a priority well. Maps of F around the wells are given in Supporting Information, Figure S3.

Our areas differ from the published ones. We measure the difference with an overlap score. It is the number of cells in both areas divided by the number in either. The published area comes from one reasonable choice of particle settings. These settings fix where recharge enters a cell, where particles stop and how particles that start in dry cells are handled. PRT on the same flow field reproduces the published area (overlap 0.998) only with all three published settings. Among particle runs that conserve water, the settings alone move the overlap from 0.62 to 0.998 (Supporting Information, Table S3).

The full-mixing areas where F exceeds 0.5 and 0.1 agree less, with overlaps of 0.41 and 0.30. We infer that the main reason is that full mixing splits each cell's water among all its outflows, while a particle follows one path. On average, the published cells send 42 % of their water to the wells. The $F > 0.1$ area holds 73 % of them. Weight-losing particles lose water at each sink as full mixing does. The $F > 0.1$ area holds 87 % of the 691 start cells where these particles deliver more than half their water to the wells.

Weak sinks add to the difference. A buried stream cell has an SFR reach and another active cell above it. Where the reach gains water, a published particle stops in the cell. All its water then counts as reaching the stream. Published particles stop in the same way at weak-sink wells. Full mixing passes the rest of the cell's water on (Supporting Information, Text S12).

6. Trade-offs and conclusions

`gwsource` builds on the full-mixing method of FlowSource (Foley and Black 2013). It extends that method to every MODFLOW 6 grid type, to package networks and linked models, and through storage in transient models. One trace of a regional model of 1.68 million cells takes seconds. Tracing is therefore cheap enough for ensembles and history matching.

But full-mixing areas are wider and more diffuse than particle areas (Section 5). Their edge is a band of cells where F lies between 0.1 and 0.9. In two simple test problems, halving the cell size made the band only about 30 % narrower (Supporting Information, Figure S4). Potter et al. (2008) also found wider spreading on coarser grids. On squares turned by 45° to the flow, the band was 1.8 times as wide as on squares aligned

with it (Supporting Information, Text S7). Where the edge of an area matters, finer cells along it and a grid aligned with the main flow narrow the band.

No single threshold on F therefore reproduces a particle area everywhere. The threshold is a judgement about the purpose of the area. It should be reported with the area, as should the accounting. In the test problems, on cells of 50 m or less, the $F > 0.5$ area was within 5 % of the size of the reference area. The $F > 0.1$ area missed at most 0.1 % of the reference area. On Neversink, the $F > 0.1$ area still missed cells that weight-losing particles assign to the wells (Section 5). So a low threshold does not guarantee a cautious area on a regional model.

Totals depend much less on mixing than edges do (Section 4.4). We would therefore use particles where a sharp edge or a first arrival matters, such as a short time-of-travel zone. We would use GWT where dispersion, sorption or decay matter, because transient tracking moves water by advection only (Langevin et al. 2022). Full mixing suits questions about many sinks, unstructured grids, package networks or many realisations. Transient tracking has so far been tested on synthetic models only.

7. Code and Data Availability

The code, `gwsource`, is open source under the MIT licence at https://github.com/rhugman/gw-source [check: public URL]. This paper uses version 0.0.1 [check: release version and tag]. Each example ships with the code as a Jupyter notebook that reproduces its numbers and figure (Supporting Information, Text S2). The Neversink model is in a USGS data release (Fienen and Corson-Dosch 2021). The files behind every figure will be archived on Zenodo [check: DOI].

References

Bedekar, V., C. Neville, M.J. Tonkin, R.D. Bartlett, and P. Plato. 2024. A unit-concentration method to quantify source contribution. *Groundwater* 62, no. 2: 303–309. https://doi.org/10.1111/gwat.13333

Black, A., and C. Foley. 2013. FlowSource: A program to efficiently delineate volumetric capture areas, pathways and source areas in groundwater models. In *Proceedings of MODFLOW and More 2013: Translating Science into Practice*, Golden, Colorado, June 2–5, 2013, 652–663. Golden, Colorado: IGWMC, Colorado School of Mines. https://groundwater-science.co.uk/wp-content/uploads/2013_FSv6_ApplicationPaper.pdf

Corson-Dosch, N.T., M.N. Fienen, J.S. Finkelstein, A.T. Leaf, J.T. White, J. Woda, and J.H. Williams. 2022. Areas contributing recharge to priority wells in valley-fill aquifers in the Neversink River and Rondout Creek drainage basins, New York. U.S. Geological Survey Scientific Investigations Report 2021–5112. Reston, Virginia: USGS. https://doi.org/10.3133/sir20215112

Environment Agency. 2019. *Manual for the Production of Groundwater Source Protection Zones*. Bristol, UK: Environment Agency. https://assets.publishing.service.gov.uk/media/5d41a020e5274a0a0bf7757c/Manual-for-the-production-of-Groundwater-Source-Protection-Zones.pdf

Fienen, M.N., and N.T. Corson-Dosch. 2021. Groundwater model archive and workflow for Neversink/Rondout Basin, New York, source water delineation. U.S. Geological Survey data release. https://doi.org/10.5066/P9HWSOHP

Fienen, M.N., N.T. Corson-Dosch, J.T. White, A.T. Leaf, and R.J. Hunt. 2022. Risk-based wellhead protection decision support: A repeatable workflow approach. *Groundwater* 60, no. 1: 71–86. https://doi.org/10.1111/gwat.13129

Foley, C., and A. Black. 2013. Efficiently delineating volumetric capture areas and flow pathways using directed acyclic graphs and MODFLOW; description of the algorithms within FlowSource. In *Proceedings of MODFLOW and More 2013: Translating Science into Practice*, Golden, Colorado, June 2–5, 2013, 571–581 [check: pages against the proceedings]. Golden, Colorado: IGWMC, Colorado School of Mines. https://groundwater-science.co.uk/wp-content/uploads/2013_FSv6_DAGPaper.pdf

Goode, D.J. 1996. Direct simulation of groundwater age. *Water Resources Research* 32, no. 2: 289–296. https://doi.org/10.1029/95WR03401

Langevin, C.D., A.M. Provost, S. Panday, and J.D. Hughes. 2022. Documentation for the MODFLOW 6 Groundwater Transport Model. U.S. Geological Survey Techniques and Methods, book 6, chap. A61. Reston, Virginia: USGS. https://doi.org/10.3133/tm6A61

Langevin, C.D., J.D. Hughes, A.M. Provost, M.J. Russcher, M.J. Reno, W.P. Bonelli, E.D. Morway, S. Titus, R.G. Niswonger, S. Panday, D. Merrick, and E.R. Banta. 2026. MODFLOW 6 Modular Hydrologic Model version 6.8.1. U.S. Geological Survey Software Release, 23 September 2026. https://doi.org/10.5066/P1PGE9XW

Neupauer, R.M., and J.L. Wilson. 1999. Adjoint method for obtaining backward-in-time location and travel time probabilities of a conservative groundwater contaminant. *Water Resources Research* 35, no. 11: 3389–3398. https://doi.org/10.1029/1999WR900190

Pollock, D.W. 2016. User guide for MODPATH Version 7—A particle-tracking model for MODFLOW. U.S. Geological Survey Open-File Report 2016–1086. Reston, Virginia: USGS. https://doi.org/10.3133/ofr20161086

Potter, S.T., E. Moreno-Barbero, and C.E. Divine. 2008. MODALL: A practical tool for designing and optimizing capture systems. *Ground Water* 46, no. 2: 335–340. https://doi.org/10.1111/j.1745-6584.2007.00410.x

Visser, A., R. Heerdink, H.P. Broers, and M.F.P. Bierkens. 2009. Travel time distributions derived from particle tracking in models containing weak sinks. *Ground Water* 47, no. 2: 237–245. https://doi.org/10.1111/j.1745-6584.2008.00542.x

White, J.T. 2018. A model-independent iterative ensemble smoother for efficient history-matching and uncertainty quantification in very high dimensions. *Environmental Modelling & Software* 109: 191–201. https://doi.org/10.1016/j.envsoft.2018.06.009

White, J.T., R.J. Hunt, M.N. Fienen, and J.E. Doherty. 2020. Approaches to highly parameterized inversion: PEST++ Version 5, a software suite for parameter estimation, uncertainty analysis, management optimization and sensitivity analysis. U.S. Geological Survey Techniques and Methods 7C26. Reston, Virginia: USGS. https://doi.org/10.3133/tm7C26

Winston, R.B., L.F. Konikow, and G.Z. Hornberger. 2018. Volume-weighted particle-tracking method for solute-transport modeling; Implementation in MODFLOW–GWT. U.S. Geological Survey Techniques and Methods, book 6, chap. A58. Reston, Virginia: USGS. https://doi.org/10.3133/tm6A58

Supporting Information (draft)

Text S1. Method in full

Section 2 of the main text gives the backward fraction (Eq. 1) and describes the rest of the method in words. This text gives the method in full. It defines the cell budget, derives the equations and shows how they are solved and why the water-budget checks must hold. Figure S1 illustrates the method. It then gives net accounting, the mean travel time and transient tracking in full. Equation numbers without an S refer to the main text.

The backward and forward fractions

Cells exchange water through the cell-to-cell flows of the MODFLOW 6 budget file (FLOW-JA-FACE; Langevin et al. 2017). The flow from cell i to its neighbour j is $q_{ij} \geq 0$. All other budget terms, such as recharge, wells, rivers and storage, are kept separate by package and boundary. A term that brings water into a cell is a source term. A term that takes water out is a sink term. If Src_i and Snk_i are the totals of a cell's source and sink terms, its total inflow, total outflow and cell budget error are (Figure S1a)

$$I_i = \sum_j q_{ji} + \mathrm{Src}_i, \qquad O_i = \sum_j q_{ij} + \mathrm{Snk}_i, \qquad r_i = I_i - O_i. \tag{S1}$$

The cell budget of a MODFLOW model never balances exactly, so r_i is small but not zero. The outflow of cell i through the destination is d_i. The inflow of cell i through the source is s_i.

Full mixing means that all water leaving a cell has the same mix of origins and fates. Take the water that leaves cell i in one day. The part d_i leaves through the destination directly. The part q_{ij} goes to neighbour j, and a share F_j of it later leaves through the destination. So the volume of water leaving cell i that ends at the destination is

$$F_i\, O_i = \sum_j q_{ij}\, F_j + d_i. \tag{S2}$$

Dividing by O_i gives Eq. (1). Let $P_{ij} = q_{ij}/O_i$ be the share of cell i's outflow that goes to cell j. Written for every cell at once, Eq. (1) becomes

$$(\mathrm{I} - \mathrm{P})\,\mathrm{F} = \mathrm{S}\,\mathrm{D}. \tag{S3}$$

Here I is the identity matrix. S holds the share of each cell's outflow that leaves through each of its sink terms. D marks which sink terms belong to which destination group. Each column of F holds the fractions to one destination group, so one solve gives every group. Under gross accounting, a sink term k in cell i takes the share $|q_k|/O_i$ of the cell's outflow. These shares are the entries of S. A cell with no outflow is given $F = 0$.

The forward fraction follows from the inflow in the same way. The water entering cell i in one day comes from the neighbours and from the source and sink terms. A share G_j of the water from neighbour j came

from the source. All of s_i came from it. So

$$G_i\, I_i = \sum_j q_{ji}\, G_j + s_i. \tag{S4}$$

Dividing by I_i and writing the result for every cell, with the inflow shares $Q_{ij} = q_{ji}/I_i$, gives

$$(\mathrm{I} - \mathrm{Q})\,\mathrm{G} = \mathrm{R}\,\mathrm{T}. \tag{S5}$$

R holds the share of each cell's inflow that enters through each source term. T marks which source terms belong to which source group. A cell with no inflow is given $G = 0$.

Volumes

A fraction says what share of a cell's water reaches the destination, but not how much water that is. A fraction times a flow gives a volume of water per unit time. The volume through cell i is $F_i O_i$. It is the part of the water passing through the cell that reaches the destination. The volume from cell i is F_i times the cell's inflow through its source terms. It is the water entering the model in that cell that reaches the destination. Summing the volume from over all cells, package by package, splits the destination's water by source (Section 4.1). A forward trace gives the matching volumes from G. They split a source's water by where it leaves the model (Text S6).

Why the water-budget checks hold exactly

The checks of Section 2.3 follow from adding up Eqs. (S2) and (S4) over all cells. Adding Eq. (S2) over all cells gives $\sum_i F_i O_i$ on the left. On the right, each flow q_{ij} appears once, multiplied by the F of the cell it enters. Summed over the cells it leaves, the flow into cell j is $\sum_i q_{ij} = I_j - \mathrm{Src}_j$. So

$$\sum_i F_i\, O_i = \sum_j F_j \left(I_j - \mathrm{Src}_j\right) + \sum_i d_i.$$

Moving terms and using $r_i = I_i - O_i$ gives the backward closure check

$$\sum_i F_i\, \mathrm{Src}_i - \sum_i F_i\, r_i = \sum_i d_i. \tag{S6}$$

It says that the source water traced to the destination, corrected for the cell budget errors, adds up to the water the destination takes. Adding Eq. (S4) over all cells gives the forward closure check in the same way:

$$\sum_i G_i\, \mathrm{Snk}_i + \sum_i G_i\, r_i = \sum_i s_i. \tag{S7}$$

The forward–backward check is a duality identity of the two systems. Multiply Eq. (S2) by G_i and Eq. (S4) by F_i, and add each over all cells. Both results then hold the same double sum of the cell-to-cell flows,

$\sum_i \sum_j q_{ij} G_i F_j$. It cancels when one result is subtracted from the other. What remains is the forward–backward check

$$\sum_i F_i s_i - \sum_i G_i d_i = \sum_i F_i G_i r_i. \tag{S8}$$

So the volume from a source to a destination is the same whether it is traced backward or forward, once the cell budget errors are included.

The boundary-control check traces every sink term of the model, each as its own destination. The sum of their fractions solves Eq. (1) with d_i replaced by the total sink outflow Snk_i. A value of 1 in every cell solves that equation, because $\sum_j q_{ij} + \mathrm{Snk}_i = O_i$. The solution is unique outside closed recirculation loops, which are described below. So the fractions to all sinks add up to 1 in every other cell with outflow.

The checks include the cell budget errors r_i. So they hold exactly for any flow field, also one that does not balance. The errors reported by the code are then round-off, unless the tracing itself is wrong. Without the error terms, the checks would hold only to within the budget error of the flow model. The code reports both values.

Solution of the linear systems

Equation (1) gives a cell's F from the F of the cells downstream of it. Where water never returns to a cell it has left, the cells can be solved one at a time along the flow paths, as in FlowSource (Foley and Black 2013).

Flow loops break this order. A flow loop is a group of cells among which water circulates, so that water leaving a cell can return to it. No order of the cells in a loop is purely downstream, so a single pass cannot solve a loop exactly. Loops arise with the XT3D option of MODFLOW 6 (Provost et al. 2017) and where stream reaches and aquifer cells exchange water in both directions. Foley and Black (2013) report loops as rare, mostly in unstable multilayer models. FlowSource deletes the smallest flow in each loop. Foley and Black (2013) expect this to change the results very little. We keep every flow and solve each loop exactly.

Equations (S3) and (S5) are solved in flow order. Where the cell-to-cell flows contain no loop, the matrix is reordered to triangular form, with every cell after the cells it depends on. It is then solved by substitution. This is the flow-order algorithm of FlowSource in matrix form. Where there are loops, the matrix is reordered to block-triangular form. Each block is one strongly connected component of the flows, which is either one flow loop or one single cell. The blocks are in flow order. The matrix is then factorised once by sparse LU decomposition in that order. The extra non-zero entries that a factorisation creates stay inside the loop blocks. So a model of a million cells with thousands of small loops is factorised in well under a second.

Each cell's outflow shares add up to at most 1. So $\mathrm{I} - \mathrm{P}$ is a weakly row-diagonally dominant M-matrix. Its factorisation therefore needs no pivoting, the row swaps that otherwise guard against the growth of round-off. The matrix is singular only on a closed recirculation loop. This is a set of cells with no outflow to any sink or to a cell outside the set. Water in such a loop never reaches a sink. These loops are found before the solve, given $F = 0$ and reported. No flows are deleted. Under gross accounting, one factorisation serves every destination group. It is reused for the travel-time system of Eq. (S10).

The code also reports every flow loop, with the flow that goes round it and its share of the flow through the model. A large loop, or one that carries much water, may point to a problem in the flow model, such as poor convergence or extreme anisotropy.

Net accounting

Net accounting reproduces the bookkeeping of FlowSource (Foley and Black 2013). It works from the cell-to-cell flows only. Each cell's source and sink terms are replaced by one net term, equal to its cell-to-cell outflow minus its cell-to-cell inflow. With I_i^e and O_i^e the cell-to-cell inflow and outflow of cell i, the net term is $n_i = O_i^e - I_i^e$. The water passing through the cell is then $T_i = I_i^e + \max(n_i, 0)$. Outside the destination cells, the backward fraction is

$$f_i = \frac{1}{T_i} \sum_j q_{ij} f_j. \tag{S9}$$

The destination cells are fixed at $f = 1$. Their outflows to other cells are ignored. A forward trace works in the same way on the reversed flows, with the source cells fixed at $g = 1$.

Which cells are fixed depends on how the group was selected. A pure cell or zone selection fixes all its cells, as FlowSource defines groups (Foley and Black 2013). A selection by package, boundary name or term fixes only the cells where a selected term flows in the traced direction. In a backward trace, these are the cells where a selected term is a sink. In a forward trace, they are the cells where it is a source. This also holds when a term criterion is combined with cells or a zone. A cell with selected terms of both signs is fixed in both directions. A group with no such term fixes no cell, so every fraction is 0. A well listed at zero rate, a drain above the water table, or a losing river cell in a backward trace is therefore not fixed. On a stream network, a package selection fixes only the reaches whose records flow in the traced direction. To fix a whole stream, select its reaches as cells.

Net accounting has no cell budget error term. The water it attributes to a group counts each passage once. It is the water passing through the fixed cells, less the water passing from one fixed cell to another, and less the water that leaves the group and reaches it again. Its closure check compares the volume from the sources with this net inflow. The check tests the sum of the equations over the cells outside the group, not each cell. Its error is exactly the sum of those cells' equation errors. Net accounting solves one destination group at a time, because each group fixes its own cells. As an option, it can delete the smallest flow in each flow loop, as FlowSource does. This option exists only to compare with studies made with FlowSource.

Mean travel time

Fractions say how much water arrives, not when. Let V_i be the volume of water in cell i. It is porosity times the saturated volume of the cell. Fractions need no porosity, but travel times do. A parcel of water that enters a fully mixed cell stays there for a random time. The mean of that time is $\tau_i = V_i / O_i$. Under full mixing, the time a parcel spends in a cell does not depend on the route by which it leaves. Let m_i be the mean travel time from entering cell i to leaving the model, counted only for water that leaves through the destination, and weighted by F_i. A parcel spends on average τ_i in cell i and then moves to cell j with probability P_{ij}. So

$$m_i = \tau_i F_i + \sum_j P_{ij} m_j. \tag{S10}$$

In matrix form this is $(\mathrm{I} - \mathrm{P})\,\mathrm{m} = \tau \circ \mathrm{F}$, where $\circ$ is the cell-by-cell product. The mean travel time of the water that reaches the destination is m_i/F_i. It is defined only under gross accounting, and only where F_i is above a small threshold.

Multiplying each cell's travel-time equation (Eq. S10) by its outflow and adding over all cells gives, with the cell budget errors r_i,

$$\sum_i \mathrm{Src}_i\, m_i - \sum_i r_i\, m_i = \sum_i V_i F_i. \tag{S11}$$

Divided by the destination inflow $\sum_i d_i$, the right-hand side is the turnover time. This is the volume of water that ends at the destination divided by the destination's inflow. By the backward closure check (Eq. S6), the left-hand side divided by the same inflow is the flow-weighted mean travel time of all water reaching the destination. The two are therefore equal once the cell budget errors are included.

The mean travel time m_i/F_i includes the time spent in the cell where the water leaves, for a well its own cell. The time until the water enters that cell is $(m_i - x_i)/F_i$, where x solves $(\mathrm{I} - \mathrm{P})\,\mathrm{x} = \tau \circ (\mathrm{S}\,\mathrm{D})$. Here x is the mean time spent in the cell of exit, weighted by the share leaving there through the destination. Particle trackers that stop particles on entering a sink cell (MODFLOW 6 PRT, MODPATH) measure this second time. It is the full-mixing time that is compared with particles in Table S4 and in Text S9. On test model 1, the water reaching the well takes 9,607 d on average including its time in the well cell, and 9,574 d to enter that cell.

Transient tracking

Transient tracking carries tagged water from step to step (Section 2.4; Figure S1d). Each cell, and each reach, lake or well added as an extra cell (Section 3), is a fully mixed volume of water. The storage terms of the flow model are not traced as source or sink terms. They change the volume of water in the cell instead. In step n, of length Δt, the volume changes from V_i^{old} to V_i^{new}. The change equals the storage release over the step. The tagged water in the cell at the end of the step is the tagged water at the start, plus what arrives, less what leaves. Let c_i be the share of a cell's water that is tagged. Step n of length Δt is then

$$V_i^{\mathrm{new}} c_i^n - V_i^{\mathrm{old}} c_i^{n-1} = \Delta t \Big[\sum_j q_{ji}\, c_j^n + s_i^n - (O_i + r_i)\, c_i^n \Big], \tag{S12}$$

where O_i now leaves out storage.

As in MODFLOW 6 GWT, the scheme is implicit in time. So outflows over the step carry the cell's mix at the end of the step. It is upstream weighted. So inflows carry the mix of the cell they come from. It adds no dispersion. It runs on the flow model's own time steps, so the budget of every step must be saved (SAVE BUDGET ALL in the Output Control file).

The cell budget error r_i leaves the cell, or enters it, at the cell's own mix of water. GWT treats the error in the same way, which Langevin et al. (2022) call the flow-imbalance correction. With this correction, Eq. (S12) leaves every tagged fraction at 1 when every source and the initial water are tagged.

For all cells, step n is one set of linear equations,

$$\mathrm{A}^n \mathrm{c}^n = \mathrm{B}^n \mathrm{c}^{n-1} + \Delta t\, \mathrm{s}^n. \tag{S13}$$

B^n is a diagonal matrix of the start volumes V_i^{old}. A^n has $V_i^{\mathrm{new}} + \Delta t\,(O_i + r_i)$ on its diagonal and $-\Delta t\, q_{ji}$ in row i, column j. Each row of A^n adds up to $V_i^{\mathrm{old}} + \Delta t\, \mathrm{Src}_i$, which is not negative. So A^n is an M-matrix, like $\mathrm{I} - \mathrm{P}$. Each step is solved in flow order as above. Because every cell holds water, no flow loop makes the matrix singular. One factorisation per step serves every tagged group.

The water in the model at the start of the simulation can be tagged as its own group, the initial water. It starts with $c = 1$ in every cell and has no source.

Water volume options Transient tracking needs the water volume of every cell at the start and end of each step. The code offers two options. In the default, called "flow", each volume starts at porosity times saturated volume. It then changes only by the storage flows of the flow model. Every cell's water balance and tagged-water balance then close exactly. In the "gwt" option, the volume is reset to porosity times saturated volume at the end of each step, as in MODFLOW 6 GWT. Forward transient tracking with this option is unit-concentration transport in GWT (Bedekar et al. 2024; Langevin et al. 2022). Where porosity differs from specific yield, the reset volume does not match the storage flows. Tagged water then appears or disappears at step boundaries. The code reports this volume. On the 30-year seasonal example model, with one transport step per flow step, the forward fractions of the two options differ by up to 1.9×10^{-4} and the backward fractions by up to 3.7×10^{-3}. The volume that appears or disappears on that model is given in Text S4. We recommend the default unless a result must match a GWT run.

With "flow" volumes, a cell whose volume would fall below zero stops the run with an error. This can happen where porosity is much smaller than the specific yield.

Transport sub-steps Implicit time steps spread tagged water in time, by an amount that grows with the step length. Long steps therefore make tagged water arrive too early (Section 4.2). Sub-steps reduce this effect without a change to the flow model. Each flow step is split into m equal transport sub-steps of length $\Delta t/m$. The flows stay constant within the flow step. The water volumes change linearly between V^{old} and V^{new}, which is what a constant storage flow gives. Outputs are reported at the ends of the flow steps. With $m = 1$ the scheme is the one above.

Backward tracking in time

Backward tracking in time is the discrete adjoint of Eq. (S13) (Neupauer and Wilson 1999; Cornaton and Perrochet 2006). The tagged water that the destination takes over the whole simulation is $J = \sum_n \Delta t^n\, \mathrm{d}^n \cdot \mathrm{c}^n$, where d^n holds the destination outflow of each cell in step n. The backward fraction in time w^n solves, from the last step N back to the first,

$$(\mathrm{A}^n)^\top \mathrm{w}^n = \Delta t^n \, \mathrm{d}^n + \mathrm{B}^{n+1}\mathrm{w}^{n+1}, \qquad \mathrm{w}^{N+1} = 0. \tag{S14}$$

The transpose swaps the roles of inflow and outflow. So the solve runs against the flow, from the end of the simulation back to the start. w_i^n is the share of the water in cell i at the start of step n, together with the water entering the cell during the step, that leaves through the destination before the simulation ends. The implicit scheme mixes these two kinds of water alike, so one value describes both.

The same backward equations give the other fates of the water. With every remaining sink as the destination, they give the fraction that leaves through any sink. With no destination, and the end volumes as the condition at the last step, they give the fraction still stored at the end. The fraction to the destination, the fraction to other sinks and the fraction still stored add up to 1 in every cell and step. The flow-imbalance correction and, with "gwt" volumes, the step-boundary changes remove a small remainder. The code reports this remainder.

The transient forward–backward check follows from Eqs. (S13) and (S7). Multiply Eq. (S13) by w^n and Eq. (S14) by c^n, and add each over all steps. The terms in A^n are equal and cancel. The terms in B cancel from one step to the next, except at the first step. What remains is

$$\sum_n \Delta t^n \, \mathrm{d}^n \cdot \mathrm{c}^n = \sum_n \Delta t^n \, \mathrm{s}^n \cdot \mathrm{w}^n + \sum_i V_i^{\mathrm{old},1} \, c_i^0 \, w_i^1. \tag{S15}$$

The check says that the tagged water the destination takes, found by forward tracking, equals the tagged inflow and the tagged initial water, each multiplied by its share that later reaches the destination. It holds exactly for either volume option and with or without sub-steps. With every source and the initial water tagged, the right-hand side splits the destination's outflow by source term, time step and initial water.

With flows held constant for long enough, the tagged fraction c tends to the steady forward fraction G, and w at the first step tends to the steady backward fraction F. The storage terms are then zero, so the tracked system and the steady system have the same flows. Test model 10 checks this limit (Table S4).

Text S2. Example and test models

This text describes every model behind the worked examples of Section 4 and of this Supporting Information, and the tests of Section 3, so that a reader can rebuild them without the code. All models are small and synthetic. The example models ship with the code as the example notebooks (Section 7). The test models and the hand-built networks ship as automated tests. Lengths are in metres and times in days. Rows and columns are counted from 1, from the north-west corner, and layers from the top.

Common settings of the example models

Every example model is a MODFLOW 6 model built with FloPy. Each saves what the code needs: the binary grid file, the budget of every time step with SAVE_FLOWS in every package, the heads, the saturation and the specific discharge. Packages that are traced as extra cells (SFR, MAW and MVR) also write their own budget files. The flow solver (IMS) uses the simple complexity option, BiCGSTAB acceleration, a head

change criterion of 10^{-9} m for the outer iterations and 10^{-10} m for the inner iterations, and a residual criterion of 10^{-8} m^3/d. Steady-state models have one stress period of 1 day with one time step.

The example notebooks (Section 7)

Each example ships with the code as a Jupyter notebook. The notebook builds the example model, runs MODFLOW 6 and reproduces the numbers and figure of its example. The table gives the run time that each notebook printed in its stored run. The run time of the ensemble notebook includes the PEST++ IES run on eight local workers.

example	notebook	run time
Section 4.1	01 Quickstart	4 s
Text S3	02 Accounting	2 s
Text S6	03 Forward mode	1 s
Text S7	04 Grids	4 s
Text S8	05 Transient snapshots	4 s
Text S9	06 Travel time	4 s
Text S10	07 Networks and multi-model	3 s
Section 4.2	08 Transient tracking	16 s
Section 4.3	09 Ensembles	71 s
Text S11	10 Unit concentration	about 2 min

The shared example model (Section 4.1, Text S6 and Text S9)

The shared model is one convertible layer (DIS) of 40×40 cells of 50 m, 2 km on each side. The top is at 20 m and the bottom at -30 m. The hydraulic conductivity is 5 m/d everywhere. The starting head is 10 m. Constant heads of 10 m (CHD) fill the 40 cells of column 1. A river (RIV) fills the 40 cells of column 31, with a stage of 6 m, a bottom of 4 m and a conductance of 500 m^2/d per cell. Its reaches in rows 1–20 carry the boundary name river_north, and those in rows 21–40 the name river_south. Recharge of 5×10^{-4} m/d (RCH) falls on every cell. The supply well (WEL, boundary name supply_well) pumps 800 m^3/d from row 21, column 29. Its cell centre is 100 m west of the river cell centres and 1.4 km east of the constant heads. The model is steady state.

The traces of Section 4.1 and Text S9 use the unchanged model. Text S9 adds a porosity of 0.3 for the mean travel times.

Particle tracking on the example models (Section 4.1 and Text S9)

The particle comparisons use MODFLOW 6 PRT on the flows of the shared model, with a porosity of 0.3. Particles are released from every source term of every cell with $F > 10^{-6}$. Each source term gets 16 release points, spread over the cell in plan. Each point carries an equal share of the term's flow as its weight. In a one-layer model there is no vertical flow, so the points are released at one height. The particles lose weight at every sink they pass, in proportion to the flow that the sink takes from the cell's outflow. On the shared

model this gives 18,208 particles from 1,133 cells. The particle share P of a cell is the weight that reaches the well divided by the weight released in the cell.

The three-layer model with a small well (Section 4.1 and Text S3)

This model splits the shared model into three layers. The layer bottoms are at 0, −12 and −30 m. The horizontal hydraulic conductivity is 10, 1 and 15 m/d from the top. The vertical conductivity is one tenth of the horizontal. Layer 1 is convertible and layers 2 and 3 are confined. The constant heads of 10 m fill column 1 of every layer. The river and the recharge act on layer 1 only, as in the shared model. The supply well pumps 800 m^3/d from layer 3 at row 21, column 29. A small well (boundary name weak_well) pumps 5 m^3/d from layer 3 at row 17, column 13. That is 800 m west and 200 m north of the supply well. Its cell carries 33.7 m^3/d, so it is a weak sink.

The worked example of Foley and Black (2013) (Text S3)

This is not a MODFLOW model. It is a block of 3 × 3 cells, labelled A to I, with the flows between them given by Foley and Black (2013). Two further nodes stand for the area outside the block. Node J sends 10 flow units into cell C. Node K receives the 5 units that cell B sends out of the block. Cell A is the destination. Under net accounting, the net sources inside the block are cells F, H and I. The published fractions, volumes through and volumes from are those of Figs 5 to 8 of Foley and Black (2013).

The field and the GWT run (Text S6)

The forward example (Text S6) uses the shared model unchanged. The field is a zone of 6 × 6 cells, 300 m × 300 m, in rows 11–16 and columns 13–18. Only the recharge on the field is traced. It is 45 m^3/d over 36 cells. The nitrate and chloride concentrations of Text S6 are invented values that show how G converts to concentrations.

The GWT model reads the saved heads and flows of the shared model. Its single stress period is 10^6 days long, in 10 equal time steps. Porosity is 0.3. Advection is upstream weighted, with no dispersion. The flow-imbalance correction is on. The river leakage has a concentration of 1, and all other inflow and the initial water a concentration of 0. MODFLOW 6 reuses the flows of the single steady-state step for every transport step. So the run carries the concentrations to equilibrium on unchanged flows. The GWT solver uses a concentration change criterion of 10^{-10} for the outer and 10^{-12} for the inner iterations, and a residual criterion of 10^{-10}.

The grids (Text S7)

Voronoi grid (DISV). The Python package vorflow (Hugman and Sanchez 2026), version 0.2.0, builds the Voronoi grid. It first meshes the 2 km × 2 km square with triangles. It then turns the triangle mesh into Voronoi cells. The mesh size is 50 m away from the well and the river, as in the DIS grid. It is 10 m at the well and 12.5 m along the river. Between these sizes the mesh grows by about 20 % from one cell to the next, the default of vorflow. The well point and the river line x = 1,525 m are part of the mesh. So the well point is the centre of the well's cell. The river cells are centred on the river line. The grid has 3,241 cells in one layer, with the top, bottom, hydraulic conductivity and recharge of the shared model. The cell centres

are the points the Voronoi cells are built around. So each connection between two cells is perpendicular to the face they share. The stresses are placed by geometry. The constant heads fill every cell with a vertex on the west edge. These cells are centred on the edge itself. The river fills every cell that the line x = 1,525 m crosses. This line is the centre line of the river column of the DIS model. The river conductance per cell is scaled so that the total conductance equals that of the DIS model. The well is in the cell centred on x = 1,425 m and y = 975 m, the centre of the DIS well cell.

Unstructured grids (DISU). Two DISU models hold the 1,600 cells of the shared model and their connections, written as an unstructured grid. One includes the cell vertices and one does not. Without vertices the model has no geometry for maps or specific discharge. The code then reads the cell areas from the DISU input.

XT3D model. This model is the shared model with the XT3D option of the flow package and an anisotropic, heterogeneous hydraulic conductivity. The conductivity along the main axis is $K = 5\exp(z)$, where z is drawn independently in each cell from a standard normal distribution (random seed 20131). The conductivity across the main axis is 0.05 times K, an anisotropy of 20:1. The main axis is rotated in plan by the angle $45° \sin(2\pi c/12) \cos(2\pi r/10)$, where r and c are the row and column counted from 0. So the rotation varies across the model between −45° and 45°.

The seasonal model for snapshots (Text S8)

This model is the shared model with storage. The layer is convertible, with a specific yield of 0.2 and a specific storage of 10^{-5} m^{-1}. The first stress period is a steady state of 1 day, with the well pumping 800 m^3/d and the mean recharge of 5×10^{-4} m/d. Twelve transient seasons of 365.25/4 = 91.3 days follow, for 3 years. Each season has three equal time steps of about 30.4 days, so the model has 37 time steps. The recharge is multiplied by 1.8 in the wet season, 1.0 in the wet-to-dry transition, 0.1 in the dry season and 1.1 in the dry-to-wet transition. The pumping is multiplied by 0.8, 1.0, 1.4 and 0.8 in the same seasons. The well therefore pumps 640, 800, 1,120 and 640 m^3/d. The 36 seasonal steps are traced as snapshots.

Streams, drains, the water mover and other models (Text S10)

Stream, drains and mover. In this model the river of the shared model becomes a stream of the SFR package. The stream has one reach in each of the 40 cells of column 31 and flows from north to south. Each reach is 50 m long and 5 m wide. Its streambed is 1 m thick, with a hydraulic conductivity of 0.5 m/d. The channel has a slope of 0.001 and a Manning roughness of 0.03. The streambed top is 6.0 m at the first reach and falls by 0.08 m per reach, to 2.88 m at the last. The upper reaches therefore lose water to the aquifer, and the lower ones gain water from it. The first reach receives an inflow of 300 m^3/d. Two drains (DRN) lie in column 15, 800 m west of the stream. Drain A is at row 9, with an elevation of 6.2 m. Drain B is at row 23, with an elevation of 6.0 m. Both have a conductance of 50 m^2/d. The water mover (MVR) passes 80 % of the outflow of drain A and all the outflow of drain B to the first reach of the stream. All other parts of the model are those of the shared model. The flow solver uses the moderate complexity option with up to 500 outer iterations.

Multi-aquifer well. This model is the three-layer model with a vertical conductivity of one hundredth of the horizontal, so that layer 2 acts as an aquitard. Only the supply well of the three-layer model is kept, pumping 800 m^3/d from layer 3. A multi-aquifer well (MAW) at row 21, column 19 is screened over the

full thickness of all three layers. Its radius is 0.15 m, its bottom is at −30 m and its conductance follows the Thiem equation. It pumps 10 m^3/d.

Split model. The FloPy model splitter (Hughes et al. 2024) cuts the shared model into three models joined by exchanges, with the exchange flows saved. Columns 1–20 form the first model. Columns 21–40 form the second model in rows 1–20 and the third in rows 21–40. The supply well and the river therefore lie in different models.

The 30-year seasonal model for transient tracking (Section 4.2)

This model is the seasonal model for snapshots run for 30 years, with one time step per season. After the 1-day steady-state period, 120 seasons of about 91 days follow, so the model has 121 time steps. The well already pumps at its mean rate in the steady-state period. So the initial water is the water of a pumped steady state, not water from before pumping began. Porosity for transport is 0.3. The tagged groups are the recharge, the river leakage, the inflow from the west edge and the initial water. The main runs split each 91-day flow step into four transport sub-steps and use the default "flow" water volumes. The comparison with MODFLOW 6 GWT tags the recharge only, with one transport step per flow step and the "gwt" water volumes. The GWT model has the settings of the GWT run of Text S6, on the flow model's own time steps.

The ensemble (Section 4.3)

The ensemble holds 50 realisations of the shared model. They differ only in their hydraulic conductivity. Each conductivity field is set at 100 pilot points and interpolated to every cell by kriging. The pilot points, the kriging and the random draws are described in Text S5. Mean travel times use a porosity of 0.3.

Percentile maps need memory. Exact percentiles keep every realisation's value of each cell, at 4 bytes per value. For 1,000 realisations of 1 million cells, that is 4 GB for each output of each destination. The code can instead keep a histogram of 200 bins in each cell. The histograms then need about 0.8 GB for each output of each destination, whatever the number of realisations.

The rebuilt model of Bedekar et al. (2024) (Text S11)

Bedekar et al. (2024, pp. 305–306 and Fig. 1) describe their model in MODFLOW-2005. We rebuilt it in MODFLOW 6 from that description. The grid has 101 × 101 cells of 10 m and three layers of 10 m, with the top at 30 m. The horizontal hydraulic conductivity is 10 and the vertical conductivity 1. The specific storage is 10^{-5} m^{-1}, the specific yield 0.1 and the porosity 0.1. Lateral inflow of 1.5 m^3/d enters every cell of the west column in all three layers, as a well package, 454.5 m^3/d in all. Recharge of 3×10^{-4} m/d falls on every cell of layer 1, 306.0 m^3/d in all. A stream (RIV) fills the east column of all three layers, with a stage of 30 m and a conductance of 1,000 m^2/d per cell. The pumping well takes 700 m^3/d. The first stress period is a steady state of 1 day without pumping. The second is 25 years of pumping.

The paper leaves some values open. We made the following choices.

- Units. The paper gives the hydraulic conductivity in feet per day and every other input in metric units. We read the conductivity as 10 and 1 m/d. A rerun with the conductivity in feet per day lowered the

head in the well cell from 26.8 to 19.1 m. It moved the long-run shares of the sources by at most 0.1 percentage points, because the inflow, recharge and pumping are fixed rates.

- Layer type. All three layers are convertible. Only the cells near the well fall below the top of their layer.
- Stream bottom. The river bottom is at the bottom of each cell, so the exchange with the stream stays linear in head.
- Well screen. The well is in layer 2, where Fig. 1 of the paper draws its screen. It is at row 51, column 86, on the centre row and 150 m west of the stream cell centres.
- Time steps. The paper gives neither the length of the pumping period nor its time steps. The pumping period is 25 years, the time axis of the paper's Fig. 2, in 300 equal steps of 30.4 days. Text S11 also reruns the first 15 years with four transport sub-steps, 7.6-day transport steps. With these shorter steps, the largest difference from the read-off curves of the paper's Fig. 2 over the first 15 years falls from 1.3 to 0.6 percentage points.
- Stored water. The paper fixes the concentration of the stored water at 1 during the first period. We tag all the water in the model at the start of the first period as initial water. In that 1-day period, about 760 m^3 of water enters from the sources, against about 3.06 million m^3 of water in the aquifer.

The tagged groups are the lateral inflow, the recharge, the stream and the stored water. The tracking uses a porosity of 0.1 and the "gwt" water volumes. For the comparison, four MODFLOW 6 GWT models carry one group each. They have the settings of the GWT run of Text S6, except a porosity of 0.1 and looser solver criteria (10^{-8} for the outer and 10^{-9} for the inner iterations, and a residual criterion of 10^{-8}). The stored-water model starts with a concentration of 1 in every cell and has no tagged inflow.

After 25 years of pumping the storage terms are close to zero. The flows are then nearly steady. The tracked shares at year 25 then lie within 0.2 percentage points of the shares from a steady-state backward trace of the last step's flows. The 0.2 % of stored water that the well still pumps makes up the difference.

The eight-cell example (Figure S1b)

The eight-cell example is a hand-built network of two rows of four cells, not a MODFLOW 6 model. Boundary inflow of 4 m^3/d enters each of the two western cells. Recharge of 1 m^3/d enters every cell. A well takes 6 m^3/d from one cell of the third column. A river takes 4 and 6 m^3/d from the two eastern cells. Inflow and outflow are both 16 m^3/d.

Test models (Section 3)

The automated tests run on ten test models and two hand-built networks. Their results are in Figure S2. Models 1 to 10 are MODFLOW 6 models built with FloPy. Each writes the binary grid file and a budget file with SAVE_FLOWS on every package. Two further cases are not MODFLOW 6 models. All cells are 50 m wide in plan, except on the Voronoi grid of model 3.

model	grid and size	packages	flow	what it tests
1	DIS, 1 layer of 20 × 30 cells, top 20 m, bottom −30 m; 6 inactive cells in one corner (594 active)	CHD on the west edge (5 m); RIV along one column (stage 6 m); WEL (800 m^3/d); RCH (1×10^{-3} m/d); K 10 m/d	steady state	the base case: closure, forward–backward and boundary-control checks, GWT at equilibrium, PRT, split into three models; the inactive cells test the mapping of cell numbers
2	DIS, 3 layers of 15 × 25 cells (1,125 cells), top 10 m, layer bottoms −10, −30 and −60 m	CHD on the west (9 m) and east (2 m) edges of every layer; RCH (5×10^{-4} m/d) on layer 1; two WEL in layer 3 (400 and 5 m^3/d); K 10, 2 and 15 m/d, vertical K one tenth of it	steady state	a weak-sink well (5 m^3/d) under gross accounting, GWT at equilibrium, PRT; a copy with recharge on the top cell face (IFLOWFACE = −1) tests PRT release on a face
3	DISV Voronoi grid over model 1's area, from a Triangle mesh with triangles of at most 2,500 m^2; all cells active	as model 1, placed by geometry; river conductance scaled to model 1's total	steady state	reading a vertex grid, PRT on a vertex grid, split into two models
4	DISU, a cell-for-cell copy of model 1, with and without cell vertices	as model 1	steady state	DISU results equal DIS results exactly

model	grid and size	packages	flow	what it tests
5	as model 1	as model 1, with XT3D; log-normal K (median 10 m/d), K across the main axis 0.05 times K, main axes rotated by up to 45°	steady state	flow loops
6	as model 1	as model 1, with STO (specific yield 0.2, specific storage 10^{-5} /m); a 1-day steady-state period, then three 100-day periods of four steps with a time-step multiplier of 1.2 (13 steps); pumping 800, 1,200, 400 and 1,000 m^3/d; recharge 1, 0.3, 1.5 and 0 times model 1's	transient	13 snapshots with storage as source and sink terms; transient tracking against GWT; transient forward–backward check; water balances; split into four models
7	as model 1	model 1 with the river replaced by an SFR stream of 20 reaches (inflow 500 m^3/d at the first reach); two DRN drains feeding the first reach through MVR (70 % and 100 % of their outflow); named wells whose list changes between two periods	steady state (two periods)	a package network (SFR and MVR); GWT at equilibrium and transient tracking against GWT with stream and mover transport (SFT and MVT)

model	grid and size	packages	flow	what it tests
8	as model 2	model 2's grid, with the 400 m^3/d well replaced by a MAW well (30 m^3/d) screened in all three layers; the 5 m^3/d WEL kept; vertical K one hundredth of K	steady state	a multi-aquifer well that moves water between layers
9	as model 2, with the layer-1 cells of two lakes removed	LAK with two lakes (lake A spills into lake B, lake B out of the model); UZF on a block of layer-1 cells, whose rejected infiltration MVR moves into lake A; RCH (4×10^{-4} m/d) elsewhere; WEL (150 m^3/d) in layer 3; CHD on the west (9 m) and east (4 m) edges; STO	transient: a 1-day steady-state period, then a 50-day period of two steps	a lake and unsaturated-zone network; transient forward–backward check; water balances
10	as model 1	as model 1, without STO; a 1-day period, then 4×10^5 d in 120 equal steps of unchanged flows	steady-state flows over many time steps	transient tracking reaches the steady-state fractions
worked example	hand-built network of 3×3 cells and two outside nodes (Foley and Black 2013)	none (flows given between cells)	steady state	net accounting against the published values

model	grid and size	packages	flow	what it tests
sub-step network	hand-built network of 15 cells with flow loops, no storage, 6 time steps	none	steady-state flows over time steps	transport sub-steps equal a flow model with proportionally more time steps

Text S3. Accounting at a small well

This text gives in full one of the worked examples summarised in Section 4.4 of the main text. The shared model is the example model of Section 4.

The two accountings of Section 2.2 differ only at weak sinks. A small well in strong regional flow is a weak sink. Its cell passes most of its water on to the neighbouring cells. This example shows how much the choice of accounting changes the water attributed to such a well. The shared model is split into three layers, of which the middle one is the least permeable (Text S2). The supply well pumps 800 m^3/d from layer 3. A second, small well pumps 5 m^3/d from layer 3 at row 17, column 13, upgradient of the supply well.

The small well's cell carries 33.7 m^3/d. The well pumps 5 m^3/d of it. Gross accounting counts only these 5 m^3/d as the well's water. F in its cell is then $5/33.7 = 0.149$. Net accounting fixes $F = 1$ in the cell. It attributes all 33.7 m^3/d to the well. This is 6.7 times what the well pumps. Both accountings find the same flow path, a narrow strip along row 17 from the west edge to the well (Figure S10b, c). Under net accounting, 93–99 % of the water in layer 3 along that strip is assigned to the small well. Under gross accounting, 82 % of the water in the small well's cell flows on to the supply well. The supply well pumps all the water that flows into its cell. It is therefore not a weak sink. For this well the two accountings agree. Gross accounting treats the well as a transport model does. Net accounting remains an option, for comparison with studies that used it.

Two checks test the code. The first is independent. It uses the worked example that Foley and Black (2013) give to explain FlowSource. It is a block of 3×3 cells with given flows and one destination cell (Figure S10a). Net accounting reproduces their published fractions, volumes through and volumes from in every cell to 1×10^{-14}. The second check is internal. Each sink package is traced as its own destination. The fractions to all sinks must then add up to 1 in every cell with outflow. We refer to this as the boundary-control check. Here the fractions add up to 1 within 1×10^{-15}. The same traces give boundary-control maps. Each map shows the share of every cell's water that leaves through one sink.

Text S4. Transient checks on the seasonal example model

All values are for the 30-year seasonal model of Section 4.2, described in Text S2. Unless stated otherwise, they use the default "flow" volumes and four transport sub-steps per flow step, as Fig. 2 of the main text does. In the last season of year 1 alone, the well's water was 95 % initial water, 3 % river leakage and under 2 % recharge. The dashed line in Fig. 2b of the main text is the cumulative share, 98 % after 1 year. Over 30 years the well pumped 8.77 million m^3. Backward tracking in time splits this into 13.8 % river leakage, 18.5 % recharge and 67.7 % initial water, which matches the forward cumulative share of 68 %. Forward transient

tracking and backward tracking in time gave the same tagged volumes to $\leq 4.3 \times 10^{-16}$ for every tag. With GWT's water volumes ("gwt") and one transport step per flow step, the tracked recharge fraction matched a GWT unit-concentration run on the same flows to 9.8×10^{-14}. The backward fractions to the well, to the river and still stored added up to 1 in every cell to within 2.5×10^{-11}, the backward closure error was 0, and the tagged-water balances closed to 8.0×10^{-16} with one transport step per flow step.

With one, four and 16 transport sub-steps per flow step, the river's share of the well's water in the last season of year 1 was 3.6, 3.1 and 3.0 %, and the initial water's share of all water pumped so far after 1 year was 96.9, 97.6 and 97.8 %. From four sub-steps to 16, the year-1 shares moved by at most 0.2 percentage points. Fig. 2 of the main text uses four. With "gwt" volumes, about 5,300 m^3 of the 45.6 million m^3 of initial water is lost over 30 years, so the year-30 share of initial water is 0.5166 against 0.5167 with "flow" volumes. With one transport step per flow step, the two volume options differed by up to 1.9×10^{-4} in the forward fractions and 3.7×10^{-3} in the backward fractions. With one transport step per flow step, the first-step share of new recharge in the well's water was 0.0078, against 0.0042 with 16 sub-steps. Long transport steps make tagged water arrive too early, which sub-steps correct.

Text S5. Ensemble and history-matching set-up

Section 4.9 traces the well in every realisation of an ensemble. It then history-matches the ensemble to head measurements with the PEST++ iterative ensemble smoother (PEST++ IES) and traces the well again. This text gives the set-up, so that the synthetic test can be repeated.

Pilot points and kriging. The hydraulic conductivity of each realisation is set at 100 pilot points. They form a regular grid of 10×10 points, 200 m apart, in rows and columns 3, 7, …, 39. Between the pilot points, $\ln K$ is interpolated by simple kriging around $\ln 5$. The correlation between two points a distance r apart is $\exp(-(r/400\ \mathrm{m})^2)$, with a nugget of 10^{-4} that keeps the kriging equations well conditioned. The kriging weights are computed once and saved.

The prior. The prior ensemble holds 50 realisations. Each draws the 100 pilot-point values as $K = 5\exp(0.8\,z)$, where z comes from a multivariate normal distribution with the correlation above (seed 3). Over the 50 prior fields, $\ln K$ has a mean of 1.60 and a standard deviation of 0.79, against targets of $\ln 5 = 1.61$ and 0.8.

The synthetic truth and its measurements. The true aquifer is a random field with the same statistics as the prior, made in another way. It is not built from pilot points. Its conductivity is $K = 5\exp(0.8\,z)$. Here z is white noise (seed 2024) smoothed by a Gaussian filter with a width of four cells (200 m), then shifted and scaled to a mean of 0 and a standard deviation of 1. A Gaussian filter of this width gives the correlation $\exp(-(r/400\ \mathrm{m})^2)$ of the prior. A kriged field is smoother between the pilot points than the truth. So no realisation can reproduce the truth exactly. The truth's $F > 0.5$ area is 1.025 km^2. The river supplies 9.4 % of its pumped water. Its steady-state heads are measured in 40 cells, drawn at random (seed 11) from all cells except the constant heads, the river and the well. Gaussian noise with a standard deviation of 0.05 m (seed 12) is added to each head. The measured heads range from 6.18 to 10.05 m.

The PEST++ run. Each model run of PEST++ writes the kriged conductivity from the pilot-point values, runs MODFLOW 6 and reads the heads at the 40 measurement cells. The 100 parameters are log-transformed. Their bounds are four prior standard deviations either side of the mean, from 0.20 to 123

m/d. Each measurement has the weight 1/0.05 m. PEST++ IES also adds noise of the same size to the measurements of each realisation. The run uses no extra realisation at the prior mean. It stops after three iterations (NOPTMAX = 3). On eight local workers, the run took 320 model runs and 61 s.

The fit by iteration. The fit of a realisation is measured by phi, the weighted sum of its squared head residuals. With weights of one over the noise, a realisation that fits the heads within the noise has a phi close to 40, the number of measurements. Each iteration runs the whole ensemble once. It also makes a few test runs on part of the ensemble to choose the size of the update. That is why an iteration takes 90 runs for 50 realisations.

iteration	model runs so far	mean phi	standard deviation	smallest	largest
0 (prior)	50	3,491.7	2,282.5	550.2	11,942.5
1	140	223.5	108.0	95.3	578.9
2	230	67.2	13.4	43.9	111.8
3 (posterior)	320	55.5	9.8	35.2	81.5

The largest phi of the posterior, 82, is below the smallest phi of the prior, 550. PEST++ IES starts from the 50 prior realisations. These were run and traced before the history matching. PEST++ keeps no model output for each realisation. So the 50 posterior realisations are rerun from their parameter values and traced in the same way as the prior.

Text S6. Where each source's water goes

This text gives in full one of the worked examples summarised in Section 4.4 of the main text. The shared model is the example model of Section 4.

Some questions start at a source rather than at a receptor, such as a well, a spring or a stream. A water-quality study may ask how much river water, or how much recharge from one field, reaches a receptor. A forward trace answers it. It gives G in every cell. G is the share of a cell's water that came from the source (Section 2.1). The model is the shared model, unchanged.

River water enters the aquifer only through the reaches in rows 19 to 23, where pumping draws the water table below the river stage. From there it spreads to the well (Figure S11a). All 113 m^3/d that the river loses reaches the well. Of the regional inflow at the west edge, 37 % reaches the well. Of the recharge, 29 % reaches the well and 71 % drains to the river (Figure S11c). G in the well cell gives the pumped water by source. The shares are 14 % river water, 15 % regional inflow and 71 % recharge, as the backward trace of Section 4.1 found.

A source can also be one zone. Here it is the recharge on a 300 m × 300 m field in rows 11 to 16 and columns 13 to 18. The field receives 45 m^3/d of recharge. Of this, 39 % reaches the well and the rest drains to the river (Figure S11b). For a solute that does not react, G is the ratio of the concentration in a cell to the concentration at the source. Suppose the field's recharge carried 50 mg/L of nitrate. The well would then pump 1.11 mg/L at equilibrium. Several sources mix in the same way. With invented chloride concentrations of 80 mg/L

in the river, 25 mg/L at the west edge and 5 mg/L in recharge, the well would pump 18.6 mg/L. These are long-run values. G gives no arrival time and ignores reactions.

The forward–backward check requires the volume from each source to the well to be the same from either direction (Section 2.3). Here the two directions agree to better than 1×10^{-6} m³/d. The difference equals the cell budget error term of Eq. (S8). The independent check is MODFLOW 6 GWT. A GWT model gave river leakage a concentration of 1 and all other inflow a concentration of 0. It used upstream weighting and no dispersion. It ran for 10^6 days, until the concentrations stopped changing. Its final concentrations equal G in every cell to 4.2×10^{-13}.

Text S7. The same trace on different grids

This text gives in full one of the worked examples summarised in Section 4.4 of the main text. The shared model is the example model of Section 4.

MODFLOW 6 models are not limited to regular grids. Some use Voronoi grids refined around wells and rivers (DISV) or fully unstructured grids (DISU). Some use the XT3D option of MODFLOW 6 for anisotropy. This example builds the shared model on four grids. The first is the regular grid (DIS). The second is a Voronoi grid (DISV) made with vorflow (Hugman and Sanchez 2026), a Python package that builds Voronoi grids for MODFLOW 6. Away from the well and the river, its cells are about 50 m across, like the regular cells. They shrink to about 10 m at the well and to 12.5 m along the river. The grid has 3,241 cells. The last two grids hold the regular cells written as DISU, with and without cell vertices. The same lines of code trace the well on each grid.

The two DISU models have the same cells and connections as the DIS model. Their F is identical to the DIS result in every cell. Without cell vertices, a DISU model gives fractions and volumes but no maps or GIS polygons. PRT runs only on DIS and DISV grids. A particle check of the edge is therefore not available on DISU grids. The Voronoi model is a different model of the same aquifer (Figure S12a, b). Its contributing area has the same shape and reach. Its expected area is 0.4 % larger, 1.178 against 1.173 km². On the north side of the area at x = 0.5 km, F falls from 0.5 to 0.1 over 186 m on the Voronoi grid, against 121 m on the regular grid. Because the water flows along the rows of the regular grid, each of its cells passes nearly all its water to one neighbour. Each Voronoi cell splits its water among two or three downstream cells, because its faces lie at many angles to the flow. We read the wider edge as a sideways spread of F by these splits. This numerical dispersion comes from the grid, not from the aquifer (Section 6). On a grid of 47 m squares turned by 45° to the flow, the edge of the same model is 215 m wide. On a Voronoi grid with cells of about 25 m, it is 126 m wide. On both grids the well's cell is centred on the well. The river cells are centred on the river line on both grids too. So the nearest river cell centre is 100 m from the well's cell centre on both grids. The river supplies 14 % of the pumped water on both grids. The largest difference is at the west edge. The regular grid holds the fixed heads in a column of 50 m cells, with their centres 25 m inside the edge. The Voronoi grid holds them in narrow cells centred on the edge itself. On the Voronoi grid the west edge supplies 13 % of the pumped water instead of 15 %. Its inflow to the aquifer is 290 m³/d instead of 324 m³/d. We read this difference as a result of where each grid places the fixed heads. We did not test this reading by moving the west edge alone.

XT3D computes the flow across a face from the heads of the surrounding cells as well. Flow can then run

against the head difference between two cells. Water can go round in flow loops (Text S1). The example uses a heterogeneous hydraulic conductivity with 20:1 anisotropy. The axes of the anisotropy rotate across the model. The trace found five groups of cells with flow loops, 40 cells in all (Figure S12c). Together they circulate 4.4 m^3/d. That is 0.016 % of the summed outflow of all cells in the model. The code solves the cells of each group together as one small block. The result equals a plain sparse solve of the whole system to 3.3 $\times 10^{-16}$. Foley and Black (2013) found flow loops rare, mostly in models with convergence problems. They delete the smallest flow in each loop. In their tests the effect was negligible. With XT3D, the loops are part of the flow solution. Under net accounting, deleting those flows on this model changes F by up to 0.155.

Text S8. The contributing area through the seasons

This text gives in full one of the worked examples summarised in Section 4.4 of the main text. The shared model is the example model of Section 4.

Recharge is highest in the wet season. Many supply wells pump most in the dry season. So the contributing area moves through the year. This example makes the shared model transient. It adds storage, with a specific yield of 0.2 and a specific storage of 1×10^{-5} m^{-1}. Recharge is scaled by 1.8 in the wet season, 1.0 in the wet-to-dry transition, 0.1 in the dry season and 1.1 in the dry-to-wet transition. The well pumps 640, 800, 1,120 and 640 m^3/d in the same seasons. After a 1-day steady-state start, the model runs for 3 years, with three steps of about 30 days in each season. Each of the 36 seasonal steps is traced as a snapshot (Section 2.4).

Figure S13a–d maps F in the middle step of each season of the last year. The $F > 0.5$ area is smallest in the wet season, at 0.59 km^2. In the wet season the well pumps least. The rising water table also puts water into storage. Storage then acts as a sink that takes part of each cell's water. In the dry season the $F > 0.5$ area grows to 1.35 km^2. Its western end moves 350 m, out to the west edge. The well's sources change too. In the dry season, water released from storage supplies 52.5 % of the pumped water. In the wet season, recharge supplies 91 %.

Statistics over the 36 steps summarise the seasons in one map (Figure S13e). Cells with $F > 0.5$ in every step form an inner zone of 0.52 km^2. Cells with $F > 0.5$ in some steps but not all add a seasonal zone of 0.93 km^2. Cells with $F > 0.1$ in at least one step make up an outer envelope of 1.86 km^2. Of that envelope, 0.41 km^2 lies outside the other two zones. These nested zones are one way to combine the maps. They are not a rule for drawing protection zones.

The code builds the statistics one step at a time, so that its memory does not grow with the number of steps. They agree with statistics recomputed from all 36 stored maps to 1×10^{-14}. In every snapshot, the traced sources add up to the pumping within 1×10^{-6} m^3/d. Both checks test the code, not the snapshot method. The snapshot method itself has no travel lag (Section 2.4). Section 4.2 compares snapshots with transient tracking of a 30-year run of the same model.

Text S9. Mean travel time to the well

This text gives in full one of the worked examples summarised in Section 4.4 of the main text. The shared model is the example model of Section 4.

Protection zones are often drawn by travel time as well as by area. A spill 50 days upgradient of a well calls for a different response from a spill 50 years upgradient. This example adds the mean travel time of Text S1 to the backward trace of the shared example model (Section 4). The only new input is a porosity of 0.3. In a steady-state model every travel time is proportional to porosity, so a range of porosities needs no new run.

The mean travel time of all the water reaching the well is 46 years. River water reaches the well in about 2 years, because the losing river cells lie next to it. Recharge takes 42 years on average. Inflow from the west edge takes 108 years, because it enters at the far end of the contributing area. A time-of-travel zone holds the cells with $F > 0.5$ whose mean travel time is shorter than a stated limit (Figure S14a). The 5-year zone covers 0.098 km^2 and the 25-year zone 0.455 km^2. Water spends about a month in the well cell, so 50 m cells cannot draw a 50-day zone.

Particle tracking with PRT gives a purely advective answer on the same flows. The particles are the weight-losing particles of Section 4.1. A particle stops when it enters the well cell, so the full-mixing times are also taken to the well cell. Over all the water, the mean particle time is 45.7 years, 0.5 % below the full-mixing time of 45.9 years. This agreement is not an independent test. In both methods, the mean travel time of all the water is close to the volume of water that will end at the well divided by the pumping rate. That volume is nearly the same in both.

The comparison cell by cell is the informative one (Figure S14b). In the 456 cells with $F > 0.5$, apart from the well cell itself, the median ratio of particle time to full-mixing time is 0.96. In the 676 cells with $F < 0.5$, it is 5.7. A particle from a cell with small F follows one slow path around the edge of the zone. Full mixing averages over all the paths that the cell's water takes. The particle time-of-travel zone is 26 % larger at 5 years and 2.2 % larger at 25 years. A mean travel time is not the first arrival of a contaminant, so short time-of-travel zones still need particles on a grid refined near the well.

Text S10. Streams, drains, wells and linked models

This text gives in full one of the worked examples summarised in Section 4.4 of the main text. The shared model is the example model of Section 4.

In many models water leaves the aquifer cells and comes back. A drain may pass its water to a stream through the water mover (MVR). The stream may then lose that water to the aquifer near a well. A trace on the aquifer cells alone stops at the stream. It reports the leakage as a source with no history. This example shows what changes when stream reaches and wells are traced as cells of their own (Section 3).

The river of the shared model becomes a stream of the SFR package, with one reach per row, flowing from north to south. The first reach receives 300 m^3/d from upstream. Two drains lie 800 m west of the stream. Through the mover, one passes 80 % of its water to the first reach and the other all of it. The upper reaches lose water to the aquifer. The reaches below the well gain water from it.

On the aquifer cells alone, 32 % of the well's water is stream leakage (Figure S15a). With the reaches traced as cells, that water splits into 129 m^3/d of upstream stream inflow and 126 m^3/d of recharge. That recharge reached the stream through the drains and the mover. The land drained by each drain therefore joins the contributing area (Figure S15b). Of the 800 m^3/d pumped, 188 m^3/d passed through the mover. The F of each reach shows which part of the stream feeds the well (Figure S15c). Only the first 21 reaches do.

A multi-aquifer well (MAW) can carry water between layers in a similar way. A three-layer version of the shared model has an aquitard as its middle layer. The supply well draws from the bottom layer. A MAW screened in all three layers pumps 10 m^3/d. Its borehole takes 24.3 m^3/d from the upper two layers and passes 14.3 m^3/d into the bottom layer. On the cells alone, those 14.3 m^3/d of the supply well's water have no origin. With the borehole traced as a cell, they are recharge that fell near the MAW. On the cells alone, the water that the borehole takes from the upper layers leaves the trace. In the MAW's cell of the top layer, F is then 0.06. With the borehole traced, it is 0.53 (Figure S15d, e).

On the stream model, the traced volumes add up to the pumping to round-off, with and without the reaches as cells. Large models are sometimes split into several linked models, for example with the FloPy model splitter (Hughes et al. 2024). The shared model, split into three models, gives F to within 2×10^{-13} of the single model. Both simulations solve the same flow equations, so this is a consistency test. It shows that no water is lost where the models meet. Movers between models are not read yet, so water moved between models still appears as a sink in one model and a source in the other.

Text S11. A new well's source mix

This text gives in full one of the worked examples summarised in Section 4.4 of the main text.

When a new well starts pumping, its water changes over the years from mostly stored water to water from the sources that feed it. Bedekar et al. (2024) showed this with the unit-concentration method on a synthetic MODFLOW-2005 and MT3D-USGS model (Section 1). Forward transient tracking solves the same transport equation without dispersion, as their example does. Their example therefore also tests transient tracking against a published result made with other codes.

We rebuilt the model in MODFLOW 6 from the paper's description. It has three layers of 10 m, each with 101×101 cells of 10 m. Water enters as lateral inflow along the west edge and as recharge. A stream bounds the east edge. A well 150 m from the stream pumps 700 m^3/d for 25 years. The paper leaves some values open, such as the time steps and the layer of the well screen. Our choices are listed in Text S2.

One forward run with four tags gives the share of the pumped water from each source (Figure S16a). The fourth tag is the stored water, which is the initial water of Section 2.4. Stream water arrives within the first year. Lateral inflow enters 850 m from the well and first appears after about 7 years. At year 25 the well's water is 48.2 % lateral inflow, 29.2 % recharge and 22.5 % stream water. The paper gives 48 %, 29 % and 23 %.

Backward tracking in time adds the time-limited contributing area (Figure S16b–e). The maps show layer 2, where the well is screened. Within 1 year, the well pumps more than half the water of 841 cells in that layer, between the well and the stream. Within 25 years the area covers 6,825 cells of the layer. That is nearly the 6,829 cells of the steady-state $F > 0.5$ area of the final flows (Figure S16f). We expect that a forward unit-concentration model would need one run per zone of the aquifer to give such a map.

Four MODFLOW 6 GWT runs, one per source, give the same fractions to 1.5×10^{-10} in every cell and step, when the tracking uses GWT's water volumes. The two codes solve the same equations, so this is a consistency test. The independent check is Figure 2 of the paper, read off to about one percentage point. Over 15 read-off times, the largest difference is 1.3 percentage points, on the lateral-inflow front at year 10.

The timing of each front depends on the length of the transport step. With 30-day steps, the stream share after 6 months is 1.1 %. With transport sub-steps of 7.6 days it is 0.4 %. Where arrival times matter, the transport step should be checked by refining it (Section 4.2).

Text S12. End states of the published particles

Each published MODPATH 7 particle on the calibrated model ends in one of three ways (MODPATH status codes 2, 3 and 5). We classed each end cell on the MODFLOW 6 budget: a strong sink sends all of its outflow to boundary sinks, a weak sink only part of it.

Table. End states of the 122,021 published particles, calibrated model.

end state (MODPATH status)	particles	end cells	particles ending in a priority well
leaves the model through a cell face (2)	89,920	top face of a stream cell with no active cell above: 88,781; side face next to a dry cell: 1,139	0
stopped on entering a weak-sink cell (3)	27,631	buried stream cells: 26,828; wells: 612; constant heads: 191	466 (SV_407 32, SV_487 97, U__55 116, U___7 58, U___8 163)
ends in a cell with no exit face (5)	4,470	wells: 2,570; buried stream cells: 1,472; constant heads: 428	514 (SV_193 48, SV_227 115, U_917 351)
all	122,021		980

Status 5 is the normal end at a strong sink, not an abnormal stop. The 980 published contributing cells are the 514 particles that end in the three priority wells that take all of their cell's outflow, plus the 466 stopped in the five priority wells that take only part of it.

The split between status 2 and status 3 shows a convention that the comparison inherits. The published runs put recharge and stream flows on the top face of the cell. MODPATH 7 does this only where the top face has no active neighbour; elsewhere the flow stays distributed in the cell. A particle that reaches a stream cell with no active cell above therefore leaves through the top face (status 2), while one that reaches a buried stream cell is stopped there as at a weak sink (status 3). Every particle that stops in a stream cell (status 3 or 5) has an active cell above it, and none of those that leave through a stream cell's top face has. The 1,139 particles that leave sideways all leave into a dry neighbour, which the published runs treat as inactive.

At the weak-sink wells the published convention and full mixing part ways. The well of U___7 takes 44 % of its cell's outflow. All the water of a published particle that enters the cell still counts as reaching U___7. Under full mixing the other 56 % of the cell's outflow passes on, most of it to U___8 and U_917, so that 97 % of the water in the cell reaches a priority well ($F = 0.97$).

Text S13. Notes and sources for the comparison of methods

This text gives fuller notes on the entries of Table S1 that the footnotes of the table shorten or leave out. The notes are ordered by table row and then by column. The sources for each entry follow, column by column. A year in parentheses in the table dates a statement to the 2013 papers. We found no published description of later versions of FlowSource.

Notes on the cells

- What is solved, and how (this paper's code). There is one set of equations for the backward fraction F and one for the forward fraction G. Without flow loops, the equations are solved cell by cell in flow order. With flow loops, they are solved loop by loop in flow order. Net accounting solves one destination group at a time. In transient tracking, each time step is one set of linear equations, implicit in time. When the water volumes change within a flow step, each sub-step is one set instead. The equations of a step or sub-step are solved for all tagged groups at once.
- What is solved, and how (GWT unit concentration). Langevin et al. (2022) state that GWT "does not have an option to calculate steady-state transport solutions". According to them, steady state is reached by running transient steps until the concentrations stabilise. The GWT Model needs the storage (MST) package. Without it, MODFLOW 6 (6.9.0.dev0) stops at input with the message "Mass storage and transfer (MST6) package not specified". In our test we set the MST porosity to 0. This use is not described in the parts of Langevin et al. (2022) that we read. One transport step on the flows of test model 1 then gave a steady-state unit concentration equal to G to within 9.5×10^{-13} with recharge tagged. With the river tagged, the difference was 9.7×10^{-13}. The list file showed no warning.
- What is solved, and how (hydraulic mixing cells). The fractions at each step are computed from the previous step's fractions and the volumes moved over the step. No system of equations is solved. The update is stable only if the volume entering or leaving a cell over a step does not exceed the cell's storage. Small cells and long steps cause oscillations.

  Later versions change the method in steps. Partington et al. (2012, Section 2.2) apply the method of Partington et al. (2011) unchanged, built into a version of HydroGeoSphere. Partington et al. (2013, Section 3.3) add overland-flow fractions, sub-time-steps and cell resets. They define the HMC ratio as the outflow over a step divided by the cell's storage at the start of the step (Eq. 2). This ratio must stay below 1. Where it exceeds 1 in any cell, each flow step is split into $s = [\text{max. HMC ratio}] + 1$ sub-steps. The fluxes and storage changes are split among the sub-steps (Eqs 3–9). A cell is reset if it meets any of five criteria, such as an HMC ratio above 10^4 or $|1 - \Sigma f| > 0.5$. Its fractions are then set to 0. Its water is assigned to a tracked "reset" fraction (Section 3.3.3). The mixing cells of 2013 are still surface cells only. They are stream and overland cells (Section 3.3.1). Partington et al. (2013) recommend tracking in the subsurface as future work (Section 6, para. 73).

  Fractions in aquifer cells came later. Schilling et al. (2017, Section 2.4.2.1) run the mixing cells on a HydroGeoSphere model of the alluvial river–aquifer system around a drinking-water wellfield in the Emme valley, Switzerland (Section 2.2). Water entering through each boundary condition is tagged. Its fraction is tracked "in each of the model cells". Figure 5 maps the river-water fraction in the aquifer. They give no update equation, stability limit or reset criterion. They keep numerical dispersion small

with a fine grid and a sub-time-stepping scheme that sets the step size automatically. They cite Partington et al. (2011) for this scheme. In our reading, sub-steps first appear in Partington et al. (2013). Fractions are computed for steady-state and transient runs (Section 2.4.1). The river-water fraction in the pumped water is compared with fractions from noble-gas recharge temperatures and helium isotope ratios (Eqs 8–9; Section 3.4, Fig. 8). This fraction is then used to choose the riverbed conductivity and aquifer porosity. No water-balance check of the fractions is reported. No transport run is reported either. Nogueira et al. (2022, Sect. 2.2, Eq. 1) track fractions in every model cell, surface and subsurface, of a riparian zone. All the versions we read step forward in time only.

- Mixing in a cell (GWT unit concentration). GWT also offers central-in-space and TVD advection, dispersion and reactions (Langevin et al. 2022). With upstream weighting and no dispersion, its steady-state limit equals G (Text S6; Figure S2). Bedekar et al. (2024) ran their examples in MT3D-USGS. They do not name the advection scheme. They left mechanical dispersion out of their synthetic example. They left dispersion and diffusion out of their field example. They warn that numerical dispersion changes the timing of source contributions. Numerical dispersion is the spreading added by the numerical scheme.
- Mixing in a cell (hydraulic mixing cells). The method follows the modified mixing cell of Campana and Simpson (1984). Water leaving a cell over a step carries the previous step's mix. Water entering a cell stays there until the next step.
- Accounting at weak sinks (FlowSource). Foley and Black (2013) define all water starting in or passing through a destination cell as reaching the destination. All the water passing through a weak-sink well's cell therefore counts as the well's water.
- Flow loops (this paper's code). A closed recirculation loop has no outflow to any sink or to a cell outside the loop. Such a loop is given $F = 0$ and reported. With net accounting, the smallest-flow connection in each loop can instead be deleted, as in FlowSource. The option for this is `remove_cycles`.
- Outputs (FlowSource). The outputs are the volume through, the volume from (by budget term) and the fraction from. They also include statistics over time steps.
- Outputs (this paper's code). The outputs also include boundary-control maps. These are the fractions to all sinks, which add up to 1 in every cell. The outputs further include the mean travel time and statistics over steps. In transient tracking, they include the fractions leaving through other sinks and the fractions still stored.
- Outputs (hydraulic mixing cells). The method tracks K flow components. These are groundwater, unsaturated flow, overland flow, preferential flow and direct rainfall. Their fractions are updated together. They sum to 1 in each cell. Initial fractions are assumed. A dummy fraction holds the initial water until it is flushed out.
- Backward in time (GWT unit concentration). Langevin et al. (2022) document no backward-in-time option. A backward steady-state run would need a flow field with reversed flows, with sources and sinks swapped. Such a run is possible but awkward. Potter et al. (2008) made such a run in MT3DMS for one well in uniform flow. They reversed the flow and turned the well into an injection well of concentration 1. Bedekar et al. (2024) list well capture analysis among the uses. In their example the

share of each source at the well is read forward in time, from the concentration simulated there. They describe no backward-in-time or reversed-flow run.

- Built-in water-budget checks (this paper's code). The code also reports closed recirculation loops. Transient tracking adds the forward–backward check in time and the water and tagged-water balances.
- Built-in water-budget checks (GWT unit concentration). With unit concentration, the solute mass is the tagged water volume. The GWT mass budget, by term and step, is therefore a tagged-water balance. The GWT budget file holds the solute mass flows of each cell by term. The terms are intercell flow, storage, source and sink mixing, and the advanced packages. The list file reports the mass budget of the whole model, with its percent discrepancy, at each saved step. We saw both in our runs. GWT has no backward solve. The backward closure, forward–backward and boundary-control checks of Section 2.3 therefore have no GWT counterpart.
- Built-in water-budget checks (hydraulic mixing cells). The relative error $e = 1 - \Sigma f$ follows from the fractions summing to 1. The global volume error compares the groundwater volume in the stream cells at the end with the exfiltration summed over the run, taken from the model's water balance. It holds only on reaches that gain water along their whole length. This comparison of a traced volume with a water-budget total is close to our closure check.
- Grids and packages (this paper's code). The code handles DIS, DISV and DISU grids and GWF-GWF exchanges. SFR reaches, lakes, MAW wells and UZF cells are added as extra cells and linked by MVR.
- Grids and packages (hydraulic mixing cells). The mixing cells are stream cells of the HydroGeoSphere surface domain. Partington et al. (2011) say the method can be implemented in any code that reports surface–subsurface exchange in a spatially distributed way.
- MODALL, all rows. MODALL (Potter et al. 2008) reads the saved cell-by-cell flows of a steady-state MODFLOW-88 model and assumes full mixing in each cell (p. 336). For each extraction well it computes the capture fraction (p. 336). This is the share of each cell's water that the well takes in the end. It is the backward fraction F of Section 2.1. The calculation starts at the well cell. There the fraction is the well's pumping divided by the cell's total inflow (Fig. 1, p. 336). At a weak-sink well the fraction thus counts only what the well pumps. This is gross accounting (Section 2.2). The other cells follow one at a time, working outward from the well. Each cell's fraction is the sum of its outflows to its neighbours, each weighted by that neighbour's fraction, divided by its inflow (Fig. 1). In our reading this is one sweep through the cells, not an iteration or a linear solve. The paper does not say how the cells are put in order. It does not say what happens where water circulates in a flow loop. Foley and Black (2013) state that MODALL does not use graphs. The flow-order sort of FlowSource rests on graphs. Black and Foley (2013) report, from a personal communication, that MODALL did not delineate the capture areas on a model with flow loops. They attribute this to the flow model, not to the MODALL method. Before the sweep, a first pass limits the calculation to the capture envelope. This is the set of cells with some flow from a source or to a sink. The other cells are treated as no-flow cells (p. 336). One output file is written per well. A further file adds them up for the whole system (p. 336). The paper says MODALL can also give the share of each cell's water that came from a source. It names recharge, rivers and drains, besides wells, as sources or sinks (pp. 335–336, 338). The worked

calculation covers extraction wells only. No water-budget check is described. For one well in uniform flow, the contour where the fraction is 0.5 matched the capture zone of an analytical solution and of MODPATH (pp. 337–338). MT3DMS run on the reversed flows gave the same contours (p. 338). The fractions spread more widely on coarser grids (p. 338). McLane and Cecan (2009) add that this spread is not hydrodynamic dispersion. They also state that the fractions are not a probability of capture. No run times are given. The authors offer the tool free of charge for unrestricted use (p. 336). The paper does not say whether the source code is available.

Sources by column

The notes below give the source for each entry of Table S1, column by column. We give page numbers where the source has them. The two 2013 conference papers (Foley and Black 2013; Black and Foley 2013) have no page numbers, so we cite them by section heading. We cite Partington et al. (2011) by section and equation number.

Read in full, and read as secondary account only

We read the following sources in full. They are Foley and Black (2013), Black and Foley (2013), the authors' manuscript of Partington et al. (2011), Bedekar et al. (2024, pp. 303–309), Partington et al. (2013), the authors' manuscript of Partington et al. (2012), Potter et al. (2008, pp. 335–340) and McLane and Cecan (2009, pp. 172–173). In Partington et al. (2013) we checked Eqs 2–9 on p. 5507. McLane and Cecan (2009) is a comment on Potter et al. (2008). Tosco et al. (2010) was read for what it says on Potter et al. (2008). From Langevin et al. (2022) we read the abstract and chapter 1 (pp. 1–1 to 1–8). We also read the formulation and flow-imbalance correction of chapter 2 (pp. 2–1, 2–6 to 2–7), mobile storage (p. 3–1) and advection weighting (pp. 4–1 to 4–2). Finally, we read the SSM Package (pp. 5–1 to 5–3) and the introduction to chapter 6 (p. 6–1). From Chowdhury (2016) we read Sections 2.3.3 and 2.4 and p. 103. From Nogueira et al. (2022) we read Sect. 2.2 and 4.5. We also read Schilling et al. (2017). We used Nogueira et al. (2022) and Schilling et al. (2017) for the note on hydraulic mixing cells only.

We also read secondary accounts of Potter et al. (2008) alongside its full text. These accounts are in McLane and Cecan (2009), Chowdhury (2016), Bedekar et al. (2024, p. 304), Foley and Black (2013), Black and Foley (2013) and Tosco et al. (2010).

FlowSource

- What is solved, and how. Foley and Black (2013, Method and Evaluation) sort the cells in flow order and then make one arithmetic pass. Earlier versions used recursive scans. Each time step is processed on its own (Foley and Black 2013, Introduction).
- Mixing in a cell. In Foley and Black (2013, Description of Calculation), a cell where the flow divides splits its water in proportion to its outflows. Chowdhury (2016, Section 2.4.3) describes this as full mixing.
- Accounting at weak sinks. Foley and Black (2013, Description of Calculation) count all water starting in or passing through a destination cell as reaching the destination. Their cell A is assigned 100 %. The volume from uses each cell's excess of outflow over inflow. The outflows of destination cells are detached so that nothing downstream is counted (Foley and Black 2013, Method).

- Flow loops. Foley and Black (2013, Method and Evaluation) remove the lowest-volume connection. In the Method section they call the choice of which connection to remove an open research question. Black and Foley (2013, Introduction to Graphs) refer to the "lowest flow volume cell connection(s)". The table dates this entry to 2013 because we found no published description of later versions.
- Outputs. Foley and Black (2013, Introduction and Figs 1–4, 6–8) give the volume and fraction through and the volume and fraction from. The volume from is split by recharge, storage and boundary term if other budget records are read. Black and Foley (2013, Introduction) give the minimum, maximum, mean, ASN and probability within a range. They also give a travel time from forward particles, based on MODPATH 6.
- Transient models. Foley and Black (2013, Introduction) and Black and Foley (2013, Introduction and Problem Description) treat each time step as a "time-instant steady state" (Rushton 2003). Particles for travel time are tracked through each step's steady-state flows (Black and Foley 2013, Introduction).
- Backward in time. Neither Foley and Black (2013) nor Black and Foley (2013) describe tracking backward in time. This follows from the snapshot treatment.
- Destinations or sources per run. In Foley and Black (2013, Evaluation) and in the river-catchment and boundary-control examples of Black and Foley (2013), up to about 150,000 destination cells are processed as one group in one calculation. The four boundary-control maps (Figs 18–21) were "processed individually". They sum to 1 in every cell.
- Built-in water-budget checks. Foley and Black (2013, Method) report flow loops to the user as a sign of a flaw in the model. No closure or other budget check is described.
- Grids and packages. Foley and Black (2013, Abstract and Introduction) read MODFLOW-96 and MODFLOW-2005 CBC files. They say the method applies to MODFLOW-USG and to finite elements. Black and Foley (2013) use MODFLOW-96. Neither paper mentions MODFLOW 6 exchanges, MVR or package networks.
- Open implementation. The end matter of Foley and Black (2013) and Black and Foley (2013) states that the program is available on request. The VB.NET source is available on request for academic use.

This paper's code

The entries rest on Sections 2–4 of this paper, on Text S1 and on the open code. The solvers work in flow order and loop by loop. Closed recirculation loops are found and reported. Net accounting is solved one destination group at a time, with the option `remove_cycles`. Transient tracking and backward tracking in time handle all tagged groups in one solve per step or sub-step. They include the water and tagged-water balances and the forward–backward check in time. The code has closure and forward–backward checks and a flow-loop report. The mean travel time (gross accounting only) comes with its own closure checks. Section 3 and Figure S2 cover the grids, exchanges and package networks. The boundary-control check is a test , not a built-in function. The table therefore does not list it. The licence is MIT.

GWT unit concentration

- What is solved, and how. The abstract of Langevin et al. (2022) describes implicit, iterative methods. It also holds the words on steady state quoted in the notes above. On p. 2–1, the cell balances form a system of linear equations. On p. 1–7 (items 4 and 10), they list central, upstream or TVD advection. They also state that there is "no option to automatically run the GWT Model to steady state using a

single time step". Steady state is found by running transient steps until the concentrations stabilise.

For the note on GWT steady state, we ran a GWT model on the saved flows of test model 1 with MODFLOW 6 6.9.0.dev0. The model used upstream advection and no dispersion, with the flow-imbalance correction on. Either the recharge or the river was tagged. The GWT outer and inner DVCLOSE were 1×10^{-12} and 1×10^{-13}. RCLOSE was 1×10^{-9}. With MST left out, the run stops at input. We then ran one transport step of 1 day with MST porosity 0. The largest $|C - G|$ over the 594 active cells is 9.5×10^{-13} with recharge tagged. It is 9.7×10^{-13} with the river tagged. With porosity 10^{-12}, the two values are 3.8×10^{-8} and 2.4×10^{-9}.

- Mixing in a cell. Langevin et al. (2022, pp. 4–1 to 4–2) describe upstream weighting. Dispersion is an option (chapter 4). Bedekar et al. (2024, pp. 303–305) state that transport represents the mixing and dilution of water from different sources. In their view, particle tracking may not represent this mixing (p. 303). Mechanical dispersion is optional. Adsorption, molecular diffusion and reactions are left out. An evapotranspiration boundary must remove solute with the water (p. 305). Weak sinks are not discussed. The match to G is this paper's own check (Text S6 and Figure S2). The difference is at most 2.8×10^{-11} at equilibrium on models 1 and 2.

- Accounting at weak sinks. Langevin et al. (2022, p. 5–3, eq. 5–7) state that, by default, water leaving a cell through a stress package leaves at the cell's concentration. The flow-imbalance correction is on p. 2–6, eq. 2–14.

- Flow loops. Langevin et al. (2022) do not discuss flow loops. The table entry is our inference.

- Outputs. In the abstract, Bedekar et al. (2024, p. 303) set the concentration to one for the source water assessed and to zero for all other water. They list the uses as source allocation, well capture analysis, and mixing and dilution. On p. 304 they read the concentration as the fraction of a cell's water that comes from the source. Any sources and sinks can be assessed, model boundaries included. On p. 306 and in Fig. 2 they show the share of each of four sources at a pumping well over 25 years. On pp. 306–307 and in Fig. 3 they show the spread of injected water around two recharge wells over 20 years. The agreement with forward tracking is shown in Section 4.2, in Text S11 and in Figure S2.

- Transient models. In Langevin et al. (2022, p. 3–1, eqs 3–2 and 3–3), the storage term holds the dissolved mass in the cell's water volume, using porosity and saturation. It is implicit in time. Bedekar et al. (2024, pp. 305–306) use a steady-state first stress period, followed by 25 years of pumping. The stored water is tagged with $C = 1$ in every cell during the first period. This gives the share of pumped water that comes from storage (Fig. 2). On p. 307 they note that arrival times scale with the porosity of the transport model. They add that a steady-state answer needs a run long enough for the concentrations to settle.

- Backward in time. The parts of Langevin et al. (2022) that we read have no reverse or adjoint option. Bedekar et al. (2024, p. 306) read capture forward in time, from the concentration at the well. They describe no backward-in-time or reversed-flow run (pp. 303–308). A backward steady-state run would need reversed flows.

- Destinations or sources per run. A GWT model holds one species (Langevin et al. 2022, p. 1–6, item 1). A simulation can hold several GWT models. Bedekar et al. (2024, p. 306) made four MT3D-USGS

runs, one per source. They note that each source could instead be a separate species in one multi-species run. On p. 308 they note that the method may take time to set up. It may also need substantial computer time.

- Built-in water-budget checks. The GWT budget file holds the solute mass flows of each cell, in mass per time, by term. The terms are FLOW-JA-FACE, STORAGE-AQUEOUS, SOURCE-SINK MIX, CNC, SRC, LKT, SFT, MWT, UZT and others. The list file holds the "MASS BUDGET FOR ENTIRE MODEL" with its "PERCENT DISCREPANCY". We saw both in the runs of the note on GWT steady state. With unit concentration, the solute mass is tagged water volume. The budget is therefore a tagged-water balance. The parts of Langevin et al. (2022) that we read describe no check of traced volumes between a source and a destination. In Bedekar et al. (2024, p. 306), the shares of the four sources at the well, each from its own run, add to 100 %. This confirms that every source is accounted for. On pp. 305 and 307 they note that numerical dispersion, oscillations and mass balance errors in the flow or transport run can give misleading water budgets.
- Grids and packages. Langevin et al. (2022, pp. 1–6 to 1–7, items 3 and 11) list the DIS, DISV and DISU grids. They also list the SFT, LKT, MWT, UZT and MVT packages. Transport in these packages is by advection only, between package features and with the aquifer.
- Open implementation. MODFLOW 6 can be downloaded free of charge from the USGS (Langevin et al. 2022, Preface).

Hydraulic mixing cells

All entries in this column rest on the authors' manuscript of Partington et al. (2011). We read it in full. The column describes the 2011 method itself. In that method the mixing cells are stream cells of the surface domain only. Section 3.1 refers to "a stream cell i". Sections 3.2–3.3 build these cells from pairs of adjacent HydroGeoSphere grid points across the stream. Later versions are described in the note on hydraulic mixing cells under "What is solved, and how". That note draws on the full texts of Partington et al. (2012, 2013), Schilling et al. (2017) and Nogueira et al. (2022).

- What is solved, and how. Eqs 8–9 in Section 3.1 give the fraction of component k in cell i at step N. The inputs are the cell's storage at $N - 1$ and N, the outflow volume over the step at the cell's own fraction at $N - 1$, and the inflow volumes at the neighbours' fractions at $N - 1$. No system of equations is solved. The stability limit is given in Section 3.1, after Eq. 9, and in Section 4. The volume entering or leaving a cell over a step must not exceed its storage. Small cells and long steps cause oscillations. Suitable time steps are therefore needed. The volumes over each step come from the flow model's fluxes at the end of the step (Eq. 11). There are no sub-steps.
- Mixing in a cell. Sections 3 and 4 base the method on the modified mixing cell of Campana and Simpson (1984). They state that "the modified mixing rule has to be used" unless mixing in the river is simulated. In Section 3.2, the outflow over a step leaves at the previous step's fractions. Water entering a cell stays there until the next step. In Section 3.1, Eq. 9 tends to the perfectly mixed cell of Eq. 10 as the step goes to 0.
- Accounting at weak sinks. In Section 3.2 and Eq. 9, every outflow of the cell, downstream or to the subsurface, uses the cell's previous-step fractions. That this amounts to gross accounting is our

reading. Partington et al. (2011) do not discuss weak sinks.

- Flow loops. Flow loops are not discussed. Sections 3 and 4 state that the coding assumes a constant stream width and a fixed stream flow direction.
- Outputs. Section 3.1 (Eqs 5–7) defines K components. These are groundwater, unsaturated flow, overland flow, preferential flow and direct rainfall. Their fractions sum to 1. Section 3.2 adds a "dummy (or undefined) fraction" for the initial water, until the stream water is turned over. The method is applied to give the groundwater component of streamflow at each stream cell (Section 3.3.2, Figs 11–12).
- Transient models. Section 3.1 (Eqs 4–6) carries the cell volumes and component volumes from step $N - 1$ to N. Section 3.2 says the initial fractions are subjective. The dummy fraction falls to zero once the stream water is turned over.
- Backward in time. There is no backward option. The method steps forward from initial fractions (Sections 3.1–3.2).
- Destinations or sources per run. All K components are updated together (Eqs 5–8).
- Built-in water-budget checks. Section 3.3.1 gives two checks. The first is the relative error e from the sum of fractions (Eq. 13). Its maximum is 1.5×10^{-3} % in test case 1 and 8.7×10^{-3} % in test case 2. The second is the global volume error (Eq. 14). It compares the summed groundwater volume in the stream cells at the end with the summed exfiltration over the run, taken from the model's water balance. It "can only be used along completely gaining sections", where there are no losses (Partington et al. 2011, Table 1). The global volume error compares a traced volume with a water-budget total, as our closure check does.
- Grids and packages. Section 3.2 lists the HydroGeoSphere output that the method uses. This output is the surface water depth, the contributing area, the surface–subsurface exchange flux, and the upstream and downstream fluxes. Sections 1 and 3 say the method can be implemented in any code that reports surface–subsurface exchange in a spatially distributed way. Section 3.1 says any finite-difference, finite-volume or finite-element scheme can be used if the cell water balance is mass conservative.
- Open implementation. Section 3.2 states that the method is "coded in Visual Basic for Excel and is used as a post-processing tool on HGS outputs". The paper makes no statement on availability.

MODALL

We read Potter et al. (2008) in full (pp. 335–340). MODALL interfaces with MODFLOW (p. 335). In step 1, a steady-state MODFLOW-88 model is run. MODALL then reads its .cbc, .bas, .bcf and .hds files, together with a user-made .all file of the injection and extraction rates (p. 336). No transient use is described. The flow allocation rests on complete mix theory (p. 336). Step 2 is a first pass that finds the capture envelope. This is the set of cells with some flow from a source or to a sink. The other cells get a "synthetic no-flow boundary condition" (p. 336). Step 3 is a second pass that starts at the sink cell. There the capture fraction CF is the sink's outflow divided by the cell's total inflow. The other cells are computed "explicitly, working from the sink outward" (p. 336, Fig. 1). Each cell's CF is the sum, over its downstream neighbours, of CF times outflow, divided by the cell's inflow. Fig. 1 is drawn for a weak sink. The sink cell's CF is therefore below 1. In our terms this is gross accounting. The paper does not say how the cells are ordered for the sweep. It does not mention flow loops, circulating flow or a water-budget check. One head-save file is written per

well, named NODES001.0 to NODES00n.0, with values from 0 to 1. Step 4 adds them by superposition into NODES000.T for the whole system (p. 336).

The abstract and p. 336 describe fractions from a source as well as fractions to a sink. P. 338 names drains and rivers as sinks. It names recharge and rivers as sources. The worked steps cover extraction wells only. The grid is a finite-difference grid. On p. 338 the authors state that MODALL "can compute three-dimensional complex systems". Both examples have one layer. The field model has 307 rows and 487 columns (p. 338).

For verification, one well with Q = 5.5 m^3/d is placed in a confined aquifer with T = 18.6 m^2/d and a gradient of 0.002. The capture envelopes of an analytical solution (Eq. 1) and of MODPATH match the CF = 0.5 contour (Fig. 2a, pp. 337–338). The flow was then reversed and the well made an injection well of concentration 1.0, with dispersivity 0. The MT3DMS contours from this run are "exactly equivalent" to the CF contours (Fig. 2b, p. 338). The spread of the contours is attributed to numerical dispersion. Finer cells shrink the area of uncertain capture. The 0.5 contour stays essentially the same (p. 338). The field use concerns a TCE plume 5000 m long, with more than 50 extraction and reinjection wells. Total pumping was cut from 3300 to 2000 m^3/d (p. 338). The paper gives no run times. It says that MODALL is much more efficient than solute transport codes because it solves no transport equations (p. 338).

MODALL was developed at ARCADIS from the early 1990s. It was first presented at a conference in 2006 (p. 336). The authors offer the tool free of charge for unrestricted use, with no warranty (p. 336). The paper says nothing of the source code or a licence.

In Sections 2.3.3 (pp. 23–24) and 2.4, Chowdhury (2016) describes MODALL as limited to steady-state MODFLOW. In that account, the outputs of MODALL equal the fraction through of FlowSource. On p. 103, Chowdhury (2016) describes full mixing and numerical dispersion on coarse grids, citing McLane and Cecan (2009). The same page describes MODALL as a simpler calculation than FlowSource, without its flow-order sort.

Quoting Potter et al., McLane and Cecan (2009, p. 172 and Fig. 1 on p. 173) state that MODALL works from the MODFLOW cell-by-cell flow terms to "determine the percentage of flow in a particular cell that has either originated from a given source or flows to a specific sink". Their tests found that it "calculates accurately and efficiently". They give no detail. For the simple example of Potter et al. at grid spacings of 25, 50, 100 and 200 ft, they state that "the larger the grid spacing, the broader the spread" of the fractions. They add that this spread "is not related in any way to mass transport hydrodynamic dispersion". They point out that fractions are plotted outside the capture zone (fig. 2a of Potter et al.). They state that the fractions are not a probability of capture. They quote Potter et al. as finding MT3DMS concentration contours with zero dispersivity "exactly equivalent" to the MODALL fractions. They do not use the words numerical dispersion. They do not describe the solution method, weak sinks, flow loops, transient use or how many sources or sinks a run handles.

In their Introduction, Foley and Black (2013) state that MODALL capture fractions are "equivalent" to the fractional volume through of FlowSource. They state that MODALL "does not apply graphs". They also state that MODALL was used to validate FlowSource. In our reading of Potter et al. (Fig. 1), the two differ at weak-sink cells and upstream of them. There FlowSource attributes all the water passing through to the destination. In their Problem Description, Black and Foley (2013) report that MODALL did not delineate the capture areas on a model with flow loops. They cite a personal communication for this. They call it "a

deficiency with the underlying groundwater model and not the MODALL method".

Tosco et al. (2010, p. 46) list MODALL among tools for choosing wells and pumping rates. They give no detail. Bedekar et al. (2024, p. 304) describe MODALL as computing cell-by-cell flow terms in MODFLOW for capture zones of pump-and-treat systems. In their account, MODALL is tied to MODFLOW output and steady-state flows. It therefore gives no arrival times. The secondary accounts agree with the full text on steady state, full mixing and the dependence on grid spacing. Only Black and Foley (2013) say anything on flow loops.

Text S14. Monte Carlo offsets

Two bookkeeping steps of the published workflow first hid the pairing of the published Monte Carlo contributing areas with the realisations. The step that wrote the areas is not archived, so both corrections are inferred.

- One row south. The published script computes the row of a particle's start cell as the 1-based row of the cell centre and the column as 0-based, so every area lies one row south of its cells. Row 0 is empty in every published area. Unshifted, 24 published cells at base pumping lie off the published start cells. Moved one row north, none do.
- Run order. The published runs are saved under their run numbers, and the areas follow those file names sorted as text, so run 100 comes before run 10 (1, 10, 100, 101, …). This order predicts the best-matching area for all 60 realisations tested. Runs 0–356 have areas. Run 357, the calibrated (base) realisation, has none.

With both corrected, PRT with the published settings on the rebuilt flow fields matches each paired published area at base pumping. The overlap is 0.989–1.000 (median 0.996, 60 realisations), against a median of 0.75 for the second-best area.

Text S15. Diagnosis of the first PRT runs

The PRT comparisons of Section 5 and Table S3 use flow-weighted release and, unless stated, weight-losing particles. Particles that lose weight only at the eight priority wells pass every other sink with full weight. So water that streams and other sinks take on the way is counted as reaching the wells. Released over the cell volume they delivered 9,555 m^3/d, 2.6 times the wells' inflow of 3,671 m^3/d (2.1–2.5 times for releases at one height). Weight loss at the other sinks removes this excess.

An earlier version of our PRT helper gave the opposite error for weight-losing particles: it delivered only 53–82 % of the inflow. To find out why, PRT was run without a stop zone and both rules for counting a particle's weight were evaluated on the same particle tracks (gate `diagnose_prt` of `studies/neversink/workflow.py`).

Table. Water delivered to the eight priority wells by PRT particles on the calibrated model (m^3/d, and share of the wells' inflow of 3,671 m^3/d), by release height and rule for counting weight.

release	weight-losing, first well cell only (earlier rule)	weight-losing, weight followed along the whole path (current)	losing weight only at the wells, whole path
at the water table	1,940 (53 %)	2,413 (66 %)	7,685 (209 %)
mid-cell	3,005 (82 %)	3,722 (101 %)	9,182 (250 %)
four heights through the cell	3,015 (82 %)	3,736 (102 %)	9,555 (260 %)

The two defects were in the helper, not in either method.

- Weight dropped in weak-sink well cells (+720 m^3/d, 20 % of the inflow, for release over the cell volume). The earlier rule stopped a particle in the first well cell it entered, assigned to the well the share of the cell's outflow that the well takes, and dropped the rest. The well of U___7 takes 44 % of its cell's outflow, but most of what passes on reaches U___8 and U_917. When the particles are followed along the whole path, they deliver 609 m^3/d more to U___8 and 111 m^3/d more to U_917. The helper now loses weight along the whole path: in each cell the wells take their share of the remaining weight and the cell's other sinks remove theirs, with no stop zone.
- Particles held at the water table (about 1,300 m^3/d less at the water table than at mid-cell). MODFLOW 6 spreads recharge and the other boundary flows through the cell volume, and PRT's velocity field matches. A particle released at the water table of a top-layer cell has zero vertical velocity there and never leaves the layer, so wells in deeper layers receive little. The helper now releases at several heights through the saturated thickness by default.

Two other explanations were ruled out. Every particle ended in a cell with no exit face (status 5) with no weight left after its last cell, so no water was lost to other end states, and no particle entered a cell twice, so weight was removed once per cell. On the three-layer test model with a weak-sink well upstream of a strong one, the same two defects gave 266 of 405 m^3/d; the current helper gives 402.6 m^3/d, which is now a regression test.

Table S1. Comparison of methods

Table. Five ways to compute the share of each cell's water that reaches a destination, or that came from a source, from the flows of a groundwater flow model. The columns are MODALL (Potter et al. 2008), FlowSource (Foley and Black 2013; Black and Foley 2013), this paper's code, unit-concentration transport in GWT (Bedekar et al. 2024; Langevin et al. 2022) and hydraulic mixing cells as published by Partington et al. (2011). Section 2 and Text S1 define the fractions F, G, c and w, and gross and net accounting. The MODALL and FlowSource columns describe the programs as published in 2008 and 2013. Years in parentheses date a statement to the 2013 papers. We found no published description of later versions. Fuller notes on each entry, and their sources, are given in Text S13.

	MODALL (Potter et al. 2008)	FlowSource (Foley and Black 2013; Black and Foley 2013)	This paper's code	GWT unit concentration (Bedekar et al. 2024; Langevin et al. 2022)	Hydraulic mixing cells (Partington et al. 2011)
What is solved, and how	Cell by cell, outward from each well; cell order not described	Fractions cell by cell in flow order; one pass per time step	Linear equations in flow order; transient tracking: implicit steps	Implicit time steps, iterative solver; no documented steady-state option[1]	Explicit, on the flow model's steps; stable only for short steps[2]
Mixing in a cell	Full mixing	Full mixing	Full mixing	Full mixing with upstream weighting and no dispersion	Modified mixing cell; tends to full mixing as steps shorten[3]
Accounting at weak sinks	Gross: well cell's fraction is pumping over inflow	Net: all water passing through a destination cell counted as reaching it	Gross (default); net as an option	Gross: sinks remove water at the cell's concentration	Outflow at the previous step's mix; gross in effect (our reading)
Flow loops	Not described	Smallest-flow connection in each loop deleted (2013)	Solved exactly; closed recirculation loops set to F = 0[4]	None needed: one implicit solution over all cells (our inference)	Not discussed; fixed stream flow direction assumed
Outputs	Capture fraction (F) per well and summed over wells	F, volumes through and from; particle travel time	F, G and volumes by term; transient tracking: c and w	Concentration, read as the share of water from the tagged source	Fractions by flow component per stream cell, plus initial water
Transient models: water carried through storage?	No: steady-state MODFLOW-88 models only	No: each step traced as a steady state (snapshots)	Yes, transient tracking (needs porosity); snapshots also	Yes (needs porosity)	Yes: stream-cell water volumes carried step to step
Backward in time?	No	No	Yes, solved from the end of the simulation	No[5]	No

	MODALL (Potter et al. 2008)	FlowSource (Foley and Black 2013; Black and Foley 2013)	This paper's code	GWT unit concentration (Bedekar et al. 2024; Langevin et al. 2022)	Hydraulic mixing cells (Partington et al. 2011)
Destinations or sources per run	One well per calculation; source fractions said possible, not described	One destination group (any number of cells) per calculation	Gross: all groups in one solve per direction; net: one group per solve	One tagged source per GWT model; several models per simulation	All flow components together; not user-chosen terms
Built-in water-budget checks	Not described	None described; flow loops reported (2013)	Closure, forward–backward, travel-time closure; more in transient tracking	Mass budget, a tagged-water balance; no backward closure or forward–backward check	Sum-of-fractions error; global volume error, gaining reaches only
Grids and packages	MODFLOW-88 finite-difference grids; wells, drains, rivers, recharge	Structured MODFLOW grids; method said to apply to unstructured grids (2013); package networks not documented	All MODFLOW 6 grid types, multi-model simulations, package networks	DIS, DISV, DISU; SFR, LAK, MAW, UZF and MVR transport	HydroGeoSphere stream cells; said to apply to other codes
Open implementation	Free from the authors; source code not mentioned	No; VB.NET source for academic use on request (2013)	Yes (`gwsource`, MIT)	Yes (MODFLOW 6, USGS)	Excel (Visual Basic) post-processor; availability not stated

[1] Steady state is reached by running transient steps until concentrations stabilise (Langevin et al. 2022). In our test, one step with porosity 0 gave the steady-state G to 1×10^{-12}. This use of porosity 0 is not documented.

[2] Each step's fractions come from the previous step's. The update is stable only while a step's inflow or outflow volume does not exceed the cell's storage. Later versions add overland and aquifer cells and sub-steps. All step forward in time only.

[3] After Campana and Simpson (1984): water leaving a cell over a step carries the previous step's mix.

[4] A closed recirculation loop is a group of cells with no outflow to any sink or to a cell outside the group. Such loops are reported. No connections are deleted.

[5] No backward option is documented (Langevin et al. 2022). Bedekar et al. (2024) read well capture forward in time, from the concentration simulated at the well.

Table S2. Inputs, selections and outputs

Table. What the code reads, how destinations and sources are chosen, and what it returns. The last column gives the worked example that shows each item, in the main text (Section 4) or in this Supporting Information. MODFLOW 6 option names are given where a user must set them.

	Item	What it is or needs	Shown in
Inputs	Binary grid file	Cell connections of a DIS, DISV or DISU grid. Written by MODFLOW 6 by default	Section 4.1, Text S7
	GWF budget file	Cell-to-cell flows and every source and sink term. SAVE_FLOWS in each package, budget saved in Output Control	Section 4.1
	Every time step saved	Needed for transient tracking (SAVE BUDGET ALL)	Section 4.2, Text S11
	Saturated thickness	For travel times and transient tracking. NPF SAVE_SATURATION, or the head file	Text S9, Section 4.2
	Porosity	Given by the user. Needed for travel times and transient tracking, not for fractions	Text S9, Section 4.2
	Package budget files	SFR, LAK, MAW, UZF and MVR budgets (BUDGET FILEOUT), to trace through package networks	Text S10
	Linked models	GWF models joined by exchanges, read as one system (SAVE_FLOWS in the exchange)	Text S10

	Item	What it is or needs	Shown in
Selections	Package	All terms of a package, such as all recharge or all wells	Section 4.1, Text S6
	Boundname	Terms with a given boundname, such as one well. Read from the package input files	Section 4.1
	Boundary number	Terms with given boundary numbers in a package	–
	Cells	All terms in the given cells (gross accounting), or the cells themselves (net accounting)	Text S3
	Zone	Cells with a given zone value, alone or with a package, such as the recharge on one field	Text S6, Text S7
Outputs	Backward fraction F	Share of each cell's water that ends at the destination	Section 4.1
	Forward fraction G	Share of each cell's water that came from the source	Text S6
	Volumes	Volume through, volume from and volume to, and their split by package	Section 4.1, Text S6
	Gross and net accounting	Water attributed to a weak-sink well under each rule. Boundary-control maps	Text S3
	Budget checks	Closure, forward–backward and boundary-control checks with every trace	Section 4.1, Text S3, Text S6
	Mean travel time	Mean time to the destination under full mixing	Text S9

	Item	What it is or needs	Shown in
	Snapshot statistics	Minimum, mean and maximum F over time steps. Cells always, sometimes or never above a threshold	Text S8
	Transient tracking	Tagged fractions c (forward) and w (backward in time). Destination's water by source, time step and initial water	Section 4.2, Text S11
	Ensemble statistics	Mean, probability of exceeding a threshold, and exact or histogram quantiles over realisations	Section 4.3
	PRT release points	Particle runs on the same flows, for comparison	Text S9
	Export	NumPy and netCDF files (Section 4.1). GeoPackage polygons for GIS (Text S7)	Section 4.1, Text S7

Table S3. Delineations on one flow field

Table. Delineations of the eight priority wells' contributing area on one flow field (calibrated Neversink model, streams as cells), against the 980 published contributing cells.

method	delineation	overlap	expected area (cells)	flow attributed to the wells (m^3/d)
Full mixing, gross accounting	$F > 0.1$	0.30	910	3,671
	$F > 0.5$	0.41	910	3,671
	area-matched (980 cells)	0.41	910	3,671
Full mixing, net accounting	$F > 0.1$	0.28	978	3,944
	$F > 0.5$	0.44	978	3,944
	area-matched (980 cells)	0.40	978	3,944

method	delineation	overlap	expected area (cells)	flow attributed to the wells (m^3/d)
PRT, flow-weighted, weight-losing	released over the cell volume, P > 0.5	0.62	794	3,736
	released mid-cell, P > 0.5	0.62	781	3,722
	released at the water table, P > 0.5	0.39	592	2,413
PRT, flow-weighted, losing weight only at wells	released over the cell volume, P > 0.5	0.29	2,857	9,555
PRT, published starts	MODFLOW 6 default, dry starts dropped to the water table	0.62	730	–
	MODFLOW 6 default, dry starts draped	0.65	754	–
	top face where open, dry starts dropped	0.96	969	–
	top face where open, dry starts draped (published settings)	0.998	982	–

Overlap: cells in both areas as a share of cells in either, on the 122,021 start cells. Thresholds are strict (F > 0.1, F > 0.5, P > 0.5). Area-matched: the 980 start cells with the largest F (F ≥ 0.28 gross, F ≥ 0.30 net). Expected area: sum of F over the start cells (full mixing), particle weight reaching the wells in cells (flow-weighted PRT), or number of start cells whose particle ends in a priority well (published starts). Flow attributed to the wells: the wells' inflow is 3,671 m^3/d. Gross accounting attributes exactly this flow to the wells. Net accounting attributes 3,944 m^3/d to the eight wells as a group. This is more than the inflow because it counts the water passing on from the well cells. The per-well net attributions sum to 4,621 m^3/d, because water passing from one well cell to another counts for both wells (Table S5). Weight-losing particles deliver within 2 % of the inflow; particles that lose weight only at the wells keep the weight that streams and other sinks take on the way. Their 9,555 m^3/d is 2.6 times the wells' inflow. It is therefore water the particles assign to the wells, not water that flows into them (Text S15). This setting gives the lowest overlap in the table, 0.29. Flow-weighted PRT: particles released from the source terms of the 30,180 cells with $F > 10^{-6}$, in all layers; P is the flow-weighted share of the water released in a start cell that particles deliver to the wells. Published starts: one unweighted particle per published start, stopped at every weak sink; "MODFLOW 6

default” spreads recharge and stream flows through the cell, “top face where open” puts them on the top face through IFLOWFACE, the MODFLOW 6 setting that assigns a boundary flow to one cell face, which PRT reads.

Figure S6 maps the model, the three regions of the published particle runs and the 980 published contributing cells. Figure S7 maps F of the calibrated model around each cluster of wells, with streams as cells and with the stream network. Figure S8 maps the $F > 0.1$ area against the published contributing cells and against the area where the particle share of weight-losing particles exceeds 0.5.

Net accounting counts all the water that reaches the well cells as the wells’ water. A published particle that stops in a weak-sink well cell does much the same. It raises the overlap of the $F > 0.5$ area only from 0.41 to 0.44. The overlap of the $F > 0.1$ area falls slightly, from 0.30 to 0.28. Table S5 gives the overlaps for each well.

On the calibrated model, the MODFLOW 6 run takes 44 s. One full-mixing trace of the nine destination groups takes 2–3 s. PRT on the same flows took about 30 s for one particle per published start, when it wrote only the end point of each particle. With full particle tracks it took about 5 min for one release height (122,112 particles) and about 13 min for four heights (488,448 particles).

Table S4. Verification errors per check and model

This item gives the values behind Figure S2. The test models are described in Text S2.

Largest error per check

Each error is the largest over the groups, group pairs and time steps of a model. Figure S2 plots these values.

check	largest error	model	test tolerance	error measure
Steady-state and snapshot checks				
backward closure	1.3×10^{-15}	6 transient, 13 snapshots	10^{-10}	relative to destination inflow[1]
forward closure	1.1×10^{-15}	6 transient, 13 snapshots	10^{-10}	relative to source inflow[1]
forward–backward	1.5×10^{-15}	7 SFR + MVR network	10^{-10}	relative to source-to-destination flow[1]
boundary control	1.8×10^{-15}	6 transient, 13 snapshots	10^{-12}	absolute (fraction)
steady-state G vs GWT at equilibrium[2]	1.0×10^{-8}	7 SFR + MVR network	10^{-7}	absolute (fraction)
DISU vs DIS	0	4 DISU (both variants)	10^{-12}	relative to output maximum

check	largest error	model	test tolerance	error measure
split vs single	7.4×10^{-10}	1 DIS, three models	10^{-8}	relative to output maximum
PRT flow to the well[3]	5.9×10^{-3}	2 DIS, 3 layers, weak sink	2×10^{-2}	relative to well inflow
Foley and Black (2013) example	0	worked example, net accounting	10^{-14}	absolute (published values)
Transient tracking checks				
transient tracking vs GWT[4]	1.0×10^{-14}	7 SFR + MVR vs SFT + MVT	10^{-8}	absolute (fraction)
transient forward–backward	7.7×10^{-16}	9 LAK + UZF + MVR network	10^{-10}	relative to source-to-destination volume
water balance ("flow")[5]	9.5×10^{-17}	9 LAK + UZF + MVR network	10^{-10}	relative to the cell's water volume
tagged-water balance ("flow")	1.0×10^{-15}	6 transient	10^{-10}	relative to the largest balance term
steady-state limit, c to G[6]	9.7×10^{-14}	10, model 1 flows held 4×10^5 d	10^{-11}	absolute (fraction)
steady-state limit, w to F[6]	6.8×10^{-10}	10, model 1 flows held 4×10^5 d	10^{-8}	absolute (fraction)
sub-steps vs refined steps	1.6×10^{-16}	hand-built 15-cell network	10^{-12}	relative to output maximum

[1] Absolute, in m^3/d, where the reference flow is below 1 m^3/d. [2] Models 1 and 2: $\leq 2.8 \times 10^{-11}$ (tolerance 10^{-10}). Model 7 is limited by the flow solver tolerance: 2.5×10^{-11} with the flow model solved about 100 times tighter. [3] 402.6 of 405 m^3/d on model 2, and 800.4 of 800 m^3/d on models 1 and 3 (tolerance 10^{-2}); a release-point error. [4] With GWT's water volumes ("gwt"). On model 6, five tagging cases. [5] Holds by construction with "flow" volumes; tests the carrying of volumes from step to step, the clipping of volumes at zero and round-off, not the flow solution. [6] Limited by the flow solver tolerance: 1.2×10^{-14} (c to G) and 1.4×10^{-11} (w to F) with the flow model solved 100 times tighter. With 30 growing time steps instead of 120 equal ones the errors were 1.4×10^{-8} and 5.9×10^{-7}.

On model 1 the flow-weighted mean time for the water reaching the well to enter its cell is 9,574 d, against 9,590 d for weight-losing PRT particles, which stop on entering it. The mean travel time of Text S1, m/F, includes the residence in the well cell and is 9,607 d (Text S1).

The split simulations divide model 1 into three models (7.4×10^{-10}), model 3 into two (1.4×10^{-10}) and model 6 into four (1.5×10^{-12}); the four-model split of model 6 also passes the transient forward–backward check (4.5×10^{-16}).

Steady-state and snapshot checks, per model

model	backward closure	forward closure	forward–backward	boundary control	steady-state G vs GWT at equilibrium	DISU vs DIS	split vs single	PRT flow to the well	Foley and Black (2013) example
Foley and Black (2013) worked example, net accounting	–	–	–	–	–	–	–	–	0
1 DIS	1.7×10^{-16}	3.3×10^{-16}	1.6×10^{-16}	5.6×10^{-16}	1.4×10^{-11}	–	7.4×10^{-10}	5.1×10^{-4}	–
2 DIS, 3 layers, weak sink	1.6×10^{-16}	1.3×10^{-16}	1.9×10^{-16}	6.7×10^{-16}	2.8×10^{-11}	–	–	5.9×10^{-3}	–
3 DISV Voronoi	2.8×10^{-16}	1.5×10^{-16}	3.2×10^{-16}	6.7×10^{-16}	–	–	1.4×10^{-10}	4.8×10^{-4}	–
4 DISU (vertices)	1.7×10^{-16}	3.3×10^{-16}	1.6×10^{-16}	5.6×10^{-16}	–	0	–	–	–
4 DISU (no vertices)	1.7×10^{-16}	3.3×10^{-16}	1.6×10^{-16}	5.6×10^{-16}	–	0	–	–	–
5 XT3D, cycles	4.1×10^{-16}	1.9×10^{-16}	2.7×10^{-16}	4.4×10^{-16}	–	–	–	–	–
6 transient (STO)	1.3×10^{-15}	1.1×10^{-15}	9.4×10^{-16}	1.8×10^{-15}	–	–	1.5×10^{-12}	–	–
7 SFR + MVR network	6.2×10^{-16}	3.4×10^{-16}	1.5×10^{-15}	1.1×10^{-15}	1.0×10^{-8}	–	–	–	–

model	backward closure	forward closure	forward–backward	boundary control	steady-state G vs GWT at equilibrium	DISU vs DIS	split vs single	PRT flow to the well	Foley and Black (2013) example
8 MAW network	7.5×10^{-16}	1.3×10^{-16}	4.8×10^{-16}	8.9×10^{-16}	–	–	–	–	–
9 LAK + UZF + MVR network	4.4×10^{-16}	3.2×10^{-16}	6.4×10^{-16}	1.1×10^{-15}	–	–	–	–	–
test tolerance	10^{-10}	10^{-10}	10^{-10}	10^{-12}	10^{-10} / 10^{-7}	10^{-12}	10^{-8}	10^{-2} / 2×10^{-2}	10^{-14}

Error measures. backward closure: relative to destination inflow (absolute in m^3/d below 1 m^3/d). forward closure: relative to source inflow (absolute in m^3/d below 1 m^3/d). forward–backward: relative to forward source-to-destination flow (absolute in m^3/d below 1 m^3/d). boundary control: absolute (fraction). steady-state G vs GWT at equilibrium: absolute (fraction). DISU vs DIS: relative to output maximum. split vs single: relative to output maximum. PRT flow to the well: relative to destination inflow. Foley and Black (2013) example: absolute (published values).

Transient tracking checks, per model

model	tracking vs GWT	transient forward–backward	water balance ("flow")	tagged-water balance ("flow")	steady-state limit, c to G	steady-state limit, w to F	sub-steps vs refined steps
6 transient (STO)	2.2×10^{-15}	5.9×10^{-16}	6.9×10^{-17}	1.0×10^{-15}	–	–	–
6 transient, split into 4 models	–	4.5×10^{-16}	–	–	–	–	–
7 SFR + MVR network	1.0×10^{-14}	4.7×10^{-16}	–	–	–	–	–

model	tracking vs GWT	transient forward–backward	water balance (“flow”)	tagged-water balance (“flow”)	steady-state limit, c to G	steady-state limit, w to F	sub-steps vs refined steps
9 LAK + UZF + MVR network	–	7.7×10^{-16}	9.5×10^{-17}	1.8×10^{-16}	–	–	–
10 model 1 flows, held 4×10^5 d	–	–	–	–	9.7×10^{-14}	6.8×10^{-10}	–
hand-built 15-cell network (not a MODFLOW 6 model)	–	–	–	–	–	–	1.6×10^{-16}
test tolerance	10^{-8}	10^{-10}	10^{-10}	10^{-10}	10^{-11}	10^{-8}	10^{-12}

Error measures. tracking vs GWT: absolute (fraction). transient forward–backward: relative to forward source-to-destination volume (absolute when zero). water balance (“flow”): relative to the cell’s water volume. tagged-water balance (“flow”): relative to largest term of the tagged-water balance. steady-state limit, c to G: absolute (fraction). steady-state limit, w to F: absolute (fraction). sub-steps vs refined steps: relative to output maximum.

Table S5. Per-well gross and net

Table. Contributing area of each priority well against its published contributing cells, under gross and net accounting (Section 2.2); calibrated Neversink model, streams as cells. Where two values are given, the first is gross accounting and the second net accounting.

well	pumping (m^3/d)	well’s share of its cell’s outflow	net attribution (m^3/d)	published contributing cells	expected area (sum of F)	overlap, F > 0.1	overlap, F > 0.5	overlap, area-matched
SV_193	63	1.00	63	48	26 / 26	0.37 / 0.37	0.00 / 0.00	0.30 / 0.30
SV_227	203	1.00	199	115	69 / 74	0.29 / 0.29	0.16 / 0.19	0.25 / 0.26

well	pumping (m^3/d)	well's share of its cell's outflow	net attribution (m^3/d)	published contributing cells	expected area (sum of F)	overlap, F > 0.1	overlap, F > 0.5	overlap, area-matched
SV_407	94	0.91	103	32	34 / 37	0.29 / 0.26	0.16 / 0.25	0.60 / 0.60
SV_487	381	0.69	545	97	65 / 94	0.18 / 0.10	0.04 / 0.15	0.17 / 0.17
U_917	1,054	1.00	1,054	351	313 / 314	0.56 / 0.56	0.53 / 0.53	0.68 / 0.68
U__55	250	0.85	293	116	81 / 97	0.06 / 0.16	0.00 / 0.00	0.13 / 0.13
U___7	516	0.44	1,167	58	94 / 214	0.20 / 0.08	0.00 / 0.00	0.05 / 0.05
U___8	1,110	0.93	1,197	163	229 / 249	0.10 / 0.10	0.00 / 0.00	0.22 / 0.22
all eight	3,671	–	3,944	980	910 / 978	0.30 / 0.28	0.41 / 0.44	0.41 / 0.40

Gross accounting counts only each well's pumping as its water. Net attribution is the source water that net accounting assigns to the well. Overlap: cells in both areas as a share of cells in either, on the 122,021 start cells; thresholds are strict. Area-matched: as many start cells as the well has published contributing cells, taken in decreasing order of F.

The per-well overlaps are lower than the group's because the wells of the U cluster share cells. A published cell belongs to the one well its particle reaches, while under full mixing a cell that sends water to several wells counts for each of them; the union of the eight wells is the fairer comparison.

Under gross accounting the per-well expected areas add up to the group's 910 cells. Under net accounting they add up to 1,104 cells against the group's 978, and the per-well net attributions to 4,621 m^3/d against 3,944 m^3/d, because a trace of one well fixes only that well's cell. The 608 m^3/d that passes from U___7's cell into U___8's, and the 70 m^3/d that leaves a well cell and reaches the group again, then count for both wells.

Net accounting changes the expected area most where the well takes a small share of its cell's outflow: from 94 to 214 cells at U___7 (44 %) and from 65 to 94 at SV_487 (69 %). At the three wells that take all of their cell's outflow it changes the area by at most 5 cells. At these three wells gross and net accounting both give about 410 cells against 514 published contributing cells. At the other five, the single-well net traces add up to 690 cells and the gross traces to 502, against 466 published contributing cells: net accounting is above the published count at SV_407, U___7 and U___8 and below it at SV_487 and U__55. One possible reading, not tested, is that stopping a particle at the first weak sink gives the well all the water reaching its cell, as net accounting does; the per-well counts do not support it.

Table S6. Ensemble statistics

Table. Ensemble maps at base pumping against the published probability of contribution (357 published Monte Carlo contributing areas, 358 realisations, published start cells). Values in brackets are against the published areas as stored, before they were moved one row north (Text S14).

map	correlation with the published probability (r)	expected area relative to the published	overlap of the areas above 0.5
mean F, streams as cells	0.80 (0.76)	0.90	0.48 (0.43)
share of realisations with F > 0.5, streams as cells	0.76 (0.71)	0.47	0.48 (0.43)
mean F, stream network	0.72 (0.70)	1.51	0.49 (0.44)

Expected area: the sum of the map over the start cells. Mean F is the full-mixing counterpart of the published probability. Figure S9 maps the published probability and the ensemble mean F around each cluster of wells.

Mean F gives 90 % of the published expected area, close to the calibrated model's 910 against 980 cells (Table S3). With the stream network it gives 1.51 times the published expected area, because it includes the area upstream that feeds the losing reaches (Section 5).

Across the 358 realisations the wells' inflow was 3,586–3,756 m^3/d and the stream share 30–45 %. Each realisation took about 50 s for the MODFLOW 6 run and 9 s for its two traces (streams as cells and stream network). The 358 realisations took 76 min in all, run in six parallel processes. Closure held to 3×10^{-12} m^3/d in every realisation.

Paired with its own published area, each realisation's F at base pumping gives an overlap of 0.42 (F > 0.5) and 0.41 (area-matched), against 0.40 with the neighbouring realisation's area and 0.37 under the uncorrected pairing. It agrees better with its own area than with the neighbour's in 315 of 357 realisations. The published area correlates with the sum of F at r = 0.56 across realisations, against −0.04 under the uncorrected pairing. In the S region the published area varies between realisations with a coefficient of variation of 32 %; PRT with the published conventions follows it (r = 0.997, 60 realisations) and the sum of F does not (r = 0.00).

Figure S1. Method schematic




Figure. Full-mixing flow tracing. (a) A fully mixed cell i with cell-to-cell flows, recharge (source term) and a well (sink term, d_i). These define I_i, O_i and r_i (Eq. S1). (b) Backward fractions F (in cells) to a 6 m³/d well in an eight-cell example (gross accounting). Water enters on the west and as recharge. It leaves through the well and a river. Arrow widths show flows. Only the well cell's flows are numbered (m³/d). In the well cell, $F = 6/11 = 0.55$. (c) Water attributed to a weak-sink well pumping 5.0 m³/d in a three-layer example model: 5.0 m³/d (gross accounting) or 33.7 m³/d (net accounting; Section 2.2). (d) Left: a snapshot traces one step on that step's flows. Storage release is a source of unknown origin. Right: transient tracking carries a cell's water volume V_i and tagged fraction c_i (shading) from step n to $n + 1$ (Section 2.4).

Figure S2. Verification on the test models




Figure. Largest error of each verification check of the automated tests. Each row is one check. Each marker is the largest error of that check on one case. The cases are the ten test models, the worked example of Foley and Black (2013) and a hand-built network of 15 cells. Markers in the "exact" column have an error of zero. The dashed line is machine precision, the size of rounding error. Light grey bars are the tolerances of the automated tests. A row with two bars has a looser tolerance for one model. Markers far above machine precision are limited by the flow solver's tolerance or, for PRT, by the number of release points. Upper block: steady-state and snapshot checks. Lower block: transient tracking checks. Its last row tests transport sub-steps. The test models are described in Text S2. Values, tolerances and error measures are in Table S4.

Figure S3. Neversink full-mixing maps




Figure. Full-mixing maps for the eight priority wells of the Neversink/Rondout model (Fienen et al. 2022; Corson-Dosch et al. 2022), in a 7.1 × 9.25 km window around four closely spaced wells. F is the share of a cell's water that ends at the wells. All panels show the uppermost active cell, with streams as cells and gross accounting. (a) F in the calibrated model. Colours: five classes of reversed viridis (light = low F), with edges at 0.01, 0.1, 0.25, 0.5, 0.75 and 1. Grey: $F < 0.01$ in the active area. Black outline with white halo: the published contributing cells, 688 of the 980 in all. (b) The $F > 0.1$ area against the published contributing cells. Dark blue: in both (538 cells in this window). Orange: published only (150). Light blue: $F > 0.1$ only (1,090). (c) The $F > 0.1$ area against the area where the particle share exceeds 0.5. The particles are PRT particles that lose weight at each sink as full mixing does. They were released over the cell volume. The particle share of a start cell is the share of its water that they deliver to the wells. Dark blue: in both (495). Orange: particles only (86). Light blue: $F > 0.1$ only (1,133). (d) Ensemble mean F over 358 realisations, in the classes of (a). Black outline with white halo: published probability of contribution 0.5, from 357 published Monte Carlo contributing areas. The stored published areas lie one row south of their cells. We moved them one row north (Text S14). Inset: the active model area, the three regions of the published particle runs and the window. Orange dots: wells. Blue lines: SFR reaches. White: inactive. Scale bar (a): 2 km.

Section 5 of the main text discusses these maps.

Figure S4. Numerical dispersion maps and time steps




Figure. Numerical dispersion maps and time steps. Colour is F, the fraction of a cell's water that reaches the well (dot); the wider the band of intermediate colours across the dashed line, the stronger the numerical dispersion. (a–h) Problem A, uniform flow along the grid rows (a–d) and at 30° to them (e–h), 50 m cells. The first column is the exact capture zone averaged over each cell, the best a cell-based method can do; dashed: analytical capture-zone edge. (i–l) Problem B: PRT on the 12.5 m grid and the three methods on 50 m cells; dashed: the PRT F = 0.5 edge; grey: gaining river. Compared west of the river only. DIS: square cells; DISV: Voronoi cells. (m) Share of the well's water that entered after tagging started, per 2,000-day flow

step, 12.5 m grid, for 1 to 64 transport sub-steps and for PRT; (n) difference to PRT.

This item gives the set-up and the numbers behind Figure S17 and Section 6. Two test problems measure how much full mixing spreads the edge of a contributing area. Problem A is a confined aquifer, 2 km × 2 km, with a transmissivity of 500 m^2/d, a regional hydraulic gradient of 0.002 and one well pumping 500 m^3/d. The perimeter cells hold the analytical head of uniform flow plus a well. The reference is the analytical capture zone of Javandel and Tsang (1986). The regional flow runs along the grid rows or at 30° to them. The grids have square cells of 200 to 12.5 m (DIS) or Voronoi cells of about the same mean size (DISV). Problem B is test model 1 without its inactive cells. It is one unconfined layer of 1.5 km × 1 km, with recharge, a river, a constant-head west edge and a well pumping 800 m^3/d. Its grids have cells of 100 to 12.5 m. Its reference is PRT on the 12.5 m grid, with about 94,000 flow-weighted particles released at the water table. East of the river, all water passes the gaining river, which is a weak sink. So the areas of problem B are compared west of the river only.

Across cell sizes, the transition band ($0.1 < F < 0.9$) was 1.2–12 cells wide. In metres, it narrowed only as about the square root of the cell size h, with fitted rates of 0.4–0.6. For cells of 50 m or less, the size of the $F > 0.5$ area was within 5 % of the reference area. The $F > 0.1$ area missed at most 0.1 % of the reference area in every run. For cells of 12.5–50 m, it was 30–90 % larger than the reference area in problem A and 8–16 % larger in problem B. Voronoi grids spread the edge no less than square cells. Face-to-face routing (Chowdhury 2016) is an experimental 2D option that passes water between cell faces instead of mixing it across the whole cell. It removed 35–70 % of the excess spreading. It did not change how fast the band narrows with h, because water still mixes across each cell face.

Totals depend much less on mixing. On the same grid, the well's shares by source were the same to three digits under full mixing, face routing and particles. For cells of 50 m or less, the flow-weighted mean travel time of all the water reaching the well was within 2 % of particle tracking in problem B and within 4 % of the analytical value in problem A.

The dispersion study draws areas with non-strict thresholds ($F \geq 0.1$, $F \geq 0.5$). The main text and the panel titles of Figure S17 write strict ones ($F > 0.1$, $F > 0.5$), as the Neversink study did. A strict threshold leaves out cells with F exactly at the threshold. No full-mixing cell in the dispersion tests has F exactly 0.1 or 0.5, so the two forms give the same full-mixing and face-routing areas there. The comparison zones in Figure S17 are different. The PRT zones hold cells at exactly 0.5, because a particle fraction is a ratio of particle counts. The cell-averaged exact zones hold cells at exactly 0.1 and 0.5. These comparison zones are drawn with $\geq$, as in the study. A strict threshold would shrink them by at most about 0.8 % of their area, about 0.007 in area error.

Problem B was also run with 2,000-day flow steps. With one transport step per flow step, the first-step share of new water was roughly doubled, 0.18 against 0.09 for the particles. Sixteen sub-steps of 125 d removed this, leaving a difference of about 0.001 at 12.5 m, averaged over the 30 steps.

Figure S5. Net attribution and PRT-area maps




Figure. Gross and net accounting, and the full-mixing areas against the PRT area; Neversink calibrated model, streams as cells. (a) Water attributed to each priority well under gross (filled) and net (open) accounting (Section 2.2). The two differ most where the well takes a small share of its cell's outflow (U___7, SV_487). (b–d) Weight-losing particles lose weight at every sink as full mixing does, so the PRT area is not an independent advective area. Start cells in the $F > 0.1$ and $F > 0.5$ areas, with the outline of the PRT area ($P > 0.5$; particles released only where $F > 10^{-6}$). Orange cells with open squares: PRT-area cells outside the $F > 0.1$ area. Of these 89 cells, 86 form a strip about 1.5 km long, 1–2.5 km west of the U wells. White: no published start cell. Coordinates in km from the grid origin.

Numbers behind the figure. U___7 takes 44 % of its cell's outflow. Net accounting gives it 2.26 times its pumping. SV_487 takes 69 % of its cell's outflow and gets 1.43 times its pumping. At SV_227 net accounting gives 2 % less than the pumping, because it leaves out the 3.7 m³/d source term of the well cell. For the eight wells together, net accounting attributes 3,944 m³/d against 3,671 m³/d pumped. The per-well net values add up to 4,621 m³/d, because single-well traces count some water for two wells. This water is the 608 m³/d that passes directly from U___7's cell into U___8's, plus the 70 m³/d that leaves a well cell and reaches the group again. PRT particles were released in 29,201 published start cells, including all 2,139 with $F > 0.1$. Start cells without particles have $P = 0$. The $F > 0.1$ area holds 87 % of the PRT area (691 cells). It misses 89 of the PRT-area cells, 74 of them published contributing cells (72 of the 86 in the strip). The particles deliver 227 m³/d to the wells from these 89 cells, 6 % of the 3,736 m³/d they deliver in all. Of the $F > 0.5$ area (445

cells), 92 % lies inside the PRT area. The flow field has no flow loops.

Figure S6. Neversink model and published regions




Figure. The Neversink/Rondout model (Fienen et al. 2022; Corson-Dosch et al. 2022). Grey: active model area. Blue lines: SFR reaches, each joined to its downstream reach. Dashed: the three regions (NE, W, S) of the published MODPATH 7 runs, whose particles start in the uppermost active cells. Black: the 980 published contributing cells. These are the start cells whose MODPATH 7 particle ends in one of the eight priority wells in the calibrated model. Because each start cell has one particle, these cells form patches and strips up to 4.3 km from their well. Orange dots: wells. The wells form the U cluster (four wells, within about 1 km of each other), SV_W (three wells) and SV_S (one well). Well names are those of the published model. Coordinates are km from the grid origin (EPSG:5070). True north is 12.9° west of grid north. We reran the published model input with MODFLOW 6 version 6.9. Its heads differ from the published run by at most 8.6 mm.

Figure S7. Neversink backward fractions




Figure. Backward fraction F of the uppermost active cell for the eight priority wells in the calibrated model. F is the share of a cell's water that ends at the wells. Colours: five classes of reversed viridis (light = low F), with edges at 0.01, 0.1, 0.25, 0.5, 0.75 and 1. Grey: $F < 0.01$ in the active area. White: inactive. Black outline, white halo: published contributing cells. Orange dots: wells. Blue lines: SFR reaches. (a–c) Streams as cells. Stream leakage is a source term of the aquifer cell. The area therefore stops at the streams. (d–f) Stream network. The SFR reaches are extra cells linked by stream routing. The wells' water then traces back to recharge. The area extends upstream along the streams (F 0.1–0.25 south-east of the U wells in d). Each panel is a 7.1×9.25 km window around one cluster of wells. Scale bar (a): 2 km.

Figure S8. Neversink areas against particle tracking




Figure. The F > 0.1 area of full mixing against two particle-tracking areas, in the windows of Figure S7. F is taken in the uppermost active cell of the calibrated model, with gross accounting and streams as cells. Dark and light blue together are the 2,139 cells of the F > 0.1 area. (a–c) Against the 980 published contributing cells. Dark blue: in both (711 cells). Orange: published only (269). Light blue: F > 0.1 only (1,428). (d–f) Against the 691 cells with a particle share above 0.5. The particles are weight-losing PRT particles released over the cell volume (Section 5). Dark blue: in both (602 cells, 87 % of the particle area). Orange: particles only (89). Light blue: F > 0.1 only (1,537). The three particles-only cells in (e) and (f) are too small to see. The windows hold every coloured cell. Grey: rest of the active area. White: inactive. Orange dots: wells. Blue lines: SFR reaches. Scale bar (a): 2 km.

Figure S9. Neversink probability of contribution




Figure. Published probability of contribution and ensemble mean F of the eight priority wells, in the windows of Figure S7. (a–c) Published probability of contribution. It is the share of the 357 published Monte Carlo contributing areas that contain a cell. (d–f) Ensemble mean F over 358 realisations, with streams as cells. (g–i) The same with the stream network. Mean F is a share of water, averaged over the realisations. The published probability is instead a share of realisations. Colours: the five classes of Figure S7. Grey: below 0.01 in the active area. White: inactive. Black outline, white halo: published probability 0.5. Orange dots: wells. Blue lines: SFR reaches. Scale bar (a): 2 km. The stored published areas lie one row south of their cells. We moved them one row north. With this and a second stored offset corrected, PRT with the published settings reproduces each of 60 tested areas (median overlap 0.996; Text S14).

Figure S10. The worked example of Foley and Black (2013) and a small well




Figure. The worked example of Foley and Black (2013) and a small well in the three-layer example model (Text S3). (a) The worked example: a block of 3×3 cells, A to I, with flows between them (arrows) and cell A as the destination. J and K (dashed) stand for the area outside the block. Shading: F under net accounting, as in the published example. (b, c) F of the 5 m³/d well in layer 3, under net accounting (b) and gross accounting (c), in a window around the well. Both panels use the same logarithmic colour scale, from dark purple to yellow. Values below 0.001 take the darkest colour. Star: the 5 m³/d well. Square: constant-head cells on the west edge.

Figure S11. Forward fractions of river water and field recharge




Figure. Where the water from each source goes in the shared example model (Text S6). G is the share of a cell's water that came from the source. Star: supply well. River cells: blue outline in (a), blue fill in (b). (a) G of river water near the well, from 0 (pale yellow) to 1 (dark red). Contours at G = 0.05, 0.2 and 0.5. (b) G

of the recharge on a 300 m × 300 m field (black square), on a logarithmic scale from pale yellow to dark red. Values below 0.001 take the lightest colour. (c) Fate of the water from each source: the volume that leaves through the well and the volume that leaves through the river.

Figure S12. Backward fractions on different grids




Figure. The same trace on different grids (Text S7). F is the share of a cell's water that ends at the well. Dashed line: F = 0.1. Solid line: F = 0.5. Star: supply well. Blue cells: river. (a) F on the regular grid of 40 × 40 cells (DIS). (b) F on a Voronoi grid (DISV) made with vorflow (Hugman and Sanchez 2026). Its cells are about 50 m across and shrink to about 10 m at the well and 12.5 m along the river. Insets in (a) and (b): the cells around the well and the river. The band between the dashed and solid lines is wider in (b) than in (a). The two DISU grids give the map of (a) cell for cell and are not shown. (c) F on the regular grid with XT3D and a rotating anisotropy. Red squares: cells in flow loops. All panels use one colour scale from 0 (dark purple) to 1 (yellow).

Figure S13. Seasonal snapshots




Figure. Snapshots of the seasonal example model (Text S8). F is the share of a cell's water that ends at the well. Star: supply well. Blue cells: river. (a–d) F in the middle time step of the wet, wet-to-dry, dry and dry-to-wet seasons of the last year, from 0 (dark purple) to 1 (yellow). Dashed white line: F = 0.1. Solid white line: F = 0.5. Panel titles give the pumping rate. (e) Nested zones from statistics over the 36 seasonal steps. Inner zone: F > 0.5 in every step. Seasonal zone: F > 0.5 in some steps but not all. Ring: F > 0.1 in at least one step but F > 0.5 in none. The three together form the outer envelope. Black line: time-weighted mean F = 0.5.

Figure S14. Mean travel time against particles




Figure. Mean travel time to the supply well under full mixing, on the shared model with a porosity of 0.3 (Text S9). (a) Mean travel time from each cell to the well, in years, shown only where F > 0.5, on a

logarithmic colour scale from 0.1 years (pale yellow) to 100 years (black). Cyan lines: the 5-year and 25-year time-of-travel zones. The river and the well are marked. (b) Mean travel time per release cell, from weight-losing PRT particles (vertical axis) and from full mixing (horizontal axis). Both times end where the water enters the well cell. Both axes are logarithmic. The dashed line marks equal times. Colour gives F in the release cell, from 0 (dark purple) to 1 (yellow). Cells with F near 1 lie close to the line. Cells at the edge of the area, with small F, lie well above it.

Figure S15. Backward fractions through streams and a multi-aquifer well




Figure. Backward fraction F to the supply well when water leaves the aquifer cells and comes back (Text S10). (a–c) A stream fed by drains replaces the river of the shared model. (a) The trace stops at the aquifer cells. Stream leakage is then a source term. The drains are sinks. (b) The stream reaches and the transfers of the water mover from the drains to the stream are traced as cells. In (a) and (b), colour gives F from 0 (dark purple) to 1 (yellow). Dashed white line: the $F > 0.1$ area. Solid white line: the $F > 0.5$ area. The stream, the two drains and the supply well are marked. (c) F of each stream reach against its position, from the first reach in the north to the last in the south. Blue dots mark reaches that lose water to the aquifer. Orange dots mark reaches that gain water from it. (d, e) A three-layer version of the shared model with a multi-aquifer well (MAW). The MAW is a borehole screened in all three layers. The middle layer is an aquitard. Each section runs from west to east along the model row that holds the MAW and the supply well. The vertical scale is exaggerated. (d) The trace stops at the aquifer cells. The MAW is then a sink in the upper two layers and a source in the bottom layer. (e) The MAW borehole is traced as a cell. Colour gives F as in (a) and (b). The MAW borehole (white line), the river and the supply well are marked.

Figure S16. The unit-concentration example rebuilt




Figure. The unit-concentration example of Bedekar et al. (2024), rebuilt in MODFLOW 6 (Text S11). (a) Share of the pumped water from stored water, lateral inflow, recharge and the stream, against time since pumping started. Lines: forward transient tracking. Open circles: values read off Figure 2 of Bedekar et al. (2024). Colours as in the published figure: grey for stored water, orange for lateral inflow, green for recharge and blue for the stream. (b–e) Backward tracking in time. The maps show layer 2, where the well is screened. For the water in each cell at the start, colour gives the fraction that the well pumps within 1, 5, 10 and 25 years, from 0 (dark purple) to 1 (yellow). (f) Steady-state backward fraction F for the flows of the last time step, for comparison. The well is marked in (b–f).

Figure S17. Numerical dispersion against cell size




Figure. Numerical dispersion of full mixing against cell size h. Top row: problem A, uniform flow to a well, with the analytical capture zone (Javandel and Tsang 1986) as reference. Flow runs along the grid rows (solid) or at 30° to them (dotted). Bottom row: problem B, an aquifer like test model 1 (Text S2). The reference is PRT on the finest grid, compared west of the river. (a, d) Width of the transition band (0.1 < F < 0.9). Dashed guide: $h^{0.5}$. Face routing: an experimental 2D option that passes water between cell faces instead of mixing it (Chowdhury 2016). The exact zone averaged onto the grid (A) and PRT on the same grid (B) show the narrowest band the grid allows. (b, e) Relative error in the size of the F > 0.1 area. (c, f) The same for the F > 0.5 area. Grey band, ±5 %. Section 6 of the main text compares the F > 0.1 and F > 0.5 areas from these tests. The test problems and the numbers behind the panels are given in Figure S4.

References cited only in the Supporting Information

Campana, M.E., and E.S. Simpson. 1984. Groundwater residence times and recharge rates using a discrete-state compartment model and C-14 data. *Journal of Hydrology* 72, no. 1–2: 171–185. https://doi.org/10.1016/0022-1694(84)90190-2

Chowdhury, M.A. 2016. Assessing the connectivity of groundwater wells to surface-water using a volumetric capture delineation tool. MASc thesis, University of Waterloo, Waterloo, Ontario, Canada. http://hdl.handle.net/10012/10981

Cornaton, F., and P. Perrochet. 2006. Groundwater age, life expectancy and transit time distributions in

advective–dispersive systems: 1. Generalized reservoir theory. *Advances in Water Resources* 29, no. 9: 1267–1291. https://doi.org/10.1016/j.advwatres.2005.10.009

Hughes, J.D., C.D. Langevin, S.R. Paulinski, J.D. Larsen, and D. Brakenhoff. 2024. FloPy workflows for creating structured and unstructured MODFLOW models. *Groundwater* 62, no. 1: 124–139. https://doi.org/10.1111/gwat.13327

Hugman, R., and O. Sanchez. 2026. vorflow: Voronoi mesh generation for MODFLOW 6. Version 0.2.0. Software, released 5 October 2026. https://github.com/rhugman/vorflow

Javandel, I., and C.-F. Tsang. 1986. Capture-zone type curves: A tool for aquifer cleanup. *Ground Water* 24, no. 5: 616–625. https://doi.org/10.1111/j.1745-6584.1986.tb03710.x

Langevin, C.D., J.D. Hughes, E.R. Banta, R.G. Niswonger, S. Panday, and A.M. Provost. 2017. Documentation for the MODFLOW 6 Groundwater Flow Model. U.S. Geological Survey Techniques and Methods, book 6, chap. A55. Reston, Virginia: USGS. https://doi.org/10.3133/tm6A55

McLane, C., and L. Cecan. 2009. Comment on "MODALL: A practical tool for designing and optimizing capture systems," by S.T. Potter, E. Moreno-Barbero, and C.E. Divine. *Ground Water* 47, no. 2: 172–173. https://doi.org/10.1111/j.1745-6584.2008.00527_1.x

Nogueira, G.E.H., C. Schmidt, D. Partington, P. Brunner, and J.H. Fleckenstein. 2022. Spatiotemporal variations in water sources and mixing spots in a riparian zone. *Hydrology and Earth System Sciences* 26, no. 7: 1883–1905. https://doi.org/10.5194/hess-26-1883-2022

Partington, D., P. Brunner, C.T. Simmons, R. Therrien, A.D. Werner, G.C. Dandy, and H.R. Maier. 2011. A hydraulic mixing-cell method to quantify the groundwater component of streamflow within spatially distributed fully integrated surface water–groundwater flow models. *Environmental Modelling & Software* 26, no. 7: 886–898. https://doi.org/10.1016/j.envsoft.2011.02.007

Partington, D., P. Brunner, C.T. Simmons, A.D. Werner, R. Therrien, H.R. Maier, and G.C. Dandy. 2012. Evaluation of outputs from automated baseflow separation methods against simulated baseflow from a physically based, surface water–groundwater flow model. *Journal of Hydrology* 458–459: 28–39. https://doi.org/10.1016/j.jhydrol.2012.06.029

Partington, D., P. Brunner, S. Frei, C.T. Simmons, A.D. Werner, R. Therrien, H.R. Maier, G.C. Dandy, and J.H. Fleckenstein. 2013. Interpreting streamflow generation mechanisms from integrated surface-subsurface flow models of a riparian wetland and catchment. *Water Resources Research* 49, no. 9: 5501–5519. https://doi.org/10.1002/wrcr.20405

Provost, A.M., C.D. Langevin, and J.D. Hughes. 2017. Documentation for the "XT3D" option in the Node Property Flow (NPF) Package of MODFLOW 6. U.S. Geological Survey Techniques and Methods, book 6, chap. A56. Reston, Virginia: USGS. https://doi.org/10.3133/tm6A56

Rushton, K.R. 2003. *Groundwater Hydrology: Conceptual and Computational Models.* Chichester, UK: John Wiley and Sons.

Schilling, O.S., C. Gerber, D.J. Partington, R. Purtschert, M.S. Brennwald, R. Kipfer, D. Hunkeler, and P. Brunner. 2017. Advancing physically-based flow simulations of alluvial systems through atmospheric

noble gases and the novel ^{37}Ar tracer method. *Water Resources Research* 53, no. 12: 10465–10490. https://doi.org/10.1002/2017WR020754

Tosco, T., A. Di Molfetta, and R. Sethi. 2010. Automatic delineation of capture zones for pump and treat systems: A case study in Piedmont, Italy. *Ground Water Monitoring & Remediation* 30, no. 2: 46–52. https://doi.org/10.1111/j.1745-6592.2010.01276.x